Beam Power Tube

The 22KV6A is the same as the 6KV6A except for:

Heater Characteristics and Ratings

| Current | 0.450 ± 0.030 | A |
|-------------------------------|-------------------|---|
| Voltage (ac or dc) at 0.450 A | 22.0 | V |
| Warm-up time (Average) | 11 | s |

24JE6A

Beam Power Tube

Novar Type

The 24JE6A is the same as the 6JE6A except for:

Heater Characteristics and Ratings

| Current. | 6 6 | 6 6 | 0 0 | ø « | 8 6 | 6 8 | - 6 | 4 | a | 0 | 0 | ą. | 9 | 8 | 0.600 ± 0.040 | A |
|----------|-----|-----|-----|-----|-----|-----|-----|----|---|---|---|----|---|---|-------------------|---|
| Voltage | (ac | or | de) | at | 0.6 | 300 | A | h. | 9 | ø | 8 | 6 | ÷ | 9 | 24.0 | V |
| Warm-up | tim | e (| Ave | rag | e) | e 6 | | 9 | 0 | 8 | B | a) | ٠ | 6 | | 8 |

24106

Beam Power Tube Novar Type

The 24LQ6 is the same as the 6LQ6 except for:

Heater Characteristics and Ratings

| Current | 8 8 8 9 5 8 | | p 4: | 0 0 | 8 6 | 4 4 | 0.600 ± 0.040 | A |
|-----------|-------------|----------|------|-----|---------|-----|--|---|
| Voltage (| (ac or dc) | at 0.600 | A | 8 B | 8 4 | a a | 24,0 | V |
| Warm-up | time (Ave | rage) | 6 8 | 0 0 | 0 0 | 0 0 | Sign and Sig | S |