



35A5

BEAM POWER AMPLIFIER

35A5

GENERAL DATA**Electrical:**


Heater, for Unipotential Cathode:

Voltage.	35.0	ac or dc volts
Current.	0.15	amp

Mechanical:

Mounting Position.	Any
Maximum Overall Length	3-5/32"
Maximum Seated Length.	2-5/8"
Maximum Diameter	1-3/16"
Bulb	T-9
Base	Lock-in 8-Pin
Basing Designation for BOTTOM VIEW	6AA

Pin 1 - Heater
 Pin 2 - Plate
 Pin 3 - Grid No.2
 Pin 4 - No
 Connection
 Pin 5 - No
 Connection



Pin 6 - Grid No.1
 Pin 7 - Cathode,
 Grid No.3
 Pin 8 - Heater
 Plug - Base
 Shell

AF POWER AMPLIFIER - Class A₁**Maximum Ratings, Design-Center Values:**

PLATE VOLTAGE.	200 max.	volts
GRID-No.2 (SCREEN) VOLTAGE	125 max.	volts
PLATE DISSIPATION.	8.5 max.	watts
GRID-No.2 DISSIPATION.	1.0 max.	watt
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode.	90 max.	volts
Heater positive with respect to cathode.	90 max.	volts

Typical Operation and Characteristics:

Plate Voltage.	110	200	volts
Grid-No.2 Voltage	110	110	volts
Grid-No.1 (Control-Grid) Voltage	-7.5	-8	volts
Zero-Signal Plate Current.	40	41	ma.
Max.-Signal Plate Current.	41	44	ma.
Zero-Signal Grid-No.2 Current.	3.0	2.0	ma.
Max.-Signal Grid-No.2 Current.	7.0	7.0	ma.
Plate Resistance (Approx.)	16000	40000	ohms
Transconductance	5800	5900	μmhos
Load Resistance.	2500	4500	ohms
Total Harmonic Distortion.	10	10	%
Max.-Sig. Power Output	1.5	3.3	watts

Maximum Circuit Values (for maximum rated conditions):

Grid-No.1-Circuit Resistance:

For fixed bias	0.1	megohm
For cathode bias	0.5	megohm