



35L6-GT

35L6-GT

BEAM POWER AMPLIFIER

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

Voltage. 35 ac or dc volts
Current. 0.15 amp

Direct Interelectrode Capacitances (Approx.):⁰

Grid No.1 to Plate 0.8 μf
Input. 13 μf
Output 9.5 μf

⁰ With no external shield.

Mechanical:

Mounting Position. Any

Maximum Overall Length 3-5/16"

Maximum Seated Length. 2-3/4"


Maximum Diameter 1-5/16"

Bulb T-9

Base Intermediate-Shell Octal 7-Pin

Basing Designation for BOTTOM VIEW G-7AC

Pin 1 - No
Connection
Pin 2 - Heater
Pin 3 - Plate
Pin 4 - Grid No.2



Pin 5 - Grid No.1
Pin 7 - Heater
Pin 8 - Cathode,
Grid No.3

AF POWER AMPLIFIER - Class A₁

Maximum Ratings, Design-Center Values:

PLATE VOLTAGE.	200 max.	volts
GRID-No.2 (SCREEN) VOLTAGE	117 max.	volts
PLATE DISSIPATION.	8.5 max.	watts
GRID-No.2 DISSIPATION.	1.0 max.	watt
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode	90 max.	volts
Heater positive with respect to cathode	90 max.	volts

Typical Operation and Characteristics:

Plate Voltage.	110	200	. .	volts
Grid-No.2 Voltage	110	110	. .	volts
Grid-No.1 (Control-Grid) Voltage	-7.5	-8	. .	volts
Peak AF Grid-No.1 Voltage.	7.5	8	. .	volts
Zero-Signal Plate Current.	40	41	. .	ma.
Max.-Signal Plate Current.	41	44	. .	ma.
Zero-Signal Grid-No.2 Current.	3	2	. .	ma.
Max.-Signal Grid-No.2 Current.	7	7	. .	ma.
Plate Resistance (Approx.)	14000	40000	. .	ohms
Transconductance	5800	5900	. .	μmhos
Load Resistance.	2500	4500	. .	ohms
Total Harmonic Distortion.	10	10	. .	%
Max.-Sig. Power Output	1.5	3.3	. .	watts

35L6-GT



35L6-GT BEAM POWER AMPLIFIER

Maximum Circuit Values (for maximum rated conditions):

Grid-No.1-Circuit Resistance:

For fixed bias	0.1 . . megohm
For cathode bias	0.5 . . megohm


Curves shown under Type 35B5 are also applicable
to the 35L6-GT.



35L6-GT

35L6-GT

AVERAGE PLATE CHARACTERISTICS PENTODE CONNECTION



AUG. 11, 1941

TUBE DEPARTMENT

92CM-6309

RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY


35L6-GT



35L6-GT

OPERATION CHARACTERISTICS

$E_f = 35$ VOLTS PLATE VOLTS = 200 GRID N^o2 VOLTS = 110
 GRID N^o1 VOLTS = -8
 SIGNAL VOLTS (RMS) = 5.65



AUG. 21, 1941

TUBE DEPARTMENT
 RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY


92CM - 6315



35L6-GT

35L6-GT AVERAGE PLATE CHARACTERISTICS TRIODE CONNECTION

$E_f = 35$ VOLTS
GRID-№2 CONNECTED TO PLATE



AUG. 6, 1941

PLATE MILLIAMPERES
TUBE DEPARTMENT
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM - 6307RI