



55

TWIN DIODE—MEDIUM-MU TRIODE

5/15/55

Heater, for Unipotential Cathode:

Voltage.	2.5	ac or dc volts
Current.	1.0	amp

Type 55 is the same as Type 85 except for heater rating.

56

MEDIUM-MU TRIODE

Heater, for Unipotential Cathode:

Voltage.	2.5	ac or dc volts
Current.	1.0	amp

Direct Interelectrode Capacitances:^o

Grid to Plate.	3.2	μf
Grid to Cathode.	3.2	μf
Plate to Cathode.	2.4	μf

^o Without external shield.*Type 56 is the same as Type 76 except for heater rating and direct interelectrode capacitances.*

57

SHARP-CUTOFF PENTODE

GENERAL DATA**Electrical:**

Heater, for Unipotential Cathode:

Voltage.	2.5	ac or dc volts
Current.	1.0	amp

Direct Interelectrode Capacitances:

Pentode Connection:

Grid No.1 to Plate ^o	0.007 max.	μf
Input ^{oo}	5	μf
Output ^{oo}	6.5	μf

Triode Connection:^{*oo}

Grid No.1 to Plate.	2	μf
Grid No.1 to Cathode.	3	μf
Plate to Cathode.	10.5	μf

Mechanical:

Mounting Position.	Any
Maximum Overall Length.	4-15/16"
Seated Length.	4-3/16" $\pm$ 1/8"
Maximum Diameter.	1-9/16"
Bulb.	ST-12

(continued on next page)

^o With external shield connected to cathode.^{oo} Without external shield.^{*} With grid No.2 and grid No.3 connected to plate.

JUNE 15, 1948

TUBE DEPARTMENT

DATA

RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY