



1631

1631
6333**BEAM POWER AMPLIFIER***For applications critical as to uniformity of characteristics*

Heater	Coated Unipotential Cathode	
Voltage	12.6	a-c or d-c volts
Current	0.45	amp.
Plate Dissipation	16 max. watts	

Other ratings, characteristics, dimensions, and socket connections for the 1631 are the same as those for Type 6L6. Typical operating data for the 6L6 also apply to the 1631 within the limitation of the maximum plate-dissipation rating.

1632

BEAM POWER AMPLIFIER*For applications critical as to uniformity of characteristics*

Heater	Coated Unipotential Cathode	
Voltage	12.6	a-c or d-c volts
Current	0.6	amp.
Plate Voltage	117 max. volts	
Screen Voltage	117 max. volts	
Plate Dissipation	5.5 max. watts	

Dimensions and socket connections for the 1632 are the same as for Type 25L6. Typical operating data for the 1632 are the same within its plate voltage and dissipation limitations as for the 25L6.

1633

TWIN-TRIODE AMPLIFIER*For applications critical as to matching of the two triode units*

Heater	Coated Unipotential Cathode	
Voltage	25	a-c or d-c volts
Current	0.15	amp.

Direct Interelectrode Capacitances (Approx.):^o

	<u>Triode Unit T_1</u>	<u>Triode Unit T_2</u>	
Grid to Plate	3.6	3.6	μf
Grid to Cathode	3.0	2.8	μf
Plate to Cathode	0.8	1.2	μf

Maximum Overall Length 3-5/16"

Maximum Seated Height 2-3/4"

Maximum Diameter 1-5/16"

Bulb T-9

Base Intermediate Shell Octal 8-Pin

Pin 1 - Grid T_2 Pin 5 - Plate T_1 Pin 2 - Plate T_2 Pin 6 - Cathode T_1 Pin 3 - Cathode T_2 Pin 7 - HeaterPin 4 - Grid T_1 Pin 8 - Heater

Mounting Position Any

BOTTOM VIEW (8BD)

For convenience, one triode unit is identified as T_1 ; the other as T_2 .^o See next page.

Nov. 15, 1945

RCA VICTOR DIVISION
 RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

DATA