

Medium-Mu Triode

9-PIN MINIATURE TYPE

GENERAL DATA

Electrical:

Heater Characteristics and Ratings (*Absolute-Maximum Values*):Voltage (AC or DC) 6.3 ± 0.6 volts

Current at heater volts = 6.3 0.300 amp

Peak heater-cathode voltage:

Heater negative with respect to cathode. 55 max. volts

Heater positive with respect to cathode. 55 max. volts

Direct Interelectrode Capacitances (Approx.):^aPlate to cathode and heater 0.55 μf Cathode to grid and heater. 9 μf Plate to grid and heater. 1.8 μf Characteristics, Class A₁ Amplifier:

Plate Supply Voltage. 130 150 volts

Grid Voltage^b 9 - volts

Cathode Resistor. 360 60 ohms

Amplification Factor. 43 43

Plate Resistance (Approx.). 1600 1700 ohms

Transconductance. 27000 25000 μmhos

Plate Current 27 25 ma

Mechanical:

Operating Position. Any

Type of Cathode Coated Unipotential

Maximum Overall Length. 1-3/4"

Maximum Seated Length 1-1/2"

Length, Base Seat to Bulb Top (Excluding tip) . 1-1/8" $\pm$ 3/32"

Diameter. 0.750" to 0.875"


Dimensional Outline See *General Section*

Bulb.T6-1/2

Base. Small-Button Noval 9-Pin (JEDEC No.E9-1)

Basing Designation for BOTTOM VIEW.9V

Pin 1 - Plate
 Pin 2 - No Internal
 Connection
 Pin 3 - Heater
 Pin 4 - Grid



Pin 5 - Grid
 Pin 6 - Cathode
 Pin 7 - Grid
 Pin 8 - Grid
 Pin 9 - Heater

AMPLIFIER — Class A₁Maximum Ratings, *Absolute-Maximum Values*:

PLATE VOLTAGE 200 max. volts

CATHODE CURRENT 38 max. ma



5842/417A

PLATE DISSIPATION. 4.5 max. watts
BULB TEMPERATURE (At hottest point on
bulb surface). 160 max. °C

- ^a Without external shield.
- ^b Measured with respect to the negative end of the cathode resistor.