



6680

6680/12AU7-A

MEDIUM-MU TWIN TRIODE

9-PIN MINIATURE TYPE

*For use in mobile communications equipment***GENERAL DATA****Electrical:**

Heater, for Unipotential Cathodes:

Heater arrangement	Series	Parallel	
Voltage.	$12.6 \pm 20\%^*$	$6.3 \pm 20\%^*$	ac or dc volts

Current:

At 12.6 volts. . .	0.15	—	amp
At 6.3 volts . . .	—	0.3	amp

Direct Interelectrode Capacitances (Approx.):

	Without External Shield	With External Shield ⁰	
Grid to plate (Each unit). . . .	1.5	1.5	μmf
Grid to cathode and heater (Each unit).	1.6	1.8	μmf
Plate to cathode and heater:			
Unit No.1.	0.4	2	μmf
Unit No.2.	0.32	2	μmf


Characteristics, Class A₁ Amplifier (Each Unit):

Heater Voltage:

For series connection.	12.6	12.6	volts
For parallel connection.	6.3	6.3	volts
Plate Voltage.	100	250	volts
Grid Voltage	0	-8.5	volts
Amplification Factor	20	17	
Plate Resistance (Approx.)	6500	7700	ohms
Transconductance	3100	2200	μmhos
Plate Current.	11.8	10.5	ma
Grid Voltage (Approx.) for plate $\mu_a = 10$.	—	-24	volts

Mechanical:

Operating Position	Any
Maximum Overall Length	2-3/16"
Maximum Seated Length.	1-15/16"
Length, Base Seat to Bulb Top (Excluding tip).	1-9/16" $\pm$ 3/32"
Diameter	0.750" to 0.875"
Dimensional Outline.	See General Section
Bulb	T6-1/2
Base	Small-Button Noval 9-Pin (JEDEC No. E9-1)
Basing Designation for BOTTOM VIEW	9A
Pin 1—Plate of Unit No.2	Pin 6—Plate of Unit No.1
Pin 2—Grid of Unit No.2	Pin 7—Grid of Unit No.1
Pin 3—Cathode of Unit No.2	Pin 8—Cathode of Unit No.1
Pins 4 & 9—Heater of Unit No.2	Pin 9—Heater Mid-Tap
Pins 5 & 9—Heater of Unit No.1	



6680



6680/12AU7-A

MEDIUM-MU TWIN TRIODE

AMPLIFIER — Class A₁

Values are for Each Unit

Maximum Ratings, Design-Maximum Values:

PLATE VOLTAGE	330 max.	volts
GRID VOLTAGE:		
Positive-bias value	0 max.	volts
PLATE DISSIPATION	3 max.	watts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect		
to cathode.	200 max.	volts
Heater positive with respect		
to cathode.	200 [▲] max.	volts

Maximum Circuit Values:

Grid-Circuit Resistance:

For fixed-bias operation.	0.25 max.	megohm
For cathode-bias operation.	1 max.	megohm

* When the heater is operated from storage-battery-with-charger supply or similar supplies, the normal battery-voltage fluctuation may be as much as 35 per cent or more. Although such variation in heater voltage is permissible for short periods, reliability can be increased with improved supply-voltage regulation.

○ With external shield JEDEC No. 315 connected to cathode of unit under test.

▲ The dc component must not exceed 100 volts.

SPECIAL RATINGS & PERFORMANCE DATA

Heater-Cycling Life Performance:

This test is performed on a sample lot of tubes from each production run. A minimum of 2000 cycles of intermittent operation is applied under the following conditions: heater volts = 15 (Series connection) cycled one minute on and one minute off, heater 135 volts positive with respect to cathode, and all other elements connected to ground. At the end of this test, tubes are checked for heater-cathode shorts and open circuits.

Transconductance at Reduced Heater Voltage:

Average Value (Each unit)	1750	μmhos
With heater volts = 10 (Series connection), plate volts = 250, and grid volts = -8.5.		