

Sharp-Cutoff Tetrode

7-PIN MINIATURE TYPE

For Mobile-Communications Equipment

GENERAL DATA

Electrical:

Heater Characteristics and Ratings (*Design-Maximum Values*):

Voltage (AC or DC) 6.3 ^{+1.2}_{-0.3} volts

Current at heater volts = 6.3 0.200 amp

Peak heater-cathode voltage:

Heater negative with respect to cathode 100 max. volts

Heater positive with respect to cathode 100^a max. volts

Direct Interelectrode Capacitances:^b

Grid No.1 to plate 0.03 max. μ f

Grid No.1 to cathode & internal shield, grid No.2, and heater 4.4 μ f

Plate to cathode & internal shield, grid No.2, and heater 2.74 μ f

Characteristics, Class A₁ Amplifier:

Plate Voltage 125 volts

Grid-No.2 Voltage 80 volts

Grid-No.1 Voltage -1 volt

Plate Resistance (Approx.) 0.125 megohm

Transconductance 8000 μ mhos

Plate Current 10 ma

Grid-No.2 Current 1.4 ma

Grid-No.1 Voltage (Approx.) for transconductance (μ mhos) = 100 -5 volts

Mechanical:

Operating Position Any

Type of Cathode Coated Unipotential

Maximum Overall Length 2-1/8"

Maximum Seated Length 1-7/8"

Length, Base Seat to Bulb Top (Excluding tip) 1-1/2" $\pm$ 3/32"

Diameter 0.650" to 0.750"

Dimensional Outline See *General Section*

Bulb T5-1/2

Base Small-Button Miniature 7-Pin (JEDEC No.E7-1)


Basing Designation for BOTTOM VIEW 7EW

Pin 1-Grid No.1

Pin 2-Cathode,
Internal
Shield

Pin 3-Heater

Pin 4-Heater



Pin 5-Plate

Pin 6-Grid No.2

Pin 7-Cathode,
Internal
Shield



7717/6CY5

AMPLIFIER — Class A₁

Maximum Ratings, Design-Maximum Values:

PLATE VOLTAGE	180 max.	volts
GRID-No.2 (SCREEN-GRID) SUPPLY VOLTAGE. . .	180 max.	volts
GRID-No.2 VOLTAGE	.See <i>Grid-No.2 Input Rating Chart</i> at front of Receiving Tube Section	
GRID-No.1 (CONTROL-GRID) VOLTAGE:		
Positive-bias value	0 max.	volts
CATHODE CURRENT	20 max.	ma
GRID-No.2 INPUT:		
For grid-No.2 voltages up to 90 volts	0.5 max.	watt
For grid-No.2 voltages be- tween 90 and 180 volts. .	.See <i>Grid-No.2 Input Rating Chart</i> at front of Receiving Tube Section	
PLATE DISSIPATION	2 max.	watts

Maximum Circuit Values:

Grid-No.1-Circuit Resistance.	0.5 max.	megohm
---------------------------------------	----------	--------

SPECIAL RATINGS & PERFORMANCE DATA

Heater-Cycling:

Cycles of Intermittent Operation.	2000 min.	cycles
---	-----------	--------

This test is performed on a sample lot of tubes from each production run under the following conditions: heater volts = 7.5 cycled one minute on and one minute off, heater 135 volts positive with respect to cathode and all other elements connected to ground. At the end of this test, tubes are checked for heater-cathode shorts and open circuits.

Transconductance at Reduced Heater Voltage:

Average Value	5900	μ mhos
-------------------------	------	------------

With heater volts = 5.0, plate volts = 125, grid-No.2 volts = 80, grid-No.1 volts = -1.

^a The dc component must not exceed 50 volts.

^b With external shield JEDEC No.316 connected to cathode.

