

Electron tubes

Book T10 1985

Plumbicon camera tubes and accessories

Elcoma – Philips Electronic Components and Materials Division – embraces a world-wide group of companies operating under the following names:

IBRAPE PHILIPS

MBLE RTC

Miniwatt **Signotics**

Mullard VALVO

Elcoma offers you a technological partnership in developing your systems to the full. A partnership to which we can bring

- world-wide production and marketing
- know-how
- systems approach
- continuity
- broad product line
- fundamental research
- leading technologies
- applications support
- quality

PLUMBICON CAMERA TUBES AND ACCESSORIES

pag	1e
eneral Section	
Principles of operation	3
Rating system	
Survey and type selection	2
Plumbicon tubes 30 mm	3
Plumbicon tubes 25,4 mm	4
Plumbicon tubes 18 mm	5
Plumbicon tubes 14 mm	6
Accessories	7
General operational notes	9
Test specification	9
evice data	
30 mm dia. Plumbicon tubes	7
25,4 mm dia. Plumbicon tubes	7
18 mm dia. Plumbicon tubes	7
14 mm dia. Plumbicon tubes	9
Deflection and focusing assemblies	9
ndex of type numbers29	3

Entropy of the paper of the entropy will be

Application of the second

DATA HANDBOOK SYSTEM

Our Data Handbook System comprises more than 60 books with specifications on electronic components, subassemblies and materials. It is made up of four series of handbooks:

ELECTRON TUBES

BLUE

SEMICONDUCTORS

RED

INTEGRATED CIRCUITS

PURPLE

COMPONENTS AND MATERIALS

GREEN

The contents of each series are listed on pages iv to viii.

The data handbooks contain all pertinent data available at the time of publication, and each is revised and reissued periodically.

When ratings or specifications differ from those published in the preceding edition they are indicated with arrows in the page margin. Where application information is given it is advisory and does not form part of the product specification.

Condensed data on the preferred products of Philips Electronic Components and Materials Division is given in our Preferred Type Range catalogue (issued annually).

Information on current Data Handbooks and on how to obtain a subscription for future issues is available from any of the Organizations listed on the back cover.

Product specialists are at your service and enquiries will be answered promptly.

ELECTRON TUBES (BLUE SERIES)

The blue series of data handbooks comprises:

T1	Tubes for r.f. heating					
T2a	Transmitting tubes fo	r communications, glass types				
T2b	Transmitting tubes fo	r communications, ceramic types				
Т3	Klystrons					
T4	Magnetrons for micro	wave heating				
T5	Cathode-ray tubes Instrument tubes, mo	nitor and display tubes, C.R. tubes for special applications				
T6	Geiger-Müller tubes					
T7	Gas-filled tubes (will not be reprinted)					
Т8	Picture tubes and components Colour TV picture tubes, black and white TV picture tubes, colour monitor tubes for data graphic display, monochrome monitor tubes for data graphic display, components for colo television, components for black and white television and monochrome data graphic display					
T9	Photo and electron m	ultipliers				
T10	Plumbicon camera tubes and accessories					
T11	Microwave semicondu	ctors and components				
T12	Vidicon and Newvicon	n camera tubes				
T13	Image intensifiers					
T14	Infrared detectors	Data collations on these subjects are available now. Data Handbooks will be published in 1985.				
T15	Dry reed switches					

Black and white TV picture tubes, monochrome data graphic display tubes, deflection units

T16

Monochrome tubes and deflection units

SEMICONDUCTORS (RED SERIES)

The red series of data handbooks comprises:

S1	$\label{eq:Diodes} \textbf{Diodes} \\ \textbf{Small-signal germanium diodes, small-signal silicon diodes, voltage regulator diodes (< 1,5 W), \\ \textbf{voltage reference diodes, tuner diodes, rectifier diodes} \\ \\ \\ \\ \textbf{Voltage resultator diodes} \\ \\ \\ \textbf{Voltage resultator diodes} $
S2a	Power diodes
S2b	Thyristors and triacs
S 3	Small-signal transistors
S4a	Low-frequency power transistors and hybrid modules
S4b	High-voltage and switching power transistors
S 5	Field-effect transistors
S6	R.F. power transistors and modules
S7	Surface mounted semiconductors
S8	Devices for optoelectronics Photosensitive diodes and transistors, light-emitting diodes, displays, photocouplers, infrared sensitive devices, photoconductive devices.
S9	Power MOS transistors
S10	Wideband transistors and wideband hybrid IC modules
S11	Microwave semiconductors (to be published in this series in 1985) At present available in Handbook T11
S12	Surface acoustic wave devices

INTEGRATED CIRCUITS (PURPLE SERIES)

The purple series of data handbooks comprises:

EXIST	TING SERIES		Superse	ded by:
IC1	Bipolar ICs for radio and audio equipment			
IC2	Bipolar ICs for video equipment			ICO2N
IC3	ICs for digital systems in radio, audio and video equipment			
IC4	Digital integrated circuits CMOS HE4000B family			
IC5	Digital integrated circuits — ECL ECL10 000 (GX family), ECL100 000 (HX family), dedicate	ed designs		IC08N
IC6	Professional analogue integrated circuits			
IC7	Signetics bipolar memories			
IC8	Signetics analogue circuits			IC11N
IC9	Signetics TTL logic		ICO9N and	IC15N
IC10	Signetics Integrated Fuse Logic (IFL)			IC13N
IC11	Microprocessors, microcomputers and peripheral circuitry			

NEW SERIES

IC01N	Radio, audio and associated systems Bipolar, MOS	
IC02N	Video and associated systems Bipolar, MOS	(published 1985)
IC03N	Telephony equipment Bipolar, MOS	
IC04N	HE4000B logic family CMOS	
IC05N	HE4000B logic family uncased integrated circuits CMOS	(published 1984)
IC06N	High-speed CMOS; PC54/74HC/HCT/HCU Logic family	(published 1985)
IC07N	PC54/74HC/HCU/HCT uncased integrated circuits HCMOS	
IC08N	10K and 100K logic family ECL	(published 1984)
IC09N	Logic series	(published 1984)
IC10N	Memories MOS, TTL, ECL	
IC11N	Linear LSI	(published 1985)
IC12N	Semi-custom gate arrays & cell libraries ISL, ECL, CMOS	
IC13N	Semi-custom Integrated Fuse Logic	(published 1985)
IC14N	Microprocessors, microcontrollers & peripherals Bipolar, MOS	
IC15N	Logic series FAST TTL	(published 1984)

Note

Books available in the new series are shown with their date of publication.

COMPONENTS AND MATERIALS (GREEN SERIES)

The g	reen series of data handbooks comprises:		
C1	Programmable controller modules PLC modules, PC20 modules		
C2	Television tuners, coaxial aerial input assemblies, surface acoustic	wave filters	
C3	Loudspeakers		
C4	Ferroxcube potcores, square cores and cross cores		
C5	Ferroxcube for power, audio/video and accelerators		
C6	Synchronous motors and gearboxes		
C7	Variable capacitors		
C8	Variable mains transformers		
C9	Piezoelectric quartz devices		
C10	Connectors		
C11	Non-linear resistors Voltage dependent resistors (VDR), light dependent resistors (LD coefficient thermistors (NTC), positive temperature coefficient t	., .	ure
C12	Potentiometers, encoders and switches		
C13	Fixed resistors		
C14	Electrolytic and solid capacitors		
C15	Ceramic capacitors		
C16	Permanent magnet materials		
C17	Stepping motors and associated electronics		
C18	Direct current motors		
C19	Piezoelectric ceramics		
C20	Wire-wound components for TVs and monitors		
C21	Assemblies for industrial use HNIL FZ/30 series, NORbits 60-, 61-, 90-series, input devices		
C22	Film capacitors		

GENERAL SECTION

PRINCIPLES OF OPERATION

1 PHOTOCONDUCTIVE CAMERA TUBES

1.1 General description

A lens system focuses an image of the scene to be televised onto the faceplate of the camera tube. A photoconductive layer on the faceplate converts this image into a charge distribution which is then scanned line-by-line by an electron beam and transformed into an electrical signal.

Figure 1 illustrates the electrode and coil arrangement for a vidicon or Plumbicon tube with magnetic focusing and deflection. An electron gun produces the scanning electron beam, which is directed by the focusing and deflection coils to land upon a target containing the photoconductive layer.




Fig. 1 Electrode and coil arrangement of a vidicon or Plumbicon tube.

The electron gun comprises an indirectly heated cathode and grids 1 to 4. The voltage on grid 1 controls the electron beam current. Grid 2 (first anode) accelerates the electrons, which subsequently pass through a cylindrical electrode (grid 3) and a fine mesh (grid 4), which establishes a uniform decelerating field in front of the target.

The focusing coil produces an axial magnetic field that, in combination with an appropriate voltage applied to grid 3, focuses the beam on the target. Focusing can be adjusted by varying either the grid 3 voltage or the focusing coil current.

Two sets of alignment coils produce an adjustable transverse magnetic field, enabling the beam to be aligned parallel to the tube axis so that it lands perpendicularly on the target.

Finally, two sets of deflection coils supply the varying magnetic field needed to deflect the beam for line-by-line scan of the target.

The target section is illustrated in Fig. 2. It consists of:

- an optically flat faceplate:
- a transparent conductive film on the inner surface of the faceplate, connected electrically to the external signal electrode contact;
- a thin layer of photoconductive material deposited on the conductive film. In darkness this material has a high specific resistance which decreases with increasing illumination.




Fig. 2 Target section.

1.2 Operation

The external signal electrode contact is connected via a load resistor to a positive voltage of e.g. 45 V, see Fig. 3. The target may be assumed to consist of a large number of target elements corresponding to the number of picture elements. Each target element may be represented by a small capacitor C_e , connected on one side to the signal electrode via the transparent conductive film and shunted by a light dependent resistor R_e .

When the target is scanned, beam electrons — approaching the target at a low velocity — will continue to land until the scanned surface is approximately at cathode potential. This is called cathode potential stabilization. In this way a voltage difference is established across the layer, with each element capacitor charged to nearly the same potential as that applied to the signal electrode.

In the dark, the photoconductive material is a fairly good insulator, so that only a minute fraction of the charge of the element capacitors will leak away between successive scans. This fraction will be restored by the beam and the resulting current to the signal electrode is called 'dark current'.

When an optical image is focused on the target, those target elements which are illuminated will become conductive and will be partly discharged. As a consequence of this a pattern of positive charges corresponding to the optical image will be produced on the side of the target facing the electron gun.

While scanning this charge pattern, the electron beam will deposit electrons on the positive elements until the latter are restored to their original cathode potential, causing a capacitive current to the signal electrode — and hence a voltage across the load resistor R_{\parallel} . This voltage is the video signal and is fed to the preamplifier.

A camera tube is called 'stabilized' when the magnitude of the beam current is sufficient to restore the scanned surface to the cathode potential. All element capacitors, including those at the highlights of the image, are then completely recharged by the passing electron beam.




Fig. 3.

1.3 Separate mesh construction

The focusing coils commonly used do not produce an ideal focusing field distribution in the vicinity of the target. The resulting 'landing errors' of the scanning beam (non-perpendicular landing outside the central area) may cause picture defects such as geometrical distortion and 'stern waves' behind moving objects. An electron-optical lens formed between grids 3 and 4 can correct these landing errors. The grids are electrically separated with grid 4 (the mesh) positive relative to grid 3. Lens action is governed by the ratio of voltages on grids 3 and 4, the optimum ratio depending upon factors such as electron gun construction and type of coil assembly used.

Besides eliminating landing errors, separate-mesh construction reduces the space charge in the field-free region near the mesh, and so provides the bonus of improved resolution compared with the integral mesh (in which grids 3 and 4 are internally connected). Moreover, since this space charge increases with increasing beam current, separate mesh tubes can operate with higher beam currents than integral mesh tubes.

All currently available Plumbicon tubes have separate mesh construction. Some vidicon tubes, however, have integral meshes.

1.4 Electrostatic focus

Focusing and deflection may both be electrostatic. Figure 4 shows a possible arrangement of electrodes and coils for a camera tube with electrostatic focusing and magnetic deflection.




Fig. 4 Schematic electrode and coil arrangement with electrostatic focusing.

In an electrostatically focused tube the electron gun includes an indirectly heated cathode, a control electrode (grid 1), a focusing electrode (grid 2), a cylindrical electrode (grid 3) and a fine mesh (grid 4). Since this tube uses no focusing coils, it dissipates significantly less power than the magnetically focused tube.

1.5 Anti-comet-tail gun

To cope with extreme highlights, which cannot be stabilized with normal beam currents, a special electron gun known as the anti-comet-tail (ACT) gun has been developed. The General Operational Notes on Plumbicon tubes give a short description of this gun.

1.6 The diode gun

In the diode gun grid 1 is made positive relative to the cathode. This modifies the electron beam and provides larger beam reserve for highlight handling. A brief description of the diode gun will be found in the General Operational Notes on Plumbicon tubes.

2 MAIN PROPERTIES

2.1 Luminous sensitivity

The *luminous sensitivity*, S_L , of a camera tube is defined as the *average* signal current, I_S , generated per unit luminous flux falling uniformly on the scanned area, A, of its target; i.e.

$$S_L = \frac{I_S}{AB_{ph}} \mu A/Iumen$$

in which $B_{\mbox{\footnotesize{ph}}}$ is the illuminance of the photoconductive layer (in lumens/m²).

Often, what is of interest to the camera designer is not the average signal current, but the current, l_p , over the active scanning line, since this a better indication of the peak signal currents likely to occur in practice. For a camera tube with a blanking period β (given as a percentage of the total line period), the signal current l_p is given by:

$$I_{p} = \frac{100}{100 - \beta} I_{s} = \alpha I_{s}.$$

For the CCIR system $\alpha = 1,3$.

For a black/white camera, the illuminance, Bph, of the photoconductive layer is related to the scene illuminance, BSC, by:

$$B_{ph} = B_{SC} \frac{RT}{4F^2 (m+1)^2}$$

in which: R is the average scene reflectivity, T the lens transmission factor, F the lens aperture, and m the linear magnification from scene to target.

A similar relationship holds for the red, green and blue channels of a colour camera, but in this case the situation is complicated by the extra components that must be included in the optical system.

2.2 Radiant sensitivity and spectral response

The radiant sensitivity, S_r , of a camera tube is the average signal current generated per unit radiant energy falling uniformly on the scanned area of its target. Radiant energy is commonly expressed in mA/W, and at a given wavelength λ it is related to the *luminous* sensitivity, S_1 by:

$$S_r(\lambda) = 0,680 \vee (\lambda)S_L(\lambda)$$

in which V (λ) is the normalized spectral sensitivity of the eye at wavelength λ . Note: V (λ) is an empirical function that has been internationally agreed; its peak value is unity which occurs at a wavelength of 555 nm.

The radiant sensitivity of a camera tube varies with wavelength. The *spectral response* curves given in Fig. 5 show this variation for some typical camera tubes; these curves are merely exemplary, and for spectral response details of specific tubes the relevant data sheet should be consulted.




Fig. 5 Spectral response of various camera tubes. (1) Plumbicon tube XQ1073; (2) Sb₂S₃ vidicon XQ1280; (3) Sb₂S₃ vidicon XQ1240; (4) Newvicon tube XQ1274; (5) Newvicon tube XQ1276.

2.3 Resolution

The resolution of a camera tube is commonly expressed in terms of its *modulation depth*, which is defined as the ratio (expressed as a percentage) of the amplitudes of a 5 MHz and a 0,5 MHz square-wave signal as measured on a waveform monitor.

The square-wave signal can be produced by a test pattern comprising vertical black and white bars of equal thickness. The pattern may be specified in terms of the video frequency, or in terms of the corresponding number of TV lines, i.e. the number of bars that will fill a TV picture when arranged horizontally. For the CCIR system (52 μ s scan), 5 MHz corresponds to about 530 vertical bars or 400 TV lines, and 0,5 MHz corresponds to about 40 TV lines.

A pattern can also be specified by the number of line-pairs per mm (lp/mm), a line-pair being an adjacent pair of black and white bars. 400 TV lines corresponds to:

- 12,5 lp/mm for a 30 mm tube with enlarged scanning (scanned area 15,6 mm x 20,8 mm);
- 15,6 lp/mm for a 30 mm tube (scanned area 12,8 mm x 17,1 mm);
- 20,8 lp/mm for a 25 mm tube (scanned area 9,6 mm x 12,8 mm);
- 30,3 lp/mm for a 18 mm tube (scanned area 6,6 mm x 8,8 mm);
- 40,6 lp/mm for a 14 mm tube (scanned area 4,8 mm x 6,4 mm).

The modulation depth values given in this handbook include the slight degradation produced by the camera lens. For the purpose of these measurements, a lens aperture of 5,6 is taken.

2.4 Lag

In a camera tube there is always a delay in establishing a new signal current following a rapid change in target illumination. This is the phenomenon of *lag*. Two types of lag occur in a photoconductive camera tube: *photoconductive lag* determined principally by the nature of the target, and *discharge* (or *capacitive*) *lag* attributed to the way in which the electron beam discharges the target.

We define two forms of lag for measurement purposes:

- decay lag occurring at the transition from light to dark. This is measured after the target has been illuminated for at least 5 s, and is usually given as the ratio (expressed as a percentage) of the residual signal current to the initial current, the residual current being measured 60 ms and 200 ms (at 50 Hz) after the light is cut off.
- build-up lag occurring at the transition from dark to light. This is measured after 10 s of darkness, and is given as the ratio (expressed as a percentage) of the intermediate signal current to the final current, the intermediate current being measured 60 ms and 200 ms (at 50 Hz) after restoring the light.

3 Camera tube types

3.1 Plumbicon tube - lead oxide photoconductive layer

The photoconductive layer forms a continuous array of reverse-biased PIN-diodes, giving it an extremely low dark current. Its linear transfer characteristic, high sensitivity, very low photoconductive lag, excellent resolution and low burn-in make it pre-eminently suited to colour TV. Lead oxide does not respond to wavelengths greater than about 650 nm, but a small amount of sulphur included in the layer extends its response to wavelengths in the deep red (extended red Plumbicon tubes).

N.B. Plumbicon tubes do not permit automatic sensitivity control by means of regulation of the signal electrode voltage. Adequate control is therefore to be achieved by other means (iris control and neutral density filters).

When the tube is to be applied in a camera originally designed for vidicons, the automatic sensitivity control circuitry should, to prevent permanent damage or destruction of the target, be made inoperative and the signal electrode voltage be set to 45 V.

3.2 Vidicon tube - antimony trisulphide (Sb₂S₃) photoconductive layer

The sensitivity of an Sb_2S_3 layer depends on the target voltage (the voltage across the layer), so it is possible to control the sensitivity by varying this voltage. The dark current is strongly dependent upon target voltage as well as upon temperature.

The Sb_2S_3 layer suffers from photoconductive lag and is prone to burn-in. The layer also has a non-linear transfer characteristic and so is less suited to colour TV. However, since the layer is thin its resolution is high.

Standard vidicons are relatively inexpensive to manufacture, so despite their drawbacks they are used extensively in less critical applications. Variants of the standard vidicon have been developed for use in medical X-ray equipment where they are coupled to an X-ray image intensifier.

3.3 Newvicon tube - heterojunction photoconductive layer

The photoconductive layer contains sublayers of zinc selenide (ZnSe) and of a zinc telluride (ZnTe) cadmium telluride (CdTe) mixture. In operation the layer is reverse-biased. The layer produces a non-negligible dark current that is temperature dependent.

The Newvicon tube has very high sensitivity which extends into the near infrared. It is not possible to adjust this sensitivity by varying the target voltage. The tube has a linear transfer characteristic and low burn-in. Its photoconductive layer is thin, so it has high lag and and high resolution.

4 Equipment design and operating conditions

4.1 Signal electrode connection

The signal electrode connection should be made by a spring contact that bears against the target connection. The spring contact may be part of the coil assembly.

4.2 Deflection circuitry

The signal current is a function of target illumination and of scanning speed. The deflection circuitry must therefore provide constant scanning speed to ensure that the variation in signal current is a true representation of the intensity profile across the target.

4.3 Electrostatic shielding

To avoid interference in the picture the signal electrode must be electrostatically shielded, e.g. by one grounded shield inside the focusing coil at the faceplate end, and one inside the deflection yoke.

4.4 Polarity of focusing coil

The polarity of the focusing coil should be such that the target end will attract (for 30 mm tubes, repel) a north seeking pole.

4.5 Full size scanning

The full scanning area should always be covered during scan; underscanning of the photoconductive layer or failure to scan, even for a short time, can cause permanent damage.

To prevent the electron beam landing on the target during vertical and horizontal flyback (which would remove some picture information from the target), a blanking pulse must be applied - either a negative pulse to the control grid or a positive pulse to the cathode.

In tubes with a separate mesh construction corner resolution can be improved by applying suitable pulses to grid 3 (*dynamic focusing* or *focus modulation*).

The resolution of most types of photoconductive camera tube increases with increasing voltage on grids 3 and 4. High voltage operation, however, requires increased power for the deflection and focusing coils.

GENERAL

RECOMMENDATIONS

- When the tube is used in a series heater chain, the heater voltage must not exceed 9,5 V (r.m.s.)
 when the supply is switched on. Preferably, each heater should be shunted by a zener diode.
- If cathode-current stabilization is used to stabilize beam current, the cathode heater should be arranged to operate for at least 1 minute before any beam current is drawn.

CAUTION

Camera tubes with photoconductive layers contain toxic compounds. Dispose of them with care. If a tube is broken, take suitable precautions in collecting and disposing of fragments. Avoid direct contact or inhalation of particles.

RATING SYSTEM

(in accordance with IEC Publication 134)

ABSOLUTE MAXIMUM RATING SYSTEM

Absolute maximum ratings are limiting values of operating and environmental conditions applicable to any electronic device of a specified type as defined by its published data, which should not be exceeded under the worst probable conditions.

These values are chosen by the device manufacturer to provide acceptable serviceability of the device, taking no responsibility for equipment variations, environmental variations, and the effects of changes in operating conditions due to variations in the characteristics of the device under consideration and of all other electronic devices in the equipment.

The equipment manufacturer should design so that, initially and throughout life, no absolute maximum value for the intended service is exceeded with any device under the worst probable operating conditions with respect to supply variation, equipment component variation, equipment control adjustment, load variations, signal variation, environmental conditions, and variations in characteristics of the device under consideration and of all other electronic devices in the equipment.

CLASSIFICATION

The devices are classified as follows:

- N = New type. Recommended for new equipment design. Data is derived from development samples, made available for evaluation. It does not necessarily imply that the device will go into regular production.
- D = Design type. Recommended for equipment design; production quantities available at date of publication.
- C = Current type. No longer recommended for equipment design; available for equipment production and for use in existing equipment.
- M = Maintenance type. No longer recommended for equipment production; available for maintenance of existing equipment.
- O = Obsolescent type. Available until present stocks are exhausted.

Obsolescent types of which all stocks are exhausted are called **obsolete**; any data still published on these types is for reference purposes only.

The status of all types is given in the Survey of Plumbicon tubes together with data in condensed form.

SURVEY OF PLUMBICON ® TUBES

Abbreviations used in the tables:

Photoconductive layer

SR = standard resolution cut-off \approx 650 nm HR = high resolution cut-off \approx 650 nm ER = with extended red response, high resolution cut-off \approx 900 nm ER(F) = with extended red response, high resolution and

IR reflecting filter on anti-halation

glass disc cut-off \approx 750 nm

Quality grade

Br = broadcast Ind = industrial Med = medical

Industrial grade (IG) versions of all tube types with broadcast quality are also available. IG types are electrically and mechanically identical to the broadcast quality types, the only difference being the degree of freedom from blemishes on the photoconductive target.

The type number of IG tubes is established by using the first three digits of the corresponding broadcast quality type, followed by a digit which is one higher than that of the broadcast type, e.g.: broadcast type XQ1020, IG type: XQ1021

XQ1427 XQ1428 XQ1505 XQ1506 XQ1523 XQ1524

Applications

B/W = for black and white cameras

L = for luminance channel

R = for red chrominance channel
G = for green chrominance channel
B = for blue chrominance channel

Med = medical; coupled to X-ray image intensifier

Sc = scientific, surveillance; coupled e.g. to image intensifier

Notes (see tables on following pages)

- 1. Without anti-halation glass disc.
- 2. With infrared reflecting filter on anti-halation glass disc.
- 3. Without anti-halation glass disc: add suffix/01 to type number.
- 4. Add suffix/02 for rear loading type, with provisions for adjustable light bias.
- 5. Add suffix/03 for front loading type, with provisions for adjustable light bias.
- 6. Add suffix/05 for rear loading type, without provisions for adjustable light bias.
- ® Registered Trade Mark for television camera tube.

PLUMBICON TUBES - 30 mm (11/4 inch)


Maintenance types 300 mA; (including adapter)

6,3 V

type		photo- quality grade applications	notes
		conductive layer Br Ind Med B/W L R G B Med	
XQ1020		SR ••••	
XQ1021	4.5	SR • • • • •	X 1 2 2
XQ1022		SR -	1
XQ1023		ER •	
XQ1024		ER -	Table 1
XQ1025		ER(F)	2
XQ1026		ER(F)	2
Design types	190 mA; 6,3 V	provision for both fixed and adjustable light biashigh resolution	
XQ1410		HR -	
XQ1413		ER •	
XQ1415		ER(F)	2
Design types	190 mA; 6,3 V	anti-comet-tail electron gun (ACT)provision for both fixed and adjustable light biashigh resolution	
XQ1520		HR -	
XQ1523		ER -	
XQ1525		ER(F)	2
New types	190 mA; 6,3 V	high resolution; "diode" electron gun (DBC)provision for both fixed and adjustable light bias	
XQ3440		HR -	
XQ3443		ER -	
XQ3445		ER(F)	2
Design type	190 mA; 6,3 V	high resolution; "diode" electron gun (DBC)enlarged scanning area	
XQ4502		ER	

GENERAL

PLUMBICON TUBES - 25 mm (1 inch)



Notes on page 12.

PLUMBICON TUBES - 18 mm (2/3 inch)

Design types	95 mA; 6,3 V	
type		photo- quality grade applications conductive layer Br Ind Med B/W L R G B
XQ1427 XQ1428	1	ER SR SR
Current types	95 mA; 6,3 V	o high resolution, "diode" electrode gun (DBC)
XQ2427 XQ2428		ER — — — — — — — — — — — — — — — — — — —
Design types	95 mA; 6,3 V	 high resolution, ''diode'' electrode gun (DBC) low output capacitance (LOC)
XQ3427 XQ3428		ER
Design type	95 mA; 6,3 V	 high resolution, "diode" electron gun (DBC) low output capacitance (LOC) magnetic focusing, electrostatic deflection (MS)
XQ3457		ER HR
Design type	95 mA; 6,3 V	electrostatic focusing
XQ3467		SR ER
New type	55 mA; 9 V	 high resolution, "HS diode" electron gun (DBC) low output capacitance (LOC) electrostatic focusing
XQ4187		HR ER

GENERAL

PLUMBICON TUBES - 14 mm (1/2 inch)

Design types	55 mA; 9 V	 high resolution, "HS diode" electron gun (DBC) low output capacitance (LOC) electrostatic focusing
type	8	photo- quality grade applications conductive layer Br Ind Med B/W L R G B
XQ4087	*	HR — • • • • • • • • • • • • • • • • • •

Accessories for Plumbicon tubes

ന്	30 mm (1¼") dia. all magnetic	dia.	30 mm (1¼") dia. enlarged scan all magnetic			25 mm (1") dia. all magnetic	1") dia. etic		
light bias		ACT DBC and LOC light bias	DBC	/02 versions light bias	/03 versions light bias	ACT and light bias	ACT ACT and and ight bias	DBC light bias LOC	DBC and light bias
	rear loading		front loading	rear loading	front loading	rear loading	front	rear loading	front loading
XQ1410	XQ1520 XQ3440	XQ3440	XQ4502	XQ1070/02 XQ1070/03 XQ1080 XQ1090 XQ3070/02	XQ1070/03	XQ1080	XQ1090	XQ3070/02	XQ2070/03
coil unit colour	AT1130S		AT1107		ATA	AT1116S (front loading) AT1119/01 (rear loading)	front loadi rear loadin	ing) ig)	
coil unit colour	AT1130/*	*.			ATA	AT1116/* (front loading) AT1126/* (rear loading)	front loadi rear loadin	ing) ig)	
56021 56025	56025	56021 56025	56021	26098	86	56026	26	26098	86
light bias lamp	56106			56106	90	56027	27	56106	90
56126▲ 56139▲	56123 56124 56125								2
	56029					56028	28		

^{*} Computer selected triplet, various versions.

▲ Adapter for fixed light bias for XQ1410 series for use in RCA TK47 camera.

^{**} Adapters for fixed light bias for XQ1410 series and XQ1520.

A Adapter for adjustable light bias for XQ1410 series for use in Marconi Mark VIII camera (variant).

Accessories for Plumbicon tubes (continued)

14 mm (½") dia. electrostatic focusing	HS DBC LOC	front loading	XQ4087	AT1120S	AT1120T		1	1
18 mm (2/3") dia. electrostatic focusing	HS DBC LOC	front loading	XQ4187	KV4736AS	KV4736AT*	1	1	56030
		front lo	X03467	KV4780	3 × KV4780	56604	1	56033
18 mm (2/3") dia. MS	DBC	front loading	X03457	KV4722	3 × KV4722	56601	I	I
18 mm (2/3") dia. all magnetic	DBC	rear loading	XQ3427	AT1109/01S	AT1109/*	946	1	56030
18 mm (2/3" all magnetic	DBC	rear lo	XQ2427	AT11	AT1109/*	56049		56033
			example	coil unit B/W	coil unit colour AT1109/* AT1109/*	socket	light bias lamp	mask

* Computer selected triplet, various versions.

GENERAL OPERATIONAL NOTES

1 Properties of the lead oxide photoconductive layer

The Plumbicon tube has a lead oxide photoconductive layer. In tubes with extended red response a small amount of sulphur is added to the lead oxide.

1.1 Sensitivity

Since the Plumbicon tube has a linear light transfer characteristic, its sensitivity can be specified completely by the number of μ A/lumen delivered to the signal electrode. A typical value for a standard layer (without extended red response) in tungsten light with a colour temperature of 2856 K would be 400 μ A/lumen (d.c. value).

Sensitivity increases with target voltage, but at the recommended voltage (45 V) it is almost at maximum and rises only slightly with further voltage increases.

For a given target illumination, the signal current is a function of the scanned area; but it can be shown that in the Plumbicon tube with its linear light transfer characteristic, camera sensitivity is independent of tube size for the same depth of field and viewing angle.

1.2 Spectral response

Figure 1 shows typical spectral response curves of some 30 mm Plumbicon tubes. Curve 1 relates to the high resolution layer used, for example, in the XQ1410; curve 2 relates to the extended-red layer as used in the XQ1413.

Because the sensitivity of the XQ1413 is high in the deep red region, an infrared reflecting filter should be used for proper colour rendition. The XQ1415, whose spectral response is given by curve 3, already has such a filter provided with the anti-halation disc cemented to its faceplate (see 1.5 below).




Fig. 1 Typical spectral response curves of 30 mm Plumbicon tubes.

1-inch Plumbicon tubes with extended red sensitivity, such as the XQ1073 and the XQ1083, have somewhat lower red and deep red sensitivities due to a smaller amount of sulphur in the photoconductive layer. For correction of the colour response therefore less filtering is needed. The Plumbicon tube types XQ1075 and XQ1085 are provided with the appropriate infrared reflecting filter.

1. 3 Resolution

The resolution of the extended-red layer is higher than that of the standard layer, which is used, for example, in the XQ1020. A high resolution layer without extended-red response has been developed, which closely approaches the resolution of the extended-red layer.

Figure 2 shows typical modulation transfer characteristics of some Plumbicon tubes, measured in green light, as a function of the number of line pairs per mm.




Fig. 2 Typical square-wave modulation transfer curves of some Plumbicon tubes.

The vertical lines in the figure correspond to $400 \, \text{TV}$ lines for $30 \, \text{mm}$ (15,6 lp/mm), 1-inch (20,8 lp/mm) and 2/3-inch (30,3 lp/mm) tubes. It can be seen that at $400 \, \text{TV}$ lines (5 MHz) resolution increases with increasing tube size (increased scanning area). For a given number of line pairs per mm the smallest tube has the highest resolution.

The XQ1020 has a standard layer, the XQ1415 and the XQ1427 have extended-red layers the XQ1410, XQ1080 and XQ1500 have high resolution layers. Due to a special gun construction the XQ1500 has an appreciably higher resolution than the XQ1080.

1.4 Lag

The photoconductive lag of the lead oxide layer is practically negligible. Due to the fact that the photoconductive layer in the tubes is relatively thick (10 to 18 μ m, depending on tube type), Plumbicon tubes show very little discharge lag at normal signal currents.

Discharge lag becomes evident under low key conditions, when signal currents are small. This type of lag depends on layer capacitance and beam resistance. The effective beam resistance is decreased by applying light bias and thereby the discharge lag is reduced. Figure 3 shows an example of the effect of light bias on discharge lag (30 mm Plumbicon tube type XQ1410, signal current of 40 nA, green light, beam setting 600 nA).




Fig. 3 Typical influence of light bias on decay lag in XQ1410.

In some types of Plumbicon tubes means are available for applying light bias on the gun side of the photoconductive layer (internal light bias). Figure 4 shows how this is achieved in the 30 mm Plumbicon tube XO1410.




Fig. 4 Light bias in the XQ1410.

Light from a small lamp falls on the pumping stem of the tube and is conveyed by a forked glass light pipe into the collector space. It then falls directly or via reflection against the collector wall on the target. The light source (fixed or adjustable) fits in a metal sleeve fixed on the pumping stem.

1.4.1 Considerations

1.4.1.1 WITH ADJUSTABLE LIGHT BIAS (VIA PUMPING STEM)

For this purpose a light bias lamp, type 56106, is available.

Amount of light bias

Black and white cameras

The amount of light bias required in a black/white camera is not critical (see published data) and may be 3 to 5 nA(p) the upper limit being determined by the onset of objectionable black shading.

Colour cameras without black shading compensation circuitry

Depending on the type of camera and the subjective judgement of the camera engineer, the light bias should generally be set to 3 nA(p) for R, 2 nA(p) for G, and 3.5 nA(p) for B tubes respectively.

A suggested procedure is as follows:

The camera is focused onto a metronome, placed in front of a dark background, and carrying a small white square, which produces a peak output current in the green channel of, for instance, 30 nA. About 2 nA(p) of light bias is applied to the green tube by adjusting the current through its lamp. Subsequently the currents through the light bias lamps of the R and B tubes are adjusted for the best compromise with respect to build-up and decay lag aiming at non-coloured lag phenomena as observed on a colour monitor. Infrared light with a wavelength > 600 nm should be avoided.

Colour cameras with black shading compensation circuitry

In colour cameras with black shading compensation still higher bias currents, and hence better lag performance, can be achieved.

1.4.1.2 WITH FIXED LIGHT BIAS

Also available for 30 mm tubes is an adapter for fixed light bias operation. The adapter carries a colour code in accordance with the application for which the tube is intended. The adapter is slipped over the pins of the tube before putting on the socket (see drawing) and connects a light bias lamp via a series resistor to the heater pins.

The light bias induced dark currents (at $6,30 \pm 0,05 \text{ V}$) will be approximately:

4.5 nA(p) for B/W tubes

3 nA(p) for R tubes

2 nA(p) for G. L tubes

3,5 nA(p) for B tubes

whereas an extra 95 mA (approx.) will be drawn from the heater supply.

Provided the heater voltage supply is capable of delivering a well stabilized voltage when these extra lamp currents are drawn, the tubes XQ1410, XQ1413, and XQ1415 — operated with the adapter — can be considered as plug-in replacements for standard tubes, however, with clearly improved lag (and resolution).

Optimum performance with repsect to non-coloured lag phenomena is obtained only when adjustable light bias is applied.

1.4.1.3 WITH LIGHT BIAS (FIXED OR ADJUSTABLE) APPLIED VIA THE OPTICAL SYSTEM

Though excellent performance with respect to speed of response can be obtained it appears to be difficult to produce sufficient uniformity of the light bias induced dark currents and, in a colour camera, to adjust the light bias per tube for neutral i.e. non-coloured lag phenomena, when televising moving objects.

1.4.1.4 WITHOUT LIGHT BIAS

Acceptable performance with respect to speed of response will only be achieved with adequate scene illumination.

The envelopes of the tubes are blackened underneath the plastic base to prevent direct transfer from light bias — if this is applied to the pumping stem — through the envelope to the target, which would cause objectionable peak white shading (often referred to as 'ears') on the black level in the picture corners. This blackening, however, also absorbs the light emitted by the heater of the cathode, light which in tubes like XQ1020 induces some artificial dark current. This absence of heater light causes a slightly increased beam discharge lag in tubes XQ1410, XQ1413, and XQ1415.

REMARK

The life expectancy of the lamps used in 56106 and the adapter is, as stated by the manufacturer, $> 2 \times 10^4$ h at full rating, i.e. 5,5 V, 110 mA, and they will therefore generally outlive the camera tubes. Spares and replacements can be supplied.




Fig. 5.

adapter for R tubes	56123	9390 270 10XX00
G, L tubes	56124	9390 270 20XX00
B tubes	56125	9390 270 30XX00

1.4.1.5 INSTRUCTIONS FOR USE OF LIGHT BIAS LAMP TYPE 56106

Light bias lamp type 56106 is intended for use with those Plumbicon tubes that have a thin metal tube (provided with a filter) cemented to the pumping stem, e.g. XQ1410 series.

INSTALLING THE LAMP

Using the XQ1410 series as an example, the following installation procedure is recommended (Fig. 5).

- 1. Insert tube A into the deflection/focusing assembly.
- 2. Push lamp B firmly into the metal tube on the pumping stem.
- 3. Mate socket C with the base pins of the tube, allowing the lamp wires to pass through the pumping stem clearance hole in the socket.




Fig. 6 Installing the light bias lamp.

SUPPLYING THE LAMP

Black/white cameras

Extreme stability is generally not needed. Lamp current can be supplied from a.c. or d.c. sources. Figure 7 shows suggested circuits.




Fig. 7 Supplying the lamp in black/white cameras.

The values of R2 and R4 should limit the lamp current to its maximum value of 110 mA at 5 V. Thus:

$$\frac{R1\ R2}{R1+R2} = \frac{V-5}{0.11}\ \Omega$$
, and $R4 = \frac{V-5}{0.11}\ \Omega$.

When fully in series with the lamp, resistors R1 and R3 should decrease the lamp current to a value which causes negligible bias light, e.g. 50 mA. Thus:

$$R1_{min} = \frac{V}{0.05} \Omega$$
, and $R3_{min} = \frac{V}{0.05} - R4 \Omega$.

Colour cameras

A stabilized d.c. supply is preferred. In cameras with automatic black level compensation, the circuits shown in Fig. 7 may be used. For long-term stability in cameras not having black level compensation, it should be noted that the bias current, set at about $10\,\text{nA}$, changes by $0.5\,\text{nA}$ when the voltage across the lamp changes by about $50\,\text{mV}$, and also when the current through the lamp changes by about $0.6\,\text{mA}$.

Figure 8 shows a recommended circuit. The maximum voltage on the base of the transistor should be about 5,5 V.




Fig. 8 Supplying the lamp in colour cameras.

1.5 Stray light

The reflectance of the target is not negligible. It is at its highest in the red part of the spectral range. Diffusely reflected light can be caught in the faceplate of the tube and cause stray light, 'halation'. To reduce this, an anti-halation glass disc is cemented on the faceplate, see Fig. 9.




Fig. 9 Anti-halation disc on faceplate.

Further reduction of stray light can be obtained by fitting a mask on the anti-halation disc with an aperture slightly larger than the used scanning area.

1.6 The anti-comet-tail gun

The transfer characteristic of a Plumbicon tube is linear up to a point determined by the available beam current. This restricts its dynamic range. Local highlight levels on the target may cause blooming due to beam-bending and, in extreme cases, loss of stabilization. As it takes a number of scannings to re-establish stabilization when an extreme highlight has moved away, 'comet tails' can occur behind a moving object.

The anti-comet-tail (ACT) gun was developed to reduce these effects. In a tube with such a gun the beam current is strongly increased during line flyback, and most of the re-charging of the target element capacitors in the areas of extreme highlight occurs in the flyback period. Figure 10 shows the principle of an ACT gun.




Fig. 10 Anti-comet-tail (ACT) gun; a = read-out mode; b = flyback mode.

The first anode - see Fig. 10 - has been split into two parts, the anode g_2 and the limiter g_4 , which are electrically connected. An additional electrode g_3 has been placed between these parts. During the normal read-out scan this extra grid is maintained at a potential close to that of g_2 and g_4 . The scanning beam will then be in focus at the target, as shown in Fig. 10a.

During line flyback a negative-going pulse is applied to g_3 to focus the scanning beam on the aperture in the limiter g_4 , as shown in Fig. 10b. At the same time the beam current is strongly increased by a positive-going pulse on g_1 . Thirdly, a positive-going pulse is applied to the cathode so that it is at a positive potential (e.g. + 8 V) during flyback.


In this way a defocused beam carrying a large current (e.g. $\approx 100~\mu A)$ scans the surface of the photoconductive layer during line flyback. This beam contains sufficient current to recharge the areas of extreme highlights; it brings the surface here to cathode potential during flyback. Potential levels below this contain picture information and are not influenced. Consequently, during normal read-out, the scanning beam does not encounter target potentials higher than the cathode potential during flyback. Therefore stabilization is possible everywhere and blooming and comet-tails are strongly reduced.

1.7 The diode gun and Dynamic Beam Control (DBC)

In the conventional triode gun, grid 1 and the anode converge the electrons emitted by the cathode to produce a crossover in the electron beam. Electron interaction in the beam, particularly in the vicinity of the crossover, increases the differential beam resistance and so increases beam-discharge lag. In the diode gun grid 1 is made positive relative to the cathode. This reduces beam convergence and so eliminates the crossover. The result is reduced differential beam resistance and a larger beam reserve. The consequent reduction in lag permits the use of thinner photoconductive layers to improve resolution (particularly in smaller tubes used in portable cameras for outside broadcasts etc.).

Moreover, with the larger beam reserve of the diode gun tube, excessive highlights can be handled using $Dynamic\ Beam\ Control\ (DBC)$. Figure 11 shows the principle of DBC. When the beam encounters a highlight, the sharp rise in signal current is detected by a feedback network which then increases the control grid voltage (V_{01}) , so raising the beam current to read out the highlight.

N.B. Avoid continuous operation at high beam currents since this will shorten tube life.



1.8 Low output-capacitance tubes

An important factor governing the performance of a TV camera is its signal-to-noise (S/N) ratio; the higher the S/N ratio the better the operational sensitivity of the camera. One way of increasing the S/N ratio is by reducing the total output capacitance of the tube/yoke assemblies within the camera.

In the range of low output-capacitance (LOC) Plumbicon tubes the capacitance of the tube in the deflection yoke is reduced by reducing the size on the transparent conductive film in the target.

1.9 Burn-in or picture sticking

The target of a Plumbicon tube has a high resistance to picture sticking but some sticking may occur at target voltages lower than specified.

1.10 Temperature effects

Plumbicon tubes tolerate short excursions of temperature up to 70 °C. Prolonged use at temperatures above 50 °C will, however, adversely influence tube life. It is therefore advisable to ensure that the faceplate temperature of a Plumbicon tube in a television camera does not exceed 50 °C under normal ambient temperature conditions.

2 RECOMMENDATIONS

- 2. 1 During transport, handling and storage the axis of the Plumbicon tube must be either vertical, with faceplate up, or horizontal. The faceplate should be covered with the hood provided.
- 2. 2 To avoid damage to the base pins, the Plumbicon tube should be inserted into its socket with care. Shocks, excessive force and bending loads on the pins are to be avoided.
- 2. 3 During prolonged idle periods days or weeks gas pressure may slowly build up in the tube due to residual gas molecules emerging from the electrodes and the glass wall. There is then a slight risk that the pressure is sufficiently high to cause cathode damage by ion bombardment if cathode current is drawn immediately after switching on the camera.

A cathode heating time of at least a minute before drawing cathode current is therefore recommended. After very long idle periods - e.g. months - it is advisable to extend this pre-heating time to 30 minutes.

- 2. 4 In isolated cases the properties of a Plumbicon tube may deteriorate slightly when it is kept idle for long periods such as may occur:
- between the factory's pre-shipment test and the actual delivery to the customer;
- between receipt of the tube and its installation;
- when the camera is not used for a long time.

Although the chances of such a deterioration are remote it is advisable to operate the tube for some hours at intervals not more than 4 weeks apart.

The following procedure and conditions are recommended then:

- Set grid g₁, bias control, to maximum negative bias (beam cut-off).
- Allow a heating-up time of the cathode of at least 1 minute before turning up the grid g₁ control
 to produce a beam.
- Set scanning amplitudes to overscan condition.
- Apply an even illumination to the target to obtain a signal of approximately 0,15 μA and adjust the beam current for correct stabilization.
- 2. 5 During long-term storage the ambient temperature should not exceed 30 °C.
- 2. 6 The light transfer characteristic of the Plumbicon tube has a gamma near unity. It may be desirable to incorporate a gamma correcting circuit in the video amplifier system with an adjustable gamma of 0,5 to 1.
- 2. 7 Plumbicon tubes do not permit automatic sensitivity control by means of regulation of the signal electrode voltage. Adequate control is therefore to be achieved by other means (iris control and neutral density filters).
- 2. 8 The beam current of a Plumbicon tube without an ACT gun is usually set at twice the value required for stabilization of normal peak white. Highlight handling is improved by using higher beam currents. Very high beam currents, however, cause increased lag, some loss of resolution, geometry shifts and reduction of tube life.

GENERAL

2.9 Alignment currents are used to correct for slight mechanical and electrical misalignments encountered in tubes and coil assemblies.

Alteration of alignment settings influences corner focus, geometry, beam size and registration. Poor alignment can moreover cause lag problems or a degradation of picture quality with regard to spots and blemishes.

- 2.10 During long standby periods, the following procedure should be adopted:
- · Cap the camera lens.
- Adjust the grid 1 voltage to its maximum negative value to cut off the beam.
- Reduce the heater voltage to about 4 V.

To resume normal operation, reverse the above sequence as follows:

- Increase heater voltage to 6,3 V.
- After allowing heater to operate at 6,3 V for at least 1 minute, adjust the grid 1 voltage to restore
 the beam current to its required level.
- Uncap the camera lens.

TEST SPECIFICATION FOR PLUMBICON® TUBES

(with plain glass faceplate)

SECTION A

Test conditions

All tests on Plumbicon tubes are carried out in the manufacturer's test channel under the following conditions:

1. Light source: 2856 K colour temperature

(broadcast and industrial tubes);

P20 light distribution

(tubes for medical X-ray equipment).

2. Filter:

For chrominance tubes colour filters are inserted in the light path:

for R tubes: Schott OG570, thickness 3 mm for G tubes: Schott VG9, thickness 1 mm for B tubes: Schott BG12, thickness 3 mm

For tubes with extended red response but without an infrared reflecting filter on the anti-halation glass disc an additional infrared reflecting filter is inserted in the light path. The filter used is Balzers Calflex B1/K1.

For X-ray tubes: Schott VG9, thickness 1 mm For transmission of the filters see Figs 4 and 5.

Test transparency, back-illuminated, projected onto the target by means of a high quality lens, producing an even illumination on the specified scanned area.

The test transparency has an aspect ratio of 3:4 for the evaluation of broadcast and industrial quality tubes. The area of the chart is divided into three quality zones by two concentric circles as shown in Fig. 1.




Fig. 1.

A circular test transparency is used for the evaluation of tubes for medical X-ray equipment. The area of the chart is divided into three quality zones by two concentric circles as shown in Fig. 2.




Fig. 2.

- 4. The video amplifier frequency response is essentially flat up to 5 MHz, with a sharp fall-off to 6 MHz.
- 5. No gamma correction or aperture correction are applied in the video amplifier.
- The light level on the Plumbicon tube target is adjusted to produce a peak signal current I_s in accordance with Table 1.
- ® Registered Trade Mark for television camera tube.

GENERAL

- 7. The electrical settings of the tube are in accordance with its published data and the "Instructions for use".
- The beam current of the Plumbicon tube is adjusted to just stabilize a peak signal current of magnitude I_b in accordance with Table 1.
- 9. Monitor. The obtained picture is observed on a monitor producing a non-blooming white.

Table I I _s and I _b settings	tube diameter		mm inch)	25 mm (1 inch)		18 mm (2/3 inch)		14 mm (½ inch)		
	scanned area	12,8 mm	12,8 mm x 17,1 mm		9,6 mm x 12,8 mm		6,6 mm x 8,8 mm		4,8 mm x 6,4 mm	
		I _s μA	Ι _b μΑ	I _s μA	Ι _b μΑ	Ι _s μΑ	l _b μΑ	Ι _s μΑ	Ι _b μΑ	
broadcast quality tubes	luminance	0,30	0,60	0,2	0,4	0,15	0,30	0,10	0,20	
	black & white	0,30	0,60	0,2	0,4	0,15	0,30	0,10	0,20	
	red R	0,15	0,30	0,1	0,2	0,075	0,15	0,05	0,10	
	green G	0,30	0,60	0,2	0,4	0,15	0,30	0,10	0,20	
	blue B	0,15	0,30	0,1	0,2	0,075	0,15	0,05	0,10	
Last	black & white	0,30	0,60	0,2	0,4	0,15	0,30	0,10	0,20	
industrial	red R	0,15	0,30	0,1	0,2	0,075	0,17	0,05	0,10	
tubes	green G	0,30	0,60	0,2	0,4	0,15	0,30	0,10	0,20	
	blue B	0,15	0,30	0,1	0,2	0,075	0,15	0,05	0,10	
X-ray medical	P20 light source		scanned area* 18 mm dia.		d area* 2 mm dia.				ter 30 mm * 26 mm dia.	
tubes**		0,15	0,30	0,1	0,2		I _s = 0,4	I _b = 0,8		

^{*} Scanning amplitude controls adjusted such that the circular quality area of the target is displayed on a standard monitor as a circular area with a diameter equal to the raster height.

SECTION B

Spurious signal specification.

Blemishes. Both spots (sharply defined) and smudges (with vague contours) are termed blemishes. Blemishes are small areas producing uneven modulation of any signal current between black level (black current) and white level (peak signal current).

^{**} For use in combination with X-ray image intensifier.

SECTION C

Broadcast quality tubes

The degrading effect caused by a blemish on the quality of the picture as observed on the monitor is expressed in its Spot Nuisance Value (S.N.V.).

The S.N.V. of a blemish is basically defined as the product of its size (measured in % of the picture height, with a special test transparency) and its contrast (or modulation depth) in % of the peak signal current produced by the circular area of the target, having a diameter of 5% of the picture height, which encircles this blemish.

The contrast is measured on a waveform oscilloscope provided with a line selector.

Tables II show which blemishes are to be neglected, because of their small size or contrast, and how the actual S.N.V. is determined per type of tube for dark and white blemishes (see also the addendum to this section).

Tables III define the maximum number of blemishes and the maximum sum of S.N.V.s per tube type, per zone, and the total which are allowed.

Tubes with 30 mm, 25 mm diameter or 18 mm diameter

notes

4

5

able II		Black and white Luminance L Green G	Red R	Blue B
To be neglected	size	≤ 0,2%	≤0,2%	≤ 0,2%
	contrast	≤ 5%	≤8%	≤8%
S.N.V. of	white blemish	2 x M.V.	1,,	M.V.
S.IV. V. OT	dark blemish	1 x M.V.	1 X	IVI. V .
Max. S.N.V.	per blemish	20	20	20

Т	a	h	le	1	I	ī	
	u	v		۰	۰		

	bl/v	wh, L,	G, R		=1	I	3	
Zone	1	П	Ш	tot.	1	11	111	tot.
Max. number	0	2	3	4	1	3	4	6
Max. sum of S.N.V.	0	30	50	60	20	45	80	90

Tubes with 14 mm diameter


able II		Black and white Green G	Red R	Blue B
To be neglected	size	≤ 0,2%	≤ 0,2%	≤ 0,2%
	contrast	≤ 6%	≤ 8%	≤ 10%
S.N.V. of	white blemish	2 x M.V.	1.0	M.V.
5.IV. V. OT	dark blemish	1 x M.V.	I X IVI. V.	
Max. S.N.V.	per blemish	20	20	20

Notes see next page.

able III	Black and white Green G		Red		R Blue		ie	B		note 4			
Zone	1	Ш	Ш	tot.	- 1	11 -	Ш	tot.	. 1.	Ш	111	tot.	
Max. number	1	2	3	4	1	3	4	6	2	4	6	8	
Max. sum of S.N.V.	10	30	50	60	15	45	80	100	20	50	90	110	5

ADDENDUM

Black blemishes with a white surrounding and white blemishes with a black core. On the oscilloscope the general shape of such a blemish will be as shown in Fig. 3.



A blemish shall be considered to be a white blemish if a ≥ b (S.N.V. = a x d or 2 x a x d in accordance with Table II) or a black blemish if b > a (S.N.V. = $b \times d$).

Notes

- 1. No blemishes > 0,2% shall be visible when the lens is capped.
- 2. Blemishes of this size are not counted unless their concentration causes a smudged appearance. Such concentrations are evaluated as blemishes and as contrast, the average contrast of the concentration
- 3. M.V. = measured value (size x contrast).
- 4. The minimum distance as measured in any direction between any two blemishes with S.N.V. ≥ 10 shall be 5% of picture height.
- 5. Arithmetic sum individual S.N.V.s.

SECTION D

notes

2

3

Industrial quality tubes

otes 1

Number, size, and location of blemishes allowed.

Dimensions of blemishes		Permitted number of blemishes						
in % of picture height	Zone I	Zone II	Zone III	Total				
≤ 2% but > 1%				75.				
≤ 1% but > 0,7%	0	1	2	2				
≤ 0,7% but > 0,45%	1	2	4	4				
≤ 0,45% but > 0,2%	2	4	6	6				
≤ 0,2%								
Total permitted number of blemishes	2	4	6	6				

Notes

- Blemishes with contrast ≤ 10% shall not be counted.
- 2. Blemishes of these dimensions are not allowed when their contrast exceeds 20%.
- Blemishes of this size are not counted unless their concentration causes a smudged appearance. Such concentrations are evaluated as blemishes and as contrast, the average contrast of the concentration is taken.
- 4. The distance between any two blemishes with dimensions > 0,45% shall be greater than 5% of picture height as measured in any direction.

SECTION E

Tubes for medical X-ray equipment

Number, size, and location of blemishes allowed.

1

Dimensions of blemishes	Permitted number of blemishes						
in % of picture height	Zone I	Zone II	Zone III				
> 0,7%	0	0	0				
≤ 0,7% but > 0,45%	0	1	3				
≤ 0,45% but > 0,2%	2	3	6				
≤ 0,2%							
Total permitted number of blemishes	2		6				

•

Notes

- 1. Blemishes with contrast \leq 6% (if black) and \leq 3% (if white) are neglected.
- Blemishes of this size are not counted unless their concentration causes a smudged appearance. Such concentrations are evaluated as blemishes and as contrast, the average contrast of the concentration is taken.

SECTION F

Sensitivity

The luminous sensitivity is measured under the following conditions:

Light source: colour temperature 2856 K.

Filter: Appropriate filter inserted in the light path.

The illuminance level of the white light at the faceplate or for chrominance tubes before the filter is adjusted to 4,54 lx.

For 30 mm tubes the luminous flux at the scanned area on the faceplate or before the filter is now 1 mlm. In this case the measured signal current in nA gives directly the sensitivity in μ A/Im(F). For 30 mm tubes with enlarged scanning the signal current readings should be multiplied by 0,67 to give the sensitivity in μ A/Im(F).

For 25 mm tubes the signal current reading should be multiplied by 1,8.

For 18 mm tubes the signal current reading should be multiplied by 3,8.

For 14 mm tubes the signal current reading should be multiplied by 7,1.

SECTION G

Resolution

 $Resolution \ is \ measured \ with \ a \ 50 \ mm \ Leitz \ Summicron \ lens \ having \ a \ sine \ response \ of \ approximately:$

85% at 400 TV lines at f: 5,6 for 30 mm and 25 mm tubes; 80% at 400 TV lines at f: 5,6 for 18 mm tubes;

80% at 320 TV lines at f : 5.6 for 14 mm tubes.

The resolution is measured with the appropriate colour filter inserted in the light path as described in section A. However, for 18 mm and 14 mm tubes a BG12 filter with a thickness of 1 mm is used for the blue tubes.

The beam current and signal current are to be adjusted as indicated in the relevant tube data. tube. The horizontal amplitude response can be raised by the application of suitable correction circuits.

SECTION H

Lag

Lag is measured with the appropriate colour filters inserted in the light path. Beam current and signal current are to be adjusted as indicated in the relevant tube data.

Build-up lag is measured after a minimum of 10 s of darkness. The figures are typical percentages of the ultimate signal current obtained 60 ms and 200 ms respectively after introduction of the illuminance.

Decay lag is measured after a minimum of 5 s of illumination on the target. The figures represent typical residual signals in percentages of the original signal current, 60 ms and 200 ms respectively after removal of the illuminance.




Fig. 4 Transmission of filters BG12, VG9 and OG570.




Fig. 5 Typical transmission curve of heat reflecting interference filter CALFLEX B1/K1.

30 mm dia. PLUMBICON TUBES

CAMERA TUBES

30 mm (1,2 in) diameter Plumbicon $^{\circledR}$ television camera tubes, with standard resolution lead-oxide photoconductive target, for use in high quality monochrome or colour cameras for broadcast, educational or industrial applications.

The XQ1020 series comprises the following versions:

XQ1020	for use in monochrome cameras
XQ1020L	for use in the luminance channel of colour cameras
XQ1020R	for use in the red channel
XQ1020G	for use in the green channel
XQ1020B	for use in the blue channel
XQ1023R	for use in the red channel; extended red response
XQ1025	for use in monochrome cameras, provided with IR filter
XQ1025L	for use in the luminance channel of colour cameras
XQ1025R	for use in the red channel; extended red response and IR filter
XQ1021	as XQ1020 series; only difference being the degree of freedom from blemishes on
	the target (industrial quality tubes)
XQ1024	as XQ1023. Industrial grade
XQ1026	as XQ1025. Industrial grade

QUICK REFERENCE DATA

Diameter		30	mm (1,2 inch)
Length	approx.		mm
Provided with anti-halation glass disc			
Focusing	magnetic		
Deflection	magnetic		
Useful target area (scanning area)	12,8 x	17,1	mm
Spectral response			
max. at	approx.	500	nm
cut-off: XQ1020	approx.	650	nm
XQ1023	approx.	850	to 950 nm
XQ1025	approx.	750	nm
Sensitivity			
XQ1020, XQ1020L	typ.	400	μA/Im
XQ1020R	typ.	80	μA/ImF
XQ1020G	typ.	165	μA/ImF
XQ1020B	typ.	38	μA/ImF
XQ1025, XQ1025L	typ.	435	μ A/Im
XQ1023R, XQ1025R	typ.	130	μA/ImF
Resolution at 400 TV lines (5 MHz)			
XQ1020, XQ1020L	typ.	40	%
XQ1020R	typ.	35	%
XQ1020G	typ.	40	%
XQ1020B	typ.	50	%
XQ1025, XQ1025L	typ.	55	%
XQ1023R, XQ1025R	typ.	55	%
Heater		6,3	V, 190 mA

[®] Registered trademark for television camera tubes.

XQ1020 SERIES

OPTICAL DATA

Quality rectangle on

photoconductive target (aspect ratio 3:4)

12,8 x 17,1 mm

Orientation of image on target:

For correct orientation of the image on the target the vertical scan should be essentially parallel to the plane passing through the tube axis and the marker line on the protecting sleeve at the base

Faceplate

Thickness 1,2 \pm 0,1 mm Refractive index n = 1,49

Anti-halation glass disc provided with

anti-reflective coating

Thickness $6 \pm 0.2 \text{ mm}$ Refractive index n = 1.52

XQ1025, R, L are provided with infrared reflecting filter

ACCESSORIES

Socket type 56021 or 56603

Deflection and focusing coil unit:

Black/white type AT1130S
Colour type AT1130T
Mask for flare reduction type 56029

ELECTRICAL DATA

Deflection magnetic

Focusing magnetic

Heating, indirect by a.c. or d.c.; parallel supply
Heater voltage

The heater voltage must not exceed an

r.m.s. value of 9,5 V. For optimum

performance (lifetime and registration stability) stabilization of the heater voltage is recommended.

Capacitance

Signal electrode to all C_{as} 3 to 6 pF

This capacitance, which is effectively the output impedance, increases when the tube is inserted in

the coil unit.

LIMITING VALUES (Absolute maximum rating system	n)			notes
Unless otherwise stated, all voltages are referred to the				
Signal electrode voltage	Vas	max.	50 V	
Grid 4 voltage	V _{g4}		100 V	
Grid 3 voltage	V _{g3}		800 V	
Voltage between grid 4 and grid 3	Vg4/g3		350 V	
Grid 2 voltage	$V_{g2}^{g4/g5}$	max.	350 V	
Grid 1 voltage				
positive	V_{g1}	max.	0 V	
negative	$-v_{g1}$	max.	125 V	
Cathode heating time before drawing				
cathode current	th	min.	1 min	
Cathode to heater voltage				
positive peak	Vkfp	max.	50 V	
negative peak	$-V_{kfp}$	max.	50 V	
Ambient temperature, storage and operation	Tamb	max.	50 °C	
		min. max.	-30 °C	
Faceplate temperature, storage and operation	T		-30 °C	1
Faceplate illuminance	E		500 lx	2
	_	IIIax.	300 IX	
OPERATING CONDITIONS				
For a scanned area of 12,8 x 17,1 mm				3
Cathode voltage	V_k		0 V	
Signal electrode voltage	Vas		45 V	
Beam current	Ь			4
Grid 4 voltage	V_{g4}		675 V	
Grid 3 voltage	V_{g3}		600 V	
Grid 1 voltage	V _{g2}		300 V	
Grid 1 voltage	V _{g1}	50	V	4
Blanking voltage on grid 1, peak to peak Blanking voltage on cathode	Vg1p-p	50	± 10 V	
Faceplate illuminance	V _{kp-p}	0.44	25 V	5
Faceplate temperature	T		0 10 lx	5
acepiate temperature	1	20 10	3 45 0	
ELECTRON GUN CHARACTERISTICS				
Cut off				
Grid 1 voltage for cut-off at V _{g2} = 300 V,				
without blanking	V_{g1}	-30 to -	100 V	
Blanking voltage, peak to peak	3			
on grid 1	V_{g1p-p}	50 =	± 10 V	
on cathode	V_{kp-p}		25 V	
Grid 2 current at normally required				
beam currents	l _{g2}	\leq	1 mA	

XQ1020 SERIES

PERFORMANCE						notes
Dark current	ld		\leq	3	nA	
Sensitivity at colour temperature of illuminance = 2856	K					
XQ1020, XQ1020L	min.	375	typ.	400	$\mu A/Im$	6
XQ1020R	min.	70	typ.	80	μA/ImF	
XQ1020G	min.	130	typ.	165	$\mu A/ImF$	
XQ1020B	min.	35	typ.	38	μA/ImF	
XQ1025, XQ1025L	min.	390	typ.	435	$\mu A/Im$	
XQ1023R, XQ1025R	min.	120	typ.	130	$\mu A/ImF$	
Gamma of transfer characteristics			$0,95 \pm$	0,05		
Spectral response, max. at	approx.			500	nm	
Spectral response, cut-off at	approx.		650 to	950	nm	

Resolution

see Figs 1, 2 and 3

Modulation depth, i.e. uncompensated amplitude response at 400 TV lines at the centre of the picture.

	XQ1020L XQ1020G	XQ1020R	XQ1020B	XQ1025 XQ1025L	XQ1023R XQ1025R	
Highlight signal current I _s Beam current I _b Modulation depth at 400 TV lines	300 600	150 300	150 300	300 600	150 300	nA nA
typ.	40	35	50	55	55	%
min.	35	30	45	45	45	%

Modulation transfer characteristics: see Fig. 4

Lag (typical values)

Spectral response curves

8


7


Light source with a colour temperature of 2856 K. Appropriate filter inserted in the light path for the chrominance tubes R, G and B.


LOW KEY CONDITIONS (without light bias)

	build-up lag I _S /I _b = 20/300 nA		decay lag		
	60 ms	200 ms	60 ms	200 ms	
XQ1020, L, G	95%	≈ 100%	10%	3,5%	
XQ1020R	85%	≈ 100%	12%	4%	
XQ1020B	70%	≈ 100%	15%	5%	
XQ1025L	80%	≈ 100%	15%	4%	
XQ1023R, XQ1025R	75%	≈ 100%	16%	5%	

MECHANICAL DATA








Mounting position: any

Net mass: ≈ 100 g



- (*) Distance between axis of anti-halation glass disc and geometrical centre of signal electrode ring, measured in plane of faceplate: max. 0,2 mm. Total glass thickness: 7,2 ± 0,2 mm; n = 1,5.
- (1) The base passes a flat gauge with a centre hole with a diameter of 8,230 ± 0,005 mm and holes for passing the pins with the following diameters: 7 holes of 1,690 ± 0,005 mm and one hole of 2,950 ± 0,005 mm. The holes may deviate max. 0,01 mm from their true geometrical position. Thickness of gauge: 7 mm.
- (2) The ends of the pins are tapered and/or rounded but not brought to a sharp point.

XQ1020 SERIES

NOTES, see also General Section.

- 1. The tube can withstand short excursions up to 70 °C without any damage or irreversible degradation in performance.
- 2. For short intervals. During storage the tube face shall be covered with the plastic hood provided; when the camera is idle the lens shall be capped, in stand-by also the beam will be cut-off.
- The operating conditions and performance data quoted relate to operation of the tube in coil unit AT1130. See relevant data of deflection/focusing assemblies.
- The beam current I_b, as obtained by adjusting the control grid (grid 1) voltage is set to 300 nA for R and B tubes, 600 nA for black and white, L and G tubes.

 $l_{\rm b}$ is not the actual current available in the scanning beam, but is defined as the maximum amount of signal current, $l_{\rm s}$, that can be obtained with this beam.

In the performance figures, for lag, the signal current and beam current conditions are given, e.g. as $I_s/I_b = 20/300$ nA. This means: with a signal current of 20 nA and a beam setting which just allows a signal current of 300 nA.

- N.B. The signal currents are measured with an integrating instrument connected in the signal electrode lead and a uniform illumination on the scanned area. The peak signal currents as measured on a waveform oscilloscope will be a factor α larger.
 - $(\alpha = \frac{100}{100 \beta}; \beta \text{ being the total blanking time in \%, for the CCIR system } \alpha \text{ amounts to 1,3}).$
- 5. Typical faceplate illumination level for the XQ1020 and XQ1020L to produce 300 nA signal current will be approx. 3,5 lx. The signal currents stated for the colour tubes XQ1020R, G, B respectively will be obtained with an incident white level (2856 K) on the filter of approx. 8,5 lx. These figures are based on the filters described in note 6, for filter BG12 however a thickness of 1 mm is chosen.
- 6. Measuring conditions:

Illumination 4,54 lx at black body colour temperature of 2856 K; the appropriate filter inserted in the light path. The signal current obtained in nA is a measure of the colour sensitivity expressed in μ A per lumen of white light before the filter. Filters used:

XQ1020R, XQ1025R	Schott	OG570	thickness	3 mm
XQ1020G	Schott	VG9	thickness	1 mm
XQ1020B	Schott	BG12	thickness	3 mm
XQ1023R	Schott	OG570	thickness	3 mm
	and Calflex	B1/K1		

For transmission curves see General Section.

- 7. As measured with 50 mm Leitz Summicron lens having a sine response of approx. 85% at 400 TV lines at f: 5,6 and appropriate filter inserted in the light path.
 - The horizontal amplitude response can be raised by means of suitable correction circuits, which affect neither the vertical resolution nor the limiting resolution.
- 8. Build-up lag.

After 10 s of darkness. The figures are typical percentages of the ultimate signal current obtained 60 ms or 200 ms, respectively, after introduction of the illuminance.

Decay lag.

After the target has been illuminated for at least 5 s. The figures represent typical signals in percentages of the original signal current 60 ms or 200 ms, respectively, after removal of the illuminance.




Fig. 1 Typical spectral response for XQ1020.




Fig. 3 Typical spectral response for XQ1025.




Fig. 2 Typical spectral response for XQ1023.




Fig. 4 Typical square-wave response curves.



CAMERA TUBE

30 mm (1,2 inch) diameter Plumbicon[®] television camera tube, with standard resolution lead-oxide photoconductive target. The XQ1022 is exclusively intended for use with X-ray image intensifiers with P20 output phosphor in medical equipment.

QUICK REFERENCE DATA

Diameter	30 mm (1,2 inch)	
Length	approx. 204 mm	
Focusing	magnetic	
Deflection	magnetic	
Useful target area, circle, diameter	18 mm	
Spectral response		
max. at	approx. 500 nm	
cut-off:	approx. 650 nm	
Sensitivity, P20 light source	typ. 530 μ A/Im	
Resolution at 10,5 lp/mm (5 MHz)	55 %	
Heater	6,3 V, 190 mA	

OPTICAL DATA

circle, diameter

18 mm

Orientation of image on target:

For correct orientation of the image on the target the vertical scan should be essentially parallel to the plane passing through the tube axis and the marker line on the protecting sleeve at the base

Faceplate Thickness

1,2 ± 0,1 mm n = 1,49

Refractive index

Without anti-halation glass disc

ACCESSORIES

Socket type 56021 or 56603
Deflection and focusing coil unit type AT1130S

ELECTRICAL DATA

Deflection magnetic
Focusing magnetic
Heating, indirect by a.c. or d.c.

Heating, muliect by a.c. of d.c.

The heater voltage must not exceed an r.m.s. value of 9,5 V. For optimum performance stabilization of the heater

voltage is recommended. Capacitance

Signal electrode to all

This capacitance, which is effectively the output impedance, increases when the tube is inserted in the coil unit.

® Registered trademark for television camera tubes.

3 to 6 pF


Cas


LIMITING VALUES (Absolute maximum rating system	n)				notes
Unless otherwise stated, all voltages are referred to the	cathode.				
Signal electrode voltage	Vas	max.	50	V	
Grid 4 voltage	V _{q4}	max.	1100	V	
Grid 3 voltage	V _{g3}	max.	800	V	
Voltage between grid 4 and grid 3	Vg4/g3	max.	350	V	
Grid 2 voltage	V_{g2}	max.	350	V	
Grid 2 dissipation	W _{g2}	max.	1	W	
Grid 1 voltage	92				
positive	V_{g1}	max.	0	V	
negative	$-v_{g1}$	max.	125	V	
Cathode heating time before drawing	91				
cathode current	th	min.	1	min.	
Cathode to heater voltage					
positive peak	Vkfp	max.	50	V	
negative peak	$-V_{kfp}$	max.	50	V	
Ambient temperature, storage and operation	T _{amb}	max.	50	oC	
Ambient temperature, storage and operation	amb	min.	-30	oC	
Faceplate temperature, storage and operation	Т	max.	50	oC	1
raceplate temperature, storage and operation		min.	-30	oC	
Faceplate illuminance	E	max.	500	lx	2
OPERATING CONDITIONS					
For a scanned circular area with a diameter of 18 mm					3
Cathode voltage	V_k		0	V	
Signal electrode voltage	Vas		45	V	
Beam current	l _b				4
Grid 4 voltage	V_{g4}		675	V	
Grid 3 voltage	V_{g3}		600	V	
Grid 2 voltage	V_{g2}		300	V	
Grid 1 voltage	V_{g1}^{92}			V	4
Blanking voltage on grid 1, peak to peak	Vg1p-p	5	0 ± 10	V	
Faceplate illuminance	E	approx	. 2	lx	
Faceplate temperature	Т	20) to 45	oC	
ELECTRON GUN CHARACTERISTICS					
Cut-off					
Grid 1 voltage for cut-off at V _{q2} = 300 V,					
without blanking	V_{a1}	-30 to	-100	V	
Blanking voltage, peak to peak	91				
on grid 1	V _{g1p-p}	5	0 ± 10	V	
on cathode	V _{kp-p}		25	V	
Grid 2 current at normally required	1, le le				
beam currents	I_{g2}	< < < < < < < < < < < < < < < < < < <	1	mA	


PERFORMANCE			notes
Dark current Sensitivity at colour temperature	Id	≤ 3 nA	notes
of illuminance = 2856 K Sensitivity with P20 light source	min. 130 min. 395	typ. 175 μA/lmF typ. 530 μA/lm	5
Peak signal current with E = 1 Ix (P20) Gamma of transfer characteristic	min. 230	typ. 305 nA 0,95 ± 0,05	6
Spectral response, max. at Spectral response, cut-off at Spectral response curve	approx. approx. see Fig. 1	500 nm 650 nm	
Resolution	see i ig. i		7
Modulation depth, i.e. uncompensated amplitude response at 10,5 lp/mm (scanned area circle, diameter 18 mm) at the centre of the picture			
(5 MHz, 400 TV lines)		typ. 55 %	
Decay lag, light source P20, measured with a signal current of 100 nA, beam adjusted for correct stabilization after the target has been illuminated for at least 5 s.			
Residual signal after dark pulse			
of 60 ms of 200 ms	max. 10	typ. 5 % typ. 2 %	
		-11-	

MECHANICAL DATA

Dimensions in mm








Mounting position: any

Net mass: ≈ 100 g



- (1) The base passes a flat gauge with a centre hole with a diameter of 8,230 ± 0,005 mm and holes for passing the pins with the following diameters: 7 holes of 1,690 ± 0,005 mm and one hole of 2,950 ± 0,005 mm. The holes may deviate max. 0,01 mm from their true geometrical position. Thickness of gauge: 7 mm.
- (2) The ends of the pins are tapered and/or rounded but not brought to a sharp point.

NOTES, see also General Section.

- The tube can withstand short excursions up to 70 °C without damage or irreversible degradation in performance.
- For short intervals. During storage the tube face shall be covered with the plastic hood provided; when the camera is idle the lens shall be capped, in stand-by also the beam will be cut-off.
- 3. The operating conditions and performance data quoted relate to operation of the tube in coil unit AT1130. See relevant data of deflection/focusing assemblies. Scanning amplitude should be adjusted such that the useful target area of 18 mm is displayed on a standard monitor as a circular area with a diameter equal to the raster height.
- 4. The beam current I_D, as obtained by adjusting the control grid (grid 1) voltage is set to max. 600 nA. I_D is not the actual current available in the scanning beam, but is defined as the maximum amount of signal, I_S, that can be obtained with this beam. See note 6.
- Measuring conditions: illuminance level 4,54 lx at a colour temperature of 2856 K and a filter Schott VG9 inserted in the light path. For transmission of the filter, see General Section.
- 6. The peak signal currents are measured on a waveform oscilloscope and with a uniform illumination on the 18 mm diameter target area. When measured with an integrating instrument connected in the signal-electrode lead the average signal currents will be smaller:
 - a. by a factor α ($\alpha = \frac{100 \beta}{100}$, β being the total blanking time in %)

For the CCIR system α amounts to 0,75

- b. by a factor δ , δ being the ratio of the active target area (circle with adjusted 18 mm diameter) to the adjusted scanning amplitudes (18 x 24 mm). This ratio amounts to δ = 0,59. The total ratio of integrated signal current, I_s, to the peak signal current, I_{sp}, amounts to α x δ = 0,44.
- 7. As measured with a 50 mm Leitz Summicron lens having a sine response of approximately 85% at 400 TV lines at f: 5,6. The published 55% typ. is uncorrected. Tube resolution is higher. Measured with 100 nA signal current and a beam current just sufficient to stabilize a signal current of 500 nA. The horizontal amplitude response can be raised by means of suitable correction circuits, which affect neither the vertical resolution nor the limiting resolution.




Fig. 1 Typical spectral response for XQ1022.

filter

CAMERA TUBES

30 mm (1,2 inch) diameter Plumbicon $^{\circledR}$ television camera tubes, with high resolution lead-oxide photoconductive target, for use in high quality monochrome or colour cameras for broadcast, educational or industrial applications.

The XQ1410 series comprises the following versions:

XQ1410	for use in monochrome cameras
XQ1410L	for use in the luminance channel of colour cameras
XQ1410R	for use in the red channel
XQ1410G	for use in the green channel
XQ1410B	for use in the blue channel
XQ1413R	for use in the red channel; extended red response
XQ1415R	for use in the red channel; extended red response and IR
XO14151	for use in the luminance channel of colour cameras

The tubes of the XQ1410 series are interchangeable with those of the XQ1020 series and feature an increased resolution and provisions for both fixed and adjustable light bias for reduction of lag under low key conditions.

QUICK REFERENCE DATA

Diameter	30 mm (1,2 inch)
Length	approx. 215 mm
Provided with anti-halation glass disc	
Focusing	magnetic
Deflection	magnetic
Useful target area (scanning area)	12,8 x 17,1 mm
Spectral response	
max, at	approx. 500 nm
cut-off: XQ1410	approx. 650
XQ1413	approx. 850 to 950 nm
XQ1415	approx. 750 nm
Sensitivity	
XQ1410, XQ1410L	typ. $400 \mu A/Im$
XQ1410R	typ. $80 \mu A/ImF$
XQ1410G	typ. $165 \mu A/ImF$
XQ1410B	typ. $38 \mu A/ImF$
XQ1413R, XQ1415R	typ. $125 \mu A/ImF$
XQ1415L	typ. $435 \mu A/Im$
Resolution at 400 TV lines (5 MHz)	
XQ1410, XQ1410L	typ. 55 %
XQ1410R	typ. 50 %
XQ1410G	typ. 55 %
XQ1410B	typ. 60 %
XQ1413R, XQ1415R	typ. 55 %
XQ1415L	typ. 60 %
Heater	6,3 V, 190 mA

[®] Registered trademark for television camera tubes.

OPTICAL DATA notes

Quality rectangle on

photoconductive target (aspect ratio 3:4)

12,8 x 17,1 mm

Orientation of image on target:

For correct orientation of the image on the target the vertical scan should be essentially parallel to the plane passing through the tube axis and the marker line on the protecting sleeve at the base

Faceplate

Thickness Refractive index 1,2 + 0,1 mm

n = 1.49

n = 1.52

Anti-halation glass disc provided with

anti reflective coating

Thickness

 $6 + 0.2 \, \text{mm}$

Refractive index XQ1415R and XQ1415L are provided with infrared reflecting filter

ACCESSORIES

Socket type 56021 or 56603

Deflection and focusing coil unit:

Black/white

1

1

type AT1130S Colour type AT1130T Mask for flare reduction type 56029

For adjustable light bias: lamp in holder type 56106 Adaptors for fixed light bias R tubes type 56123 Adaptors for fixed light bias G, L tubes type 56124

Adaptors for fixed light bias B tubes type 56125

ELECTRICAL DATA

Deflection magnetic Focusing magnetic

Heating, indirect by a.c. or d.c.; parallel supply

Heater voltage 6.3 V ± 5% Heater current at Vf = 6,3 V If nom. 190 mA Heater current with light bias adaptor 300 mA

The heater voltage must not exceed an

r.m.s. value of 9,5 V. For optimum

performance (lifetime and registration stability)

stabilization of the heater voltage is recommended. Capacitance

Signal electrode to all Cas 3 to 6 pF

This capacitance, which is effectively the output impedance, increases when the tube is inserted in

the coil unit.

LIMITING VALUES (Absolute maximum rating sys	stem)				notes
Unless otherwise stated, all voltages are referred to t					11000
Signal electrode voltage		max.	50 V		
Grid 4 voltage	V _{as} V _{g4}		100 V		
Grid 3 voltage	Vg3	max.	800 V		
Voltage between grid 4 and grid 3	Vg4/g3	max.	350 V		
Grid 2 voltage	V _{g2}	max.	350 V		
Grid 2 dissipation	W _{g2}	max.	1 W		
Grid 1 voltage	gz				
positive	V_{g1}	max.	0 V		
negative	-V _{g1}	max.	125 V		
Cathode heating time before drawing	* 91	max.	120 V		
cathode current	th	min.	1 m	in	
Cathode to heater voltage	511				
positive peak	V_{kfp}	max.	50 V		
negative peak	-V _{kfp}	max.	50 V		
		max.	50 0		
Ambient temperature, storage and operation	Tamb	min.	-30 o		
_		max.	50 0		2
Faceplate temperature, storage and operation	Т		-30 o		_
Faceplate illuminance	Е	max.	500 lx		3
OPERATING CONDITIONS					
For a scanned area of 12,8 x 17,1 mm					4
Cathode voltage	$V_{\mathbf{k}}$		0 V		-
Signal electrode voltage	Vas		45 V		
Beam current	l _b		45 V		5
Grid 4 voltage	V _{q4}		675 V		3
Grid 3 voltage	V _{g3}		600 V		
Grid 2 voltage	V _{g2}		300 V		
Grid 1 voltage	Vg1		V		5
Blanking voltage on grid 1, peak to peak	V = 1 = =	50	± 10 V		0
Faceplate illuminance	V _{g1p-p}		o 10 lx		6
Temperature of faceplate	Ť		0 45 0		0
		20 (0 43		
ELECTRON GUN CHARACTERISTICS					
Cut off					
Grid 1 voltage for cut-off at V _{q2} = 300 V,					
without blanking	V _{g1}	-30 to -	-100 V		
Blanking voltage, peak to peak	9 '				
on grid 1	Vg1p-p	50	± 10 V		
on cathode	V _{kp-p}		25 V		
Grid 2 current at normally required	KP P				
beam currents	I _{g2}	<	1 m	A	
	34				

Resolution

PERFORMANCE						notes
Dark current (without lightbias)	ld		<	2	nA	
Sensitivity at colour temperature of illuminance = 28						7
XQ1410, XQ1410L	min.	365	typ.	400	μ A/Im	
XQ1410R	min.	70	typ.	80	$\mu A/ImF$	
XQ1410G	min.	135	typ.	165	$\mu A/ImF$	
XQ1410B	min.	35	typ.	38	$\mu A/ImF$	
XQ1415L	min.	390	typ.	435	$\mu A/ImF$	
XQ1413R, XQ1415R	min.	115	typ.	125	$\mu A/Im$	
Gamma of transfer characteristics			0,95	0,05		
Spectral response, max. at	approx			500	nm	
Spectral response, cut-off at	approx		650 t	o 950	nm	
Spectral response curves	see Figs	s 1, 2 and	3			

Modulation depth, i.e. uncompensated amplitude response at 400 TV lines at the centre of the picture.

	XQ1410L XQ1410G	XQ1410R	XQ1410B	XQ1415L	XQ1413R XQ1415R	
Highlight signal current I _S Beam current I _b Modulation depth at 400 TV lines	300 600	150 300	150 300	300 600	150 300	nA nA
typ.	55	50	60	60	55	%
min.	50	40	50	50	45	%

Modulation transfer characteristics: see Fig. 4.

Lag (typical values)

Light source with a colour temperature of 2856 K. Appropriate filter inserted in the light path for the chrominance tubes R, G and B.

LOW KEY CONDITIONS (with light bias of 3 nA)

4 - A-100E-	build-up lag I _S /I _b = 20/300 nA		decay lag I _s /I _b = 20/300 nA	
	60 ms	200 ms	60 ms	200 ms
XQ1410, L, G	98%	≈ 100%	7%	2%
XQ1410R	98%	≈ 100%	8%	3%
XQ1410B	95%	≈ 100%	11%	3.5%
XQ1413R	90%	≈ 100%	13%	3,5%
XQ1415R	90%	≈ 100%	13%	3.5%
XQ1415L	95%	≈ 100%	8%	3%


Typical effect of light bias on build-up and decay lag under low key signal current and beam settings are shown in Figs 5 to 14 Shading of light bias induced dark current


12,5%


11

9, 10

MECHANICAL DATA








Mounting position: any

Mass: ≈ 100 g



- (*) Distance between axis of anti-halation glass disc and geometrical centre of signal electrode ring, measured in plane of faceplate: max. 0,2 mm. Total glass thickness: 7,2 ± 0,2 mm.
- (1) The base passes a flat gauge with a centre hole 8,230 ± 0,005 mm diameter and holes for passing the pins with the following diameters: 7 holes of 1,690 ± 0,005 mm and one hole of 2,950 ± 0,005 mm. The holes may deviate max. 0,01 mm from their true geometrical position. Thickness of gauge 7 mm.
- (2) The ends of the pins are tapered and/or rounded but not brought to a sharp point.

NOTES, see also General Section.

- 1. a. Adjustable light bias. The light bias lamp assembly as supplied with each tube, type 56106, fits in the metal tube cemented to the pumping stem of the tube. The tube and the light bias lamp assembly will fit properly in the sockets type 56021 and 56025. The wires should be connected to a source, capable of supplying max. 110 mA at 5 V. Considerations and recommendations for the choice of such a source, depending on the application, are supplied with each tube. The light bias lamp projects its light via a blue-green transmitting filter on the pumping stem where it is conducted to the target to cause a bias illumination. The desired amount of light bias can be obtained by adjusting the current through the filament of the lamp. See also note 10.
 - b. Fixed light bias. An adapter is supplied with each tube, connecting a small lamp via a calibrated series resistor to the heater pins. The heater supply should be stabilized at $6.3 \pm 0.1 \text{ V}$ and be capable of supplying an additional current of 95 mA. The adaptor is colour coded according to the application of the tube.
- The tube can withstand short excursions up to 70 °C without damage or irreversible degradation in performance.
- 3. For short intervals. During storage the tube face shall be covered with the plastic hood provided; when the camera is idle the lens shall be capped, in stand-by also the beam will be cut-off.
- The operating conditions and performance data quoted relate to operation of the tube in coil unit AT1130. See relevant data of deflection/focusing assemblies.
- 5. The beam current I_b, as obtained by adjusting the control grid (grid 1) voltage is set to 300 nA for R and B tubes, 600 nA for black and white, L and G tubes. I_b is not the actual current available in the scanning beam, but is defined as the maximum amount of signal current, I_s, that can be obtained with this beam.

In the performance figures for lag, the signal current and beam current conditons are given, e.g. as $\rm l_s/l_b=20/300$ nA. This means: with a signal current of 20 nA and a beam setting which just allows a signal current of 300 nA.

N.B. The signal currents are measured with an integrating instrument connected in the signal electrode lead and a uniform illumination of the scanned area.

The peak signal currents as measured on a waveform oscilloscope will be a factor α larger.

$$\alpha = \frac{100}{100-\beta}$$
; β being the total blanking time in %: for the CCIR system $\alpha = 1,3$.

- 6. Typical faceplate illumination level for the XQ1410 and XQ1410L to produce 300 nA signal current will be approx. 3,5 lx. The signal currents stated for the colour tubes XQ1410R, G and B will be obtained with an incident white light level (2856 K) on the filter of approx. 8,5 lx. These figures are based on the filters described in note 7. For filter BG12, however, a thickness of 1 mm is chosen.
- Measuring conditions: illuminance level 4,54 lx at a colour temperature of 2856 K and the
 appropriate filter inserted in the light path. The signal current obtained in nA is a measure of
 the colour sensitivity expressed in μA per lumen of white light before the filter. Filters used are:

XQ1410R, XQ1415R	Schott	OG570	thickness	3 mm
XQ1410G	Schott	VG9	thickness	1 mm
XQ1410B	Schott	BG12	thickness	3 mm
XQ1413R	Schott	OG570	thickness	3 mm
aı	d Calflex	B1/K1		

For transmission curves see General Section.

- 8. As measured with a 50 mm Leitz Summicron lens having a sine response of approximately 85% at 400 TV lines at f: 5,6 and the appropriate filter inserted in the light path. The horizontal amplitude response can be raised by means of suitable correction circuits, which affect neither the vertical resolution nor the limiting resolution.
- 9. Build-up lag

After 10 s of darkness. The figures are typical percentages of the ultimate signal current obtained 60 ms and 200 ms, respectively, after the introduction of the illuminance.

Decay lag

After the target has been illuminated for at least 5 s. The figures represent typical signals in percentages of the original signal current 60 ms and 200 ms, respectively, after removal of the illuminance.

- 10. A reduction lag, especially under low key conditions is obtained when light bias is applied. Infrared light with a wavelength > 600 nm in the light bias should be avoided.
 - a. For monochrome operation a light bias corresponding to 4,5 nA dark current is usually adequate for excellent speed of response. The adapter as supplied with the tube will produce a fixed light bias in the order of this magnitude.
 - b. Adjustable light bias (colour camera).
 - In a colour camera the speeds of response of the tubes can be balanced by adjusting the amount of light bias per tube.
 - In a 3-tube colour camera for instance it is recommended to first adjust the tubes to their normal highlight signal current and beam current settings and then point the camera at a dark scene comprising a metronome. The moving hand of the metronome carries a small white square. The illuminance should be chosen such that the square produces a peak signal of approximately 50 nA in the green chrominance channel. A maximum of 3 nA artificial dark current shall then be introduced in the green chrominance tube. Subsequently light bias shall be applied to the tubes in the red and blue channels until the lag of the three tubes is neutralized.
 - c. Fixed light bias (colour camera).
 - A typical setting for correct speeds of response in a 3-tube colour camera would be approximately 3 nA(p) (R), 2 nA(p) (G) and 3,5 nA(p) (B). The adapters as supplied with the tubes will produce fixed bias of the same magnitude.
- 11. Deviation of the level of any of the four corners, i.e. 10% inwards in H and V direction from the level in the picture centre. With the settings suggested in note 10 black shading compensation in the camera video processing amplifier will not normally be required. Further improvement in lag can be obtained by applying still higher light bias levels. It may then be necessary to use black shading compensation in the video processing amplifier.

XQ1410 SERIES




Fig. 1 Typical spectral response for XQ1410.




Fig. 3 Typical spectral response for XQ1415.




Fig. 2 Typical spectral response for XQ1413.







Fig. 4 Typical square wave response curves.





.5. 0.



Build-up lag (see note 9)

Light bias induced dark current as parameter.

Fig. 5 XQ1410R : $I_s/I_b = 20/300 \text{ nA}$. Fig. 6 XQ1410, XQ1410L, XQ1419G:

 $I_s/I_b = 40/600 \text{ nA}.$

Fig. 7 XQ1410B : $I_s/I_b = 20/300 \text{ nA}$.

January 1985

Fig. 7.

(x 20 ms)

XQ1410 SERIES





Fig. 8.



7Z72983


Fig. 9.

Build-up lag (see note 9)

Light bias induced dark current as parameter.

Fig. 8 XQ1415L: $I_s/I_b = 40/600 \text{ nA}$.

Fig. 9 XQ1413R, XQ1415R: $I_s/I_b = 20/300 \text{ nA}$.







Fig. 11.



Light bias induced dark current as parameter.

Fig. 10 XQ1410R : $I_s/I_b = 20/300 \text{ nA}$.

Fig. 11 XQ1410, XQ1410L, XQ1410G:

 $I_s/I_b = 40/600 \text{ nA}.$

Fig. 12 XQ1410B : $I_s/I_b = 20/300 \text{ nA}$.





Fig. 12.

XQ1410 SERIES








Fig. 14.

Decay lag (see note 9)

Light bias induced dark current as parameter.

Fig. 13 XQ1415L : $I_s/I_b = 40/600 \text{ nA}$.

Fig. 14 XQ1413R, XQ1415R: $I_s/I_b = 20/300 \text{ nA}$.

CAMERA TUBES

30 mm (1,2 inch) diameter Plumbicon [®] television camera tubes, with high resolution lead-oxide photoconductive target, for use in high quality monochrome or colour cameras for broadcast; educational or industrial applications.

The XQ1520 series comprises the following versions:

XQ1520	for use in monochrome cameras
XQ1520L	for use in the luminance channel of colour cameras
XQ1520R	for use in the red channel
XQ1520G	for use in the green channel
XQ1520B	for use in the blue channel
XQ1523R	for use in the red channel; extended red response
XQ1525R	for use in the red channel; extended red response and IR filt
XQ1525L	for use in the luminance channel of colour cameras

Special features are:

- Anti-Comet-Tail (ACT) electron gun for highlight handling
- New photoconductive target for increased resolution
- Provisions for light bias to reduce lag

QUICK REFERENCE DATA

ACT electron gun			
Diameter		30	mm (1,2 inch)
Length	approx.	215	mm
Provided with anti-halation glass disc			
Focusing	magnetic		
Deflection	magnetic		
Useful target area (scanning area)	12,8 >	(17,1	mm
Spectral response		n infini	
max, at	approx.	500	nm
cut-off: XQ1520	approx.	650	nm
XQ1523	approx.	850	to 950 nm
XQ1525	approx.	750	nm
Sensitivity			
XQ1520, XQ1520L	typ.	400	μ A/Im
XQ1520R	typ.	80	μA/ImF
XQ1520G	typ.	165	μA/ImF
XQ1520B	typ.	38	μA/ImF
XQ1523R, XQ1525R	typ.	125	μA/ImF
XQ1525L	typ.	435	μA/Im
Resolution at 400 TV lines (5 MHz)			
XQ1520, XQ1520L	typ.	55	%
XQ1520R	typ.	50	
XQ1520G	typ.	55	
XQ1520B	typ.	60	
XQ1523R, XQ1525R	typ.	55	
XQ1525L	typ.	60	
Heater		6,3	V, 190 mA

[®] Registered trademark for television camera tubes.

OPTICAL DATA

Quality rectangle on

photoconductive target (aspect ratio 3:4)

12,8 x 17,1 mm

notes

Orientation of image on target:

For correct orientation of the image on the target the vertical scan should be essentially parallel to the plane passing through the tube axis and the marker line on the protecting sleeve at the base

Faceplate

Thickness
Refractive index

Anti-halation glass disc provided with

anti-reflective coating

Thickness

Refractive index

6 ± 0,2 mm

 1.2 ± 0.1 mm

n = 1.49

n = 1,52

type AT1130S

XQ1525R and XQ1525L are provided with an infrared reflecting filter

ACCESSORIES

Socket type 56025

Deflection and focusing coil unit:

Black/white

Colour type AT1130T Mask for flare reduction type 56029

For adjustable light bigs, law

For adjustable light bias: lamp in holder type 56106
Adapters for fixed light bias R tubes type 56123
Adapters for fixed light bias G, L tubes type 56124

Adapters for fixed light bias B tubes type 56125

ELECTRICAL DATA

Deflection magnetic Focusing magnetic

Heating, indirect by a.c. or d.c.; parallel supply

Heater voltage V_f 6,3 $V \pm 5\%$

Heater current at $V_f = 6.3 \text{ V}$ If nom. 190 mA

Heater current with light bias adapter 300 mA

The heater voltage must not exceed an r.m.s. value of 9,5 V. For optimum

performance (lifetime and registration stability)

stabilization of the heater voltage is recommended.

Capacitance

Signal electrode to all Cas 3 to 6 pF

This capacitance, which is effectively the output impedance, increases when the tube is inserted in

the coil unit.

	notes
	110100
x. 50 V	
x. 1100 V	
x. 800 V	
x. 350 V	
A. 000 V	
x. 350 V	
x. 350 V	
x. 0 V	
x. 200 V	
n. 1 min	
50.17	
x. 50 V x. 50 V	
x. 50 °C	
x. 50 °C	
130 °C	2
x. 500 lx	3
	4, 5
	6, 7, 8
	-, -, -
0 V	
0 to 15 V	
45 V	
675 V	
600 V	
300 V	
	8
	8
	10
	8
50 V	
	50 V

XQ1520 SERIES

notes

Typical	beam	current,	signal	current
1	1	-441		

P 48		XQ1520 XQ1520L XQ1525L	XQ1520F XQ1523F XQ1525F	1	XQ1520)G	XQ15	520B
Signal current, peak	I _{sp}	0,3	0,15		0,3		0,1	5 μΑ
Beam current, peak	lbp	0,6	0,3		0,6		0,3	μΑ
ACT level, peak		0,4	0,2		0,4		0,2	μΑ
Cathode pulse	V_{kp}	7	3,5		7		3,5	V
Grid 1 pulse	V_{g1p}	27	23,5		27		23,5	V
Grid 3 pulse	V _{g3p}						see r	note 8
Faceplate illuminance	e				0 to	10 lx	(11
Faceplate temperatur	е				20 to	45 0	С	2
ELECTRON GUN CH	HARACTE	RISTICS						
Cut off Grid 1 voltage for without blanking o	cut-off at V	/ _{g2,4} = 300 V, ses	V_{g1}		-40 to -	110 V		
Blanking voltage, pea on grid 1	k to peak a	$t V_{g2,4} = 300 V$	V _{g1p} -	р	50 ±	10 V		12
Grids 2 and 4 current			lg2,4		<	0,2 m	ıΑ	13
Grids 3, 5 and 6 curre	ent		lg3,5,	6				13
Pulse timing and amp	litude requ	irements (ACT)						7
PERFORMANCE								
Dark current, withou	t light bias		ld			≤1 n	A	
Sensitivity at colour 1 XQ1520, XQ1520 XQ1520R XQ1520G XQ1520B XQ1523R, XQ152 XQ1525L	L	e of illuminance =	2856 K min. min. min. min. min.	365 70 135 35 115 390	typ. typ. typ. typ.	165 μ. 38 μ. 125 μ.	A/Im A/ImF A/ImF A/ImF A/ImF	14
Gamma of transfer ch	naracteristic	cs			$0,95 \pm 0$,05		
Light transfer charact	eristics wit	h ACT			see Fig. :	2		
Highlight handling					≥5 lens	stops		15
Spectral response, ma			approx	Κ.	5	500 ni	m	
Spectral response, cut			approx	Κ.		350 ni		
Spectral response, cut			approx	Κ.	850 to 9			
Spectral response, cut	-off: XQ1	525	approx	Κ.	7	750 ni	m ,	
Spectral response cur	ves				see Figs	3, 4 ar	nd 5	

notes

Resolution

16

Modulation depth, i.e. uncompensated amplitude response at 400 TV lines at the centre of the picture. The figures shown represent the horizontal amplitude response as measured with a lens aperture f: 5.6.

Modulation transfer characteristics

see Fig. 6

*		XQ1520 XQ1520L	XQ1520R	XQ1520G	XQ1520B	XQ1523R XQ1525R	
Highlight signal current	Is	300	150	300	150	150	nA
Beam current	Ib	600	300	600	300	300	nA
Modulation depth at 400 TV lines				*			
typ.		55	50	55	60	55	%
min.		50	40	50	50	45	%

Lag (typical values)

17

Light source with a colour temperature of 2856 K. Appropriate filter inserted in the light path for the chrominance tubes R, G and B

LOW KEY CONDITIONS (without light bias)

	build-up lag		dec	cay lag
	I _s /I _b =	20/300 nA	I _s /I _b =	= 20/300 nA
	60 ms	200 ms	60 ms	200 ms
XQ1520, L, G	95%	~ 100%	9%	3%
XQ1520R	85%	~ 100%	13%	3,5%
XQ1520B	70%	~ 100%	15%	5,5%
XQ1523L	65%	~ 100%	15%	5%
XQ1525R	65%	~ 100%	15%	5%
XQ1525L	95%	~ 100%	10%	3%

LOW KEY CONDITIONS (with light bias)

18


Typical effect of light bias on build-up and decay lag under low key signal current and beam settings are shown in Figs 7 to 16.

Shading of light bias induced dark current

12,5%

18

XQ1520 SERIES



- (*) Distance between axis of anti-halation glass disc and geometrical centre of signal electrode ring, measured in plane of faceplate: max. 0,2 mm. Total glass thickness: 7,2 ± 0,2 mm.
- (1) The base passes a flat gauge with a centre hole $8,230 \pm 0,005$ mm diameter and holes for passing the pins with the following diameters: 7 holes of $1,690 \pm 0,005$ mm and one hole of $2,950 \pm 0,005$ mm. The holes may deviate max. 0,01 mm from their true geometrical position. Thickness of gauge 7 mm.
- (2) The ends of the pins are tapered and/or rounded but not brought to a sharp point.

pulsed:

NOTES, see also General Section

- a. Adjustable light bias. The light bias lamp assembly as supplied with each tube, type 56106, fits in the metal tube cemented to the pumping stem of the tube. The tube and the light bias lamp assembly will fit properly in the sockets, type 56021 and 56025. The wires should be connected to a source, capable of supplying max. 110 mA at 5 V.
 Considerations and recommendations for the choice of such a source, depending on the application, are supplied with each tube. The light bias lamp projects its light via a blue-green transmitting filter on the pumping stem where it is conducted to the target to cause a bias illumination. The desired amount of light bias can be obtained by adjusting the current through the filament of the lamp. See also note 18.
 - b. Fixed light bias. An adapter is supplied with each tube, connecting a small lamp via a calibrated series resistor to the heater pins. The heater supply should be stabilized at $6.3 \pm 0.1 \, \text{V}$ and be capable of supplying an additional current of 95 mA. The adapter is colour coded according to the application of the tube.
- The tube can withstand short excursions up to 70 °C without damage or irreversible degradation in performance.
- 3. For short intervals, During storage the tube face shall be covered with the plastic hood provided; when the camera is idle the lens shall be capped, in stand-by also the beam will be cut-off.
- The operating conditions and performance data quoted relate to operation of the tube in coil unit AT1130. See relevant data of deflection/focusing assemblies.
- 5. When the tube is to be used without ACT action, grid 3 should be connected to grids 2 and 4 and no ACT pulses should be applied to the cathode and grid 1. The performance of the tube will then be as described herein with the exception of the highlight handling.
- a. For proper ACT action the d.c. voltage supply and/or pulse supply to the various electrodes should have sufficiently low impedance; see note 13.
 - b. Video preamplifier: In the presence of highlights, peak signal currents of the order of 15 to 45 μ A may be offered to the preamplifier during flyback. Special measures have to be taken in the preamplifier to prevent temporary overloading.
- 7. a. Read-out mode: Defined as the operating conditions during the active line scan (full line period-line blanking interval). For the CCIR system this will amount to 64 μ s 12 μ s = 52 μ s.
 - b. ACT mode: Defined as the operating conditions during that part of the line blanking interval during which the ACT electrode gun is fully operative. The ACT interval is equal to or slightly within the line flyback time.
- 8. Pulse timing (CCIR) and amplitudes for ACT action: (blanking applied to grid 1, see note 12)
 a. For proper operation and setting up of the ACT electron gun three electrodes have to be
 - Cathode: A positive-going pulse, V_{kp}, with an adjustable amplitude of 0 to 20 V. This pulse can be chosen to coincide with the camera blanking period (approx. 11 μs). The amplitude of this pulse determines the ACT cutting level and may in general be preset to 7; 3,5; 7 and 3,5 V, for black/white, R, G, and B application respectively. An amplitude of 20 V should be available to preset the I_s/I_b; see note 10.
 - Grid 1: A positive-going pulse, V_{g1p}, with such an amplitude that during the ACT mode the grid 1 bias is effectively reduced by 25 V, (V_{g1p} = 25 V + V_{kp}), to produce an extra amount of cathode current. The duration of this pulse should be so chosen that it is just within the flyback period (approx. 5 µs).

- Grid 3: A negative-going pulse, V $_{\rm g3p}$, timing and duration coinciding with V $_{\rm g1p}$, with: either an adjustable amplitude and superimposed on a fixed grid 3 voltage of 250 to 300 V, or with fixed amplitude and superimposed on an adjustable grid 3 voltage of 250 to 300 V, in either case, adjusted to result in a grid 3 voltage of 8,5 V with respect to the cathode voltage during the ACT mode. This pulse ensures that an adequate amount of beam current is drawn from the cathode current.
- b. A suggested pulse timing and amplitude diagram is shown in Fig. 1.
- 9. Operation with ACT at V_{a6} > 750 V is not recommended since this may introduce dark current.
- 10. Adjusted with the ACT made inoperative, e.g. by setting the cathode pulse to 20 V. The control grid voltage is adjusted to produce a beam current just sufficient to allow a peak signal current of twice the typical value, I_{SP}, as observed and measured on a waveform oscilloscope. This amount of beam current is termed I_{bP}. I_b is set at 300 nA for R and B tubes and at 600 nA for L and G tubes.
 - N.B. The signal current, I_s , and the beam current, I_b , conditions quoted with the performance figures for e.g. lag relate to measurements with an integrating instrument connected in the signal electrode lead and a uniform illuminance on the scanned area. The corresponding peak currents, I_{sp} and I_{bp} , as measured on a waveform oscilloscope will be a factor α larger. $\alpha = 100/100 \beta$; β being the total blanking time in %; for CCIR system $\alpha = 1,3$.
- 11. Typical faceplate illumination level for the XQ1520 and XQ1520L to produce 300 nA signal current will be approx. 3,5 lx. The signal currents stated for the colour tubes R, G and B will be obtained with an incident white light level (2856 K) on the filter of approx. 8,5 lx. These figures are based on the filters described in note 14. For filter BG12, however, a thickness of 1 mm is chosen.
- 12. Blanking can also be applied to the cathode:
 - without ACT action; required cathode pulse approx. 25 V
 - with ACT action; timing, polarity and amplitudes of the ACT pulses will have to be adapted.
- 13. The d.c. voltage supply and/or pulse supply to these electrodes should have a sufficiently low impedance to prevent distortion caused by the peak currents drawn during the ACT mode. These peak currents may amount to:

cathode	2 mA
grid 1	0 mA
grids 2 and 4	1 mA
grid 3	150 μΑ
grid 5	300 μΑ
grid 6	300 μΑ

The cathode impedance should preferably be chosen \leq 300 Ω .

14. Measuring conditions: illuminance level 4,54 lx at a colour temperature of 2856 K and the appropriate filter inserted in the light path. The signal current obtained in nA is a measure of the colour sensitivity expressed in μ A per lumen of white light before the filter. Filters used are:

XQ1520R, XQ1525R	Schott	OG570	thickness	3 mm
XQ1520G	Schott	VG9	thickness	1 mm
XQ1520B	Schott	BG12	thickness	3 mm
XQ1523R	Schott	OG570	thickness	3 mm
	and Calflex	B1/K1		

For transmission curves see General Section.

15. With pulses applied as indicated in note 8 the tube will properly handle a highlight with a diameter of 10% of picture height and with a luminance corresponding to 32 times peak signal white, I_{SD}. 16. As measured with a 50 mm Leitz Summicron lens having a sine response of approximately 85% at 400 TV lines at f: 5,6 and the appropriate filter inserted in the light path. The horizontal amplitude response can be raised by means of suitable correction circuits, which affect neither the vertical resolution nor the limiting resolution.

17. Build-up lag

After 10 s of darkness. The figures are typical percentages of the ultimate signal current obtained 60 ms and 200 ms, respectively, after the introduction of the illuminance.

Decay lag

After the target has been illuminated for at least 5 s. The figures represent typical signals in percentages of the original signal current 60 ms and 200 ms, respectively, after removal of the illuminance.

- 18. A reduction of lag, especially under low key conditions is obtained when light bias is applied. Infrared light with a wavelength > 600 nm in the light bias should be avoided.
 - a. For monochrome operation a light bias corresponding to 4,5 nA dark current is usually adequate for excellent speed of response. The adapter as supplied with the tube will produce a fixed light bias in the order of this magnitude.
 - b. Adjustable light bias (colour camera).


In a colour camera the speeds of response of the tubes can be balanced by adjusting the amount of light bias per tube.

In a 3-tube colour camera for instance it is recommended to first adjust the tubes to their normal highlight signal current and beam current settings and then point the camera at a dark scene comprising a metronome. The moving hand of the metronome carries a small white square. The illuminance should be chosen such that the square produces a peak signal of approximately 50 nA in the green chrominance channel.

A maximum of 3 nA artificial dark current shall then be introduced in the green chrominance tube. Subsequently light bias shall be applied to the tubes in the red and blue channels until the lag of the three tubes is neutralized.

- c. Fixed light bias (colour camera).
 - A typical setting for correct speeds of response in a 3-tube colour camera would be approximately 3 nA(p) (R), 2 nA(p) (G) and 3.5 nA(p) (B). The adapters as supplied with the tubes will produce fixed bias of the same magnitude.
- 19. Deviation of the level of any of the four corners, i.e. 10% inwards in H and V direction from the level in the picture centre. With the settings suggested in note 18 black shading compensation in the camera video processing amplifier will not normally be required. Further improvement in lag can be obtained by applying still higher light bias levels. It may then be necessary to use black shading compensation in the video processing amplifier.

XQ1520 SERIES



. .5.




Fig. 2 Typical light transfer characteristics with ACT applied.

XQ1520 SERIES




Fig. 3 Typical spectral response for XQ1520, L, G, B.




Fig. 5 Typical spectral response for XQ1525R.




Fig. 4 Typical spectral response for XQ1523R.




Fig. 6 Typical square-wave response curves.





Fig. 7.






Fig. 8.

Build-up lag (note 17)

Light bias induced dark current as parameter.

Fig. 7, XQ1520R: $I_s/I_b = 20/300 \text{ nA}$

Fig. 8, XQ1520, XQ1520L, XQ1520G:

 $I_{s}/I_{b} = 40/600 \text{ nA}$

Fig. 9, XQ1520B: $I_s/I_b = 20/300 \text{ nA}$

XQ1520 SERIES






Fig. 10.





rig. ii.




Fig. 12.




Fig. 13.




Fig. 14.

Decay lag (note 17)


Light bias induced dark current as parameter.


Fig. 12, XQ1520R: $I_s/I_b = 20/300 \text{ nA}$.

Fig. 13, XQ1520, XQ1520L, XQ1520G: $I_s/I_b = 40/600 \text{ nA}.$

Fig. 14, XQ1520B: $I_s/I_b = 20/300 \text{ nA}$.

XQ1520 SERIES





Decay lag (see note 17)

Light bias induced dark current as parameter

Fig. 15, XQ1525L: $I_s/I_b = 40/600 \text{ nA}$

Fig. 16, XQ1523R; XQ1525R: $I_s/I_b = 20/300 \text{ nA}$

DEVELOPMENT DATA

This data sheet contains advance information and specifications are subject to change without notice.

XQ3440 SERIES

CAMERA TUBES

30 mm (1,2 inch) diameter Plumbicon[®] television camera tubes, with high resolution lead-oxide photoconductive target, for use in high quality monochrome or colour cameras for broadcast, educational or industrial applications.

The XQ3440 series comprises the following versions:

XO3440 for use in monochrome cameras

XQ3440L for use in the luminance channel of colour cameras

XQ3440R for use in the red channel

XQ3440G for use in the green channel

XQ3443R for use in the red channel; extended red response

for use in the blue channel

XQ3445R for use in the red channel; extended red response and IR filter

Special features are:

XQ3440B

- New photoconductive target for increased resolution
- "Diode" electron gun with high beam reserve for dynamic beam control (DBC) to minimize comet-tailing and blooming (notes 1 and 2)
- Provisions for light bias to reduce lag
- Low output capacitance (LOC) for high signal to noise ratio

QUICK REFERENCE DATA

"Diode" electron gun

Diameter		30	mm(1,2 inch)
Length	approx.	215	mm
Provided with anti-halation glass disc			
Focusing	magnetic		
Deflection	magnetic		
Useful target area (scanning area)	12,8 x	17,1	mm
Spectral response			
max. at	approx.	500	nm
cut-off: XQ3440	approx.	650	nm
XQ3443	approx.	850	to 950 nm
XQ3445	approx.	750	nm
Sensitivity			
XQ3440, XQ3440L	typ.	375	μA/Im
XQ3440R	typ.	80	μA/ImF
XQ3440G	typ.	150	μA/ImF
XQ3440B	typ.	36	μA/ImF
XQ3443R, XQ3445R	typ.	105	μA/ImF
Resolution at 400 TV lines (5 MHz)			
XQ3440, XQ3440L	typ.	65	%
XQ3440R	typ.	55	%
XQ3440G	typ.	65	%
XQ3440B	typ.		%
XQ3443R, XQ3445R	typ.		%
Heater		6,3	V, 190 mA

[®] Registered trademark for television camera tubes.

OPTICAL DATA notes

Quality rectangle on

photoconductive target (aspect ratio 3:4) 12,8 x 17,1 mm

Orientation of image on target:

For correct orientation of the image on the target the vertical scan should be essentially parallel to the plane passing through the tube axis and the marker line on the protecting sleeve at the base.

Faceplate

Thickness $1.2 \pm 0.1 \, \text{mm}$ n = 1.49

Refractive index

Anti-halation glass disc

Thickness 6 ± 0.2 mm Refractive index n = 1.52

XQ3445R is provided with an infrared reflecting filter

ACCESSORIES

Socket type 56021 or 56025

Deflection and focusing coil unit, rear loading:

Black/white type AT1131S Colour

type AT1131T Mask for flare reduction type 56029

For adjustable light bias: lamp in holder type 56106

3

Adapters for fixed light bias R tubes type 56123 Adapters for fixed light bias G, L tubes type 56124

Adapters for fixed light bias B tubes type 56125

ELECTRICAL DATA

Deflection magnetic Focusing magnetic

Heating, indirect by a.c. or d.c.; parallel supply Heater voltage 6.3 V ± 5%

Heater current at Vf = 6,3 V 190 mA If nom.

The heater voltage must not exceed an

r.m.s. value of 9.5 V. For optimum performance (lifetime and registration stability)

stabilization of the heater voltage is recommended.

Capacitance

Signal electrode to all Cas approx. 3 pF

This capacitance, which is effectively the output impedance, increases when the tube is inserted in

the coil unit.

_						-		
	LIMITING VALUES (Absolute maximum rating system)			JEST ABOVE.	-	notes	
	Unless otherwise stated, all voltages are referred to the c							
	Signal electrode voltage		may	50	V			
	Grid 4 voltage	Vas	max.					
	Grid 3 voltage	V _g 4		1100				
	9	V _{g3}	max.	800				
	Voltage between grid 4 and grid 3	Vg4/g3	max.					
	Grid 2 voltage	V_{g2}	max.	350	V			
	Grid 1 voltage,			05				
	positive	Vg1	max.	25				
	negative	-V _{g1}	max.	200				
	Grid 1 current (approx. I _k current)	g1	max.		mA			
	Grid 1 current (peak current with DBC)	g1p	max.	10	mA			
	Cathode to heater voltage	N/						
	positive peak	Vkfp	max.	50				
	negative peak	$-V_{kfp}$	max.	50	V			
	Cathode heating time before							
	drawing cathode current	^t h	min.	1	min			
	External resistance between cathode							
	and heater at $V_{kfp} > 10 V$	Rkf	min.		$k\Omega$			
	Ambient temperature, storage and operation	Tamb	max.		oC		4	
	ramporate to report terror of the terror of	amb	min.					
	Faceplate temperature, storage and operation	Т	max.	50	oC			
			min.	-30	oC			
	Faceplate illuminance	Е	max.	500	lx		5	
	OPERATING CONDITIONS with ACT action						6	
	For a scanned area of 12,8 x 17,1 mm							
	Cathode voltage	$V_{\mathbf{k}}$		0	V			
	Signal electrode voltage	Vas		45				
	Beam current	l _b	max.	600			7	
	Grid 4 voltage		max.	675			,	
	Grid 3 voltage	V _g 4		600				
	Grid 2 voltage	V _{g3}		300				
	Grid 1 voltage for I _b = 600 nA	V _{g2}		+ 8			7	
	Blanking voltage on grid 1, peak to peak	Vg1		25			/	
	Faceplate illuminance	V _{g1p-p}	0	to 10			8	
	Faceplate temperature			to 45			0	
	raceplate temperature		20	10 45	00			
	ELECTRON GUN CHARACTERISTICS							
	Cut-off							
	Grid 1 voltage for cut-off at							
	$V_{g2} = 300 \text{ V}$, without blanking	V_{g1}	-1	0 to 0	V			
	Grid 1 voltage for normal beam setting	Vg1w	<	15				
	Blanking voltage, peak to peak	giw						
	on grid 1	V_{g1p-p}		25	V			
	on cathode	V _{kp-p}		25				
	Grid 1 current at normally	Kh-h						
	required beam currents	l _q 1	<	5	mA			
	Grid 2 current at normally	91						
	required beam currents	I_{g2}	\leq	0,25	mA			
		92		-,	109(58-45)			

Resolution

PERFORMANCE						notes
Dark current						
XQ3440	ld		<	1	nA	
XQ3443, XQ3445	ld		<	2	nA	
Sensitivity at colour temperature of illuminance =	2856 K					9
XQ3440	min.	330	typ.	375	$\mu A/Im$	
XQ3440R	min.	70	typ.	80	μA/ImF	
XQ3440G	min.	120	typ.	150	$\mu A/ImF$	
XQ3440B	min.	32	typ.	36	$\mu A/ImF$	
XQ3443R, XQ3445R	min.	70	typ.	105	$\mu A/ImF$	
Gamma of transfer characteristic			0,95 to	0,05		
Spectral response, max. at	approx	κ.		500	nm	
Spectral response, cut-off at	approx	Κ.	650 t	o 950	nm	

Spectral response curves see Figs 1, 2 and 3

Modulation depth, i.e. uncompensated amplitude response at 400 TV lines at the centre of the picture.

		XQ3440 XQ3440L XQ3440G	XQ3440R	XQ3443R XQ3445R	XQ3440B	
Highlight signal current Beam current Modulation depth	I _s	300 600	150 300	150 300	150 300	nA nA
at 400 TV lines typ. min.		65 55	55 45	60 50	70 60	% %

10

11, 12

Modulation transfer characteristics: see Fig. 4

Lag (typical values, without light bias)


Light source with a colour temperature of 2856 K. Appropriate filter


inserted in the light path.


	build-u	p lag	decay	lag	
	$I_s/I_b = 20/300 \text{ nA}$		$I_{s}/I_{b} = 20/300 \text{ nA}$		
	60 ms	200 ms	60 ms	200 ms	
XQ3440, XQ3440L	95%	~ 100%	9%	3%	
XQ3440R	85%	~ 100%	13%	3,5%	
XQ3440G	95%	~ 100%	10%	3%	
XQ3440B	70%	~ 100%	13%	5.5%	
XQ3443R	90%	~ 100%	15%	3%	
XQ3445R	90%	~ 100%	15%	4%	

Shading of light bias induced dark current 12,5% 13
Highlight handling capability with DBC 4 lens stops 14


MECHANICAL DATA







Mounting position: any Mass: $\approx 100 \text{ g}$



- (*) Distance between axis of centring ring and geometrical centre of mesh electrode ring, measured in plane of faceplate: max. 0,1 mm. Total glass thickness: 7,2 ± 0,2 mm.
- (1) The base passes a flat gauge with a centre hole 8,230 ± 0,005 mm diameter and holes for passing the pins with the following diameters: 7 holes of 1,690 ± 0,005 mm and one hole of 2,950 ± 0,005 mm. The holes may deviate max. 0,01 mm from their true geometrical position. Thickness of gauge 7 mm.
- (2) The ends of the pins are tapered and/or rounded but not brought to a sharp point.

NOTES, see also General Section

 "Diode" electron gun is a triode gun operating in a diode mode, providing a very high beam reserve. Since the "Diode" gun operates with a positive grid 1 voltage, causing some grid current, cameras designed around XQ1410 tubes will require modification.

N.B.

Avoid continuous operation at high beam currents since this will shorten tube life. Full advantage of the high beam reserve to reduce comet-tailing and blooming can be made with DBC circuitry which, during highlights, feeds positive-going pulses derived from the video signal to grid 1, to increase the beam current momentarily.

2. The ''diode'' gun operates with a positive (\leq 15 V) grid 1 voltage (adjusted for correct beam settings, see note 7), hence draws some grid 1 current:

without DBC: ≤ 5 mA (peak) with blanking

with DBC: < 10 mA (peak) with blanking measured with oscilloscope.

The DBC circuitry should, in the case of highlights, supply positive-going pulses of 10 V above V_{q1w} (see note 7) and up to 10 mA peak to grid 1.

N.B.

Applying higher pulses than 10 V is not recommended since this will shorten tube life, impair resolution and may introduce oscillations,

- a. Adjustable light bias. The light bias lamp assembly as supplied with each tube, type 56106, fits
 in the metal tube cemented to the pumping stem of the tube. The tube and the light bias lamp
 assembly will fit properly in the sockets, type 56021 and 56025. The wires should be connected
 to a source, capable of supplying max. 110 mA at 5 V.
 - Considerations and recommendations for the choice of such a source, depending on the application, are supplied with each tube. The light bias lamp projects its light via a blue-green transmitting filter on the pumping stem where it is conducted to the target to cause a bias illumination. The desired amount of light bias can be obtained by adjusting the current through the filament of the lamp. See also note 12.
 - b. Fixed light bias. An adapter is supplied with each tube, connecting a small lamp via a calibrated series resistor to the heater pins. The heater supply should be stabilized at $6.3 \pm 0.1 \text{ V}$ and be capable of supplying an additional current of 95 mA. The adapter is colour coded according to the application of the tube.
- The tube can withstand short excursions up to 70 °C without damage or irreversible degradation in performance.
- For short intervals. During storage the tube face shall be covered with the plastic hood provided; when the camera is idle the lens shall be capped, in stand-by also the beam will be cut-off.
- The operating conditions and performance data quoted relate to operation of the tube in coil unit AT1131. See relevant data of deflection/focusing assemblies.
- The beam current I_b, as obtained by adjusting the control grid (grid 1) voltage is set to 300 nA
 for R and B tubes, 600 nA for black and white, L and G tubes. I_b is not the actual current available
 in the scanning beam, but is defined as the maximum amount of signal current, I_s, that can be
 obtained with this beam.

In the performance figures for lag, the signal current and beam current conditions are given, e.g. as $l_{\rm s}/l_{\rm b}=20/300$ nA. This means: with a signal current of 20 nA and a beam setting which just allows a signal current of 300 nA.

The signal currents are measured with an integrating instrument connected in the signal electrode lead and a uniform illumination of the scanned area.

The peak signal currents as measured on a waveform oscilloscope will be a factor α larger. $\alpha = 100/100$ - β ;

 β being the total blanking time in %, for the CCIR system α = 1,3.

- 8. Typical faceplate illumination level for the XQ3440 and XQ3440L to produce 300 nA signal current will be approx. 3,5 lx. The signal currents stated for the colour tubes R, G and B will be obtained with an incident white light level (2856 K) on the filter of approx. 9 lx. These figures are based on the filters described in note 9. For filter BG12, however, a thickness of 1 mm is chosen.
- Measuring conditions: illuminance level 4,54 lx at a colour temperature of 2856 K and the appropriate filter inserted in the light path. The signal current obtained in nA is a measure of the colour sensitivity expressed in μA per lumen of white light before the filter. Filters used are:

XQ3440R, XQ3445R	Schott	OG570	thickness	3 mm
XQ3440G	Schott	VG9	thickness	1 mm
XQ3440B	Schott	BG12	thickness	3 mm
XQ3443R	Schott	OG570	thickness	3 mm
	and Calflex	B1/K1		

For transmission curves see General Section.

- 10. As measured with a 50 mm Leitz Summicron lens having a sine response of approximately 85% at 400 TV lines at f: 5,6 and the appropriate filter inserted in the light path. The horizontal amplitude response can be raised by means of suitable correction circuits, which affect neither the vertical resolution nor the limiting resolution.
- 11. Build-up lag

After 10 s of darkness. The figures are typical percentages of the ultimate signal current obtained 60 ms and 200 ms, respectively, after the introduction of the illuminance.

Decay lag

After the target has been illuminated for at least 5 s. The figures represent typical signals in percentages of the original signal current 60 ms and 200 ms, respectively, after removal of the illuminance.

- 12. A reduction of lag, especially under low key conditions is obtained when light bias is applied. Infrared light with a wavelength > 600 nm in the light bias should be avoided.
 - For monochrome operation a light bias corresponding to 5 nA dark current is usually adequate for excellent speed of response.
 - b. In a colour camera the speeds of response of the tubes can be balanced by adjusting the amount of light bias per tube.
 - In a 3-tube colour camera for instance it is recommended to first adjust the tubes to their normal highlight signal current and beam current settings and then point the camera at a dark scene comprising a metronome. The moving hand of the metronome carries a small white square. The illuminance should be chosen such that the square produces a peak signal of approximately 50 nA in the green chrominance channel. A maximum of 3 nA artificical dark current shall then be introduced in the green chrominance tube. Subsequently light bias shall be applied to the tubes in the red and blue channels until the lag of the three tubes is neutralized.
- 13. Deviation of the level of any of the four corners, i.e. 10% inwards in H and V direction from the level in the picture centre. With the settings suggested in note 12 black shading compensation in the camera video processing amplifier will not normally be required. Further improvement in lag can be obtained by applying still higher light bias levels. It may then be necessary to use black shading compensation in the video processing amplifier.
- 14. a. With DBC applied (see note 2) the tube will properly handle highlights with a diameter of 10% of the picture height and with a brightness corresponding to 16 times peak signal white, I_{SD}.
 - b. The maximum peak signal currents in the case of highlights will be 2,5 μ A. Video preamplifiers should be designed to accomodate these.

XQ3440 SERIES




Fig. 1 Typical spectral response for XO3440, L, G, B.




Fig. 3 Typical spectral response for XQ3445R,




Fig. 2 Typical spectral response for XQ3443R.




Fig. 4 Typical square wave response curves.

notes 1 2

CAMERA TUBES

Plumbicon[®], 30 mm/45 mm diameter television camera tubes with very high resolution lead-oxide photoconductive target, exclusively intended for use with X-ray image intensifiers in medical equipment. Special features are:

- Large scan area,
- New photoconductive target for increased resolution,
- "Diode" electron gun for high beam reserve, improved beam acceptance, low lag,
- Low output capacitance for high signal-to-noise ratio.

QUICK REFERENCE DATA

"Diode" electron aun

Diode ciccion gan	110 203 1, 2
Diameter	47 mm/30 mm
Length	≈ 216 mm
Focusing	magnetic
Deflection	magnetic
Useful target area; circle, diameter	26 mm
Spectral response	
max, at	≈ 500 nm
cut-off at	\approx 850 to 950 nm
Sensitivity, typ.	115 μA/ImF
Modulation depth at 400 TV lines (5 MHz)	95%
Heater	6,3 V, 190 mA

OPTICAL DATA notes

Dimensions of quality area of target, circle of 26 mm diameter

Orientation of image on target.

For correct orientation of the image on the target the vertical scan should be essential parallel to the plane through the tube axis and the index pin.

Faceplate

Thickness 3 mm
Refractive index 1,49 mm

Anti halation glass disc

Thickness 8 mm
Refractive index 1.52 mm

ACCESSORIES

Socket type 56021
Deflection and focusing coil unit type AT1107

® Registered Trade Mark for TV camera tube.

3

ELECTRICAL DATA

DEFLECTION

magnetic

FOCUSING

magnetic

HEATING

Indirect by a.c. or d.c.

Heater voltage

 V_f

6,3 V ± 5 %

50 V

Heater current, nom.

lf 190 mA

max.

The heater voltage must never exceed 9,5 V (r.m.s.). For optimum performance stabilization of the heater voltage is recommended.

CAPACITANCE

notes

Signal electrode to all, typ.

Signal electrode voltage

Cas

5 pF

This capacitance increases slightly when the tube is inserted in the coil unit.

LIMITING VALUES (Absolute maximum rating system)

All voltages are referred to the cathode, unless otherwise stated.

	as					
Grid 4 (mesh) voltage	V_{g4}	max.	1100	V		
Grid 3 voltage	V_{g3}	max.	800	V		
Voltage between grid 4 and grid 3	V_{g4}/V_{g3}	max.	450	V	5	
Grid 2 voltage	V_{g2}	max.	350	V		
Grid 1 voltage positive	V_{g1}	max.	20	V		
Grid 1 voltage negative	$-V_{g1}$	max.	125	V		
Grid 1 current (≈ cathode current)	l _{g1}	max.	10	mA	4	
Cathode to heater voltage, positive peak	V _{kfp}	max.	50	V		
Cathode to heater voltage, negative peak	$-V_{kfp}$	max.	125	·V		
Cathode heating time before drawing cathode current	th	min.	1	min		
External resistance between cathode and heater						
at $V_{kf} > 10 V$	Rkf	min.	2	kΩ		
Ambient temperature, storage and operation	T _{amb}	max. min.	50 -30	°C	6	
Faceplate temperature, storage and operation	Т	max. min.	50 -30	oC oC		
Faceplate illuminance	E	max.	500	lx		

Gamma of transfer characteristic

OPERATING CONDITIONS AND PERFORMANCE					notes
Conditions					
Cathode voltage	V_k		0	V	
Signal electrode voltage	Vas		45	V	
Beam current	lb				8,9
Grid 4 voltage	V _{q4}		960	V	5
Grid 3 voltage	V_{g3}		600	V	5
Grid 2 voltage	V_{q2}		300	V	
Grid 1 voltage	V_{g1}	0	to 20	V	
Blanking voltage on grid 1, peak-to-peak	Vg1p-p		25	V	
Focusing and deflection coil currents					10
Faceplate illuminance	E	0	to 10	lx	
Faceplate temperature	T_{as}	20	to 40	oC	
ELECTRON GUN CHARACTERISTICS					
Cut-off Grid 1 voltage for cut-off at V _{g2} = 300 V					
without blanking	V_{g1}	-1	0 to 0	V	
Grid 1 voltage for normal beam current	V_{g1w}		9	V	
Blanking voltage with respect to	V/		25	1/	
V _{g1w} , peak-to-peak, on grid 1 on cathode	V _{g1p-p}		25		
	V _{kp-p}				
Grid 1 current at normally required beam currents	g1	\left\		mA	
Grid 2 current at normally required beam currents	g2	\leq	0,1	mA	
Performance					
Dark current	ld	<	3	nA	
Sensitivity at colour temperature of 2856 K		typ.	115	μA/ImF	11
Sensitivity with P20 light source		typ.	350	$\mu A/Im$	
Peak signal current with E = 1 lx (P20)	Isp	typ.	420	nA	12
Peak signal current (26 mm dia.)			3500	nA	
Spectral response: max. response at		\approx	500	nm	
Spectral response: cut-off at		850 t	o 950	nm	
Spectral response curve	see Fig.	2			

 $0,95 \pm 0,05$

XQ4502 SERIES

Resolution notes

Modulation depth, i.e. uncompensated amplitude response at 400 TV lines at centre of the picture.

XQ4502	
400 nA	1 1 1 1
800 nA	
95	
90	
	400 nA 800 nA 95

13

8,14,15,16

Limiting resolution 2500 TV lines


Modulation transfer characteristic see Fig. 5
Lag (typical values, no light bias applied)


Light source with a colour temperature of 2856 K. Appropriate filter inserted in light path.


Low key conditions (percentage) see Figs 3 and 4

MECHANICAL DATA

Dimensions in mm







Mounting position: any

Mass ≈ 125 g

XQ4502 SERIES

NOTES, see also General Section

- Diode Gun is a triode gun operating in a diode mode, providing a very high beam reserve.
 Continuous operation with a high beam setting is to be avoided since this will shorten tube life.
 High I_b settings should be used under high light intensity conditions only, such as pulsed mode and rad mode. All other modes of operation should use normal I_b settings or have beam cut off.
- 2. The Diode Gun requires a positive grid 1 voltage, and draws some grid current.
- Underscanning of the specified target area (26 mm diam.), or failure of scanning, should be avoided since damage to the target may occur. Cathode blanking should be used to provide a circular image. Video blanking could cause beam to scan mesh ring, with possible consequent degradation of tube life.
- A current limiter must be incorporated to limit total cathode current to 10 mA maximum.
 Camera design should allow for 10 mA operation.
- 5. The optimum voltage ratio V_{g4}/V_{g3} to minimize beam landing errors (preferable < 1 V) depends on the type of coil used. For type AT1107, a ratio of 1,7 is recommended. Under no circumstances should grid 4 (mesh) be allowed to operate at a voltage below that of grid 3 as this may damage the target.
- The tube can withstand short excursions to 70 °C without any damage or irreversible degradation in performance.
- 7. This rating is for short intervals only. During storage the tube must be covered (a plastic hood is provided for this purpose) and when the camera is idle the lens must be capped. If camera is in standby operation, the lens must be capped and the beams turned off.
- 8. The beam current I_b, as obtained by adjusting the control grid voltage (grid 1), is set at 800 nA. I_b is not the total current available in the scanning beam, but is defined as the maximum amount of signal current, I_s, with this particular beam setting. In the performance figures, e.g. for resoltuion and lag, the signal current and beam current conditions are given e.g. as I_s/I_b = 400/800 nA. This means: with signal current of 400 nA and a beam setting which just allows a signal current of 800 nA.
 - N.B. The signal currents are measured with an integrating instrument connected in the signal electrode lead and a uniform illumination of the scanned area. The peak signal currents as measured on a waveform oscilloscope will be a factor α larger. See note 12.
- 9. The maximum peak signal which the XQ4502 can handle is 4 μ A. Video amplifiers should be designed to accommodate this.
- See published data of deflection/focusing assemblies. The direction of the current through the
 focusing coil should be cosen such that a north-seeking pole will be attracked at the faceplate
 end of the coil.
- Measuring conditions: Illuminance level 3,1 lx at colour temperature of 2856 K. Filters Schott VG9 (1 mm) and Calflex B1/K1 inserted in the light path. For transmission curves see General Section.
- 12. The peak signal currents are measured on a waveform oscilloscope and with a uniform illumination on the 26 mm ϕ target area. When measured with an integrating instrument connected in the signal-electrode lead the average signal currents will be smaller:
 - a. By a factor α ($\alpha = \frac{100 \cdot \beta}{100}$), β being the total blanking time in %: for the CCIR system α amounts to 0.75.
 - b. By a factor δ , δ being the ratio of the active target area (circle with 26 mm ϕ) to the area which would correspond with the adjusted scanning amplitudes (26 mm x 34,6 mm) this ratio amounts to δ = 0,59.

The total ratio of integrated signal current, I_S, to the peak signal current, I_{SP}, amount to $\alpha \times \delta = 0.44$.

the illumination has been applied.

- 13. As measured with a 50 mm Leitz Summicron lens having a sine response of approximately 96% at 8 lp/mm (400 TV lines at 26 mm dia.) at f: 5,6. The published 95% typ. is uncorrected. Tube resolution is higher.
 - The horizontal amplitude response can be raised by means of suitable correction circuits, which affect neither the vertical resolution nor the limiting resolution.

lag represent the typical percentages of the ultimate signal obtained as a function of time, after

- 14. Measured with 100 nA signal current and a beam current just sufficient to stabilize a signal current of 800 nA.
 15. Build-up lag. After 10 seconds of complete darkness. Values and curves shown relating to build-up
- 16. Decay lag. After a minimum of 5 seconds of illumination of the target. Values and curves shown relating to decay lag represent the residual signal currents in percentages of the original signal current as a function of time, after the illumination has been removed.

XQ4502 SERIES




Fig. 1 Beam current versus grid 1 voltage, typical, see note 9.





Fig. 3 Build-up lag, $I_{\rm s}/I_{\rm b}=100/800~{\rm nA}$ without bias light. (Lag can be improved by using bias light).






Fig. 2 Typical spectral response.





Fig. 4 Decay lag, $I_{\rm S}/I_{\rm b}=100/800$ nA without bias light. (Lag can be improved by using bias light).

Fig. 5 Typical square wave response curve.

25,4 mm dia. PLUMBICON TUBES



CAMERA TUBES

25,4 mm (1 in) diameter Plumbicon[®] television camera tubes, with standard resolution lead-oxide photoconductive target, for use in high quality monochrome or colour cameras for broadcast, educational or industrial applications.

The XQ1070 series comprises the following front loading versions:

XQ1070	for use in monochrome cameras
XQ1070L	for use in the luminance channel of colour cameras
XQ1070R	for use in the red channel
XQ1070G	for use in the green channel
XQ1070B	for use in the blue channel
XQ1071	as XQ1070 series; only difference being the degree of freedom from blemishes
	on the target (industrial quality tubes)
XQ1073R	for use in the red channel; extended red response
XQ1074	as XQ1073, Industrial grade
XQ1075R	for use in the red channel; extended red response and IR filter
XQ1076	as XQ1075. Industrial grade

Mechanical variants of the XQ1070 series are also available. Such variants are defined by a suffix as follows:

 $XQ\dots$ /02, R, G, B, L: rear loading versions with provision for internal light bias, target contact ring with 2 target contacts, metal sleeve on pumping stem to mount bias lamp,

XQ..../03, R, G, B, L: front loading versions with provision for internal light bias, metal ring target contact, metal sleeve on pumping stem to mount bias light lamp.

Special features are:

- Mechanically interchangeable with 1 inch Vidicon tubes with separate mesh.
- Same resolving power as the 30 mm tubes from the XQ1020 series.

QUICK REFERENCE DATA

Separate mesh			
Diameter		25,4	mm (1 inch)
Length	approx	165	mm
Provided with anti-halation glass disc			
Focusing	magnet	ic	
Deflection	magnet	ic	
Useful target area (scanning area)	9,	6 x 12,8	mm
Spectral response			
max, at	approx	500	nm
cut-off: XQ1070	approx	650	nm
XQ1073	approx	. 850	to 950 nm
XQ1075	approx	750	nm
Sensitivity			
XQ1070, XQ1070L	typ.	400	μ A/Im
XQ1070R	typ.	80	μA/ImF
XQ1070G	typ.	165	μA/ImF
XQ1070B	typ.	38	μA/ImF
XQ1073R, XQ1075R	typ.	115	μA/ImF
Resolution at 400 TV lines (5 MHz)			
XQ1070, XQ1070L	typ.	40	%
XQ1070R	typ.	35	%
XQ1070G	typ.	40	%
XQ1070B	typ.	50	%
XQ1073R, XQ1075R	typ.	45	%
Heater		6,3	V, 95 mA

[®] Registered trademark for television camera tubes.

XQ1070 SERIES

OPTICAL DATA

notes

Quality rectangle on

photoconductive target (aspect ratio 3:4)

9.6 x 12.8 mm

Orientation of image on target:

For correct orientation of the image on the target the vertical scan should be essentially parallel to the plane passing through the tube axis and the marker line on the protecting sleeve at the base.

Faceplate

Thickness

 $1,2 \pm 0,1 \text{ mm}$ n = 1.49

Refractive index

Anti-halation glass disc provided with

anti-reflective coating

Thickness Refractive index 5 ± 0,1 mm n = 1,52

XQ1075R is provided with infrared reflecting filter

ACCESSORIES

Socket

Deflection and focusing coil unit:

type 56098 or equivalent rear loading front loading

Black/white

type AT1126S

Colour

type AT1126T

type 56028

Mask for flare reduction Light bias lamp in holder for versions /02 and /03

type 56106

1

AT1116/06S AT1116/06T

ELECTRICAL DATA

Deflection

Focusing

magnetic magnetic

Heating, indirect by a.c. or d.c.; parallel supply

Heater voltage

6.3 V ± 5% Vf

Heater current at V_f = 6,3 V

If nom.

95 mA

The heater voltage must not exceed an

r.m.s. value of 9,5 V. For optimum

performance (lifetime and registration stability)

stabilization of the heater voltage is recommended.

Capacitance

Signal electrode to all

rear loading types

Cas Cas

2.5 to 3.5 pF 3 to 5 pF

front loading types This capacitance, which is effectively the

output impedance, increases when the tube is inserted in the coil unit.

						-
LIMITING VALUES (About to accompany)	\					otes
LIMITING VALUES (Absolute maximum rating system					110	otes
Unless otherwise stated, all voltages are referred to the		1		17		
Signal electrode voltage	Vas	max.	50			
Grid 4 voltage	V _g 4		1100			
Grid 3 voltage	V _{g3}	max.				
Voltage between grid 4 and grid 3	Vg4/g3	max.				
Grid 2 voltage	V_{g2}	max.	350	V		
Grid 1 voltage						
positive	V _{g1}	max.	0.000	V		
negative	$-V_{g1}$	max.	125	V		
Cathode to heater voltage	17		105			
positive peak	Vkfp	max.				
negative peak	$-V_{kfp}$	max.	50	V		
Cathode heating time before						
drawing current	th	min.	- 1	min		
External resistance between cathode			_			
and heater at $-V_{kfp} > 10 V$	Rkf	min.	770	kΩ		
Ambient temperature, storage and operation	Tamb	max.		oC		
Ambient temperature, storage and operation	· amb	min.				
Faceplate temperature, storage and operation	Т	max.		oC		2
Tucopiate temperature, storage and operation		min.	Val. (1997)			
Faceplate illuminance	E	max.	500	lx		3
OPERATING CONDITIONS						
For a scanned area of 9,6 x 12,8 mm						4
Cathode voltage	Vk		0	V		
Signal electrode voltage	Vas		45	V		
Beam current	l _b					5
Grid 4 voltage	V _{g4}		960	V		
Grid 3 voltage	V_{g3}		600	V		
Grid 2 voltage	V_{g2}^{g3}		300	V		
Grid 1 voltage	V_{g1}^{g2}			V		5
Blanking voltage on grid 1, peak to peak	Vg1p-p		50	V		
Faceplate illuminance	E	(to 10	lx		6
Faceplate temperature	Т	20) to 45	oC		2
adoptato tomporataro						
ELECTRON GUN CHARACTERISTICS						
Cut off						
Grid 1 voltage for cut-off at $V_{q2} = 300 \text{ V}$,						
without blanking	V_{g1}	-35 tc	-100	V		
Blanking voltage, peak to peak	91					
on grid 1	V_{g1p-p}	5	0 ± 10	V		
on cathode	V _{kp-p}		25			
Grid 2 current at normally required	· kh-h					
beam currents	lg2	<	0,5	mA		
	92					

XQ1070 SERIES

PERFORMANCE						notes
Dark current	ld		\leq	3	nA	
Sensitivity at colour temperature of illuminance = 2						7
XQ1070, XQ1070L	min.	375	typ.	400	$\mu A/Im$	
XQ1070R	min.	70	typ.	80	μA/ImF	
XQ1070G	min.	130	typ.	165	μA/ImF	
XQ1070B	min.	35	typ.	38	μA/ImF	
XQ1073R, XQ1075R	min.	75	typ.	115	$\mu A/ImF$	
Gamma of transfer characteristics			0,95 ±	0,05		
Spectral response, max. at				500	nm	
Spectral response, cut-off at			650 t	o 950	nm	
Spectral response curves	see Fi	gs 1, 2 ar	1d 3			
Resolution						8

Modulation depth, i.e. uncompensated amplitude response at 400 TV lines at the centre of the picture.

	XQ1070 XQ1070L XQ1070G	XQ1070R	XQ1070B	XQ1073R XQ1075R		5
Highlight signal current I _s Beam current I _b Modulation depth at 400 TV lines	200 400	100 200	100 200	100 200	nA nA	
typ. min.	40 35	35 30	50 45	40 35	%	

Modulation transfer characteristics: see Figs 4 and 5

Lag (typical values, without light bias)

11, 12

Light source with a colour temperature of 2856 K. Appropriate filter inserted in the light path for the chrominance tubes R, G and B.

LOW KEY CONDITIONS

	build-up lag I _S /I _b = 20/300 nA		decay lag I _s /I _b = 20/300 nA		
	60 ms	200 ms	60 ms	200 ms	
XQ1070, XQ1070L	95%	≈ 100%	9%	3%	
XQ1070G	95%	≈ 100%	9%	3%	
XQ1070R	90%	≈ 100%	11%	4%	
XQ1070B	90%	≈ 100%	11%	4%	
XQ1073R, XQ1075R	85%	≈ 100%	11%	4%	


Shading of light bias induced dark current


12,5%


MECHANICAL DATA

Mounting position: any Mass: approx. 60 g

Base: JEDEC E8-11, IEC 67-I-33a










XQ1070/03

XQ1070 SERIES










(1) The distance between the geometrical centres of diameter A of the reference ring and diameter B of the mesh electrode ring is < 100 μ m.

XQ1070/02







XQ1070/02 XQ1070/03

NOTES, see also General Section.

1. For adjustable light bias in versions /02 and /03.

The light bias lamp assembly as supplied with each tube, type 56106, fits in the metal tube cemented to the pumping stem of the tube. The tube and the light bias lamp assembly will fit properly in the socket. The wires should be connected to a source, capable of supplying max. 110 mA at 5 V. Considerations and recommendations for the choice of such a source, depending on the application, are supplied with each tube. The light bias lamp projects its light via a bluegreen transmitting filter on the pumping stem where it is conducted to the target to cause a bias illumination. The desired amount of light bias can be obtained by adjusting the current through the filament of the lamp. See also note 10.

- The tube can withstand short excursions up to 70 °C without damage or irreversible degradation in performance.
- For short intervals. During storage the tube face shall be covered with the plastic hood provided; when the camera is idle the lens shall be capped, in stand-by also the beam will be cut-off.
- The operating conditions and performance data quoted relate to operation of the tube in coil units AT1116 or AT1126. See relevant data of deflection/focusing assemblies.
- The beam current I_b, as obtained by adjusting the control grid (grid 1) voltage is set to 200 nA for R and B tubes, 400 nA for black and white, L and G tubes. I_b is not the actual current available in the scanning beam, but is defined as the maximum amount of signal current, I_s, that can be obtained with this beam.

In the performance figures for lag, the signal current and beam current conditions are given, e.g. as $I_s/I_b = 20/300$ nA. This means: with a signal current of 20 nA and a beam setting which just allows a signal current of 300 nA.

N.B. The signal currents are measured with an integrating instrument connected in the signal electrode lead and a uniform illumination of the scanned area. The peak signal currents on a waveform oscilloscope will be a factor α larger.

$$\alpha = \frac{100}{100 - \beta} \; ;$$

 β being the total blanking time in %; for CCIR system α = 1,3.

- 6. Typical faceplate illumination level for the XQ1070 and XQ1070L to produce 200 nA signal current will be approx. 4 lx. The signal currents stated for the colour tubes R, G and B will be obtained with an incident white light level (2856 K) on the filter of approx. 10 lx. These figures are based on the filters described in note 7. For filter BG12, however, a thickness of 1 mm is chosen.
- 7. Measuring conditions: illuminance level 4,54 lx at a colour temperature of 2856 K and the appropriate filter inserted in the light path. The signal current obtained in nA is a measure of the colour sensitivity expressed in µA per lumen of white light before the filter. Filters used are:

XQ1070R, XQ1075R	Schott	OG570	thickness	3 mm
XQ1070G	Schott	VG9	thickness	1 mm
XQ1070B	Schott	BG12	thickness	3 mm
XQ1073R	Schott	OG570	thickness	3 mm
an	d Calflex	B1/K1		

For transmission curves see General Section.

8. As measured with a 50 mm Leitz Summicron lens having a sine response of approximately 85% at 400 TV lines at f: 5,6 and the appropriate filter inserted in the light path. The horizontal amplitude response can be raised by means of suitable correction circuits, which affect neither the vertical resolution nor the limiting resolution.

9. Build-up lag

After 10 s of darkness. The figures are typical percentages of the ultimate signal current obtained 60 ms and 200 ms, respectively, after the introduction of the illuminance.

Decay lag

After the target has been illuminated for at least 5 s. The figures represent typical signals in percentages of the original signal current 60 ms and 200 ms, respectively, after removal of the illuminance.

- 10. A reduction of lag, especially under low key conditions is obtained when light bias is applied in versions /02 and /03. Infrared light with a wavelength > 600 nm in the light bias should be avoided.
 - a. For monochrome operation a light bias corresponding to 2 to 3 nA extra dark current is usually adequate for excellent speed of response.
 - b. In a colour camera the speeds of response of the tubes can be balanced by adjusting the amount of light bias per tube.

In a 3-tube colour camera, for instance, it is recommended first to adjust the tubes to their normal highlight signal current and beam current settings and then point the camera at a dark scene comprising a metronome. The moving hand of the metronome carries a small white square. The illuminance should be chosen such that the square produces a peak signal of approximately 50 nA in the green chrominance channel. A maximum of 3 nA artificial dark current shall then be introduced in green chrominance tube. Subsequently light bias shall be applied to the tubes in the red and blue channels until the lag of the three tubes is neutralized.

11. Deviation of the level of any of the four corners, i.e. 10% inwards in H and V direction from the level in the picture centre. With the settings suggested in note 10 black shading compensation in the camera video processing amplifier will not normally be required. Further improvement in lag can be obtained by applying still higher light bias levels. It may then be necessary to use black shading compensation in the video processing amplifier.




Fig. 1 Typical spectral response for XQ1070, L, G, B, R.




Fig. 2 Typical spectral response for XQ1073R.




Fig. 3 Typical spectral response for XQ1075R.




Fig. 4 Typical square-wave response curves for XQ1070.




Fig. 5 Typical square-wave response curves for XQ1073 and XQ1075.

6.3 V, 95 mA

15 mm

CAMERA TUBE

25,4 mm (1 inch) diameter Plumbicon[®] television camera tube, with standard resolution lead-oxide photoconductive target. The XQ1072 is exclusively intended for use with X-ray image intensifiers with P20 output phosphor in medical equipment.

QUICK REFERENCE DATA

Diameter		25,4	mm (1 inch)
Length	approx.	160	mm
Focusing	magnetic		
Deflection	magnetic		
Useful target area, circle, diameter		15	mm
Spectral response			
max, at	approx.	500	nm
cut-off:	approx.	650	nm
Sensitivity, P20 light source	typ.	500	μ A/Im
Resolution at 13 lp/mm (5 MHz)		70	%

OPTICAL DATA

Heater

Quality area on photoconductive target, circle, diameter

Orientation of image on target:

For correct orientation of the image on the target the vertical scan should be essentially parallel to the plane passing through the tube axis and the marker line on the protecting sleeve at the base

Faceplate

Thickness 1,2 \pm 0,1 mm Refractive index n = 1,49 Without anti-halation glass disc

ACCESSORIES

Socket type 56098
Deflection and focusing coil unit type AT1116S

ELECTRICAL DATA

Deflection magnetic Focusing magnetic

Heating, indirect by a.c. or d.c.;

Heater voltage $V_f = 6.3 \text{ V} \pm 5\%$ Heater current at $V_f = 6.3 \text{ V} \pm 16\%$

The heater voltage must not exceed an r.m.s. value of 9,5 V. For optimum performance stabilization of the heater voltage is recommended.

Capacitance

Signal electrode to all C_{as} 3 to 5 pF

This capacitance, which is effectively the output impedance, increases when the tube is inserted in the coil unit.

® Registered trademark for television camera tubes.


LIMITING VALUES (Absolute maximum rating syst Unless otherwise stated, all voltages are referred to the				notes
Signal electrode voltage	Vas	max.	50 V	
Grid 4 voltage	V_{g4}	max. 11	00 V	
Grid 3 voltage	V_{g3}	max. 8	00 V	
Voltage between grid 4 and grid 3	Vg4/g3	max. 4	50 V	
Grid 2 voltage	V_{g2}	max. 3	50 V	
Grid 2 dissipation	W _{g2}	max.	1 W	
Grid 1 voltage,				
positive	V_{g1}	max.	0 V	
negative	$-v_{g1}$	max. 1	25 V	
Cathode to heater voltage	4.4			
positive peak	V_{kfp}		25 V	
negative peak	$-V_{kfp}$	max.	50 V	
Cathode heating time before drawing				
cathode current	th	min.	1 min	
External resistance between cathode	-		0.10	
and heater at $-V_{kfp} > 10 V$	Rkf	min.	2 kΩ	
Ambient temperature, storage and operation	Tamb		0 °C	
	umb		30 °C	1
Faceplate temperature, storage and operation	Т		0 °C	. 1
F 1-1- 70 1	Е		30 °C	0
Faceplate illuminance	Е	max. 50	00 lx	2
OPERATING CONDITIONS				
For a scanned circular area with a diameter of 15 mm				3
Cathode voltage	V_k		0 V	
Signal electrode voltage	Vas	4	15 V	
Beam current	lb			4
Grid 4 voltage	V_{g4}		00 V	
Grid 3 voltage	V_{g3}		00 V	
Grid 2 voltage	V_{g2}	30	00 V	
Grid 1 voltage	V _{g3} V _{g2} V _{g1}		V	4
Blanking voltage on grid 1, peak to peak	V _{g1p-p}	50 ±	10 V	
Faceplate illuminance		approx.		
Faceplate temperature	Т	20 to 4	15 °C	
ELECTRON GUN CHARACTERISTICS				
Cut off				
Grid 1 voltage for cut-off at $V_{g2} = 300 \text{ V}$,				
without blanking	V_{q1}	-35 to -10	00 V	
Blanking voltage, peak to peak at $V_{q2,4} = 300 \text{ V}$,	9.			
on grid 1	V _{g1p-p}	50 ± 1	0 V	
on cathode	V _{kp-p}	1-1	25 V	
Grid 2 current at normally required				
beam currents	lg2	≤ 0	,5 mA	


PERFORMANCE						notes
Dark current	Id		\leq	3	nA	
Sensitivity at colour temperature						
of illuminance = 2856 K	min.	130	typ.		μA/ImF	5
Sensitivity with P20 light source	min.	395	typ.		μ A/Im	
Peak signal current with E = 1 Ix (P20)	min.	160	typ.	200	nA	6
Gamma of transfer characteristic			$0.95 \pm$	0,05		
Spectral response,						
max. at	approx			500	nm	
cut-off at	approx			650	nm	
Spectral response curve	see Fig.	. 1				
Resolution						
Modulation depth, i.e. uncompensated						7
amplitude response at 13 lp/mm						
(scanned area circle, diameter 15 mm)						
at the centre of the picture.						
(5 MHz, 400 TV lines)			typ.	70	%	
Modulation transfer characteristic	see Fig.	. 2				
Decay lag, P20 light source, measured with						
a signal current of 200 nA, beam adjusted						
for correct stabilization after the target						
has been illuminated for at least 5 s.						
Residual signal after dark pulse						
of 60 ms	max.	6	typ.	4	%	
of 200 ms	max.	2,5	typ.	1,5	%	


MECHANICAL DATA


Mounting position: any Net mass: approx. 60 g

Base: IEC 67-I-33a (JEDEC E8-11)










NOTES, see also General Section

- The tube can withstand short excursions up to 70 °C without damage or irreversible degradation in performance.
- For short intervals. During storage the tube face shall be covered with the plastic hood provided; when the camera is idle the lens shall be capped, in stand-by also the beam will be cut-off.
- 3. The operating conditions and performance data quoted relate to operation of the tube in coil unit AT1116S. See relevant data of deflection/focusing assemblies. Scanning amplitude should be adjusted such that the useful target area of 15 mm is displayed on a standard monitor as a circular area with a diameter equal to the raster height.
- 4. The beam current I_b, as obtained by adjusting the control grid (grid 1) voltage is set to max. 500 nA. I_b is not the actual current available in the scanning beam, but is defined as the maximum amount of signal, I_c, that can be obtained with this beam. See note 6.
- Measuring conditions: illuminance level 4,54 lx at a colour temperature of 2856 K and a filter Schott VG9 inserted in the light path. For transmission of the filter, see General Section.
- 6. The peak signal currents are measured on a waveform oscilloscope and with a uniform illumination on the 15 mm diameter target area. When measured with an integrating instrument connected in the signal-electrode lead the average signal currents will be smaller:
 - a. by a factor $\alpha=100-\beta/100$, β being the total blanking time in %; for the CCIR system α amounts to 0.75.
 - b. by a factor δ , δ being the ratio of the active target area (circle with 15 mm diameter) to the area which would correspond with the adjusted scanning amplitudes (15 x 20 mm). This ratio amounts to δ = 0,59. The total ratio of integrated signal current, I_s, to the peak signal current, I_{sp}, amounts to α x δ = 0.44.
- 7. As measured with a 50 mm Leitz Summicron lens having a sine response of approximately 85% at 400 TV lines at f: 5,6. The published 70% typ. is uncorrected. Tube resolution is higher. Measured with 100 nA signal current and a beam current just sufficient to stabilize a signal current of 500 nA. The horizontal amplitude response can be raised by means of suitable correction circuits, which affect neither the vertical resolution nor the limiting resolution.








Fig. 2 Typical square-wave response curve.

210:01

A ROLL OF THE LOCAL PROPERTY OF THE LOCAL PR

CAMERA TUBE

25.4 mm (1 inch) diameter Plumbicon® television camera tube, with high resolution lead-oxide photoconductive target. The XQ1073X is provided with a green BG18 anti halation glass disc for reduction of flare and is exclusively intended for use with X-ray image intensifiers with P20 output phosphor in medical equipment.

QUICK REFERENCE DATA

Diameter		25,4	mm (1 inch)	
Length	approx.	162	mm	
Focusing	magnetic			
Deflection	magnetic			
Useful target area, circle, diameter		15	mm	
Spectral response				
max. at	approx.	500	nm	
cut-off:	approx.	650	nm	
Sensitivity, P20 light source	typ.	485	μA/Im	
Resolution at 13 lp/mm (5 MHz)		75	%	
Heater		6,3	V, 95 mA	

OPTICAL DATA

Quality area on photoconductive target, circle, diameter

15 mm

Orientation of image on target:

For correct orientation of the image on the target the vertical scan should be essentially parallel to the plane passing through the tube axis and the marker line on the protecting sleeve at the base.

Faceplate

Thickness 1.2 ± 0.1 mm n = 1.49Refractive index With anti-halation glass disc, BG18

Thickness 1,07 ± 0,05 mm Refractive index n = 1.53

ACCESSORIES

Socket type 56098 Deflection and focusing coil unit type AT1116S

ELECTRICAL DATA

Deflection magnetic Focusing magnetic

Heating, indirect by a.c. or d.c.;

Heater voltage 6.3 V ± 5% 95 mA Heater current at V_f = 6.3 V If nom.

The heater voltage must not exceed an r.m.s. value of 9,5 V. For optimum performance stabilization of the heater voltage is recommended.

Capacitance

Signal electrode to all Cas 3 to 5 pF This capacitance, which is effectively the output impedance,

increases when the tube is inserted in the coil unit. ® Registered trade mark for television camera tubes.

LIMITING VALUES (Absolute maximum rating system)			notes
Unless otherwise stated, all voltages are referred to the ca	athode.			
Signal electrode voltage	Vas	max. 50	V	
Grid 4 voltage	V_{q4}	max. 1100	V	
Grid 3 voltage	V _{g3}	max. 800		
Voltage between grid 4 and grid 3	Vg4/g3	max. 450	V	
Grid 2 voltage	V_{a2}	max. 350	V	
Grid 2 dissipation	W _{g2}	max. 1	W	
Grid 1 voltage, positive	V _{a1}		V	
Grid 1 voltage, negative	$-v_{g1}$	max. 125	V	
Cathode to heater voltage				
positive peak	V_{kfp}	max. 125		
negative peak	$-V_{kfp}$	max. 50	V	
Cathode heating time before drawing				
cathode current	th	min. 1	min	
External resistance between cathode	-			
and heater at $-V_{kfp} > 10 \text{ V}$	Rkf	100000000	kΩ	
Ambient temperature, storage and operation	Tamb	100,000,000	oC	
	dillo	min. -30		
Faceplate temperature, storage and operation	T		oC	1
Ferendate illuminance	E	min30		2
Faceplate illuminance	_	max. 100	IX	2
OPERATING CONDITIONS				
For a scanned circular area with a diameter of 15 mm				3
Cathode voltage	Vk	0	V	
Signal electrode voltage	Vas	45	V	
Beam current	lb			4
Grid 4 voltage	V_{q4}	960	V	
Grid 3 voltage	V_{g3}	600	V	
Grid 2 voltage	V_{q2}	300	V	
Grid 1 voltage	Vg1		V	4
Blanking voltage on grid 1, peak to peak	Vg1p-p	50 ± 10	V	
Faceplate illuminance	E	app. 0	lx	
Faceplate temperature	Т	20 to 45	oC	
ELECTRON GUN CHARACTERISTICS				
Cut off Grid 1 voltage for cut-off at $V_{q2} = 300 \text{ V}$,				
without blanking Blanking voltage, peak to peak at V _{q2,4} = 300 V,	V _{g1}	−35 to −100	V	
on grid 1	V _{g1p-p}	50 ± 10	V	
on cathode	V _{kp-p}	25		
Grid 2 current at normally required				
beam currents	lg2	≤ 0,5	mA	


PERFORMANCE					n	otes
Dark current	ld		<	3	nA	
Sensitivity at colour temperature						
of illuminance = 2856 K	min.	90	typ.	115	μA/ImF	5
Sensitivity with P20 light source	min.	400	typ.	485	$\mu A/Im$	
Peak signal current with E = 1 1x (P20)	min.	160	typ.	195	nA	6
Gamma of transfer characteristic			0,95	0,05		
Spectral response,						
max. at	approx.	ci .		500	nm	
cut-off at	approx.			650	nm	
Spectral response curve	see Fig.	1				
Resolution						7
Modulation depth, i.e. uncompensated						
amplitude response at 13 lp/mm						
(scanned area circle, diameter 15 mm)						
at the centre of the picture.						
(5 MHz, 400 TV lines)			typ.	75	%	
Modulation transfer characteristic	see Fig.	2				
Decay lag, P20 light source, measured with						
a signal current of 200 nA, beam adjusted						
for correct stabilization after the						
target has been illuminated for at least 5 s.						
Residual signal after dark pulse						
of 60 ms	max.	6	typ.	4	%	
of 200 ms	max.	2,5	typ.	1,5	%	


MECHANICAL DATA


Mounting position: any

Mass: approx. 60 g

Base: JEDEC E8-11, IEC 67-I-33a







7Z61434.1

NOTES, see also General Section

- The tube can withstand short excursions up to 70 °C without damage or irreversible degradation in performance.
- For short intervals. During storage the tube face shall be covered with the plastic hood provided; when the camera is idle the lens shall be capped, in stand-by also the beam will be cut-off.
- 3. The operating conditions and performance data quoted relate to operation of the tube in coil unit AT1116S. See relevant data of deflection/focusing assemblies. Scanning amplitude should be adjusted such that the useful target area of 15 mm is displayed on a standard monitor as a circular area with a diameter equal to the raster height.
- 4. The beam current I_b, as obtained by adjusting the control grid (grid 1) voltage is set to max. 500 nA. I_b is not the actual current available in the scanning beam, but is defined as the maximum amount of signal, I_s, that can be obtained with this beam. See note 6.
- Measuring conditions: illuminance level 4,54 Ix at a colour temperature of 2856 K and a filter Schott VG9 inserted in the light path. For transmission of the filter, see General Section.
- 6. The peak signal currents are measured on a waveform oscilloscope and with a uniform illumination on the 18 mm diameter target area. When measured with an integrating instrument connected in the signal-electrode lead the average signal currents will be smaller:
 - a. by a factor α , ($\alpha = \{100 \beta\}/100$, β being the total blanking time in %; for the CCIR system α amounts to 0,75.
 - b. by a factor δ , δ being the ratio of the active target area (circle with 15 mm diameter) to the area which would correspond with the adjusted scanning amplitudes (15 x 20 mm). This ratio amounts to δ = 0,59. The total ratio of integrated signal current, I_{SD}, amounts to α x δ = 0,44.
- 7. As measured with a 50 mm Leitz Summicron lens having a sine response of approximately 85% at 400 TV lines at f: 5,6. The published 75% typ. is uncorrected. Tube resolution is higher. Measured with 100 nA signal current and a beam current just sufficient to stabilize a signal current of 500 nA. The horizontal amplitude response can be raised by means of suitable correction circuits, which affect neither the vertical resolution nor the limiting resolution.




Fig. 1 Typical spectral response.




Fig. 2 Typical square-wave response curve.

CAMERA TUBES

25,4 mm (1 inch) diameter Plumbicon[®] television camera tubes, with standard resolution lead-oxide photoconductive target, for use in high quality monochrome or colour cameras for broadcast, educational or industrial applications.

The XQ1080 series comprises the following versions:

XQ1080	for use in monochrome cameras
XQ1080L	for use in the luminance channel of colour cameras
XQ1080R	for use in the red channel
XQ1080G	for use in the green channel
XQ1080B	for use in the blue channel
XQ1083R	for use in the red channel; extended red response
X01085B	for use in the red channel; extended red response and IR fil-

Special features are:

- Anti-Comet-Tail (ACT) electron gun for highlight handling
- Extremely low lag
- Provisions for light bias to reduce lag
- Target centring ring for precise optical alignment
- Low output capacitance for optimum signal-to-noise ratio
- Rear loading

QUICK REFERENCE DATA

ACT electron gun	
Diameter	25,4 mm (1 inch)
Length	approx. 165 mm
Provided with anti-halation glass disc	
Focusing	magnetic
Deflection	magnetic
Useful target area (scanning area)	9,6 x 12,8 mm
Spectral response	
max, at	approx. 500 nm
cut-off: XQ1080	approx. 650 nm
XQ1083	approx. 850 to 950 nm
XQ1085	approx. 750 nm
Sensitivity	
XQ1080, XQ1080L	typ. $400 \mu A/Im$
XQ1080R	typ. 80 μ A/ImF
XQ1080G	typ. $155 \mu A/ImF$
XQ1080B	typ. $38 \mu A/ImF$
XQ1083R, XQ1085R	typ. $100 \mu A/ImF$
Resolution at 400 TV lines (5 MHz)	
XQ1080, XQ1080L	typ. 40 %
XQ1080R	typ. 35 %
XQ1080G	typ. 40 %
XQ1080B	typ. 50 %
XQ1083R, XQ1085R	typ. 45 %
Heater	6,3 V, 95 mA

[®] Registered trademark for television camera tubes.

OPTICAL DATA notes

Quality rectangle on

9,6 x 12,8 mm photoconductive target (aspect ratio 3:4)

Orientation of image on target:

For correct orientation of the image on the target the vertical scan should be essentially parallel to the plane passing through the tube axis and the marker line on the protecting sleeve at the base

type AT1119/01

type AT1126T

type 56028

type 56027

6.3 V ± 5%

2,5 to 3,5 pF

95 mA

If nom.

Cas

Faceplate

Thickness $1.2 \pm 0.1 \, \text{mm}$ n = 1.49

Refractive index

Anti-halation glass disc provided with anti-reflective coating

Thickness $5 \pm 0.1 \, \text{mm}$ Refractive index n = 1,52

XQ1085R is provided with an infrared reflecting filter

ACCESSORIES

Socket type 56026

Deflection and focusing coil unit:

Black/white

Colour

Mask for flare reduction

Light bias lamp in holder

ELECTRICAL DATA

Deflection magnetic Focusing magnetic

Heating, indirect by a.c. or d.c.; parallel supply

Heater voltage

Heater current at Vf = 6,3 V

The heater voltage must not exceed an r.m.s. value of 9.5 V. For optimum

performance lifetime and registration stability

stabilization of the heater voltage is recommended.

Capacitance

Signal electrode to all

This capacitance, which is effectively the output impedance, increases when the tube is inserted in

the coil unit.

LIMITING VALUES (Absolute maximum rating syst	rom)		notes
AND THE RESERVE OF THE PARTY OF			110163
Unless otherwise stated, all voltages are referred to the	ie catnode.		
Signal electrode voltage	V_{as}	max. 50 V	
Grid 6 (mesh) voltage	V_{g6}	max. 1100 V	
Grid 5 (collector) voltage	V_{g5}	max. 800 V	
Voltage between grid 6 and grid 5	$V_{g6/g5}$	max. 350 V	
Grid 4 (limiter) and grid 2 (accelerator,	3 . 3		
first anode) voltage	$V_{g2,4}$	max. 350 V	
Grid 3 (auxiliary) voltage	V_{g3}	max. 350 V	
Grid 1 (control) voltage	5		
positive	V_{q1}	max. 0 V	
negative	$-v_{g1}$	max. 200 V	
Cathode heating time before drawing			
cathode current	^t h	min. 1 min	
Cathode to heater voltage			
positive peak	V_{kfp}	max. 125 V	
negative peak	$-V_{kfp}$	max. 50 V	
External resistance between cathode			
and heater at $-V_{kfp} > 10 \text{ V}$	Rkf	min. $2 k\Omega$	
		max. 50 °C	
Ambient temperature, storage and operation	T _{amb}	min30 °C	
	Т	max. 50 °C	2
Faceplate temperature, storage and operation	1	min30 °C	2
Faceplate illuminance	E	max. 500 lx	3
OPERATING CONDITIONS with ACT action			4, 5
For a scanned area of 9,6 x 12,8 mm. All voltages			
are specified with respect to the cathode			
potential during the read-out mode,			
unless otherwise indicated.			6, 7, 8
Cathode voltage			
during read-out mode	V_{k}	0 V	
during ACT mode	v _k	0 to 15 V	
Signal electrode voltage	Vas	45 V	
Grid 6 (mesh) voltage	V_{g6}	750 V	9
Grid 5 (collector) voltage	V _{g5}	475 V	
Grid 4 (limiter) and grid 2 (accelerator,	90		
or first anode) voltage	$V_{g2,4}$	300 V	
Grid 3 (auxiliary) voltage	92,7		
during read-out mode	V_{g3}		8
The state of the s	V_{g3}^{g3}		8
during ACT mode	90		
during ACT mode Grid 1 (control) voltage			
			10
Grid 1 (control) voltage	V _{g1} V _{g1}		10 8

XQ1080 SERIES

0.23		XQ1080 XQ1080L	XQ1080R XQ1083R XQ1085R	XQ10	80G	XQ108	0B		
Signal current, peak Beam current, peak ACT level, peak Cathode pulse Grid 1 pulse Grid 3 pulse	I _{sp} I _{bp} V _{kp} V _{g1p} V _{g3p}	0,2 0,4 0,28 8 28	0,1 0,2 0,14 4 24	0,2 0,4 0,2 8 28	В	0,1 0,2 0,14 4 24	4	μΑ μΑ μΑ V V	
Faceplate illuminance Faceplate temperature						0 to 10 0 to 45			11
Cut off Grid 1 voltage for c without blanking oo Blanking voltage, peak on grid 1 Grids 2 and 4 current Grids 3, 5 and 6 curre Pulse timing and ampl	r ACT puls to peak a (d.c. value nt	ses of $V_{g2,4} = 300$	V _{g1r} I _{g2,4} I _{g3,5}			0 –110 60 ± 10 0,2			12 13 13 8
PERFORMANCE	,	,,,,,							
Dark current, without Sensitivity at colour to XQ1080, XQ1080L XQ1080R XQ1080G XQ1080B XQ1083R, XQ1085R	emperature		e = 2856 K min. min. min. min. min.	330 70 130 35 75	typ. typ. typ. typ. typ. typ.	400 80 155 38	nA μA/Im μA/ImF μA/ImF μA/ImF μA/IMF	l all	14
Gamma of transfer cha Light transfer characte Highlight handling Spectral response, max Spectral response, cut XQ1080	eristics wit		see F ≥ 5 I appro	ens stops		± 0,05 500 650	0		15
XQ1083			appro		050	to 950			

notes 16

Resolution

Modulation depth, i.e. uncompensated amplitude response at 400 TV lines at the centre of the picture. The figures shown represent the horizontal amplitude response as measured with a lens aperture f: 5,6.

Modulation transfer characteristics

see Figs 6 and 6a

	XQ1080 XQ1080L	XQ1080R	XQ1080G	XQ1080B	XQ1083R XQ1085R	
Highlight signal current I _S Beam current I _D Modulation depth at 400 TV lines	200	100	200	100	100	nA
	400	200	400	200	200	nA
typ.	40	35	40	50	45	%
min.	35	30	35	45	35	%

Lag (typical values)

17

Light source with a colour temperature of 2856 K. Appropriate filter inserted in the light path for the chrominance tubes R, G and B.

LOW KEY CONDITIONS (with light bias of 3 nA)

	build-up lag I _S /I _b = 20/300 nA		decay lag		
			$I_{s}/I_{b} = 20/300 \text{ nA}$		
	60 ms	200 ms	60 ms	200 ms	
XQ1080, XQ1080L, XQ1080G	98%	≈ 100%	6%	1,5%	
XQ1080R	95%	≈ 100%	6%	2,5%	
XQ1080B	95%	≈ 100%	8,5%	3,5%	
XQ1083R	95%	≈ 100%	8%	3%	
XQ1085R	95%	≈ 100%	8%	3%	

Typical effect of light bias on built-up and decay lag under low key signal current and beam settings are shown in Figs 7 to 14. Shading of light bias induced dark current


18


12,5%


19


XQ1080 SERIES


MECHANICAL DATA












Mounting position: any

Mass: ≈ 70 g

Base: IEC 67-I-33a (JEDEC E8-11)

(1) The distance between the geometrical centres of the diameter A of the reference ring and the diameter B of the mesh-electrode ring is $\leq 100~\mu m.$



NOTES, see also General Section.

- The light bias lamp in its holder fits into the socket type 56026 and requires maximum 5 V, 110 mA. Its light is projected on to the pumping stem via a blue-green transmitting filter and is conducted to cause a bias illuminance on the target. The required amount of light bias can be obtained by adjusting the filament current of the lamp.
- The tube can withstand short excursions up to 70 °C without damage or irreversible degradation in performance.
- 3. For short intervals. During storage the tube face shall be covered with the plastic hood provided; when the camera is idle the lens shall be capped, in stand-by also the beams will be cut-off.
- The operating conditions and performance data quoted relate to operation of the tube in coil units AT1126 and AT1119. See relevant data of deflection/focusing assemblies.
- 5. When the tube is to be used without ACT action, grid 3 should be connected to grids 2 and 4 and no ACT pulses should be applied to the cathode and grid 1. The performance of the tube will then be as described herein with the exception of the highlight handling.
- a. For proper ACT action the d.c. voltage supply and/or pulse supply to the various electrodes should have sufficiently low impedance; see note 13.
 - b. Video preamplifier: In the presence of highlights, peak signal currents of the order of 15 to 45 μ A may be offered to the preamplifier during flyback. Special measures have to be taken in the preamplifier to prevent temporary overloading.
- 7. a. Read-out mode: Defined as the operating conditions during the active line scan (full line period-line blanking interval). For the CCIR system this will amount to $64 \mu s 12 \mu s = 52 \mu s$.
 - b. ACT mode: Defined as the operating conditions during that part of the line blanking interval during which the ACT electrode gun is fully operative. The ACT interval is equal to or slightly within the line flyback time.
- 8. Pulse timing (CCIR) and amplitudes for ACT action: (blanking applied to grid 1, see note 12)
 - a. For proper operation and setting up of the ACT electron gun three electrodes have to be pulsed:
 - Cathode: A positive-going pulse, V_{kp}, with an adjustable amplitude of 0 to 20 V. This pulse
 can be chosen to coincide with the camera blanking period (approx. 11 µs). The amplitude
 of this pulse determines the ACT cutting level and may in general be preset to 8, 4, 8 and 4 V,
 for black/white, R, G, and B application respectively. An amplitude of 20 V should be
 available to preset the I_S/I_b; see note 10.
 - Grid 1: A positive-going pulse, V_{g1p} , with such an amplitude that during the ACT mode the grid 1 bias is effectively reduced by 20 V, $(V_{g1p} = 20 \text{ V} + V_{kp})$, to produce an extra amount of cathode current. The duration of this pulse should be so chosen that it is just within the flyback period (approx. 5 μ s).
 - Grid 3: A negative-going pulse, V_{q3p}, timing and duration coinciding with V_{g1p}, with:
 - either an adjustable amplitude and superimposed on a fixed grid 3 voltage of 250 to 300 V,
 - or with fixed amplitude and superimposed on an adjustable grid 3 voltage of 250 to 300 V, in either case, adjusted to result in a grid 3 voltage of 8,5 V with respect to the cathode voltage during the ACT mode. This pulse ensures that an adequate amount of beam current is drawn from the cathode current.
 - b. A suggested pulse timing and amplitude diagram is shown in Fig. 1.
- 9. Operation with ACT at $V_{q6} > 750 \text{ V}$ is not recommended since this may introduce dark current.

XQ1080 SERIES

10. Adjusted with the ACT made inoperative, e.g. by setting the cathode pulse to 20 V. The control grid voltage is adjusted to produce a beam current just sufficient to allow a peak signal current of twice the typical value, I_{sp}, as observed and measured on a waveform oscilloscope. This amount of beam current is termed I_{bp}. I_b is set at 200 nA for R and B tubes and at 400 nA for L and G tubes. N.B. The signal current, I_s, and the beam current, I_b, conditions quoted with the performance figures for e.g. lag relate to measurements with an integrating instrument connected in the signal electrode lead and a uniform illuminance on the scanned area. The corresponding peak currents I_{sp} and I_{bp}, as measured on a waveform oscilloscope will be a factor α larger.

$$\alpha = \frac{100}{100 - \beta} \; ;$$

 β being the total blanking time in %; for CCIR system α = 1,3.

- 11. Typical faceplate illumination level for the XQ1080 and XQ1080L to produce 200 nA signal current will be approx. 4 lx. The signal currents stated for the colour tubes R, G and B will be obtained with an incident white light level (2856 K) on the filter of approx. 8,5 lx. These figures are based on the filters described in note 14. For filter BG12, however, a thickness of 1 mm is chosen.
- 12. Blanking can also be applied to the cathode:
 - without ACT action; required cathode pulse approx. 25 V
 - with ACT action; timing, polarity and amplitudes of the ACT pulses will have to be adapted.
- 13. The d.c. voltage supply and/or pulse supply to these electrodes should have a sufficiently low impedance to prevent distortion caused by the peak currents drawn during the ACT mode. These peak currents may amount to:

cathode	2 mA
grid 1	0 mA
grids 2 and 4	1 mA
grid 3	150 μΑ
grid 5	300 μΑ
grid 6	300 μΑ

The cathode impedance should be preferably be chosen $\leq 300 \Omega$.

14. Measuring conditions: illuminance level 4,54 lx at a colour temperature of 2856 K and the appropriate filter inserted in the light path. The signal current obtained in nA is a measure of the colour sensitivity expressed in μ A per lumen of white light before the filter. Filters used are:

XQ1080R, XQ1085R	Schott	OG570	thickness	3 r	mm
XQ1080G	Schott	VG9	thickness	1 r	mm
XQ1080B	Schott	BG12	thickness	3 r	mm
XQ1083R	Schott	OG570	thickness	3 r	mm
	and Calflex	B1/K1			

For transmission curves see General Section.

- 15. With pulses applied as indicated in note 8 the tube will properly handle a highlight with a diameter of 10% of picture height and with a luminance corresponding to 32 times peak signal white, I_{SD}.
- 16. As measured with a 50 mm Leitz Summicron lens having a sine response of approximately 85% at 400 TV lines at f: 5,6 and the appropriate filter inserted in the light path. The horizontal amplitude response can be raised by means of suitable correction circuits, which affect neither the vertical resolution nor the limiting resolution.
- 17. Build-up lag

After 10 s of darkness. The figures are typical percentages of the ultimate signal current obtained 60 ms and 200 ms, respectively, after the introduction of the illuminance.

Decay lag

After the target has been illuminated for at least 5 s. The figures represent typical signals in percentages of the original signal current 60 ms and 200 ms, respectively, after removal of the illuminance.

- 18. A reduction of lag, especially under low key conditions is obtained when light bias is applied. Infrared light with a wavelength > 600 nm in the light bias should be avoided.
 - a. For monochrome operation a light bias corresponding to 2 to 3 nA dark current is usually adequate for excellent speed of response.
 - b. Adjustable light bias (colour camera).

In a colour camera the speeds of response of the tubes can be balanced by adjusting the amount of light bias per tube.

In a 3-tube colour camera for instance it is recommended to first adjust the tubes to their normal highlight signal current and beam current settings and then point the camera at a dark scene comprising a metronome. The moving hand of the metronome carries a small white square. The illuminance should be chosen such that the square produces a peak signal of approximately 50 nA in the green chrominance channel. A maximum of 3 nA artificial dark current shall then be introduced in green chrominance tube. Subsequently light bias shall be applied to the tubes in the red and blue channels until the lag of the three tubes is neutralized.

A typical setting for correct speeds of response in a 3-tube colour camera would be approximately 3 nA(p) (R), 2 nA(p) (G) and 3,5 nA(p) (B).

19. Deviation of the level of any of the four corners, i.e. 10% inwards in H and V direction from the level in the picture centre. With the settings suggested in note 18 black shading compensation in the camera video processing amplifier will not normally be required. Further improvement in lag can be obtained by applying still higher light bias levels. It may then be necessary to use black shading compensation in the video processing amplifier.




Fig. 1 Pulse timing and amplitude diagram.





Fig. 2 Typical light transfer characteristics with ACT applied.

XQ1080 SERIES







Fig. 3 Typical spectral response for XQ1080.






Fig. 5 Typical spectral response for XQ1085R.




Fig. 6 Typical square-wave response curves for XQ1080.






Fig. 6a Typical square-wave response curves for XQ1083, XQ1085.





Build-up lag (see note 17)
Light bias induced dark current

as parameter. Fig. 7 XQ1080, XQ1080L, XQ1080G.

 $I_{s}/I_{b} = 40/400 \text{ nA}.$

Fig. 8 XQ1080R. $I_{s}/I_{b} = 20/200 \text{ nA}.$

Fig. 9 XQ1080B. $I_s/I_b = 20/200 \text{ nA}$.






Fig. 9.




Build-up lag (See note 17) Light bias induced dark current as parameter. XQ1083R, XQ1085R;

 $I_s/I_b = 20/200 \text{ nA}.$



Decay lag (See note 17) Light bias induced dark current as parameter. XQ1083R, XQ1085R; I_S/I_b = 20/200 nA.



10 2 nA 8 4nA 6 8nA 4 10 nA 2 0 40 80 120 160 200 (ms)

12


(%)

OnA

-1nA

Fig. 12.

Fig. 13.




Decay lag (see note 17)

Light bias induced dark current as parameter.

Fig. 12 XQ1080, XQ1080L, XQ1080G. $I_{\rm S}/I_{\rm D}$ = 40/400 nA.

Fig. 13 XQ1080R. $I_s/I_b = 20/200 \text{ nA}$.

Fig. 14 XQ1080B. $I_s/I_b = 20/200 \text{ nA}$.



CAMERA TUBES

25,4 mm (1 inch) diameter Plumbicon[®] television camera tubes, with standard resolution lead-oxide photoconductive target, for use in high quality monochrome or colour cameras for broadcast, educational or industrial applications.

The XQ1090 series comprises the following versions:

XQ1090	for use in monochrome cameras
XQ1090L	for use in the luminance channel of colour cameras
XQ1090R	for use in the red channel
XQ1090G	for use in the green channel
XQ1090B	for use in the blue channel
XQ1093R	for use in the red channel; extended red response
XQ1095R	for use in the red channel; extended red response and IR filter

The tubes of the XQ1090 series are provided with an ACT electron gun and provisions for light bias like the tubes of the XQ1080 series but are front loading types.

The electrical and mechanical data of the tubes are identical to those of the XQ1080 series with the following exceptions.

ELECTRICAL DATA

Capacitance

Signal electrode to all

Cas

3 to 5 pF

ACCESSORIES

Deflection and focusing coil unit


AT1116/06


[®] Registered trade mark for camera tubes.


XQ1090 SERIES




Dimensions in mm









CAMERA TUBES

25,4 mm (1 inch) diameter Plumbicon® television camera tubes, with high resolution lead-oxide photoconductive target, for use in high quality monochrome or colour cameras for broadcast, educational or industrial applications.

The XQ1500 series comprises the following versions:

XQ1500 for use in monochrome cameras
XQ1500L for use in the luminance channel of colour cameras
XQ1500R for use in the red channel
XQ1500B for use in the green channel
XQ1500B for use in the blue channel
XQ1503R for use in the red channel: extended red response

XQ1505R for use in the red channel; extended red response and IR filter

Special features are:

- · Anti-Comet-Tail (ACT) electron gun for highlight handling
- Extremely low lag
- Provisions for light bias to reduce lag
- · Target centring ring for precise optical alignment
- Low output capacitance for optimum S/N ratio
- Increased resolving power as compared with XQ1080 series
- Rear loading

ACT electron gun

QUICK REFERENCE DATA

Diameter		25,4 mm (1 inch)
Length	approx.	165 mm
Provided with anti-halation glass disc		
Focusing	magnetic	;
Deflection	magnetic	
Useful target area (scanning area)	9,6 >	12,8 mm
Spectral response		
max. at	approx.	500 nm
cut-off: XQ1500	approx.	650 nm
XQ1503	approx.	850 to 950 nm
XQ1505	approx.	750 nm
Sensitivity		
XQ1500, XQ1500L	typ.	375 μA/Im
XQ1500R	typ.	80 μA/ImF
XQ1500G	typ.	155 μA/ImF
XQ1500B	typ.	38 μA/ImF
XQ1503R, XQ1505R	typ.	100 μA/ImF
Resolution at 400 TV lines (5 MHz)		
XQ1500, XQ1500L	typ.	50 %
XQ1500R	typ.	40 %
XQ1500G	typ.	50 %
XQ1500B	typ.	55 %
XQ1503R, XQ1505R	typ.	50 %
Heater		6,3 V, 190 mA

[®] Registered trade mark for television camera tubes.

OPTICAL DATA notes

Quality rectangle on

photoconductive target (aspect ratio 3:4) 9,6 x 12,8 mm

Orientation of image on target:

For correct orientation of the image on the target the vertical scan should be essentially parallel to the plane passing through the tube axis and the marker line on the protecting sleeve at the base

Faceplate

Thickness 1,2 \pm 0,1 mm Refractive index n = 1,49

Anti-halation glass disc provided with

anti-reflective coating

Thickness 5 ± 0.1 mm Refractive index n = 1.52

XQ1505R is provided with an infrared reflecting filter.

ACCESSORIES

Socket type 56026

Deflection and focusing coil unit:

 Black/white
 type AT1119/01

 Colour
 type AT1126T

 Mask for flare reduction
 type 56028

Light bias lamp in holder type 56027

ELECTRICAL DATA

Deflection magnetic Focusing magnetic

Heating, indirect by a.c. or d.c.; parallel supply

Heater voltage V_f 6,3 V \pm 5%

Heater current at $V_f = 6.3 \text{ V}$ If nom. 190 mA

The heater voltage must not exceed an r.m.s. value of 9,5 V. For optimum

performance (lifetime and registration stability)

stabilization of the heater voltage is recommended.

Capacitance

Signal electrode to all Cas 2,5 to 3,5 pF

This capacitance, which is effectively the output impedance, increases when the tube is inserted in

the coil unit.

em)				notes
				11000
	2000	50	V	
v g6/g5	IIIax.	330	V	
V 0 4	may	350	V	
v g2,4				
v g3	IIIdX.	330	V	
V/ 4	may	0	V	
vgi				
-v _{g1}	max.	200	V	
+1	min	1	min	
rh	mm.	1	111111	
1/1.6	P2 01/	50	1/	
vktp				
-vkfp	max.	50	V	
D		2	1.0	
rkf				
Tamb				
umb				0
T				2
_				0
E	max.	500	IX	3
				4,5
				6,7,8
Vk		0	V	
	(to 15	V	
Vac		45	V	
				9
Va5				
95				
Va2 1		300	V	
92,4				
V _{u3}				8
90				8
V _{u3}				
V _{g3}				
				10
V _g 3 V _g 1 V _g 1				10
	Vk Vk Vk Vas Vg6 Vg5 Vg2,4 Vg3	e cathode. Vas max. Vg6 max. Vg5 max. Vg6/g5 max. Vg6/g5 max. Vg2,4 max. Vg3 max. Vg1 maxVg1 maxVg1 max. Th min. Vkfp maxVkfp maxVkfp max. Rkf min. T amb min. T max. min. E max.	e cathode. Vas max. 50 Vg6 max. 1100 Vg5 max. 800 Vg6/g5 max. 350 Vg2,4 max. 350 Vg1 max. 0 -Vg1 max. 200 th min. 1 Vkfp max. 50 -Vkfp max. 50 Rkf min. 2 Tamb min30 T max. 50 min30 E max. 500 Vk 0 to 15 Vas 45 Vg6 750 Vg2,4 300 Vg3	e cathode. Vas

XQ1500 SERIES

					1	
	XQ1500 XQ1500L	XQ1500R XQ1503R XQ1505R	XQ1500G	XQ1500	В	
Signal current, peak I _{sp}	0,2	0,1	0,2	0,1	μΑ	1.1, 1
Beam current, peak Ibp	0,4	0,2	0,4	0,2	μΑ	
ACT level, peak	0,28	0,14	0,28	0,14	μΑ	
Cathode pulse V _{kp}	8	4	8	4	V	
Grid 1 pulse Vg1p Grid 3 pulse Vg3p	28	24	28	24	V	- 0
, 90p					see not	e 8
aceplate illuminance				0 to 10		11
Faceplate temperature				20 to 45	00	2
ELECTRON GUN CHARAC	CTERISTICS					
Cut off						
Grid 1 voltage for cut-off	at V ₂₂ 4 = 300	V				
without blanking or ACT		• ,	V _{a1} -	-40 to -110	V	
Blanking voltage, peak to pe		00 V	· g1	10 10 110	•	
on grid 1	92,4		V_{q1p-p}	50 ± 10	V	12
Grids 2 and 4 current			la2.4	< 0.2		13
Grids 3, 5 and 6 current			lg3,5,6	-,-		13
Pulse timing and amplitude i	requirements (A	CT)	90,0,0			8
PERFORMANCE						
	oias		I _d	≤ 1	nA	
Dark current, without light l Gensitivity at colour tempera		ance = 2856 K	· u	≤ 1	nA	14
Dark current, without light light light light light light light sensitivity at colour temperated (\$\text{Q1500}, \times \text{Q1500} L		ance = 2856 K			nA μΑ/Im	14
Dark current, without light l Sensitivity at colour tempera KQ1500, XQ1500L KQ1500R		ance = 2856 K	min. 330 min. 70	typ. 375 typ. 80	μΑ/Im μΑ/ImF	14
Dark current, without light l Sensitivity at colour tempera (Q1500, XQ1500L (Q1500R (Q1500G		ance = 2856 K	min. 330 min. 70 min. 135	typ. 375 typ. 80 typ. 155	μΑ/Im μΑ/ImF μΑ/ImF	14
Dark current, without light l Sensitivity at colour tempera KQ1500, XQ1500L KQ1500R KQ1500G KQ1500B		ance = 2856 K	min. 330 min. 70 min. 135 min. 35	typ. 375 typ. 80 typ. 155 typ. 38	μΑ/Im μΑ/ImF μΑ/ImF μΑ/ImF	14
Dark current, without light I Sensitivity at colour tempera KQ1500, XQ1500L KQ1500R KQ1500G KQ1500B KQ1503, XQ1505R	ature of illumina	ance = 2856 K	min. 330 min. 70 min. 135 min. 35 min. 75	typ. 375 typ. 80 typ. 155 typ. 38 typ. 100	μΑ/Im μΑ/ImF μΑ/ImF	14
Dark current, without light I Sensitivity at colour tempera (Q1500, XQ1500L (Q1500R (Q1500G (Q1500B (Q1503, XQ1505R Gamma of transfer character	ature of illumina	ance = 2856 K	min. 330 min. 70 min. 135 min. 35 min. 75	typ. 375 typ. 80 typ. 155 typ. 38	μΑ/Im μΑ/ImF μΑ/ImF μΑ/ImF	14
Dark current, without light light light light without light at colour temperate (21500, XQ1500L) (21500G) (21500B) (21503, XQ1505R) (215037, X	ature of illumina	ance = 2856 K	min. 330 min. 70 min. 135 min. 35 min. 75 see Fig. 2	typ. 375 typ. 80 typ. 155 typ. 38 typ. 100 0,95 ± 0,05	μΑ/Im μΑ/ImF μΑ/ImF μΑ/ImF μΑ/ImF	
Dark current, without light light light light with the colour temperated to the colour temperated temp	ature of illumina	ance = 2856 K	min. 330 min. 70 min. 135 min. 35 min. 75 see Fig. 2	typ. 375 typ. 80 typ. 155 typ. 38 typ. 100 0,95 ± 0,05	μΑ/Im μΑ/ImF μΑ/ImF μΑ/ImF μΑ/ImF μΑ/ImF	14
Dark current, without light logerstivity at colour temperated (201500, XQ1500L) KQ1500R KQ1500B KQ1503, XQ1505R Gamma of transfer character is ticked the colour colou	istics with ACT	ance = 2856 K	min. 330 min. 70 min. 135 min. 35 min. 75 see Fig. 2 ≥ approx.	typ. 375 typ. 80 typ. 155 typ. 38 typ. 100 0,95 ± 0,05	μA/Im μA/ImF μA/ImF μA/ImF μA/ImF μA/ImF	
Dark current, without light logerstivity at colour temperated (201500, XQ1500L) KQ1500R KQ1500B KQ1503, XQ1505R Gamma of transfer character is ticked the colour colou	istics with ACT	ance = 2856 K	min. 330 min. 70 min. 135 min. 35 min. 75 see Fig. 2 ≥ approx. approx.	typ. 375 typ. 80 typ. 155 typ. 38 typ. 100 0,95 ± 0,05 5 500 650	μA/Im μA/ImF μA/ImF μA/ImF μA/ImF μA/ImF μA/ImF	
PERFORMANCE Dark current, without light In Sensitivity at colour temperate XQ1500, XQ1500L XQ1500R XQ1500B XQ1500B XQ1503, XQ1505R Gamma of transfer character Light transf	istics with ACT	ance = 2856 K	min. 330 min. 70 min. 135 min. 35 min. 75 see Fig. 2 ≥ approx.	typ. 375 typ. 80 typ. 155 typ. 38 typ. 100 0,95 ± 0,05	μA/Im μA/ImF μA/ImF μA/ImF μA/ImF μA/ImF μA/ImF nm	

notes 16

Resolution

Modulation depth, i.e. uncompensated amplitude response at 400 TV lines at the centre of the picture. The figures shown represent the horizontal amplitude response as measured with a lens aperture f: 5,6

Modulation transfer characteristics: see Figs 6 and 6a

	XQ1500 XQ1500L	XQ1500R	XQ1500G	XQ1500B	XQ1503R XQ1505R	
Highlight signal						
current Is	200	100	200	100	100	nA
Beam current Ib	400	200	400	200	200	nA
Modulation depth						
at 400 TV lines						
typ.	50	40	50	55	50	%
min.	45	35	45	50	45	%

Lag (typical values)

17

Light source with a colour temperature of 2856 K. Appropriate filter inserted in the light path for the chrominance tubes R, G and B.


LOW KEY CONDITIONS (with light bias of 3 nA)


	build-up lag $I_{S}/I_{D} = 20/300 \text{ nA}$		decay lag $I_{S}/I_{b} = 20/300 \text{ nA}$	
	60 ms	200 ms	60 ms	200 ms
XQ1500, XQ1500L, XQ1500G	98%	≈ 100%	6%	2%
XQ1500R	95%	≈ 100%	7%	3%
XQ1500B	95%	≈ 100%	9%	3,5%
XQ1503R	95%	≈ 100%	7%	3%
XQ1505R	95%	≈ 100%	7%	3%


Typical effect of light bias on build-up and decay lag under low key signal current 18 and beam settings are shown in Figs 7 to 14. Shading of light bias induced dark current 12,5% 19

XQ1500 SERIES

MECHANICAL DATA








Mounting position: any

Mass: $\approx 70 \text{ g}$

Mase: IEC67-I-33a (JEDEC E8-11)

(1) The distance between the geometrical centres of the diameter A of the reference ring and the diameter B of the mesh-electrode ring is $<100~\mu m.$



NOTES, see also General Section

- The light bias lamp in its holder fits into the socket type 56026 and requires maximum 5 V, 110 mA. Its light is projected on to the pumping stem via a blue-green transmitting filter and is conducted to cause a bias illuminance on the target. The required amount of light bias can be obtained by adjusting the filament current of the lamp. See also note 18.
- The tube can withstand short excursions up to 70 °C without damage or irreversible degradation in performance.
- For short intervals. During storage the tube face shall be covered with the plastic hood provided; when the camera is idle the lens shall be capped, in stand-by also the beams will be cut-off.
- The operating conditions and performance data quoted relate to operation of the tube in coil units AT1126 and AT1119. See relevant data of deflection/focusing assemblies.
- 5. When the tube is to be used without ACT action, grid 3 should be connected to grids 2 and 4 and no ACT pulses should be applied to the cathode and grid 1. The performance of the tube will then be as described herein with the exception of the highlight handling.
- a. For proper ACT action the d.c. voltage supply and/or pulse supply to the various electrodes should have sufficiently low impedance; see note 13.
 - b. Video preamplifier: In the presence of highlights, peak signal currents of the order of 15 to $45 \,\mu\text{A}$ may be offered to the preamplifier during flyback. Special measures have to be taken in the preamplifier to prevent temporary overloading.
- 7. a. Read-out mode: Defined as the operating conditions during the active line scan (full line period-line blanking interval). For the CCIR system this will amount to 64 μ s 12 μ s = 52 μ s.
 - b. ACT mode: Defined as the operating conditions during that part of the line blanking interval during which the ACT electrode gun is fully operative. The ACT interval is equal to or slightly within the line flyback time.
- 8. Pulse timing (CCIR) and amplitudes for ACT action (blanking applied to grid 1, see note 12).
 - a. For proper operation and setting up of the ACT electron gun three electrodes have to be pulsed:
 - Cathode: A positive-going pulse, V_{kp}, with an adjustable amplitude of 0 to 20 V. this pulse
 can be chosen to coincide with the camera blanking period (approx. 11 μs). The amplitude
 of this pulse determines the ACT cutting level and may in general be preset to 8, 4, 8 and
 4 V, for black/white, R, G, and B application respectively. An amplitude of 20 V should be
 available to preset the I_s/I_b; see note 10.
 - Grid 1: A positive-going pulse, V_{g1p}, with such an amplitude that during the ACT mode the grid 1 bias is effectively reduced by 20 V, (V_{g1p} = 20 V + V_{kp}), to produce an extra amount of cathode current. The duration of this pulse should be so chosen that it is just within the flyback period (approx. 5 µs).
 - Grid 3: A negative-going pulse, V_{g3p} , timing and duration coinciding with V_{g1p} , with: either and adjustable amplitude and superimposed on a fixed grid 3 voltage of 250 to 300 V,
 - or with fixed amplitude and superimposed on an adjustable grid 3 voltage of 250 to 300 V, in either case, adjusted to result in a grid 3 voltage of 8,5 V with respect to the cathode voltage during the ACT mode. This pulse ensures that an adequate amount of beam current is drawn from the cathode current.
 - b. A suggested pulse timing and amplitude diagram is shown in Fig. 1.
- 9. Operation with ACT at $V_{q6} > 750 \text{ V}$ is not recommended since this may introduce dark current.

XQ1500 SERIES

- 10. Adjusted with the ACT made inoperative, e.g. by setting the cathode pulse to 20 V. The control grid voltage is adjusted to produce a beam current just sufficient to allow a peak signal current of twice the typical value, I_{sp}, as observed and measured on a waveform oscilloscope. This amount of beam current is termed I_{bp}. I_b is set at 200 nA for R and B tubes and at 400 nA for L and G tubes.
 - N.B. The signal current, I_s , and the beam current, I_b , conditions quoted with the performance figures for e.g. lag relate to measurements with an integrating instrument connected in the signal electrode lead and a uniform illuminance on the scanned area. The corresponding peak currents, I_{sp} and I_{bp} , as measured on a waveform oscilloscope will be a factor α larger. ($\alpha = 100/\{100-\beta\}$; β being the total blanking time in %; for CCIR system $\alpha = 1,3$).
- 11. Typical faceplate illumination level for the XQ1080 and XQ1080L to produce 200 nA signal current will be approx. 4,3 Ix. The signal currents stated for the colour tubes R, G and B will be obtained with an incident white light level (2856 K) on the filter of approx. 11 Ix. These figures are based on the filters described in note 14. For filter BG12, however, a thickness of 1 mm is chosen.
- 12. Blanking can also be applied to the cathode:
 - without ACT action; required cathode pulse approx. 25 V
 - with ACT action; timing, polarity and amplitudes of the ACT pulses will have to be adapted.
- 13. The d.c. voltage supply and/or pulse supply to these electrodes should have a sufficiently low impedance to prevent distortion caused by the peak currents drawn during the ACT mode. These peak currents may amount to:

cathode	2	mA
grid 1	0	mA
grids 2 and 4	1	mA
grid 3	150	μΑ
grid 5	300	μΑ
grid 6	300	μΑ

The cathode impedance should preferably be chosen $\leq 300 \Omega$.

14. Measuring conditions: illuminance level 4,54 lx at a colour temperature of 2856 K and the appropriate filter inserted in the light path. The signal current obtained in nA is a measure of the colour sensitivity expressed in μ A per lumen of white light before the filter. Filters used are:

XQ1500R, XQ1505R	Schott	OG570	thickness	3	mm
XQ1500G	Schott	VG9	thickness	1	mm
XQ1500B	Schott	BG12	thickness	3	mm
XQ1503R	Schott	OG570	thickness	3	mm
and	Calflex	B1/K1			

For transmission curves see General Section.

- 15. With pulses applied as indicated in note 8 the tube will properly handle a highlight with a diameter of 10% of picture height and with a luminance corresponding to 32 times peak signal white, $I_{\rm SD}$.
- 16. As measured with a 50 mm Leitz Summicron lens having a sine response of approximately 85% at 400 TV lines at f: 5,6 and the appropriate filter inserted in the light path. The horizontal amplitude response can be raised by means of suitable correction circuits, which affect neither the vertical resolution nor the limiting resolution.
- 17. Build-up lag

After 10 s of darkness. The figures are typical percentages of the ultimate signal current obtained 60 ms and 200 ms, respectively, after the introduction of the illuminance.

Decay lag

After the target has been illuminated for at least 5 s. The figures represent typical signals in percentages of the original signal current 60 ms and 200 ms, respectively, after removal of the illuminance.

- 18. A reduction of lag, especially under low key conditions is obtained when light bias is applied. Infrared light with a wavelength > 600 nm in the light bias should be avoided.
 - a. For monochrome operation a light bias corresponding to 2 to 3 nA dark current is usually adequate for excellent speed of response.
 - Adjustable light bias (colour camera).
 In a colour camera the speeds of response of the tubes can be balanced by adjusting the
 - amount of light bias per tube. In a 3-tube colour camera for instance it is recommended to first adjust the tubes to their normal highlight signal current and beam current settings and then point the camera at a dark scene comprising a metronome. The moving hand of the metronome carries a small white square. The illuminance should be chosen such that the square produces a peak signal of approximately 50 nA in the green chrominance channel. A maximum of 3 nA artificial dark current shall then be introduced ingreen chrominance tube. Subsequently light bias shall be applied to the tubes in the red and blue channels until the lag of the three tubes is neutralized. A typical setting for correct speeds of response in a 3-tube colour camera would be approximately 3 nA(p) (R), 2nA(p) (G) and 3,5 nA(p) (B).
- 19. Deviation of the level of any of the four corners, i.e. 10% inwards in H and V direction from the level in the picture centre. With the settings suggested in note 18 black shading compensation in the camera video processing amplifier will not normally be required. Further improvement in lag can be obtained by applying still higher light bias levels. It may then be necessary to use black shading compensation in the video processing amplifier.




Fig. 1 Pulse timing and amplitude diagram.





Fig. 2 Typical light transfer characteristics with ACT applied.

XQ1500 SERIES



300 spectral response (mA/W) 200 100 400 500 600 700 wavelength (nm)

Fig. 3 Typical spectral response for XQ1500.




Fig. 4 Typical spectral response for XQ1503R.

300 spectral response (mA/W) 200 100 500 400 600 700 wavelength (nm)

Fig. 5 Typical spectral response for XQ1505R.




Fig. 6 Typical square-wave response curves for XQ1503R, XQ1505R.




Fig. 6a Typical square-wave response curves for XQ1500.




Fig. 7.




Fig. 8.




Fig. 9.

Build-up lag (see note 17)


Light bias induced dark current as parameter.

Fig. 7 XQ1500, XQ1500L, XQ1500G. $I_s/I_b = 40/400 \text{ nA}.$

Fig. 8 XQ1500R. $I_s/I_b = 20/200 \text{ nA}$.

Fig. 9 XQ1500B. $I_s/I_b = 20/200 \text{ nA}$.

XQ1500 SERIES






Fig. 10.


Build-up lag (See note 17)


Light bias induced dark current as parameter XQ1503R, XQ1505R; $I_s/I_b = 20/200$ nA.

Fig. 11.

Decay lag (See note 17)


Light bias induced dark current as parameter XQ1503R, XQ1505R; $I_S/I_D = 20/200$ nA.






Decay lag (see note 17)
Light bias induced dark current as parameter
Fig. 12 XQ1500, XQ1500L, XQ1500G.
I_S/I_D = 40/400 nA.
Fig. 13 XQ1500R. I_S/I_D = 20/200 nA.

Fig. 14 XQ1500B. $I_s/I_b = 20/200 \text{ nA}$.





CAMERA TUBES

25,4 mm (1 inch) diameter Plumbicon $^{\textcircled{8}}$ televison camera tubes, with high resolution lead-oxide photoconductive target, for use in high quality monochrome or colour cameras for broadcast, educational or industrial applications.

The XQ1510 series comprises the following versions:

XQ1510	for use in monochrome cameras
XQ1510L	for use in the luminance channel of colour cameras
XQ1510R	for use in the red channel
XQ1510G	for use in the green channel
XQ1510B	for use in the blue channel
XQ1513R	for use in the red channel; extended red response

XQ1515R for use in the red channel; extended red response and IR filter

The tubes of the XQ1510 series are provided with ACT electron gun and provisions for light bias like the tubes of the XQ1500 series but are front loading types.

The electrical and mechanical data of the tubes are identical to those of the XQ1500 series with the following exceptions.

ELECTRICAL DATA

Capacitance

Signal electrode to all

Cas

3 to 5 pF

ACCESSORIES

Deflection and focusing coil unit


AT1116/06


[®] Registered trade mark for camera tube.


XQ1510 SERIES




Dimensions in mm









CAMERA TUBES

25,4 mm (1 inch) diameter Plumbicon® television camera tubes, with high resolution lead-oxide photoconductive target, for use in high quality monochrome or colour cameras for broadcast, educational or industrial applications.

The XQ2070 series comprises the following versions:

XO2070L for use in monochrome cameras
XO2070L for use in the luminance channel of colour cameras
XO2070R for use in the red channel
XO2070G for use in the green channel
XO2070B for use in the blue channel
XO2071 as XO2070 series; only difference being the degree of freedom from blemishes on the target (industrial quality tubes)
XO2073R for use in the red channel; extended red response
XO2074 as XO2073. Industrial grade
XO2075R for use in the red channel; extended red response and IR filter

XQ2075R for use in the red channel; extended red response and IR 3 XQ2076 as XQ2075. Industrial grade

These tubes are available in rear loading (/02 and /05) and front loading (/03) versions.

Special features are:

- New photoconductive target for increased resolution,
- "Diode" electron gun with high beam reserve for dynamic beam control (DBC) to minimize comet-tailing and blooming (notes 1, 2, 3)
- Provision for light bias to reduce lag (except types XQ /05)

QUICK REFERENCE DATA

"Diada" alastron gun

Heater

"Diode" electron gun				
Diameter		25,4	mm (1 inch)
Length	approx.	170	mm	
Provided with anti-halation glass disc				
Focusing	magnetic			
Deflection	magnetic			
Useful target area (scanning area)	9,6 x	12,8	mm	
Spectral response				
max. at	approx.	500	nm	
cut-off: XQ2070	approx.	650	nm	
XQ2073	approx.	850	to 950 nm	
XQ2075	approx.	750	nm	
Sensitivity				
XQ2070, XQ2070L	typ.	350	$\mu A/Im$	
XQ2070R	typ.	70	μA/ImF	
XQ2070G	typ.	145	μA/ImF	
XQ2070B	typ.	38	μA/ImF	
XQ2073R, XQ2075R	typ.	100	μA/ImF	
Resolution at 400 TV lines (5 MHz)				
XQ2070, XQ2070L	typ.	60	%	
XQ2070R	typ.	45	%	
XQ2070G	typ.		%	
XQ2070B	typ.		%	
XO2073R, XO2075R	typ.	55	%	

[®] Registered trade mark for television camera tubes.

6.3 V, 95 mA

MECHANICAL VARIANTS

notes

Variants are defined by a suffix as follows:

XQ /02, R,G,B,L: rear loading versions with provision for internal light bias, target contact ring with 2 target contacts, metal sleeve on pumping stem to mount bias lamp.

XQ /03, R,G,B,L: front loading versions with provision for internal light bias, metal ring target contact, metal sleeve on pumping stem to mount bias light lamp.

XQ /05, R,G,B,L: as/02, however without provision for light bias.

OPTICAL DATA

Quality rectangle on

photoconductive target (aspect ratio 3:4)

9,6 x 12,8 mm

Orientation of image on target:

For correct orientation of the image on the target the vertical scan should be essentially parallel to the plane passing through the tube axis and the marker line on the protecting sleeve at the base.

Faceplate

Thickness 1.2 ± 0.1 mm Refractive index n = 1.49

Anti-halation glass disc provided with

anti-reflective coating

Thickness 5 ± 0.1 mm Refractive index n = 1,52

XQ2075R is provided with infrared reflecting filter

ACCESSORIES

Socket	type 56098	
Deflection and focusing coil unit:	rear loading	front loading
Black/white	type AT1119/01	AT1116/06S
Colour	type AT1126T	AT1116/06T
Mask for flare reduction	type 56028	
Light higs lamp in holder for versions /02 and /03	type 56106	Δ

ELECTRICAL DATA

Deflection		magnetic
Focusing		magnetic
Heating, indirect by a.c. or d.c.; parallel supply		
Heater voltage	Vf	6,3 V ± 5%
Heater current at V _f = 6,3 V	If nom.	95 mA
The heater current and the heater voltage must not	•	
exceed r.m.s. values of 150 mA and 9.5 V. For		

Capacitance

Signal electrode to all

recommended.

rear loading types 2,5 to 4 pF Cas front loading types 3 to 5 pF Cas

This capacitance, which is effectively the output impedance, increases when the tube is inserted in the coil unit.

optimum performance (lifetime and registration stability) stabilization of the heater voltage is

LIMITING VALUES (Absolute maximum rating syst	em)			notes
				110163
Unless otherwise stated, all voltages are referred to the			FO 14	
Signal electrode voltage Grid 4 voltage	Vas	max.	50 V	
Grid 3 voltage	V _g 4		1100 V 800 V	
Voltage between grid 4 and grid 3	V _g 3	max.	450 V	
Grid 2 voltage	Vg4/g3	max.	340 V	
Grid 1 voltage,	V_{g2}	max.	340 V	
positive	V-4	max.	25 V	
negative	$\begin{array}{c} V_{g1} \\ -V_{g1} \end{array}$	max.	200 V	
Grid 1 current (≈ I _k current)		max.	5 mA	
Grid 1 current (peak to peak with DBC)	lg1	max.	8 mA	2
Cathode heating time before drawing	lg1p	IIIax.	o IIIA	2
cathode current	+1-	min.	1 min	
Cathode to heater voltage	^t h	111111.	1 111111	
positive peak	V_{kfp}	max.	125 V	
negative peak	−V _{kfp}	max.	50 V	
Cathode heating time before	• ктр	max.	00 V	
drawing current	th	min.	1 min	
External resistance between cathode	511	1111111		
and heater at V _{kfp} > 10 V	Rkf	min.	2 kΩ	
		max.	50 °C	
Ambient temperature, storage and operation	T_{amb}	min.	−30 °C	
_		max.	50 °C	
Faceplate temperature, storage and operation	Т	min.	_30 °C	
Faceplate illuminance	E	max.	500 lx	5
, 400		1114711		-
OPERATING CONDITIONS				6
For a scanned area of 9,6 x 12,8 mm				
Cathode voltage	Vk		0 V	
Signal electrode voltage	Vas		45 V	
Beam current	Ib			7
Grid 4 voltage	V _{g4}		960 V	
Grid 3 voltage	V _{g3}		600 V	
Grid 2 voltage	V_{g2}^{g3}		300 V	
Grid 1 voltage	V _{q1}		V	7
Blanking voltage on grid 1, peak to peak	Vg1p-p		25 V	
Faceplate illuminance	E	0	to 10 Ix	8
Faceplate temperature	T	20	to 45 °C	9
ELECTRON GUN CHARACTERISTICS				
Cut off				
Grid 1 voltage for cut-off at $V_{g2} = 300 \text{ V}$,				
without blanking	V _g 1		0 to 0 V	
Grid 1 voltage for normal beam setting	V_{g1w}	\leq	15 V	
Blanking voltage, peak to peak				
on grid 1	V _{g1p-p}		25 V	
on cathode	V _{kp-p}		25 V	
Grid 1 current at normally required				0
beam currents	lg1	\leq	1,5 mA	2
Grid 2 current at normally required	L		0.1 4	2
beam currents	lg2	\leq	0,1 mA	2

XQ2070 SERIES

the picture.

PERFORMANCE					notes
Dark current	ld		< ′	2 nA	
Sensitivity at colour temperature of illuminance = 2856					10
XQ2070,L	min.	300	typ. 350	$\mu A/Im$	
XQ2070R	min.	63	typ. 70	μA/ImF	
XQ2070G	min.	130	typ. 145	μA/ImF	
XQ2070B	min.	35	typ. 38	β μA/ImF	
XQ2073R, XQ2075R	min.	80	typ. 100	μA/ImF	
Gamma of transfer characteristics			0,95 ± 0,05	5	
Spectral response, max. at			500	nm (
Spectral response, cut-off at			650 to 950	nm (
Spectral response curves	see F	igs 1,	2		
Resolution					11
Modulation depth, i.e. uncompensated amplitude respons	se at 40	OTV	lines at the	centre of	

	XQ2070,L XQ2070G	XQ2070R	XQ2070B	XQ2073R XQ2075R	7,11
Highlight signal					
current Is	200	100	100	100	nA
Beam current Ib	400	200	200	200	nA
Modulation depth at 400 TV lines					
typ.	60	45	60	55	%
min.	55	40	55	50	%

Modulation transfer characteristics: see Figs 3 and 4

Lag (typical values, with light bias of 3 nA)

4.12

Light source with a colour temperature of 2856 K. Appropriate filter inserted in the light path for the chrominance tubes R, G and B

LOW KEY CONDITIONS

	build-	up lag	decay lag		
	$I_{s}/I_{b} = 20/300 \text{ nA}$		$I_{s}/I_{b} = 20/300 \text{ nA}$		
	60 ms	200 ms	60 ms	200 ms	
XQ2070	95%	≈ 100%	9%	2,5%	
XQ2070G	95%	≈ 100%	9%	2,5%	
XQ2070R	95%	≈ 100%	9%	2,5%	
XQ2070B	90%	≈ 100%	12%	4%	
XQ2073R, XQ2075R	90%	≈ 100%	11%	3%	


Shading of light bias induced dark current Highlight handling capacity with DBC 12,5%


14


15


MECHANICAL DATA


Rear loading tubes XQ2070/02












(1) The distance between the geometrical centres of diameter A of the reference ring and diameter B of the mesh electrode ring is $<100~\mu\text{m}.$


Mounting position: any


Mass: ≈ 70 g



XQ2070 SERIES

Front loading tubes XQ2070/03







Mounting position: any


Mass:


≈ 70 g


Rear loading tubes XQ2070/05












(1) The distance between the geometrical centres of diameter A of the reference ring and diameter B of the mesh electrode ring is < 100 µm.

Mounting position: any

Mass: ≈ 70 g

Base: IEC 67-I-33a (JEDEC E8-11)



XQ2070 SERIES

NOTES, see also General Section

- "Diode" electron gun is a triode gun operating in a diode mode, providing a very high beam reserve.
 - N.B. Avoid continuous operation at high beam currents since this will shorten tube life. Full advantage of the high beam reserve to reduce comet-tailing and blooming can be made with DBC circuitry which, during highlights, feeds positive-going pulses derived from the video signal to grid 1, to increase the beam current momentarily.
- The "diode" gun operates with a positive (≤ 15 V) grid 1 voltage (adjusted for correct beam settings, see note 7), hence draws some grid 1 current:

without DBC: ≤ 1,5 mA (peak) with blanking

with DBC:

8 mA (peak) with blanking measured with oscilloscope.

The DBC circuitry should, in the case of highlights, supply positive-going pulses of 7 V above V_{a1w} (see note 12) and up to 8 mA peak to grid 1.

N.B. Applying higher pulses than 7 V is not recommended since this will shorten tube life, impair resolution and may introduce oscillations.

- The rear loading tubes closely resemble mechanically the tubes of the XQ1080/XQ1500 series.
 The front loading types resemble the tubes of the XQ1070 series. Since, however, the "Diode" electron gun draws some grid 1 current (see note 2), cameras designed around XQ1080/XQ1500 and XQ1070 tubes will require some modification.
- 4. For adjustable light bias in versions /02 and /03. The light bias lamp assembly as supplied with these tubes, type 56106, fits in the metal tube cemented to the pumping stem of the tube. The tube and the light bias lamp assembly will fit properly in the socket, type 56098. The wires should be connected to a source, capable of supplying max. 110 mA at 5 V. The desired amount of light bias can be obtained by adjusting the current through the filament of the lamp. For black/white operation a light bias corresponding to 2 to 3 nA extra dark current is usually adequate for excellent speed of response. In a colour camera the speeds of response of the tubes can be balanced by adjusting the amount of light bias per tube. A typical setting in a 3-tube colour camera could be 3 nA (R), 2 nA (G), and 6 nA (B). Infrared light with a wavelength > 600 nm in the light bias should be avoided.
- 5. For short intervals. During storage the tube face shall be covered with the plastic hood provided; when the camera is idle the lens shall be capped, in stand-by also the beam will be cut-off.
- 6. The operating conditions and performance data quoted relate to operation of the tube in coil unit AT1126 and AT1116. See relevant data of deflection/focusing assemblies.
- 7. The beam current I_D, as obtained by adjusting the control grid (grid 1) voltage is set for 1 stop over peak white and is 200 nA for R and B tubes, 400 nA for black/white and G tubes. I_D is not the total current available in the scanning beam, but is defined as the maximum amount of signal current, I_S, that can be obtained with this beam.
 - In the performance figures e.g. for lag, the signal current and beam current conditions are given as $I_s/I_b=20/300$ nA. This means: with a signal current of 20 nA and a beam setting which just allows a signal current of 300 nA.
- 8. Typical faceplate illumination level for the XQ2070 and XQ2070L to produce 200 nA signal current will be approx. 4,6 lx. The signal currents stated for the colour tubes R, G and B will be obtained with an incident white light level (2856 K) on the filter of approx. 11 lx. These figures are based on the filters described in note 10. For filter BG12, however, a thickness of 1 mm is chosen.
- The tube can withstand short excursions up to 70 °C without damage or irreversible degradation in performance.

10. Measuring conditions: illuminance level approx. 4,54 lx at a colour temperature of 2856 K and the appropriate filter inserted in the light path. Filters used are:

XQ2070R, XQ2075R	Schott	OG570	thickness	3	mm
XQ2070G			thickness	1	mm
XQ2070B	Schott	BG12	thickness	3	mm
XQ2073R	Schott	OG570	thickness	3	mm
and	Calflex	B1/K1			

For transmission curves see General Section.

- 11. As measured with a 50 mm Leitz Summicron lens having a sine response of approximately 85% at 20,6 lp/mm (400 TV lines at 9,6 mm picture height) at f: 5,6 and the appropriate filter inserted in the light path. The amplitude response can be raised by means of suitable correction circuits.
- 12. Adjusted for sum of dark current, leakage current and light bias current of 3 nA.
- 13. Build-up lag

After 10 s of darkness. The figures are typical percentages of the ultimate signal current obtained 60 ms and 200 ms, respectively, after the introduction of the illuminance.

Decay lag

After the target has been illuminated for at least 5 s. The figures represent typical signals in percentages of the original signal current 60 ms and 200 ms, respectively, after removal of the illuminance.

- 14. Deviation of the level of any of the four corners, i.e. 10% inwards in L and V direction, from the level in the picture centre. The observed shading is composed of slight parabolic and sawtooth components in both line and frame direction which can be sufficiently compensated by suitable black shading compensation circuitry.
- 15. a. With DBC applied (see note 2) the tube will properly handle highlights with a diameter of 10% of the picture height and with a brightness corresponding to 16 times peak signal white, I_{SD}.
 - b. The maximum peak signal currents in the case of highlights will be 2,5 μ A. Video preamplifiers should be designed to accompdate these.

XQ2070 SERIES




Fig. 1 Typical spectral response for XQ2070, R, G, B, L.




Fig. 3 Typical square-wave response curves for XQ2070.




Fig. 2 Typical spectral responses for XQ2073R - XQ2075R.




Fig. 4 Typical square-wave response curves for XQ2073/XQ2075.

CAMERA TUBES

25,4 mm (1 inch) diameter Plumbicon $^{\circledR}$ television camera tubes with high resolution lead-oxide photoconductive target, exclusively for use with X-ray image intensifiers with P20 output phosphor in medical equipment.

The XQ2172 series comprises the following versions:

XQ2172/02 Rear loading, with target centring ring and standard anti halation glass disc.

XQ2172/03 Front loading, with metal ring, without anti-halation glass disc.

XQ2172/03X Front loading, with metal ring and BG18 anti-halation glass disc.

Special features are:

- New photoconductive target for increased resolution;
- "Diode" electron gun with special cathode for high beam current operation, improved beam acceptance and low lag;
- · Provision for light bias to reduce lag.

QUICK REFERENCE DATA

"Diode" electron gun	
Diameter	25,4 mm (1 in)
Length	approx. 170 mm
Focusing	magnetic
Deflection	magnetic
Useful target area, circle diameter	16,2 mm
Spectral response maximum at cut-off at	≈ 500 nm ≈ 850 to 950 mm
Sensitivity with P20 light source XQ2172/02 XQ2172/03 XQ2172/03X	typ. 440 μ A/ImF typ. 490 μ A/ImF typ. 465 μ A/ImF
Resolution	typ. 60%
Heater	6,3 V, 190 mA

[®] Registered Trade Mark for television camera tube.

XQ2172 SERIES

OPTICAL DATA

Dimensions of quality area on photoconductive target

circle, dia. 16,2 mm

Orientation of image on target

For correct orientation of the image on the target the vertical scan should be essentially parallel to the plane passing through the tube axis and the mark on the tube base.

Faceplate

thickness 1,2 mm refractive index 1,49

Standard anti-halation glass disc (XQ2172/02)

thickness 5 mm refractive index 1,52

BG18 anti-halation glass disc (XQ2172/03X)

thickness 1,07 mm refractive index 1,54

ACCESSORIES

Socket type 56098

Deflection and focusing coil unit,

XQ2172/02 AT1119, AT1126S XQ2172/03 (X) AT1116S

ELECTRICAL DATA

Deflection magnetic

Focusing magnetic

Heating

Indirect by a.c. or d.c.

Heater voltage $V_f = 6.3 \text{ V} \pm 5\%$ Heater current, at $V_f = 6.3 \text{ V}$ $I_f = 190 \text{ mA}$

The heater voltage must not exceed 9,5 V r.m.s. For optimum performance stabilization of the heater voltage is recommended.

Capacitance

Signal electrode to all

XQ2172/02 2,5 to 4 pF XQ2172/03 3 to 5 pF

These capacitances, which are effectively the output impedances, increase when the tubes are inserted in the coil unit.

Faceplate illuminance

LIMITING VALUES (Absolute maximum rating system)					
All voltages are referred to the cathode, unless otherwise stated.					notes
Signal electrode voltage	Vas	max.	50	V	
Grid 4 voltage (mesh)	V_{q4}	max.	1100	V	
Grid 3 voltage	V_{g3}	max.	800	V	
Voltage between grid 4 and grid 3	V _{g4/g3}	max.	450	V	
Grid 2 voltage	V_{g2}	max.	350	V	
Grid 1 voltage, positive	V_{g1}	max.	20	٧	
Grid 1 voltage, negative	$-V_{g1}$	max.	200	V	
Grid 1 current (≈ cathode current)	I _{q1}	max.	10	mA	3
Cathode to heater voltage, positive peak	Vkfp	max.	50	V	
Cathode to heater voltage, negative peak	$-V_{kfp}$	max.	125	V	
Cathode heating time before drawing cathode current	th	min.	1	min	
External resistance between cathode and heater					
at $V_{kfp} > 10 V$	Rkf	min.		kΩ	
Ambient temperature, storage and operation	T _{amb}	max. min.	50 -30	oC oC	
Faceplate temperature, storage and operation	Т	max. min.	50 -30	oC oC	4

E max.

500 lx 5

XQ2172 SERIES

OPERATING CONDITIONS AND PERFORMANCE			notes
Conditions			6
Cathode voltage	V_k	0	V
Signal electrode voltage	V_{as}	45	V
Beam current	Ib		7,8
Grid 4 voltage	V_{g4}	960	V 9
Grid 3 voltage	V_{g3}	600	V 9
Grid 2 voltage	V_{q2}	300	V
Grid 1 voltage	V_{g1}	0 to 20	V
Blanking voltage on grid 1, peak to peak	V _{g1 p-p}	30	V
Focusing coil current	3-1-1		6
Deflection and alignment currents			6
Faceplate illuminance (P20 light source)	E	0 to 10	lx
Faceplate temperature	T - *	20 to 45	oC
ELECTRON GUN CHARACTERISTICS			
Grid 1 voltage for cut-off at V _{q2} = 300 V	V_{q1}	-10 to 0	V
Grid 1 voltage for normal beam setting	V _{a1w}	≤ 20	V
Grid 1 current at normally required beam currents	I _{g1}	≤ 5	mA
Grid 2 current at normally required beam currents	I _{g2}	≤ 0,1	mA
Blanking voltage, peak to peak, with respect to V_{g1w}	V _{g1 p-p}	30	V
Performance			
Dark current	ld	< 2	nA
Sensitivity at colour temperature of 2856K			10
XQ2172/02 XQ2172/03	min. 130	typ. 145	
XQ2172/03 XQ2172/03X	min. 145 min. 90	typ. 155 typ. 110	
Sensitivity with P20 light source		typ. 110	μητητιτιτ
XQ2172/02	min. 395	typ. 440	$\mu A/Im$
XQ2172/03	min. 440	typ. 490	· ·
XQ2172/03X	min. 400	typ. 465	$\mu A/Im$
Peak signal current with E = 1 Ix (P20)			11
XQ2172/02 I _s XQ2172/03 I _s		typ. 205	
XQ2172/03 XQ2172/03X	P	typ. 225 typ. 215	
Peak signal current (16,2 mm dia scanning)	P	2000	

Signal current after 60 ms illumination

XQ2172 SERIES


Gamma of transfer characteristic	0,95 ± 0,05
Spectral response: max. response at cut-off at	≈ 500 nm 800 to 950 nm
response curves Resolution	see Fig. 4
Modulation depth i.e. uncompensated amplitude response at 20,3 lp/mm (scanned area 9,6 x 12,8 mm) at the centre of the picture (5 MHz, 400 TV lines)	min. 50 % typ. 60 %
Modulation depth at 12 lp/mm (scanned area 16,2 mm diameter) at the centre of the picture (5 MHz 400 TV lines) Modulation transfer characteristic, see Fig. 7	min. 70 % typ. 80 %
Decay lag (no light bias applied) Fig. 6	13
Residual signal after dark pulse of 60 ms	max. 18 % 14 typ. 12 %
Residual signal after dark pulse of 200 ms	max. 7 % typ. 4 ,5 %
Build-up lag (no light bias applied) Fig. 5	min. 50 % 15

typ. 95 %


XQ2172 SERIES

MECHANICAL DATA

Rear loading tubes XQ2172/02



Front loading tubes XQ2172/03



Front loading tubes XQ2172/03X




Fig. 1.


Mounting position: any

Mass:

≈ 70 g

Base:

IEC 67-I-33a (JEDEC E8-11)






Fig. 2b.

(1) The distance between the geometrical centres of diameter A of the reference ring and diameter B of the mesh electrode ring is < 100 μm .




Fig. 2c.

XQ2171 SERIES

NOTES, see also General Section

- The "Diode" gun operates with a positive grid 1 voltage, hence draws some grid current. The grid 1 voltage (d.c.) must be adjusted for correct beam current as described in note 8.
- 2. "Diode" gun is a triode gun operating in a diode mode, providing a very high beam reverse. Continuous operation with a high beam setting is to be avoided since this will shorten tube life. High I_D settings should be used under high light intensity conditions only. All other modes of operation should be normal I_D settings or have them cut off.
- 3. A current limiter must be incorporated to limit total cathode current to 10 mA maximum.
- The tube can withstand short excursions up to 70.°C without any damage or irreversible degradation in performance.
- For short intervals. During storage the tube face shall be covered with the plastic hood provided; when the camera is idle the lens shall be capped, in stand-by also the beam will be cut-off.
- 6. The operating conditions and performance data quoted, relate to operation of the tube in coil units AT1116, AT1119 or AT1126. See relevant data of deflection/focusing assemblies. Scanning amplitude should be adjusted such that the useful target area of 16,2 mm dia. is displayed on a standard monitor as a circular area with a diameter equal to the raster height.
- 7. The maximum peak signal which can be handled is 3 μ A. Video amplifiers should be designed to accommodate this.
- 8. The beam current I_b, as obtained by adjusting the control grid voltage (grid 1) is set at 400 nA. I_b is not the total current available in the scanning beam, but is defined as the maximum amount of signal current I_s, that can be obtained with this beam.
 In the performance figures, e.g. for resolution and lag, the signal current and beam current conditions are given, e.g. as I_s/I_b = 20/300 nA. This means: with a signal current of 20 nA and a beam setting which just allows a signal current of 300 nA.
 - N.B. The signal currents are measured with an integrating instrument connected in the signal electrode lead and a uniform illumination of the scanned area. See note 11.
- 9. The optimum voltage ratio V_{g4}/V_{g3} to minimize beam landing errors (preferably \leq 1 V) depends on the type of coil unit used. For types AT1116, AT1119 and AT1126 a ratio of 1,6 is recommended. Grid 4 (mesh) should under no circumstances be allowed to operate at a voltage below that of grid 3 as that might damage the target.
- Measuring conditions: illuminance level 4,54 lx at a colour temperature of 2856K and filters, Schott VG9 and Calflex B1/K1 inserted in the light path. For transmission of the filters, see General Section.

NOTES (continued)

11. The peak signal currents are measured on a waveform oscilloscope and with a uniform illumination on the 16,2 mm @ target area.

When measured with an integrating instrument connected in the signal-electrode lead the average signal currents will be smaller:

- a. By a factor α ($\alpha = \frac{100 \beta}{100}$), β being the total blanking time in %; for the CCIR system α amounts to 0.75.
- b. By a factor δ , δ being the ratio of the active target area (circle with: 16,2 mm \emptyset) to the area which would correspond with the adjusted scanning amplitude (16,2 mm x 21,6 mm) this ratio amounts to δ = 0,59.

The total ratio of integrated signal current, I_S , to the peak signal current, I_{SP} , amount to $\alpha \times \delta = 0.44$.

- 12. As measured with a 50 mm Leitz Summicron lens having a sine response of approximately 85% at 400 TV lines at f:5,6. The published 60% typ. is uncorrected. Tube resolution is higher. Measured with 200 nA signal current and a beam current just sufficient to stabilize a signal current of 400 nA. The horizontal amplitude response can be raised by means of suitable correction circuits, which affect neither the vertical resolution nor the limiting resolution.
- Measured with a 20 nA signal current and a beam current just sufficient to stabilize a signal current of 300 nA.
- 14. Decay lag. After a minimum of 5 s of illumination of the target. Values and curves shown relating to decay lag represent the residual signal currents in percentages of the original signal current as a function of time, after the illumination has been removed.
- 15. Build-up lag. After 10 s of complete darkness. Values and curves shown relating to build-up lag represent the typical percentages of the ultimate signal obtained as a function of time, after the illumination has been applied.




Fig. 3 Average beam current versus grid 1 voltage (see note 11).




Fig. 4 Typical spectral response curve.

XQ2172 SERIES




Fig. 5 Build-up lag, see note 15. Light-bias induced dark current as parameter. $I_g/I_b = 20/300 \text{ nA}$.




Fig. 6 Decay lag, see note 14. $I_s/I_b = 20/300 \text{ nA}$.




Fig. 7 Typical square-wave transfer characteristic.

CAMERA TUBES

25,4 mm (1 in) diameter Plumbicon[®] television camera tubes, with high resolution lead-oxide photoconductive target, for use in high quality monochrome or colour cameras for broadcast, educational or industrial applications.

The XQ3070 series comprises the following front loading versions:

for use in monochrome cameras XQ3070 XQ3070L for use in the luminance channel of colour cameras XQ3070R for use in the red channel XQ3070G for use in the green channel XQ3070B for use in the blue channel as XQ3070 series; only difference being the degree of freedom from blemishes XQ3071 on the target (industrial quality tubes) XQ3073R for use in the red channel; extended red response XQ3074 as XQ3073. Industrial grade XQ3075R for use in the red channel; extended red response and IR filter XQ3076 as XQ3075. Industrial grade

These tubes are available in rear loading versions (/02,/05,/12 and /15) only.

Special features are:

//D:-----

- New photoconductive target for increased resolution
- "Diode" electron gun with high beam reserve for dynamic beam control (DBC) to minimize cometailing and blooming (notes 1, 2, 3)
- Provision for light bias to reduce lag
- Low output capacitance (LOC) for high signal-to-noise ratio

QUICK REFERENCE DATA

"Diode" electron gun				
Diameter		25,4	mm (1 inch)	
Length	approx.	170	mm	
Provided with anti-halation glass disc				
Focusing	magnetic			
Deflection	magnetic			
Useful target area (scanning area)	9,6	x 12,8	mm	
Spectral response				
max. at	approx.	500	nm	
cut-off: XQ3070	approx.	650	nm	
XQ3073	approx.	850	to 950 nm	
XQ3075	approx.	750	nm	
Sensitivity				
XQ3070, XQ3070L	typ.	350	$\mu A/Im$	
XQ3070R	typ.	70	μA/ImF	
XQ3070G	typ.	145	μA/ImF	
XQ3070B	typ.	38	μA/ImF	
XQ3073R, XQ3075R	typ.	100	μA/ImF	
Resolution at 400 TV lines (5 MHz)				
XQ3070, XQ3070L	typ.	60	%	
XQ3070R	typ.	45	%	
XQ3070G	typ.	60	%	
XQ3070B	typ.	60	%	
XQ3073R, XQ3075R	typ.	55	%	
Heater		6,3	V, 95 mA	

[®] Registered trademark for television camera tubes.

XQ3070 SERIES

MECHANICAL VARIANTS

Variants are defined by a suffix as follows:

XQ /02, R, G, B, L: rear loading versions with provision for internal light bias, target contact ring with 1 target contact, metal sleeve on pumping stem to mount light bias lamp.

XQ /05, R, G, B, L: as /02, however without provision for light bias lamp.

XQ /12, R, G, B, L: as /02, however with 2 contacts on the target ring.

XQ..../15, R. G. B. L: as /05, however with 2 contacts on the target ring.

OPTICAL DATA

notes

Quality rectangle on

photoconductive target (aspect ratio 3:4)

9.6 x 12.8 mm

Orientation of image on target:

For correct orientation of the image on the target the vertical scan should be essentially parallel to the plane passing through the tube axis and the marker line on the protecting sleeve at the base.

Faceplate

Thickness

 $1.2 \pm 0.1 \, \text{mm}$ n = 1.49

Refractive index

Anti-halation glass disc provided with

anti reflective coating

Thickness

 $5 \pm 0.1 \, \text{mm}$

Refractive index

n = 1.52

XQ3075R is provided with infrared reflecting filter

ACCESSORIES

Socket

type 56098

Deflection and focusing coil unit:

Black/white

type AT1126S

Colour

type AT1126T

Mask for flare reduction

type 56028

Light bias lamp in holder

type 56106

4

ELECTRICAL DATA

Deflection

magnetic

Focusing

magnetic

Heating, indirect by a.c. or d.c.; parallel supply

Vf

6,3 V ± 5%

Heater voltage

If nom.

95 mA

Heater current at Vf = 6,3 V

The heater current and the heater voltage must not exceed r.m.s. values of 150 mA and 9,5 V. For optimum

performance (lifetime and registration stability)

stabilization of the heater voltage is recommended.

Capacitance

Signal electrode to all

rear loading types /02 and /05

Cas

approx. 2,1 pF

rear loading types /12 and /15 This capacitance, which is effectively the output Cas

approx. 2,5 pF

impedance, increases when the tube is inserted in

the coil unit.

LIMITING VALUES (Absolute maximum rating sys	tem)				notes	
Unless otherwise stated, all voltages are referred to t	he cathode.					
Signal electrode voltage	Vas	max.	50	\/		
Grid 4 voltage	Vas Vg4		1100	78.1		
Grid 3 voltage	V _g 3	max.	800			
Voltage between grid 4 and grid 3	V _{g4/g3}	max.	450			
Grid 2 voltage	V _{g2}	max.	340			
Grid 1 voltage.	* g2	mux.	040	•		
positive	V_{g1}	max.	25	V		
negative	$-V_{g1}$	max.	200			
Grid 1 current	* g i	max.	200	V		
≈ Ik current, without blanking	I _{q1}	max.	5	mA		
peak to peak with DBC		max.		mA	2	
A PART PRODUCTION AND A PART OF THE PART O	g1p	mux.	U	III/A	2	
Cathode to heater voltage	1/		105	1/		
positive peak	Vkfp	max.	125			
negative peak	$-V_{kfp}$	max.	50	V		
Cathode heating time before						
drawing current	th	min.	1	min		
External resistance between cathode						
and heater at V _{kfp} > 10 V	Rkf	min.		kΩ		
Ambient temperature, storage and operation	Tamb	max.	50	oC		
Ambient temperature, storage and operation	amb	min.	-30	oC		
Faceplate temperature, storage and operation	Т	max.	50	oC		
r aceptate temperature, storage and operation	1	min.	-30	oC		
Faceplate illuminance	E	max.	500	lx	5	
OPERATING CONDITIONS						
For a scanned area of 9,6 x 12,8 mm					6	
Cathode voltage	V_k		0	V		
Signal electrode voltage	Vas		45	V		
Beam current	l _b				7	
Grid 4 voltage	V _{g4}		960	V	•	
Grid 3 voltage	V-2		600			
Grid 2 voltage	V _g 3		300			
Grid 1 voltage	V _{g2}			V	7	
	Vg1		25	•	1	
Blanking voltage on grid 1, peak to peak Faceplate illuminance	V _{g1p-p}	0	to 10		8	
and the state of t	T		to 45		9	
Faceplate temperature	1	20	10 45		9	
ELECTRON GUN CHARACTERISTICS						
Cut off						
Grid 1 voltage for cut-off at $V_{g2} = 300 \text{ V}$,						
without blanking	V_{g1}	-1	0 to 0	V		
Grid 1 voltage for normal beam setting	V _{g1w}	<	15			
Blanking voltage, peak to peak	9144					
on grid 1	V_{g1p-p}		25	V		
on cathode	V _{kp} -p		25			
Grid 1 current at normally required	- kh-h			ď		
beam currents	I _{g1}	<	1.5	mΑ	2	
Grid 2 current at normally required	·91		,,0		_	
beam currents	I _{q2}	<	0.1	mA	2	
	·g2		0,1		~	

XQ3070 SERIES

PERFORMANCE						notes
Dark current	Id		\leq	2	nA	
Sensitivity at colour temperature of illuminance = 28						10
XQ3070, L	min.	300	typ.	350	$\mu A/Im$	
XQ3070R	min.	63	typ.	70	$\mu A/ImF$	
XQ3070G	min.	130	typ.	145	μA/ImF	
XQ3070B	min.	35	typ.	38	$\mu A/ImF$	
XQ3073R, XQ3075R	min.	80	typ.	100	$\mu A/ImF$	
Gamma of transfer characteristic			0,95 ±	0,05		
Spectral response, max. at				500	nm	
Spectral response, cut-off at			650 t	o 950	nm	
Spectral response curves	see Fig	s 1, 2				
Resolution						11

Modulation depth, i.e. uncompensated amplitude response at 400 TV lines at the centre of the picture.

		XQ3070 XQ3070L XQ3070G	XQ3070R	XQ3070B	XQ3073R XQ3075R		7, 11
Highlight signal current Beam current Modulation depth	I _s	200 400	100 200	100 200	100 200	nA nA	
at 400 TV lines typ. min.		60 55	45 40	60 55	55 50	% %	

Modulation transfer characteristics: see Figs 3 and 4 $\,$

Lag (typical values, with light bias of 3 nA)

12, 13

Light source with a colour temperature of 2856 K. Appropriate filter inserted in the light path for the chrominance tubes R, G and B

LOW KEY CONDITIONS

	build	-up lag	decay	lag	
	I _s /I _b = 20/300 nA		$I_{s}/I_{b} = 20/300 \text{ nA}$		
	60 ms	200 ms	60 ms	200 ms	
XQ3070, L	95%	~ 100%	9%	2,5%	
XQ3070G	95%	~ 100%	9%	2,5%	
XQ3070R	95%	~ 100%	9%	2,5%	
XQ3070B	90%	~ 100%	12%	4%	
XQ3073R, XQ3075R	90%	~ 100%	11%	3%	

Shading of light bias induced dark current Highlight handling capability with DBC

12,5%

14

15


MECHANICAL DATA


Rear loading tubes XQ3070/02 and XQ3070/12


Mounting position: any

Mass:


≈ 70 g










FRONT VIEW XQ /02



FRONT VIEW XQ..../12








centres of diameter A of the reference ring and diameter B of the mesh electrode ring is $< 100 \ \mu m$.

i.c.

XQ3070 SERIES



NOTES, see also General Section

"Diode" electron gun is a triode gun operating in a diode mode, providing a very high beam reserve.
 N.B.

Avoid continuous operation at high beam currents since this will shorten tube life. Full advantage of the high beam reserve to reduce comet-tailing and blooming can be made with DBC circuitry which, during highlights, feeds positive-going pulses derived from the video signal to grid 1, to increase the beam current momentarily.

 The "diode" gun operates with a positive (≤ 15 V) grid 1 voltage (adjusted for correct beam settings, see note 7), hence draws some grid 1 current:

without DBC: ≤ 1,5 mA (peak) with blanking

with DBC: ≤8 mA (peak) with blanking, measured with oscilloscope.

The DBC circuitry should, in the case of highlights, supply positive-going pulses of 7 V above V_{g1W} (see note 7) and up to 8 mA peak to grid 1. N.B.

Applying higher pulses than 7 V is not recommended since this will shorten tube life, impair resolution and may introduce oscillations.

- The XQ3070 tubes closely resemble mechanically the tubes of the XQ1080/XQ1500 series. Since, however, the "Diode" electron gun draws some grid 1 current (see note 2), cameras designed around XQ1080/XQ1500 tubes will require some modification.
- 4. For adjustable light bias in versions /02 and /12. The light bias lamp assembly as supplied with these tubes, type 56106, fits in the metal tube cemented to the pumping stem of the tube. The tube and the light bias lamp assembly will fit properly in the socket, type 56098. The wires should be connected to a source, capable of supplying max. 110 mA at 5 V.
 The desired amount of light bias can be obtained by adjusting the current through the filament of the lamp. For black/white operation a light bias corresponding to 2 to 3 nA extra dark current is usually adequate for excellent speed of response. In a colour camera the speeds of response of the tubes can be balanced by adjusting the amount of light bias per tube. A typical setting in a

3-tube colour camera could be 3 nA (R), 2 nA (G), and 6 nA (B). Infrared light with a wavelength

- > 600 nm in the light bias should be avoided.

 5. For short intervals. During storage the tube face shall be covered with the plastic hood provided;
- when the camera is idle the lens shall be capped, in stand-by also the beam will be cut-off.

 6. The operating conditions and performance data quoted relate to operation of the tube in coil unit AT1126. See relevant data of deflection/focusing assemblies.
- 7. The beam current I_b, as obtained by adjusting the control grid (grid 1) voltage is set for 1 stop over peak white and is 200 nA for R and B tubes, 400 nA for black/white and G tubes. I_b is not the total current available in the scanning beam, but is defined as the maximum amount of signal current, I_s, that can be obtained with this beam.
 - In the performance figures e.g. for lag, the signal current and beam current conditions are given as $I_s/I_b = 20/300$ nA. This means: with a signal current of 20 nA and a beam setting which just allows a signal current of 300 nA.
- 8. Typical faceplate illumination level for the XQ3070 and XQ3070L to produce 200 nA signal current will be approx. 4,6 lx. The signal currents stated for the colour tubes R, G and B will be obtained with an incident white light level (2856 K) on the filter of approx. 11 lx. These figures are based on the filters described in note 10. For filter BG12, however, a thickness of 1 mm is chosen.
- The tube can withstand short excursions up to 70 °C without damage or irreversible degradation in performance.

XQ3070 SERIES

10. Measuring conditions: illuminance level 4,54 lx at a colour temperature of 2856 K and the appropriate filter inserted in the light path. Filters used are:

XQ3070R, XQ3075R	Schott	OG570	thickness	3 mm
XQ3070G	Schott	VG9	thickness	1 mm
XQ3070B	Schott	BG12	thickness	3 mm
XQ3073R	Schott	OG570	thickness	3 mm
а	nd Calflex	B1/K1		

For transmission curves see General Section.

- 11. As measured with a 50 mm Leitz Summicron lens having a sine response of approximately 85% at 20,6 lp/mm (400 TV lines at 9,6 mm picture height) at f: 5,6 and the appropriate filter inserted in the light path. The amplitude response can be raised by means of suitable correction circuits.
- 12. Adjusted for sum of dark current, leakage current and light bias current of 3 nA.
- 13. Build-up lag

After 10 s of darkness. The figures are typical percentages of the ultimate signal current obtained 60 ms and 200 ms, respectively, after the introduction of the illuminance.

Decay lag

After the target has been illuminated for at least 5 s. The figures represent typical signals in percentages of the original signal current 60 ms and 200 ms, respectively, after removal of the illuminance

- 14. Deviation of the level of any of the four corners, i.e. 10% inwards in L and V direction, from the level in the picture centre. The observed shading is composed of slight parabolic and sawtooth components in both line and frame direction which can be sufficiently compensated by suitable black shading compensation circuitry.
- 15. a. With DBC applied (see note 2) the tube will properly handle highlights with a diameter of 10% of the picture height and with a brightness corresponding to 16 times peak signal white, I_{SD}.
 - b. The maximum peak signal currents in the case of highlights will be 2,5 μ A. Video preamplifiers should be designed to accommodate these.




Fig. 1 Typical spectral response XQ3070, R, G, B.




Fig. 3 Typical square-wave response curves XQ3070.




Fig. 2 Typical spectral response XQ3073R, XQ3075R.




Fig. 4 Typical square-wave response curves XQ3073/XQ3075.



ENSO HEDRETER ON THE W

CAMERA TUBES

18 mm (2/3 in) diameter Plumbicon® television camera tubes, with standard resolution lead-oxide photoconductive target, for use in high quality monochrome or colour cameras for broadcast, educational or industrial applications.

The XQ1427 series comprises the following versions:

XQ1427	for use in monochrome cameras
XQ1427R	for use in the red channel
XQ1427G	for use in the green channel
XQ1427B	for use in the blue channel
XO1428	as XO1427 series only difference

as XQ1427 series; only difference being the degree of freedom from blemishes on

the target (industrial quality tubes).

Special feature:

• Mechanically interchangeable with 2/3 inch diameter Vidicon tubes with separate mesh. See note 1.

QUICK REFERENCE DATA

Separate mesh			
Diameter		17,8	mm (2/3 inch)
Length	approx.	108	mm .
Provided with anti-halation glass disc			
Focusing	magnetic		
Deflection	magnetic		
Useful target area (scanning area)	6,6	x 8,8	mm
Spectral response			
max. at	approx.	500	nm
cut-off: XQ1427R	approx.	850	nm
XQ1427, XQ1427G	approx.	650	to 850 nm
XQ1427B	approx.	650	nm
Sensitivity			
XQ1427	typ.	365	μA/Im
XQ1427R	typ.	100	μA/lmF
XQ1427G	typ.	135	μA/ImF
XQ1427B	typ.	38	μA/ImF
Resolution at 320 TV lines (4 MHz)			
XQ1427	typ.	60	%
XQ1427R	typ.	52	%
XQ1427G	typ.	60	
XQ1427B	typ.	65	
Heater		6,3	V, 95 mA

[®] Registered trade mark for television camera tubes.

OPTICAL DATA notes

Quality rectangle on

photoconductive target (aspect ratio 3:4)

6.6 x 8.8 mm

Orientation of image on target:

For correct orientation of the image on the target the vertical scan sould be essentially parallel to the plane passing through the tube axis and the gap between pins 1 and 7.

Faceplate

Thickness

Refractive index

 2.3 ± 0.1 mm n = 1.49

Refractive index

Anti-halation glass disc provided with anti reflective coating

Thickness

 $3.7 \pm 0.1 \, \text{mm}$

n = 1,52

ACCESSORIES

Deflection and focusing coil unit:

type 56049 rear loading type AT1109S

front loading AT1106S

Black/white Colour

Mask for flare reduction

type AT1109T type 56033

AT1106T

ELECTRICAL DATA

Deflection

Focusing

magnetic magnetic

Heating, indirect by a.c. or d.c.; parallel supply

Heater voltage

6.3 V ± 5%

Heater current at Vf = 6,3 V

If nom.

95 mA

The heater voltage must not

exceed an r.m.s. value of 9 V. For optimum

performance (lifetime and registration stability)

stabilization of the heater voltage is recommended.

Capacitance

Signal electrode to all

Cas

1.5 to 3 pF

This capacitance, which is effectively the output impedance, increases when the tube is inserted in the coil unit.

								_
LIMITING VALUES (Absolute maximum	m rating syst	em)					notes	
Unless otherwise stated, all voltages are r	eferred to th	e cathode.						
Signal electrode voltage		Vas	max.	50	V		1	
Grid 4 voltage		V _{q4}		1000				
Grid 3 voltage		V_{g3}^{g4}	max.	750				
Voltage between grid 4 and grid 3		V _{94/q3}	max.	400	V			
Grid 2 voltage		$V_{g2}^{g1/g0}$	max.	350	V			
Grid 1 voltage,		3-						
positive		V_{g1}	max.	0	V			
negative		$-V_{q1}$	max.	200	V			
Cathode heating time before drawing		3						
cathode current		th	min.	1	min			
Cathode to heater voltage								
positive peak		V_{kfp}	max.	125				
negative peak		$-V_{kfp}$	max.	50	V			
External resistance between cathode and								
heater at $-V_{kfp} > 10 V$		Rkf	min.		kΩ			
Ambient temperature, storage and opera	tion	Tamb	max.	50				
, instant temperature, storage and opera		· amb	min.	-30				
Faceplate temperature, storage and opera	ation	Т	max.				2	
	acion		min.	-30			_	
Faceplate illuminance		E	max.	500	Ix		3	
OPERATING CONDITIONS								
For a scanned area of 6,6 x 8,8 mm.							4	
Cathode voltage		Vk		0	V			
Signal electrode voltage		Vas		45	V			
Beam current		lb					5	
		low voltage	mode l	nigh vol	tage r	node	9	
Grid 4 voltage	V_{q4}	500		750	V			
Grid 3 voltage	V_{g3}	285		430	V		6	
Grid 2 voltage	V_{q2}	300	1	300	V			
Grid 1 voltage	V_{g1}						5	
Blanking voltage on grid 2, peak to peak		V_{g1p-p}		50	V			
Faceplate illuminance				to 10			7	
Faceplate temperature			20	to 45	oC			
ELECTRON GUN CHARACTERISTICS	S							
Cut off								
Grid 1 voltage for cut-off at $V_{q2} = 300$ V	/							
without blanking	ν,	V _{a1}	_30 t	o -80	V			
Grid 1 voltage for normal beam setting		V _{q1w}		o -10				
Blanking voltage, peak to peak		* g i w	00 1	0 10				
on grid 1		V_{g1p-p}	5	0 ± 10	V			
on cathode		V _{kp-p}		25				
Grid 2 current at normally required		Wh h						
beam currents		I _{g2}	\leq	0,5	mA			
		3-						

XQ1427 SERIES

PERFORMANCE						notes
Dark current	ld		<	1,5	nA	
Sensitivity at colour temperature of illuminance = 2856	K					7
XQ1427	min.	330	typ.	365	$\mu A/Im$	
XQ1427R	min.	75	typ.	100	μA/ImF	
XQ1427G	min.	110	typ.	135	μA/ImF	
XQ1427B	min.	35	typ.	38	μA/ImF	
Gamma of transfer characteristics			0,95	± 0,05		
Spectral response, max. at	approx			500	nm	9
Spectral response, cut-off at	approx		650 t	o 850	nm	
Spectral response curves	see Fig	. 1				
Resolution						
Modulation depth, i.e. uncompensated amplitude						

		XQ1427	XQ1427R	XQ1427G	XQ1427B	
Highlight signal						
current Is		150	75	150	75	nA
Beam current Ib		300	150	300	150	nA
Modulation depth at	- 77					
320 TV lines (4 MH	z)					
high voltage mode,	typ.	60	52	60	65	%
	min.	55	47	55	60	%
low voltage mode,	typ.	55	47	55	60	%
	min.	50	40	50	55	%

Modulation transfer characteristics: see Figs 2 and 3 Lag (typical values, no light bias applied) Light source with a colour temperature of 2856 K. Appropriate filter inserted in the light path for the chrominance tubes R, G and B.

response at 320 TV lines at the centre of the picture (4 MHz)


11,12

10


LOW KEY CONDITIONS

	build-up lag		decay lag $I_S/I_D = 20/300 \text{ nA}$		
	60 ms	200 ms	60 ms	200 ms	
XQ1427, XQ1427G	90	≈ 100	9	3 %	
XQ1427R	90	≈ 100	9,5	4 %	
XQ1427B	90	≈ 100	9,5	4 %	

MECHANICAL DATA



The distance between the geometrical centres of diameters A (anti-halation disc), B (signal-electrode ring), and the geometrical centre of diameter C (tube envelope) is $\leq 200~\mu m$.



0,63 max

Mounting position: any

Mass: ≈ 23 g Base: EIA E7-91

XQ1427 SERIES

NOTES, see also General Section

- Plumbicon tubes do not permit automatic sensitivity control by means of regulation of the signal electrode voltage. Adequate control is therefore to be achieved by other means (iris control and neutral density filters).
 - N.B. When the tube is to be used in a camera originally designed for vidicon tubes, the automatic sensitivity control circuitry should be made inoperative and the signal electrode voltage be set to 45 V, in order to prevent damage or destruction of the target.
- The tube can withstand short excursions up to 70 °C without damage or irreversible degradation in performance.
- 3. For short intervals. During storage the tube face shall be covered with the plastic hood provided; when the camera is idle the lens shall be capped, in stand-by also the beam will be cut-off.
- The operating conditions and performance data quoted relate to operation of the tube in coil unit AT1109. See relevant data of deflection/focusing assemblies.
- The beam current I_b, as obtained by adjusting the control grid (grid 1) voltage is set to 150 nA for R and B tubes, 300 nA for black and white and G tubes. I_b is not the actual current available in the scanning beam, but is defined as the maximum amount of signal current, I_s, that can be obtained with this beam.
 - In the performance figures for lag, the signal current and beam current conditions are given, e.g. as $I_s/I_b = 20/300 \, \text{nA}$. This means: with a signal current of 20 nA and a beam setting which just allows a signal current of 300 nA.
 - The signal currents are measured with an integrating instrument connected in the signal electrode lead and a uniform illumination of the scanned area. The peak signal currents as measured on a waveform oscilloscope will be a factor α larger. α = 100/ $\{100 \beta\}$, β being the total blanking time in %; for the CCIR system α = 1,3.
- 6. a. The optimum voltage ratio V_{g4}/V_{g3} to minimize beam landing errors (preferably < 1 V) depends on the type of coil unit used. In the coil AT1109 a ratio of 1,75 is required. Under no circumstances should grid 4 (mesh) be allowed to operate at a voltage below that of grid 3 as this may damage the target.
 - b. An attractive gain in resolving power is obtained when the tubes are operated with higher grid 3 and grid 4 potentionals.
 - N.B. Since such operation requires increased focusing and deflection power, special measures (air cooling, heatsinks) have to be taken in the camera design to prevent faceplate temperatures exceeding the limiting value of 50 °C, which would otherwise affect tube performance and life. See also General Operational notes.
- 7. Typical faceplate illumination level for the XQ1427 to produce 150 nA signal current will be approx. 7 lx. The signal currents stated for the colour tubes R, G and B will be obtained with an incident white light level (2856 K) on the filter of approx. 19 lx. These figures are based on the filters described in note 8. For filter BG12, however, a thickness of 1 mm is chosen.
- Measuring conditions: illuminance level 4,54 lx at a colour temperature of 2856 K and the appropriate filter inserted in the light path.

Filters used are:

XQ1427G	Schott	VG9	thickness	1	mm
XQ1427B	Schott	BG12	thickness	3	mm
XQ1427R	Schott	OG570	thickness	3	mm
	and Calflex	B1/K1			

For transmission curves see General Section.

For true tonal rendition in black/white cameras and for true colorimetry in colour cameras an
integral filter to eleminate response to near infrared radiation should be incorporated in the optical
system, together with an integral B1/K1 filter or equivalent.

- 10. As measured with a 50 mm Leitz Summicron lens having a sine response of approximately 80% at 400 TV lines at f: 5,6 and the appropriate filter inserted in the light path. The horizontal amplitude response can be raised by means of suitable correction circuits, which affect neither the vertical resolution nor the limiting resolution.
- 11. Build-up lag

After 10 s of darkness. The figures are typical percentages of the ultimate signal current obtained 60 ms and 200 ms, respectively, after the introduction of the illuminance.

Decay lag

After the target has been illuminated for at least 5 s. The figures represent typical signals in percentages of the original signal current 60 ms and 200 ms, respectively, after removal of the illuminance

12. A reduction of lag, especially under low key conditions is obtained when light bias (up to 5 nA peak) is applied via the optical system. Infrared light with a wavelength > 600 nm in the light bias should be avoided.




Fig. 1 Typical spectral response.

XQ1427 SERIES




Fig. 2 Typical square wave response curves (low voltage mode).




Fig. 3 Typical square wave response curves (high voltage mode).

CAMERA TUBES

18 mm (2/3 in) diameter Plumbicon® television camera tubes, with high resolution lead-oxide photoconductive target, for use in high quality monochrome or colour cameras for broadcast, educational or industrial applications.

The XQ2427 series comprises the following versions:

XQ2427 for use in monochrome cameras
XQ2427R for use in the red channel
XQ2427G for use in the green channel
XQ2427B for use in the blue channel
XQ2428 as XQ2427 series; only difference

as XQ2427 series; only difference being the degree of freedom from blemishes on the target (industrial quality tubes).

Special features are:

- New photoconductive target for increased resolution
- "Diode" electron gun with high beam reserve for dynamic beam control (DBC) to minimize comet-tailing and blooming, see notes 1 and 2.

QUICK REFERENCE DATA

"Diode" electron gun		
Diameter	1	7,8 mm (2/3 inch)
Length	approx.	108 mm
Provided with anti-halation glass disc		
Focusing	magnetic	
Deflection	magnetic	
Useful target area (scanning area)	6,6 x	8,8 mm
Spectral response		
max. at	approx.	500 nm
cut-off: XQ2427R	approx.	350 nm
XQ2427, XQ2427G	approx.	650 to 850 nm
XQ2427B	approx.	350 nm
Sensitivity		
XQ2427	typ.	320 μA/Im
XQ2427R	typ.	$95 \mu A/ImF$
XQ2427G	typ.	125 μA/ImF
XQ2427B	typ.	$38 \mu A/ImF$
Resolution at 400 TV lines (5 MHz)		
XQ2427	typ.	50 %
XQ2427R	typ.	45 %
XQ2427G	typ.	50 %
XQ2427B	typ.	55 %
Heater		6,3 V, 95 mA

[®] Registered trade mark for television camera tubes.

XQ2427SERIES

OPTICAL DATA notes

Quality rectangle on

photoconductive target (aspect ratio 3:4)

6,6 x 8,8 mm

Orientation of image on target:

For correct orientation of the image on the target the vertical scan should be essentially parallel to the plane passing through the tube axis and the gap between pins 1 and 7.

Faceplate

Thickness 2,3 \pm 0,1 mm Refractive index n = 1,49

Anti-halation glass disc provided with

anti-reflective coating

Thickness

Refractive index

2.5 ± 0.1 mm

n = 1.52

type 56033

ACCESSORIES

Socket type 56049

Deflection and focusing coil unit:

Black/white

Colour

type AT110

type AT1109S AT1106S type AT1109T AT1106T

front loading

Mask for flare reduction

ELECTRICAL DATA

Deflection magnetic Focusing magnetic

Heating, indirect by a.c. or d.c.; parallel supply

Heater voltage $V_f = 6.3 \text{ V} \pm 5\%$ Heater current at $V_f = 6.3 \text{ V}$

The heater voltage must not

exceed an r.m.s. value of 9 V. For optimum performance (lifetime and registration stability) stabilization of the heater voltage is recommended.

Capacitance

Signal electrode to all Cas 1,5 to 3 pF

This capacitance, which is effectively the output impedance, increases when the tube is inserted in the coil unit.

February 1985

198

					-	
LIMITING VALUES (Absolute maximum	n rating system)				notes
Unless otherwise stated, all voltages are re	eferred to the ca	athode.				
Signal electrode voltage			may	50	\/	3
Grid 4 voltage		Vas	max.	1000		3
Grid 3 voltage		V _g 4	max.	750		
Voltage between grid 4 and grid 3		V _{g3}	max.	400		
Grid 2 voltage		V _g 4/ _g 3	max.	350		
Grid 1 voltage,		V_{g2}	IIIax.	330	V	
positive		V _{a1}	max.	25	V	
negative		-Vg1	max.	200		
Grid 1 current (≈ I _k)		l _{g1}	max.		mA	4
Grid 1 current (peak with DBC)			max.		mA	
Cathode heating time before drawing		g1p	max.	0	1117	
cathode current		th	min.	1	min	
Cathode to heater voltage		-11				
positive peak		V_{kfp}	max.	125	V	
negative peak		-V _{kfp}	max.	50		
External resistance between		• ктр	max.	50	V	
cathode and heater at V _{kfp} > 10 V		Rkf	min.	2	kΩ	
			max.		OC	
Ambient temperature, storage and operat	ion	Tamb	min.	-30		
			max.		oC	5
Faceplate temperature, storage and opera	ition	Т	min.	-30		
Faceplate illuminance		E	max.			6
OPERATING CONDITIONS						7
For a scanned area of 6,6 x 8,8 mm.						
Cathode voltage		V_k		0	V	
Signal electrode voltage		Vas		45		
Beam current		l _b		75	٧	8
Dean Current		low voltage r	node	high vo	oltane	
Grid 4 voltage	V_{g4}	500	iloue	750		9
Grid 4 voltage	Vg3	285		430		9
Grid 2 voltage	Vg3 Vg2	300		300		Ü
Grid 1 voltage	Vg2 Vg1	300		500	V	8
Blanking voltage on grid 2, peak to peak	*91	Vg1p-p		25	V	J
Faceplate illuminance		vg1p-p	0	to 10		10
Faceplate temperature				to 45		
ELECTRON GUN CHARACTERISTICS						
Cut off						
Grid 1 voltage for cut-off at $V_{g2} = 300 \text{ V}$,			0. 6		
without blanking		Vg1		0 to 0		0
Grid 1 voltage for normal beam setting		V _{g1w}	<	15	V	8
Blanking voltage, peak to peak		V .		25	1/	
on grid 1		V _{g1p-p}		25	100	
on cathode		V _{kp-p}		25	V	
Grid 1 current at normally required		La	<	1 E	m A	
beam currents		^J g1		1,5	mA	
Grid 2 current at normally required beam currents		I _{g2}	<	0,1	mA	
		y-				

XQ2427 SERIES

PERFORMANCE						notes
Dark current	ld		<	1,0	nA	
Sensitivity at colour temperature of illuminance = 2856	K					11
XQ2427	min.	275	typ.	320	$\mu A/Im$	
XQ2427R	min.	80	typ.	95	μA/ImF	
XQ2427G	min.	95	typ.	125	μA/ImF	
XQ2427B	min.	35	typ.	38	μA/ImF	
Gamma of transfer characteristics			0,95 ±	0,05		
Spectral response, max. at	approx			500	nm	12
Spectral response, cut-off at	approx		650 t	o 850	nm	
Spectral response curves	see Fig	. 1				
Resolution						13
Modulation depth, i.e. uncompensated amplitude response at 400 TV lines at the centre of the picture (5 M	ЛHz)					

		XQ2427	XQ2427R	XQ2427G	XQ2427B	
Highlight signal	n1	200	150	200	150	- 0
current Is		200	150	200	150	nA
Beam current Ib		400	300	400	300	nA
Modulation depth at						
400 TV lines (5 MH	z)					
high voltage mode,	typ.	50	45	50	55	%
	min.	45	40	45	50	%
low voltage mode,	typ.	45	40	45	50	%
	min.	40	35	40	45	%

Modulation transfer characteristics: see Fig. 2 Lag (typical values, without light bias)

14,15

Light source with a colour temperature of 2856 K. Appropriate filter inserted in the light path for the chrominance tubes R, G and B.


LOW KEY CONDITIONS

	build-up lag $I_s/I_b = 20/300 \text{ nA}$		decay lag I _S /I _D = 20/300 nA		
	60 ms	200 ms	60 ms	200 ms	
XQ2427, XQ2427G	95	≈ 100	7,5	3 %	
XQ2427R	95	≈ 100	9	3,5 %	
XQ2427B	95	≈ 100	10	4 %	


Highlight handling capability with DBC


16

MECHANICAL DATA



The distance between the geometrical centres of diameters A (anti-halation disc), B (signal-electrode ring), and the geometrical centre of diameter C (tube envelope) is $\leq 200~\mu m$.





Mounting position: any

Mass: ≈ 23 g Base: EIA E7-91

XQ2427SERIES

NOTES, see also General Section

- "Diode" electron gun is a triode gun operating in a diode mode, providing a very high beam
 reserve. Since the "Diode" gun operates with a positive grid 1 voltage, causing some grid current,
 cameras designed around XQ1427 tubes will require modification.
 N.B. Avoid continuous operation at high beam currents since this will shorten tube life. Full advantage
 of the high beam reserve to reduce comet-tailing and blooming can be made with DBC circuitry
 which, during highlights, feeds positive-going pulses derived from the video signal to grid 1, to
- increase the beam current momentarily.
 The "diode" gun operates with a positive (≤ 15 V) grid 1 voltage (adjusted for correct beam settings, see note 8), hence draws some grid 1 current: without DBC: ≤ 1,5 mA (peak) with blanking

with DBC:

8 mA (peak) with blanking, measured with oscilloscope.

The DBC circuitry should, in the case of highlights, supply positive-going pulses of 10 V above V_{g1w} (see note 8) and up to 8 mA peak to grid 1.

N.B. Applying higher pulses than 10 V is not recommended since this will shorten tube life, impair resolution and may introduce oscillations.

- Plumbicon tubes do not permit automatic sensitivity control by means of regulation of the signal electrode voltage. Adequate control is therefore to be achieved by other means (iris control and neutral density filters).
 - N.B. When the tube is to be used in a camera originally designed for vidicon tubes, the automatic sensitivity control circuitry should be made inoperative and the signal electrode voltage be set to 45 V, in order to prevent damage or destruction of the target.
- 4. Peak value, measured with an oscilloscope.
- The tube can withstand short excursions up to 70 °C without damage or irreversible degradation in performance.
- For short intervals. During storage the tube face shall be covered with the plastic hood provided; when the camera is idle the lens shall be capped, in stand-by also the beam will be cut-off.
- 7. The operating conditions and performance data quoted relate to operation of the tube in coil unit AT1109. See relevant data of deflection/focusing assemblies.
- The beam current I_b, as obtained by adjusting the control grid (grid 1) voltage is set to 300 nA for R and B tubes, 400 nA for black and white and G tubes. I_b is not the actual current available in the scanning beam, but is defined as the maximum amount of signal current, I_s, that can be obtained with this beam.
 - In the performance figures for lag, the signal current and beam current conditions are given, e.g. as $I_s/I_b = 20/300$ nA. This means: with a signal current of 20 nA and a beam setting which just allows a signal current of 300 nA.
 - The signal currents are measured with an integrating instrument connected in the signal electrode lead and a uniform illumination of the scanned area. The peak signal currents as measured on a waveform oscilloscope will be a factor α larger. α = 100/{100 β }, β being the total blanking time in %; for the CCIR system α = 1,3.
- 9. a. The optimum voltage ratio V_{g4}/V_{g3} to minimize beam landing errors (preferably < 1 V) depends on the type of coil unit used. In the coil AT1109 a ratio of 1,75 is required. Under no circumstances should grid 4 (mesh) be allowed to operate at a voltage below that of grid 3 as this may damage the target.
 - b. An attractive gain in resolving power is obtained when the tubes are operated with higher grid 3 and grid 4 potentionals.
 - N.B. Since such operation requires increased focusing and deflection power, special measures (air cooling, heatsinks) have to be taken in the camera design to prevent faceplate temperatures exceeding the limiting value of 50 °C, which would otherwise affect tube performance and life. See also General Operational notes.

- 10. Typical faceplate illumination level for the XQ2427 to produce 200 nA signal current will be approx. 10 lx. The signal currents stated for the colour tubes R, G and B will be obtained with an incident white light level (2856 K) on the filter of approx. 25 lx. These figures are based on the filters described in note 11. For filter BG12, however, a thickness of 1 mm is chosen.
- Measuring conditions: illuminance level 4,54 Ix at a colour temperature of 2856 K and the appropriate filter inserted in the light path.

Filters used are:

XQ2427G	Schott	VG9	thickness	1	mm
XQ2427B	Schott	BG12	thickness	3	mm
XQ2427R	Schott	OG570	thickness	3	mm
	and Calflex	B1/K1			

For transmission curves see General Section.

- 12. For true tonal rendition in black/white cameras and for true colorimetry in colour cameras an integral filter to eleminate response to near infrared radiation should be incorporated in the optical system, together with a heat reflecting filter B1/K1 or equivalent.
- 13. As measured with a 50 mm Leitz Summicron lens having a sine response of approximately 80% at 30 Ip/mm (400 TV lines at 6,6 mm x 8,8 mm) at f: 5,6 and the appropriate filter inserted in the light path. The horizontal amplitude response can be raised by means of suitable correction circuits, which affect neither the vertical resolution nor the limiting resolution.
- 14. Build-up lag

After 10 s of darkness. The figures are typical percentages of the ultimate signal current obtained 60 ms and 200 ms, respectively, after the introduction of the illuminance.

Decay lag

After the target has been illuminated for at least 5 s. The figures represent typical signals in percentages of the original signal current 60 ms and 200 ms, respectively, after removal of the illuminance.

- 15. A reduction of lag, especially under low key conditions is obtained when light bias (up to 5 nA peak) is applied via the optical system. Infrared light with a wavelength > 600 nm in the light bias should be avoided.
- 16. a. With DBC applied (see note 2) the tube will properly handle highlights with a diameter of 10% of the picture height and with a brightness corresponding to 16 times peak signal white, I_{SD}.
 - b. The maximum peak signal currents in the case of highlights will be 2,5 μ A. Video preamplifiers should be designed to accommodate these.

XQ2427 SERIES




Fig. 1 Typical spectral response.




Fig. 2 Typical square wave response curve.

CAMERA TUBES

18 mm (2/3 in) diameter Plumbicon® television camera tubes, with high resolution lead-oxide photoconductive target, for use in high quality monochrome or colour cameras for broadcast, educational or industrial applications.

The XQ3427 series comprises the following versions:

XQ3427 for use in monochrome cameras XQ3427R for use in the red channel XQ3427G for use in the green channel XQ3427B for use in the blue channel

Special features are:

un: 1 1/ 1 .

- New photoconductive target for increased resolution
- "Diode" electron gun with high beam reserve for dynamic beam control (DBC) to minimize comet-tailing and blooming, see notes 1 and 2
- Low output capacitance (LOC) for high signal to noise ratio.

QUICK REFERENCE DATA

"Diode" electron gun		
Diameter		17,8 mm (2/3 inch)
Length	approx.	108 mm
Provided with anti-halation glass disc		
Focusing	magnetic	
Deflection	magnetic	
Useful target area (scanning area)	6,6	6 x 8,8 mm
Spectral response		
max. at	approx.	500 nm
cut-off: XQ3427R	approx.	850 nm
XQ3427, XQ3427G	approx.	650 to 850 nm
XQ3427B	approx.	650 nm
Sensitivity		
XQ3427	typ.	320 μA/Im
XQ3427R	typ.	95 μ A/ImF
XQ3427G	typ.	$125 \mu A/ImF$
XQ3427B	typ.	$38 \mu A/ImF$
Resolution at 400 TV lines (5 MHz)		
XQ3427	typ.	50 %
XQ3427R	typ.	45 %
XQ3427G	typ.	50 %
XQ3427B	typ.	55 %
Heater		6,3 V, 95 mA

[®] Registered trade mark for television camera tubes.

XQ3427 SERIES

OPTICAL DATA notes

Quality rectangle on

photoconductive target (aspect ratio 3:4)

6.6 x 8.8 mm

Orientation of image on target:

For correct orientation of the image on the target the vertical scan should be essentially parallel to the plane passing through the tube axis and the gap between pins 1 and 7.

Faceplate

Thickness

 2.3 ± 0.1 mm n = 1,49

Refractive index

Anti-halation glass disc provided with

anti-reflective coating

Thickness Refractive index 2.5 ± 0.1 mm

n = 1,52

ACCESSORIES

Socket

type 56049

Deflection and focusing coil unit:

Black/white

type 1109/10S

Colour

type 1109/10T type 56030

Mask for flare reduction

ELECTRICAL DATA

Deflection

magnetic magnetic

Focusing

Heating, indirect by a.c. or d.c.; parallel supply

Heater voltage

Vf If nom. 6.3 V ± 5%

Heater current at Vf = 6,3 V

The heater voltage must not

95 mA

exceed an r.m.s. value of 9 V. For optimum

performance (lifetime and registration stability)

stabilization of the heater voltage is recommended.

Capacitance

Signal electrode to all This capacitance, which is effectively the output

impedance, increases when the tube is inserted in the coil unit.

Cas

typ. 1,5 pF

LIMITING VALUES (Absolute maximur	m rating system	1)				notes
Unless otherwise stated, all voltages are re	eferred to the o	cathode.				
Signal electrode voltage		Vas	max.	50	V	4
Grid 4 voltage		V _{g4}		1000	-	
Grid 3 voltage		V_{g3}	max.	750		
Voltage between grid 4 and grid 3		Vg4/g3	max.	400	V	
Grid 2 voltage		V_{q2}	max.	350	V	
Grid 1 voltage,		92				
positive		V_{g1}	max.	25	V	
negative		$-V_{q1}$	max.	200	V	
Grid 1 current (≈ I _k)		la1	max.		mΑ	5
Grid 1 current (peak with DBC)		lg1p	max.		mΑ	2
Cathode heating time before drawing		'gip	max.	U		_
cathode current		th	min.	1	min	
Cathode to heater voltage		*[]	ann.			
positive peak		Vkfp	max.	125	V	
negative peak		-V _{kfp}	max.	50		
External resistance between		· Kih	iliak.	00		
cathode and heater at V _{kfp} > 10 V		Rkf	min.	2	kΩ	
			max.	50		
Ambient temperature, storage and operat	tion	Tamb	min.	-30		
_			max.	50		6
Faceplate temperature, storage and opera	ation	Т	min.	-30		0
Faceplate illuminance		E	max.	500		7
OPERATING CONDITIONS						8
For a scanned area of 6,6 x 8,8 mm.						
Cathode voltage		$V_{\mathbf{k}}$		0	\/	
Signal electrode voltage		Vas		45		
Beam current		lb				9
		low voltage	mode	high vo	tage n	node
Grid 4 voltage	V_{q4}	500		750		10
Grid 3 voltage	V _{g3}	285		430		10
Grid 2 voltage	V _{q2}	300		300		10
Grid 1 voltage	Vg1	000		000		9
Blanking voltage on grid 2, peak to peak	v g i	V _{g1p-p}		25	V	
Faceplate illuminance		vg1p-p	0	to 10	-	10
Faceplate temperature				to 45		10
Tarana and a sample and a sampl			20	.0 .0	-	
ELECTRON GUN CHARACTERISTICS	;					
Cut off						
Grid 1 voltage for cut-off at $V_{g2} = 300 \text{ V}$	/,					
without blanking		V _{g1}		0 to 0		
Grid 1 voltage for normal beam setting		V_{g1w}	\leq	15	V	9
Blanking voltage, peak to peak						
on grid 1		Vg1p-p		25		
on cathode		V _{kp-p}		25	V	
Grid 1 current at normally required						
beam currents		lg1	\leq	1,5	mA	
Crid 2 aureant at narmally required		-				
Grid 2 current at normally required			<	0.1		

XQ3427 SERIES

PERFORMANCE					1	notes
Dark current	ld		<	1,0	nA	
Sensitivity at colour temperature of illuminance = 2856	K					12
XQ3427	min.	275	typ.	320	$\mu A/Im$	
XQ3427R	min.	80	typ.	95	$\mu A/ImF$	
XQ3427G	min.	95	typ.	125	$\mu A/ImF$	1
XQ3427B	min.	35	typ.	38	μA/ImF	
Gamma of transfer characteristics			0,95 ±	0,05		
Spectral response, max. at	approx			500	nm	13
Spectral response, cut-off at	approx		650 to	850	nm	
Spectral response curves	see Fig.	. 1				
Resolution						14
Modulation depth, i.e. uncompensated amplitude						
response at 400 TV lines at the centre of the picture (5 M	ЛHz)					

		XQ3427	XQ3427R	XQ3427G	XQ3427B	
Highlight signal						
current Is		200	150	200	150	nA
Beam current Ib		400	300	400	300	nA
Modulation depth at						
400 TV lines (5 MH	lz)					
high voltage mode,	typ.	50	45	50	55	%
	min.	45	40	45	50	%
low voltage mode,	typ.	45	40	45	50	%
	min.	40	35	40	45	%

Modulation transfer characteristics: see Fig. 2 Lag (typical values, without light bias)

15,16

Light source with a colour temperature of 2856 K. Appropriate filter inserted in the light path for the chrominance tubes R, G and B


LOW KEY CONDITIONS

	build-up lag I _S /I _b = 20/300 nA		decay lag $I_s/I_b = 20/300 \text{ nA}$		
	60 ms	200 ms	60 ms	200 ms	
XQ3427, XQ3427G	95	≈ 100	7,5	2,5 %	
XQ3427R	95	≈ 100	9	3,5 %	
XQ3427B	95	≈ 100	10	3,5 %	


Highlight handling capability with DBC

17

MECHANICAL DATA



The distance between the geometrical centres of diameters A (anti-halation disc), B (metal ring), and the geometrical centre of diameter C (tube envelope) is $\leq 200 \ \mu m$.



Mounting position: any

Mass: ≈ 23 g Base: EIA E7-91

XQ3427 SERIES

NOTES, see also General Section

- 1. "Diode" electron gun is a triode gun operating in a diode mode, providing a very high beam reserve. Since the "Diode" gun operates with a positive grid 1 voltage, causing some grid current, cameras designed around XQ1427 tubes will require modification.
 - N.B. Avoid continuous operation at high beam currents since this will shorten tube life. Full advantage of the high beam reserve to reduce comet-tailing and blooming can be made with DBC circuitry which, during highlights, feeds positive-going pulses derived from the video signal to grid 1, to increase the beam current momentarily.
- 2. The "diode" gun operates with a positive (≤15 V) grid 1 voltage (adjusted for correct beam settings, see note 9), hence draws some grid 1 current: without DBC: ≤ 1,5 mA (peak) with blanking

≤ 8 mA (peak) with blanking measured with oscilloscope.

The DBC circuitry should, in the case of highlights, supply positive-going pulses of 10 V above V_{a1w} (see note 9) and up to 8 mA peak to grid 1.

N.B. Applying higher pulses than 10 V is not recommended since this will shorten tube life, impair resolution and may introduce oscillations.

- 3. Metal ring not electrically connected.
- 4. Plumbicon tubes do not permit automatic sensitivity control by means of regulation of the signal electrode voltage. Adequate control is therefore to be acieved by other means (iris control and neutral density filters).
 - N.B. When the tube is to be used in a camera originally designed for vidicon tubes, the automatic sensitivity control circuitry should be made inoperative and the signal electrode voltage be set to 45 V, in order to prevent damage or destruction of the target.
- 5. Peak value, measured with an oscilloscope.
- 6. The tube can withstand short excursions up to 70 °C without damage or irreversible degradation in performance.
- 7. For short intervals. During storage the tube face shall be covered with the plastic hood provided; when the camera is idle the lens shall be capped, in stand-by also the beam will be cut-off.
- 8. The operating conditions and performance data quoted relate to operation of the tube in coil unit AT1109. See relevant data of deflection/focusing assemblies.
- 9. The beam current Ih, as obtained by adjusting the control grid (grid 1) voltage is set to 300 nA for R and B tubes, 400 nA for black and white and G tubes. Ib is not the actual current available in the scanning beam, but is defined as the maximum amount of signal current, Is, that can be obtained with this beam.

In the performance figures for lag, the signal current and beam current conditions are given, e.g. as I_S/I_h = 20/300 nA. This means: with a signal current of 20 nA and a beam setting which just allows a signal current of 300 nA.

The signal currents are measured with an integrating instrument connected in the signal electrode lead and a uniform illumination of the scanned area. The peak signal currents as measured on a waveform oscilloscope will be a factor α larger. $\alpha = 100/\{100-\beta\}$, β being the total blanking time in %; for the CCIR system $\alpha = 1,3$.

- 10. a. The optimum voltage ratio V_{q4}/V_{q3} to minimize beam landing errors (preferably < 1 V) depends on the type of coil unit used. In the coil AT1109 a ratio of 1,75 is required. Under no circumstances should grid 4 (mesh) be allowed to operate at a voltage below that of grid 3 as this may damage the target.
 - b. An attractive gain in resolving power is obtained when the tubes are operated with higher grid 3 and grid 4 potentionals.
 - N.B. Since such operation requires increased focusing and deflection power, special measures (air cooling, heatsinks) have to be taken in the camera design to prevent faceplate temperatures exceeding the limiting value of 50 °C, which would otherwise affect tube performance and life. See also General Operational notes.

- 11. Typical faceplate illumination level for the XQ3427 to produce 200 nA signal current will be approx. 10 lx. The signal currents stated for the colour tubes R, G and B will be obtained with an incident white light level (2856 K) on the filter of approx. 25 lx. These figures are based on the filters described in note 12. For filter BG12, however, a thickness of 1 mm is chosen.
- Measuring conditions: illuminance level 4,54 Ix at a colour temperature of 2856 K and the appropriate filter inserted in the light path.

Filters used are:

XQ3427G		Schott	VG9	thickness	1	mm
XQ3427B		Schott	BG12	thickness	3	mm
XQ3427R		Schott	OG570	thickness	3	mm
	and	Calflex	B1/K1			

For transmission curves see General Section.

- 13. For true tonal rendition in black/white cameras and for true colorimetry in colour cameras an integral filter to eleminate response to near infrared radiation should be incorporated in the optical system, together with a heat reflecting filter B1/K1 or equivalent.
- 14. As measured with a 50 mm Leitz Summicron lens having a sine response of approximately 80% at 30 Ip/mm (400 TV lines at 6,6 mm x 8,8 mm) at f: 5,6 and the appropriate filter inserted in the light path. The horizontal amplitude response can be raised by means of suitable correction circuits, which affect neither the vertical resolution nor the limiting resolution.
- 15. Build-up lag

After 10 s of darkness. The figures are typical percentages of the ultimate signal current obtained 60 ms and 200 ms, respectively, after the introduction of the illuminance.

Decay lag

After the target has been illuminated for at least 5 s. The figures represent typical signals in percentages of the original signal current 60 ms and 200 ms, respectively, after removal of the illuminance.

- 16. A reduction of lag, especially under low key conditions is obtained when light bias up to 5 nA (peak) is applied via the optical system. Infrared light with a wavelength > 600 nm in the light bias should be avoided.
- 17. a. With DBC applied (see note 2) the tube will properly handle highlights with a diameter of 10% of the picture height and with a brightness corresponding to 16 times peak signal white, I_{SD}.
 - b. The maximum peak signal currents in the case of highlights will be 2,5 μ A. Video preamplifiers should be designed to accommodate these.

XQ3427 SERIES




Fig. 1 Typical spectral responses.




Fig 2 Typical square wave response curves (high voltage mode).

CAMERA TUBES

18 mm (2/3 in) diameter Plumbicon® television camera tubes with high resolution leadoxide photoconductive target, magnetic focusing electrostatic deflection.

The XQ3457 series is intended for use in high quality monochrome and colour cameras in broadcast, educational and industrial applications.

The XQ3457 series comprises the following versions:

XQ3457 for monochrome cameras;

XQ3457R for the red channel of colour cameras:

XQ3457G for the green channel;

XQ3457B for the blue channel.

Special features are:

- MS type (Magnetic-Static) providing short tube length
- New photoconductive target for increased resolution
- "Diode" electron gun for D.B.C. (Dynamic Beam Control) to minimize comet tailing and highlight blooming (notes 1 and 2)
- · Low output capacitance for high signal to noise ratio

QUICK REFERENCE DATA

"Diode" electron gun

Diameter	17,8 mm (2/3")
Length	approx. 87,5 mm
Provided with anti-halation glass disc, thickness	2,5 mm
Focusing	magnetic
Deflection	electrostatic
Useful target area	6,6 mm x 8,8 mm
Spectral response max. at	≈ 500 nm
Spectral response cut-off XQ3457R XQ3457, XQ3457G, XQ3457B	≈ 850 nm ≈ 650 nm
Sensitivity	
XQ3457 XQ3457R XQ3457G XQ3457B	typ. $320 \mu\text{A/Im}$ typ. $100 \mu\text{A/ImF}$ typ. $125 \mu\text{A/ImF}$ typ. $36 \mu\text{A/ImF}$
Modulation depth at 400 TV lines (5 MHz) XQ3457	typ. 50%
Heater	6,3 V; 95 mA

[®] Registered trademark for television camera tube.

XQ3457 SERIES

OPTICAL DATA

Dimensions of quality area of target (aspect ratio 3:4)

6,6 mm x 8,8 mm

Orientation of image on target

For correct orientation of the image on the target the horizontal scan should be essentially parallel to the long side of the anti-halation glass disc.

Faceplate

thickness $2,3 \pm 0,1 \text{ mm}$ refractive index 1.49

Anti-halation glass disc

thickness $2,5 \pm 0,1 \text{ mm}$ refractive index 1,52

ACCESSORIES

Socket 56601

Focusing coil unit KV4722 or equivalent

ELECTRICAL DATA

Deflection electrostatic

Focusing magnetic

HEATING

Indirect by a.c. or d.c. parallel supply

Heater voltage $V_{\rm f} = 6.3~{\rm V} \pm 5~{\rm \%}$ Heater current $I_{\rm f} = {\rm nom.~95~mA}$

The heater current and heater voltage must never exceed 150 mA and 9,5 V (r.m.s.)

For optimum performance (lifetime and registration stability) stabilization of the heater voltage is recommended.

INTERELECTRODE CAPACITANCE

Signal electrode to all Cas typ. 3 pF

This capacitance increases slightly when the tube is inserted in the coil unit.

LIMITING VALUES (Absolute maximum rating system)				notes	
All voltages are referred to the cathode, unless otherwise stated.					
Signal electrode voltage	Vas	max.	50 \	/	
Grid 4 voltage (mesh electrode)	V_{g2}	max.	500 \	/	
Grid 3 voltage (deflection electrode, DC component)	V_{g3}	max.	300 \	/	
Voltage between grid 4 and grid 3	V _{g3/g4}	max.	300 \	/	
Grid 2 voltage	V_{g2}	max.	350 \	/	
Grid 1 voltage positive	V_{g1}	max.	20 \	/	
Grid 1 voltage negative	$-V_{q1}$	max.	50 \	/	
Grid 1 current (≈ cathode current)	l _{g1}	max.	5 n	nA 3	
Grid 1 current (peak current with DBC)	I _{g1p}	max.	8 n	nA 2	
Cathode to heater voltage positive peak	V _{kfp}	max.	125 \	/	
Cathode to heater voltage negative peak	$-V_{kfp}$	max.	50 \	/	
Cathode heating time before drawing cathode current	th	min.	1 r	nin	
External resistance between cathode and heater at $V_{ m kf}\!>\!10~{ m V}$	Rkf	min.	2 k	Ω :	
Ambient temperature, storage and operation	T _{amb}	max. min.	50 °C		
Faceplate temperature, storage and operation	Т	max. min.	50 °C		
Faceplate illuminance	E	max.	500 I	x 5	

XQ3457 SERIES

OPERATING CONDITIONS				notes
for a scanned area of 6,6 mm x 8,8 mm				6
Cathode voltage	V_k	0	V	
Signal electrode voltage	Vas	45	V	
Beam current	Ib			7
Grid 4 voltage	V_{g4}	340	V	
Grid 3 voltage (DC component)	V_{g3}	220	V	
Grid 2 voltage	V_{g2}	250	V	
Grid 1 voltage	V _{g1}	0 to 10	V	7
Blanking voltage on grid 1, peak-peak	V_{g1p-p}	25	V	
Beam focus magnetic field		7,3	mT	9
Grid 3 deflection voltage, horizontal	$V_{g3 \times p-p}$	155	V	
Grid 3 deflection voltage, vertical	V _{g3 y p-p}	116	V	
Faceplate illuminance	E	0 to 10	lx	10
Faceplate temperature	Tas	20 to 45	oC	
ELECTRON GUN CHARACTERISTICS				
Grid 1 voltage for cut-off at $V_{0.2} = 250 \text{ V}$ without blanking	V_{g1}	-10 to 0	V	
Grid 1 voltage for normal beam current	V _{g1w}		V	
Blanking voltage with respect to V _{q1w} peak to peak	*g I W	10	•	
on grid 1	V_{g1p-p}	25	V	
on cathode	V _{k p-p}	25	V	
Grid 1 current at normally required beam currents	l _{g1}	≤ 3	mA	
Grid 2 current at normally required beam currents	I _{g2}	≤ 0,1	mA	
PERFORMANCE				
Dark current	Id	≤ 2	nA	
Sensitivity at colour temperature of 2856K				11
XQ3457 XQ3457R	min. 270 min. 75	typ. 320 typ. 100		
XQ3457G	min. 90	typ. 100		
XQ3457B	min. 33	typ. 36		
Gamma of transfer characteristic		0,95 ± 0,05		
Spectral response				12
max. response at			nm	
cut-off XQ3457R cut-off XQ3457, XQ3457G			nm nm	
cut-off XQ3457B			nm	
response curves		see Fig. 5		
Resolution				
Modulation depth, i.e. uncompensated amplitude respon	ise at 400 TV			13
lines at centre of the picture.				

note 14, 15

Table 1

		XQ3457	XQ3457R	XQ3457G	XQ3457B
Highlight signal current	Is	200 nA	150 nA	200 nA	150 nA
Beam current	1 _b	400 nA	300 nA	400 nA	300 nA
Modulation depth at 400 TV	lines				
(5 MHz) in %	typ.	50	40	50	55
	min.	40	32	40	40

Modulation transfer characteristics see Fig. 6.

Lag (typical values, no light bias applied).

Light source with a colour temperature of 2856 K.

Appropriate filter inserted in light path.

Table 2

		build-up lag $l_s/l_b = 20/300 \text{ nA}$		
	60 ms	200 ms	60 ms	200 ms
XQ3457	95	≈ 100%	8	3 %
XQ3457G	95	≈ 100%	8	3 %
XQ3457R	95	≈ 100%	9	3,5%
XQ3457B	95	≈ 100%	10	4 %

Highlight handling capability with DBC.

note 16

XQ3457 SERIES

MECHANICAL DATA

Outlines





Fig. 1.

36° (10×)



7Z90843

Fig. 2.





Fig. 4.



0 0

short cut pin

7Z90844

1,0 (10×)

Fig. 3.

Ø15,8-

Mounting position: any

Mass:

≈ 19 g

NOTES, see also General Section

"Diode" electron gun is a triode gun operating in a diode mode, providing a very high beam reserve.
 Since the "Diode" gun operates with a positive grid 1 voltage, causing some grid current.

N.B.

Avoid continuous operation at high beam currents since this will shorten tube life. Full advantage of the high beam reserve to reduce comet-tailing and blooming can be made with DBC circuitry which, during highlights, feeds positive-going pulses derived from the video signal to grid 1, to increase the beam current momentarily.

2. The "Diode" gun operates with a positive (≤ 10 V) grid 1 voltage (adjusted for correct beam settings, see note 9), hence draws some grid 1 current:

without DBC: ≤3 mA (peak) with blanking

with DBC: < 5 mA (peak) with blanking measured with oscilloscope.</pre>

The DBC circuitry should, in the case of highlights, supply positive-going pulses of 8 V_{p-p} and up to 8 mA_{D-D} peak to grid 1.

N.B.

Applying higher pulses than 8 V is not recommended since this will shorten tube life, impair resolution and may introduce oscillations.

- 3. Maximum d.c. value.
- 4. The tube can withstand short excursions up to 70 °C without damage or irreversible degradation in performance.
- For short intervals. During storage the tube face shall be covered with the plastic hood provided; when the camera is idle the lens shall be capped, in stand-by also the beam will be cut-off.
- The operating conditions and performance data quoted relate to operation in coil unit KV4722. See relevant data.
- The beam current I_b, as obtained by adjusting the control grid (grid 1) voltage is set to 300 nA for R and B tubes, 400 nA for black and white and G tubes. I_b is not the actual current available in the scanning beam, but is defined as the maximum amount of signal current, I_s, that can be obtained with this beam.
- 8. The optimum voltage ratio V_{g3}/V_{g4} to minimize beam landing errors (preferably < 1 V) depends on the type of coil unit used.
- 9. See relevant data of deflection/focusing assemblies.
- 10. Typical faceplate illumination level for the XQ3457 to produce 200 nA signal current will be approx. 10 lx. The signal currents stated for the colour tubes R, G and B will be obtained with an incident white light level (2856 K) on the filter approx. 25 lx. These figures are based on the filters described in note 11. For filter BG12, however, a thickness of 1 mm is chosen.
- 11. Measuring conditions: illuminance level before the filter 4,54 lx at a colour temperature of 2856 K and the appropriate filter inserted in the light path for the chrominance tubes. Filters used are:

XQ3457G	Schott	VG9	thickness	1 mm
XQ3457B	Schott	BG12	thickness	3 mm
XQ3457R	Schott	OG570	thickness	3 mm
	and Calflex	B1/K1		

For transmission curves see General Section.

XQ3457 SERIES

NOTES (continued)

- 12. For true tonal rendition in monochrome cameras, and for true colorimetry in colour cameras, an integral filter to eliminate response to near infrared radiation must be incorporated in the optical system.
- 13. Uncompensated amplitude response at 5 MHz at the centre of the picture.
 - The figures shown represent the horizontal amplitude response of the tube as obtained with lens aperture of f: 5.6.
 - The highlight signal current and beam current conditions are given, $I_S = 200 \text{ nA/I}_D = 400 \text{ nA}$ for monochrome and G tubes, and $I_S = 150 \text{ nA/I}_D = 300 \text{ nA}$ for R and B tubes.
 - The horizontal amplitude response can be raised by means of suitable correction circuits, which
 affect neither the vertical resolution nor the limiting resolution.
- 14. Build up lag. After 10 s of darkness. The figures represent typical signals in percentages of the ultimate signal current, obtained 60 ms or 200 ms respectively, after introduction of the illuminance. Decay lag. After the target has been illuminated for at least 5 s. The figures represent typical

signals in percentages of the original signal current, 60 ms or 200 ms respectively, after removal of the illuminance.

- 15. An attractive reduction of lag, especially under low key conditions may be obtained when light bias (up to 5 nAp-p) is applied via the optical system. Infrared light with a wavelength > 600 mm in the light bias should be avoided.
- 16. With DBC applied (see Note 2) the tube will properly handle highlights with a diameter of 10% of picture height and with a brightness corresponding to 16 times peak signal white.
 - The max. peak signal currents in the case of highlights will be 2,5 μ A. Video preamplifiers must be designed to accommodate these.




Fig. 5 Typical spectral response curves.




Fig. 6 Typical square-wave response curves.

CAMERA TUBES

18 mm (2/3 inch) diameter Plumbicon[®] television camera tubes with standard resolution leadoxide photoconductive target, intended for use in low-weight monochrome and colour cameras in broadcast, educational or industrial applications.

The XQ3467 series comprises the following versions:

XQ3467 for monochrome cameras

XQ3467R for the red channel of colour cameras

XQ3467G for the green channel

XO3467B for the blue channel

Special features are:

- Low power consumption due to electrostatic focusing
- Low weight

QUICK REFERENCE DATA

Se	parate	mesh
----	--------	------

Diameter max. 18 mm (2/3 inch)

Length approx. 108

Anti-halation glass disc, thickness 3,7 mm

Focusing electrostatic

Deflection magnetic

Useful target area (scanning area) 6,6 mm x 8,8 mm

Spectral response max, at

cut-off at approx, 650 to 850 nm

type XQ3467 | XQ3467R | XQ3467G | XQ3467B

Sensitivity, typ. 375 95 150 36 μ A/Im(F)

approx. 500 nm

Resolution at 320 TV lines (4 MHz) 45 40 45 50 %

Heater 6 V, 75 mA

OPTICAL DATA

Quality rectangle on photoconductive target (aspect ratio 3 : 4) 6,6 mm x 8,8 mm

Orientation of image on target

For correct orientation of the image on the target the horizontal scan should be essentially parallel to the plane passing through the tube axis and the index pin.

Faceplate

thickness 2,3 ± 0,1 mm refractive index 1,49

Anti-halation glass disc with AR-coating

 $\begin{array}{ll} \text{thickness} & 3,7 \pm 0,1 \text{ mm} \\ \text{refractive index} & 1,52 \end{array}$

[®] Registered trade mark for television camera tube.

XQ3467 SERIES

ACCESSORIES

Socket

type 56604

Deflection coil unit

type KV4780 or equivalent

ELECTRICAL DATA

Heating

notes

Indirect by a.c. or d.c.; parallel supply

Heater voltage

Vf

6 V ± 5%

Heater current, at V_f = 6,0 V

If

75 mA nom.

The heater voltage must never exceed 9 V r.m.s.

For optimum performance (lifetime and registration stability) use a stabilized supply.

Inter-electrode capacitance

Signal electrode to any other contact

Cas

2,5 pF

typ.

This capacitance increases slightly when the tube is inserted in the coil unit.

Deflection

magnetic

Focusing

electrostatic

LIMITING VALUES (Absolute maximum rating system)

All voltages are referred to the cathode, unless otherwise stated

50 V Signal electrode voltage Vas max. Grid 6 voltage + grid 3 voltage (int. connected) 1200 V V_{q3+6} max. Grid 5 voltage 600 V V_{a5} max. Grid 4 voltage, focus 250 V V_{q4} max. Grid 2 voltage V_{q2} 350 V max. Grid 1 voltage, positive 0 V V_{q1} max. Grid 1 voltage, negative 200 V $-V_{a1}$ max. V_{kfp} Cathode to heater voltage, positive peak 125 V max. $-V_{kfp}$ Cathode to heater voltage, negative peak max. 50 V Cathode heating time before drawing cathode current min. 1 min th

Ambient temperature, storage and operation

Tamb T

-30 °C min. 50 °C max.

Faceplate temperature, storage and operation

Faceplate illuminance (intermittent)

E

-30 °C min. max.

max.

500 lx

50 °C

OPERATING CONDITIONS AND PERFORMANCE for a scanned area of 6,6 mm x 8,8 mm							notes
Conditions							
Cathode voltage	Vk				0	V	
Signal electrode voltage	V_{as}				45	V	
Beam current	lb						4
Grid 6 voltage + grid 3 voltage	V _{g3+6}				1000	V	
Grid 5 voltage	V_{g5}				500	V	
Grid 4 voltage, focus	V _{g4}			90 t	o 130	V	
Grid 2 voltage	V_{g2}				300	V	
Grid 1 voltage	V_{g1}			-10 to	o –30	V	4
Blanking voltage on grid 1, peak to peak	V _{g1} p- ₁				75	V	
Faceplate illuminance	E E	p		0	to 10		5
	T				to 45		5
Faceplate temperature	1			20	10 45		
Electron gun characteristics							
Cut-off							
Grid 1 voltage for cut-off without blanking Grid 1 voltage for 400 nA beam current	V _{g1} V _{g1w}			-30 to			4
Blanking voltage, peak to peak on grid 1	V _{g1} p-	р			75	V	
Performance							
Dark current	ld			<	1,0	nA	
Sensitivity at colour temperature of illuminance = 28	356 K						6
XQ3467	min.	325		typ.	375	$\mu A/Im$	
XQ3467R	min.	75		typ.		μA/ImF	
XQ3467G	min.	110		typ.		μA/ImF	
XQ3467B	min.	32		typ.	36	μA/ImF	
Gamma of transfer characteristic				0,95	+ 0,05		
Spectral response:							
max. response at			~			nm	7
cut-off XQ3467R			~			nm	
cut-off XQ3467, XQ3467G			~	650 t	o 850		
cut-off XQ3467B			~		650	nm	
response curves			see	Fig. 1			

XQ3467 SERIES

Resolution

notes

Modulation depth, i.e. uncompensated amplitude response at 320 TV lines at the centre of the picture.

8

		XQ3467	XQ3467R	XQ3467G	XQ3467B
Highlight signal current	Is	200 nA	150 nA	200 nA	150 nA
Beam current	Ib	400 nA	300 nA	400 nA	300 nA
Modulation depth at 320 TV lines (4 MHz) in %	typ. min.	45 % 35 %	40 % 30 %	45 % 35 %	50 % 40 %

Modulation transfer characteristics

see Fig. 2

Lag (typical values, no light bias applied)
Light source with a colour temperature of 2856 K
Appropriate filter inserted in light path


9, 10


Low key conditions (percentages)


	bu	ild-up lag	decay lag $I_s/I_b = 20/300 \text{ nA}$			
	$I_s/I_b = 2$	20/300 nA				
	60 ms	200 ms	60 ms	200 ms		
XQ3467	95	~ 100	8,0	3,0		
XQ3467R	95	~ 100	8,0	3,0		
XQ3467G	95	~ 100	8,0	3,0		
XQ3467B	95	~ 100	9,0	3,5		

MECHANICAL DATA

Dimensions in mm







Mounting position: any

Mass: $\approx 27 \text{ g}$

Base:

XQ3467 SERIES

NOTES, see also General Section.

- The tube can withstand short excursions up to 70 °C without damage or irreversible degradation in performance.
- For short intervals. During storage the tube face shall be covered with the plastic hood provided; when the camera is idle the lens shall be capped, in stand-by also the beam will be cut-off.
- The operating conditions and performance data quoted relate to operation in the coil unit KV4780.
 See relevant data of deflection/focusing assemblies.
- 4. The beam current I_b, as obtained by adjusting the control grid voltage (grid 1) is set at 300 nA for R and B tubes, 400 nA for black/white, and G tubes. I_b is not the total current available in the scanning beam, but is defined as the maximum amount of signal current, I_s, that can be obtained with this beam.

In the performance figures, e.g. for resolution and lag, the signal current and beam current conditions are given, e.g. as $I_s/I_b = 20/300$ nA. This means: with a signal current of 20 nA and a beam setting which just allows a signal current of 300 nA.

N.B. The signal currents are measured with an integrating instrument connected in the signal electrode lead and a uniform illumination of the scanned area.

The peak signal currents as measured on a waveform oscilloscope will be a factor α larger.

$$\alpha = \frac{100}{100-\beta}$$
; β being the total blanking time in %: for the CCIR system α amounts to 1,3).

- 5. Typical faceplate illumination level for the XQ3467 to produce 200 nA signal current will be approx. 10 lx. The signal currents stated for the colour tubes R, G and B will be obtained with an incident white light level (2856 K) on the filter of approx. 25 lx. These figures are based on the filters described in note 11. For filter BG12, however, a thickness of 1 mm is chosen.
- Measuring conditions: illuminance level before the filter approx. 4,54 lux at a colour temperature of 2856 K and the appropriate filter inserted in the light path for the chrominance tubes.
 Filters used are:

XQ3467G	Schott	VG9	thickness	1 mm
XQ3467B	Schott	BG12	thickness	3 mm
XQ3467R	Schott	OG570	thickness	3 mm
	and Calflex	B1/K1		

For transmission curves see General Section.

- For true tonal rendition in black/white cameras and for true colorimetry in colour cameras an integral filter to eliminate response to near infrared radiation should be incorporated in the optical system.
- 8. As measured with a 50 mm Leitz Summicron lens having a sine response of approximately 80% at 30,3 lp/mm (400 TV lines at 6,6 mm x 8,8 mm) at f: 5,6. The horizontal amplitude response can be raised by means of suitable correction circuits, which affect neither the vertical resolution nor the limiting resolution.
- 9. Build-up lag

After 10 s of darkness. The figures are typical percentages of the ultimate signal current obtained 60 ms and 200 ms, respectively, after the introduction of the illuminance.

Decay lag

After the target has been illuminated for at least 5 s. The figures represent typical signals in percentages of the original signal current 60 ms and 200 ms, respectively, after removal of the illuminance.

10. A reduction lag, especially under low key conditions is obtained when light bias up to 5 nA (peak) is applied via the optical system. Infrared light with a wavelength > 600 nm in the light bias should be avoided.




Fig. 1 Typical spectral responses.





Fig. 2 Typical square wave response curves.



DEVELOPMENT DATA

This data sheet contains advance information and specifications are subject to change without notice.

XQ4187 SERIES

CAMERA TUBES

 $\frac{1}{3}$ inch HS "Diode" Plumbicon[®] television camera tubes with high resolution lead-oxide photoconductive target for use in low weight high quality monochrome and colour cameras in broadcast, educational or industrial applications.

The XQ4187-series comprises the following versions:

- XQ4187 for monochrome cameras
- XQ4187R for the red channel of colour cameras
- XQ4187G for the green channel
- XQ4187B for the blue channel

Special features are:

- High stability construction (HS).
- "Diode" electron gun for D.B.C. (dynamic beam control) to minimize comet-tailing and blooming (notes 1 and 2).
- Low output capacitance, achieved by a special signal plate with contact through the window.
- Low deflection field damping by wall electrodes.
- Reduced line pick-up due to side connection of the mesh.
- Low power consumption due to electrostatic focusing.
- Low weight and small size.

QUICK REFERENCE DATA

"Diede" electron gun

Diode electron gun				22	
Diameter		n	nax.		mm
Length		а	pprox.	92	mm
Provided with anti-halation glass disc, thickness				2,5	mm
Focusing		е	lectrostatic		
Deflection		n	nagnetic		
Useful target area (scanning area)				$6,6 \times 8,8$	mm
Spectral response					
maximum at		а	pprox.	500	nm
cut-off at		а	pprox.	650 to 850	nm
type	XQ4187	XQ4187R	XQ4187G	XQ4187	В
Sensitivity, typical	320	90	130	38	$\mu A/Im(F$
Resolution at 400 TV lines (5 MHz), typical	47	37	47	55	%
Heater			9 V, 55 m	A	

OPTICAL DATA

Quality rectangle on photoconductive target (aspect ratio 3 : 4)

6.6 mm x 8.8 mm

Orientation of image on target

For correct orientation of the image on the target the vertical scan should be essentially parallel to the plane passing through the tube axis and the Index slot at the base. Mounted in the deflection coil, the target contact should be at the upper side during scanning.

[®] Registered trade mark for television camera tube.

XQ4187 SERIES

Faceplate

thickness refractive index $2,3 \pm 0,1 \text{ mm}$

1,52

Anti-halation glass disc provided with anti-reflective coating

thickness refractive index $2,5 \pm 0,1 \text{ mm}$

1,52

ACCESSORIES

Socket is integrated in the deflection coil

→ Deflection coil unit

type KV4736

ELECTRICAL DATA

Heating

Indirect by a.c. or d.c.: parallel supply

The heater voltage must never exceed

Heater voltage

 V_{f}

9 V ± 5%

Heater current, at $V_f = 9.0 \text{ V}$

nom. 55 mA

12 V r.m.s.

For optimum performance (lifetime and registration stability) stabilization of the heater voltage is recommended.

Capacitance

Signal electrode to all (with floating indium ring)

285

approx. 1,6 pF

This capacitance, which is effectively the output impedance, increases when the tube is inserted in the coil unit.

Deflection

magnetic

Focusing

electrostatic

min.

max.

-30 °C

100 lx

Faceplate temperature, storage and operation

Faceplate illuminance (intermittent)

						_
LIMITING VALUES (Absolute maximum rating system)					-	
All voltages are referred to the cathode, unless otherwise stated.					notes	
Signal electrode voltage	Vas	max.	50	V		
Grid 4 voltage	V_{q4}	max.	1200	V		
Grid 3 voltage	V_{g3}	max.	500	V		
Voltage between grid 4 and grid 3	$V_{g4/g3}$	max.	850	V		
Grid 2 voltage, focus	V_{g2}	max.	75	V		
Grid 1 voltage, positive	V_{g1}	max.	75	V	3	
Grid 1 voltage, negative	$-V_{g1}$	max.	50	V	3	
Grid 1 current (≈ IK current)	Ig1 d.c.	max.	3,5	mA		
Grid 1 current (peak current with D.B.C.)	lg1p	max.	12	mA	2	
Cathode to heater voltage, positive peak	Vkfp	max.	50	V		
Cathode to heater voltage, negative peak	$-V_{kfp}$	max.	50	V	3	
Cathode heating time before drawing cathode current	th	min.	1	min		
Ambient temperature, storage and operation	T _{amb}	max. min.	50 -30	°C	7	
Facenlate temperature storage and operation	Т	max.	50	oC		

XQ4187 SERIES

OPERATING CONDITIONS AND PERFORMANCE for a scanned area of 6,6 mm x 8,8 mm				notes 6
Conditions				
Cathode voltage	\vee_k	0	V	
Signal electrode voltage	Vas	45	V	
Beam current	1 _b			7
Grid 4 voltage	V_{g4}	1100	V	
Grid 3 voltage	V_{q3}	400	V	
Grid 2 voltage, focus	V_{g2}	44 V ± 3	V	
Grid 1 voltage	V_{g1}			7
Blanking voltage on grid 1, peak to peak without D.B.C.	V _{g1 p-p}	50	V	
Faceplate illuminance	E	0 to 10	lx	8
Faceplate temperature	T	20 to 45	oc	
Electron gun characteristics				
Cut-off				
Grid 1 voltage for cut-off without blanking Grid 1 voltage for 400 nA beam current	V_{g1} V_{g1w}	-5 to 0 10 to 20		
Blanking voltage, peak to peak on grid 1, without D.B.C.	V _{g1 p-p}	50	V	3
Grid currents at grid 1 grid 3 grid 4	l _b 400 l _{g1} max. l _{g3} max. 1 l _{g4} max.	3 10 00 200	D.B.0 mA μA μA	<u>. </u>
Performance				
Dark current	l _d ≤	2	nA	
Sensitivity at colour temperature of illuminance = 2856 K XQ4187 XQ4187R XQ4187G XQ4187B	min. 275 min. 75 min. 105 min. 35	typ. 320 typ. 90 typ. 130 typ. 38	μΑ/ μΑ/	lmF lmF
Gamma of transfer characteristic	0,95	+ 0,05		
Spectral response: max. response at cut-off XQ4187R cut-off XQ4187 cut-off XQ4187B, XQ4187G response curves	≈	500 850 650 to 850 650 Fig. 1	nm nm	10

Resolution

notes

11

Modulation depth, i.e. uncompensated amplitude response at 400 TV lines (5 MHz) at the centre of the picture.

		XQ4187	XQ4187R	XQ4187G	XQ4187B
Signal current	Is	200	150 nA	200 nA	150 nA
Beam current	lb	400	300 nA	400 nA	300 nA
Modulation depth at 400 TV lines (5 MHz)	typ. min.	47 40	37 % 32 %	47 % 40 %	55 % 50 %

Modulation transfer characteristics

see Fig. 2

Lag (typical values, no light bias applied)

12, 13

Light source with a colour temperature of 2856 K Appropriate filter inserted in light path


Low key conditions

	build	d-up lag	decay lag		
	$I_{s}/I_{b} = 20/300 \text{ nA}$		$I_{s}/I_{b} = 20/300 \text{ n}$		
	60 ms	200 ms	60 ms	200 ms	
XQ4187, G	95%	≈ 100%	6%	2%	
XQ4187R	95%	≈ 100%	7%	2,5%	
XQ4187B	95%	≈ 100%	7%	3%	

Highlight handling capability with D.B.C.

14

XQ4187 SERIES




NOTES, see also General Section.


- Avoid continuous operation at high beam currents since this will shorten tube life. Full advantage
 of the high beam reserve to reduce comet-tailing and blooming can be made with DBC circuitry
 which, during highlights, feeds positive-going pulses derived from the video signal to grid 1, to
 increase the beam current momentarily.
- The "diode" gun operates with a positive (≤ 30 V) grid 1 voltage adjusted for correct beam settings, see note 7.

The DBC circuitry should, in the case of highlights, supply positive-going pulses with a maximum of 50 V to grid 1 above the normal V_{n1} setting for $I_b = 400$ nA.

of 50 V to grid 1 above the normal V_{g1} setting for I_b = 400 nA. N.B. Applying higher pulses than 50 V is not recommended since this will shorten tube life, impair resolution and may introduce oscillations.

3. The following circuitry and tube settings are recommended.





- The tube can withstand short excursions up to 70 °C without damage or irreversible degradation in performance.
- 5. During storage the tube face shall be covered with the plastic hood provided; when the camera is idle the lens shall be capped, in stand-by also the beam will be cut-off.
- The operating conditions and performance data quoted relate to operation in the coil unit KV4736. See relevant data of deflection/focusing assemblies.
- 7. The beam current I_b, as obtained by adjusting the control grid (grid 1) voltage is set to 300 nA for R and B tubes, 400 nA for black and white and G tubes. I_b is not the actual current available in the scanning beam, but is defined as the maximum amount of signal current, I_s, that can be obtained with this beam.

In the performance figures for lag, the signal current and beam current conditions are given, e.g. as $I_s/I_b = 20/300$ nA. This means: with a signal current of 20 nA and a beam setting which just allows a signal current of 300 nA.

N.B. The signal currents are measured with an integrating instrument connected in the signal electrode lead and a uniform illumination of the scanned area. The peak signal currents as measured on a waveform oscilloscope will be a factor α larger.

 $\alpha = \frac{100}{100 - \beta}$; β being the total blanking time in %; for the CCIR system $\alpha = 1,3$.

NOTES (continued)

- 8. Typical faceplate illumination level for the XQ4187 to produce 200 nA signal current will be approx. 10 lx. The signal currents stated for the colour tubes R, G and B will be obtained with an incident white light level (2856 K) on the filter of approx. 25 lx. These figures are based on the filters described in note 9. For filter BG12, however, a thickness of 1 mm is chosen.
- 9. Measuring conditions.

Illuminance level 4,54 lx at a colour temperature of 2856 K. Filters are inserted in the light path for the chrominance tubes.

Filters used are:

XQ4187R: B1/K1 and Schott OG570, thickness 3 mm. XQ4187G: Schott VG9, thickness 1 mm. XQ4187B: Schott BG12, thickness 3 mm.

For transmission curves see General Section.

- 10. For true tonal rendition in black/white cameras, and for true colorimetry in colour cameras, an integral filter to eliminate response to near infrared radiation should be incorporated in the optical system, together with an integral B1/K1 filter or equivalent.
- 11. As measured with a 50 mm Leitz Summicron lens having a sine response of approx. 80% at 30 lp/mm (400 TV lines at 6,6 mm x 8,8 mm) at f: 5,6. The horizontal amplitude response can be raised by means of suitable correction circuits, which affect neither the vertical resolution nor the limiting resolution.
- 12. Build-up lag.

After 10 s of darkness. The figures are typical percentages of the ultimate signal current obtained 60 ms or 200 ms, respectively, after introduction of the illuminance.

Decay lag.

After the target has been illuminated for at least 5 s. The figures respresent typical signal in percentages of the original signal current 60 ms or 200 ms, respectively, after removal of the illuminance.

- 13. A reduction of lag, especially under low key conditions, is to be obtained when light bias up to 5 nAp is applied via the optical system. Infrared light with a wavelength > 600 nm in the light bias should be avoided.
- 14. With D.B.C. applied (see notes 2 and 3) the tube will properly handle highlights with a diameter of 10% of the picture height and with a brightness corresponding to 8 times the brightness for normal peak signal. The maximum peak signal currents in the case of highlights will be 1400 nA. Video amplifiers should be designed to accommodate these.




Fig. 1 Typical spectral responses.





Fig. 2 Typical square wave response curves.



14 mm dia. PLUMBICON TUBES

CAMERA TUBES

14 mm (½ inch) HS "Diode" Plumbicon® television camera tubes with high resolution lead-oxide photoconductive target for use in low weight high quality colour cameras in broadcast, educational or industrial applications.

The XQ4087 series comprises the following versions:

XQ4087R for the red channel of colour cameras

XQ4087G for the green channel

XQ4087B for the blue channel

Special features are:

- High stability construction (HS).
- "Diode" electron gun for D.B.C. (dynamic beam control) to minimize comet-tailing and blooming (notes 1 and 2).
- Low output capacitance, achieved by a special signal plate with contact through the window.
- Low deflection field damping by wall electrodes.
- Reduced line pick-up due to side connection of the mesh.
- Low power consumption due to electrostatic focusing.
- Low weight and small size.

QUICK REFERENCE DATA

"Diode" electron gun					
Diameter		max.	18	mm	
Length		approx.	73	mm	
Provided with anti-halation glass disc, thickness	3		3	mm	
Focusing		electrost	tatic		
Deflection		magnetic	C		
Useful target area (scanning area)		4	,8 mm x 6,4	mm	
Spectral response					
max. at		approx.	500	nm	
cut-off at		approx.	650 to 850	nm	
type	XQ4087R	XQ4087G	XQ4087B		
Sensitivity, typ.	85	100	25	$\mu A/ImF$	
Resolution at 320 TV lines (4 MHz)	40	45	50	%	
Heater			9 V, 55	mA	

OPTICAL DATA

Quality rectangle on photoconductive target

(aspect ratio 3:4)

4,8 mm x 6,4 mm

Orientation of image on target

For correct orientation of the image on the target the vertical scan should be essentially parallel to the plane passing through the tube axis and the index slot at the base. Mounted in the deflection coil, the target contact should be at the upper side during scanning.

® Registered trade mark for television camera tubes.

XQ4087 SERIES

Faceplate

thickness refractive index 1,6 ± 0,1 mm 1,51

Anti-halation glass disc with AR-coating

thickness refractive index 3 ± 0,1 mm 1,51

ACCESSORIES

Socket is integrated in the deflection coil.

Deflection coil unit

type AT1120

ELECTRICAL DATA

Heating

Indirect by a.c. or d.c.; parallel supply

Heater voltage

 V_{f}

9 V ± 5%

Heater current, at V_f = 9,0 V

If

nom. 55 mA

The heater voltage must never exceed 12 V r.m.s. For optimum performance (lifetime and registration stability) stabilization of the heater voltage is recommended.

Capacitance

Signal electrode to all

Cas

approx. 1,7 pF

This capacitance, which is effectively the output impedance, increases when the tube is inserted in the coil unit.

Deflection

magnetic

Focusing

electrostatic

LIMITING VALUES (Absolute maximum rating system)

All voltages are referred to the cathode, unless otherwise stated.

					notes
Signal electrode voltage	Vas	max.	30	V	
Grid 4 voltage	V_{g4}	max.	850	V	
Grid 3 voltage	V_{g3}	max.	350	V	
Voltage between grid 4 and grid 3	$V_{g4/g3}$	max.	600	V	
Grid 2 voltage, focus	V_{g2}	max.	50	V	
Grid 1 voltage, positive	V_{g1}	max.	80	V	
Grid 1 voltage, negative	$-V_{g1}$	max.	50	V	
Grid 1 current (≈ IK current), with D.B.C.	lg1dc	max.	5	mA	
Grid 1 current (peak current with D.B.C.)	lg1p	max.	12	mA	
Cathode to heater voltage, positive peak	Vkfp	max.	50	V	
Cathode to heater voltage, negative peak	$-V_{kfp}$	max.	50	V	3
Cathode heating time before drawing cathode current	th	min.	1	min	
Ambient temperature, storage and operation	T_{amb}	max. min.	50 -30	oC oC	
Faceplate temperature, storage and operation	Т	max. min.	50 -30	oC oC	4
Faceplate illuminance (intermittent)	E	max.	100	Ix	5

XQ4087 SERIES

OPERATING CONDITIONS AND PERFORM, for a scanned area of 4,8 mm × 6,4 mm	ANCE						not
Conditions							
Cathode voltage	V_k				0	V	
Signal electrode voltage	Vas				25	V	
Beam current	I _b						7
Grid 4 voltage	V _{g4}				750	V	
Grid 3 voltage	V _{g3}				250	V	
Grid 2 voltage, focus	V_{q2}				30 ± 3	V	
Grid 1 voltage	V _{g1}						7
Blanking voltage on grid 1, peak to peak without D.B.C.					30	V	
Faceplate illuminance	V _{g1 p-p} E				0 to 10		8
Faceplate temperature	T			2	0 to 45		0
racepiate temperature	1				0 10 43	C	
Electron gun characteristics							
Cut-off							
Grid 1 voltage for cut-off without blanking Grid 1 voltage for 200 nA beam current	V_{g1} V_{g1w}				–5 to 0 ≤ 25		7
Blanking voltage, peak to peak on grid 1, without D.B.C. on cathode	V _{g1 p-p} V _{k p-p}				30 30	-	
Grid currents at	lb		200 nA	max	D.B.C.		
grid 1	l _{q1}	max.	3,5		12	mA	
grid 3	lg3	max.			40	μA	
grid 4	lg4	max.	1		4	μΑ	
Performance							
Dark current	ld				≤ 1,0	nA	
Sensitivity at colour temperature of illuminance XQ4087R	e = 2856 K	min.	65	typ.	85	μA/ImF	9
XQ4087G		min.	75	typ.		$\mu A/ImF$	
XQ4087B		min.	22	typ.		μA/ImF	
Gamma of transfer characteristic				0,95	+0,05		
Spectral response:							10
max. response at			~		500		
cut-off XQ4087R			~	050	850		
cut-off XQ4087G			≈	650	to 850		
cut-off XQ4087B response curves			~	Fig. 1	650	пm	

XQ4087 SERIES

Resolution

notes

Modulation depth, i.e. uncompensated amplitude response at 320 TV lines (4 MHz) at the centre of the picture.

11

12, 13

		XQ4087R	XQ4087G	XQ4087B
Signal current	Is	50 nA	100 nA	50 nA
Beam current	Ib	100 nA	200 nA	100 nA
Modulation depth at 320 TV lines (4 MHz)	typ. min.	40 % 30 %	45 % 35 %	50 % 40 %

Modulation transfer characteristics

see Fig. 2

Lag (typical values, no light bias applied)

Light source with a colour temperature of 2856 K

Appropriate filter inserted in light path

Low key conditions


	buile	d-up lag	deca	y lag
	$I_{s}/I_{b} = 20/300 \text{ nA}$		$I_{s}/I_{b} = 20$	0/300 nA
	60 ms	200 ms	60 ms	200 ms
XQ4087G	95	~ 100	8,0	3,0
XQ4087R	95	~ 100	8,0	3,0
XQ4087B	95	~ 100	9,0	3,5

Highlight handling capability with D.B.C.

14

XQ4087 SERIES

MECHANICAL DATA



Mounting position: any

Mass

: ≈ 23 g

Base

: EIA E7-91

BOTTOM VIEW

7Z95198

NOTES, see also General Section.

- Avoid continuous operation at high beam currents since this will shorten tube life. Full advantage
 of the high beam reserve to reduce comet-tailing and blooming can be made with D.B.C. circuitry
 which, during highlights, feeds positive-going pulses derived from the video signal to grid 1 to
 increase the beam current momentarily.
- 2. The diode gun operates with a positive (\leq 25 V) grid 1 voltage adjusted for correct beam currents, see note 7. The D.B.C. circuitry should, in the case of highlights, supply positive-going pulses with a maximum of 30 V to grid 1 above the normal V_{q1} setting for I_b = 200 nA.
 - N.B. Applying higher pulses than 30 V peak is not recommended since this will shorten the tube life, impair resolution and may cause oscillations.
- 3. The resistance of the external circuitry between K and F should be at least 1000 Ω when V_f is positive with respect to V_k.
- 4. Short temperature excursions up to 70 °C during operation are allowed.
- 5. During storage cover the tube face with the plastic hood provided; when the camera is idle cap the lens. In stand-by also the beam will be cut-off.
- The operating conditions and performance quoted relate to operation in the coil unit AT1120. See relevant data of deflection/focusing assemblies.
- 7. The beam current I_b , as obtained by adjusting the control grid voltage (grid 1) is set at 100 nA for R and B tubes, 200 nA for G tubes. I_b is not the total current available in the scanning beam, but is defined as the maximum amount of signal current, I_s , that can be obtained with this beam. In the performance figures for lag, the signal current and beam current conditions are given, e.g. as $I_s/I_b = 20/300$ nA. This means: with a signal current of 20 nA and a beam setting which just allows a signal current of 300 nA.
 - N.B. The signal currents are measured with an integrating instrument connected in the signal electrode lead and a uniform illumination of the scanned area.

The peak signal currents as measured on a waveform oscilloscope will be a factor $\boldsymbol{\alpha}$ larger.

$$\alpha = \frac{100}{100-\beta}$$
; β being the total blanking time in %: for the CCIR system α = 1,3.

- 8. Typical faceplate illumination level for the XQ4087 to produce 100 nA signal current will be approx. 12 lx. The signal currents stated for the colour tubes R, G and B will be obtained with an incident white light level (2856 K) on the filter of approx. 25 lx. These figures are based on the filters described in note 9. For filter BG12, however, a thickness of 1 mm is chosen.
- 9. Measuring conditions.

Illuminance level 4,54 lx at a colour temperature of 2856 K. Filters are inserted in the light path for the chrominance tubes.

Filters used for

XQ4087R: B1/K1 and Schott OG570, thickness 3 mm.

XQ4087G: B1/K1 and Schott VG9, thickness 1 mm.

XQ4087B: B1/K1 and Schott BG12, thickness 3 mm.

For transmission curves see General Section.

NOTES, continued

- 10. For true tonal rendition in black/white cameras, and for true colorimetry in colour cameras, an integral filter to eliminate response to near infrared radiation should be incorporated in the optical system, together with an integral B1/K1 filter or equivalent.
- 11. As measured with 50 mm Leitz Summicron lens having a sine response of approx. 80% at 32,5 lp/mm (320 TV lines at 4,8 mm x 6,4 mm) at f: 5,6. The horizontal amplitude response can be raised by means of suitable correction circuits, which affect neither the vertical resolution nor the limiting resolution.
- 12. Build-up lag.

After 10 s of darkness. The figures are typical percentages of the ultimate signal current obtained 60 ms or 200 ms, respectively, after introduction of the illuminance.

Decay lag.

After the target has been illuminated for at least 5 s. The figures represent typical signals in percentages of the original signal current 60 ms or 200 ms, respectively, after removal of the illuminance.

- 13. A reduction of lag, especially under low key conditions, is to be obtained when light bias is applied via the optical system. Infrared light with a wavelength > 600 nm in the light bias should be avoided.
- 14. With D.B.C. applied (see note 2) the tube will properly handle highlights with a diameter of 10% of the picture height and with a brightness corresponding to 8 times the brightness for normal peak signal. The maximum peak signal currents in the case of highlights will be 800 nA. Video amplifiers should be designed to accommodate these.




Fig. 1 Typical spectral responses.




Fig. 2 Typical square wave response curves.

DEFLECTION AND FOCUSING ASSEMBLIES

SURVEY

remarks		rear loading + alignment coils	front loading + alignment coils	front loading + alignment coils	rear loading + alignment coils	rear loading + alignment coils	rear loading + alignment rings	rear loading + alignment rings	for L.O.C. tubes, alignment rings					
	d.c. focus	35	35	32	32	108	108	30	30	120	120	115	and through	
current	p-p frame	55	92	36	36	34	34	80	08	114	114	104		
	p-p line	180	180	260	260	280	280	230	230	260	260	230	-	
	focus	1125	1125	1718	1718	140	140	1300	1300	09	09	09		
resistance Ω	frame	14,5	14,5	62	62	62	62	10	10	12,7	12,7	12,7		
	line	2,1	2,1	2,2	2,2	2,2	2,2	2,2	2,2	3,8	3,8	3,8		
inductance mH	frame	5,5	5,5	26	26	28	28	4,4	4,4	2,8	2,8	2,8		
induc	line	0,84	0,84	0,79	62'0	62'0	62'0	8′0	8,0	0,91	0,91	0,91		
triplet or	single	-	S	-	S	-	S	—	S	-	S	—		
type number and	cat. number	AT1130T 3122 137 18880	AT1130S 3122 137 18890	AT1115/01 3122 137 12710	AT1119/01 3122 137 12700	AT1116/06 3122 137 15040	AT1116S 3122 137 15050	AT1126T 3122 137 19060	AT1126S 3122 137 19050	AT1109/01 3122 137 18280	AT1109/01S 3122 137 18290	AT1109/10 3122 137 18730		
tube diameter		30 mm (11/4")		25 mm (1")						18 mm (2/3")				
	1													_

	for L.O.C. tubes, alignment rings	for L.O.C. tubes, alignment rings	for M.S. tubes	for H.S. tubes	for H.S. tubes	for tubes with electrostatic focus	for H.S. tubes	for H.S. tubes
	115	115	201	Ţ	J	1	Ī	Í
	104	104	1	92	92	30	92	92
	230	230	1	185	185	75	06	190
	09	09	22,7	1	I	1	1	1
	12,7	12,7	1	24	24,8	33	14,1	14,1
	3,8	3,8	I	4,5	4	5,03	6,2	6,2
	2,8	2,8	1	2,41	2,41	5,3	1,1	1,1
	0,91	0,91	1	1,15	1,15	1,17	0,325	0,325 1,1
	S	-	S	S	-	S	S	-
	AT1109/16S 8222 034 80190	AT1109/16T 8222 034 80160	KV4722 9390 304 60000	KV4736-3AS 9390 304 80000	KV4736-3AT 9390 304 90000	KV4780 9390 304 70000	AT1120S 3122 137 18870	AT1120T
							14 mm (½")	
-				-				

DEFLECTION UNITS FOR 2/3-INCH PLUMBICON TUBE

QUICK REFERENCE DATA

	inductance	resistance
Line deflection coils	0,91 mH	3,8 Ω
Frame deflection coils	2,8 mH	12,7 Ω
Focus coil		60 Ω

APPLICATION

The AT1109/01 is a triplet of rear-loaded deflection units for use in colour television cameras using 2/3 inch pick-up tubes e.g. Plumbicon® tubes, types XQ1427 and XQ2427.

Their small dimensions and low weight make them specially suitable for use in portable ENG cameras.

DESCRIPTION

The deflection units contain the deflection and focus coils and are provided with permanent magnet alignment rings. The effective alignment field intensities and directions can be adjusted, the minimum field strength position is indicated. The focus coil is situated inside the deflection coils, hence the focus power is reduced.

The housing consists of a mu-metal can for optimum screening from external magnetic fields and to form the required magnetic circuit for the deflection fields.

The camera tubes are secured in position by an aluminium nut-ring at the rear of the units and by means of a nylon glass tube.

The target contact can be removed and replaced by a contact of own design, e.g. incorporating a video preamplifier.

Warning


No deformation of the calibrated mu-metal housing is allowed as this will strongly influence the performance and adjustments of the units.

Catalogue number

The catalogue number of the triplet is 3122 137 18280.

The catalogue number of a single unit, AT1109/01S, is 3122 137 18290.

[®] Registered trade mark for television camera tubes.



254 February 1981

MECHANICAL DATA

ELECTRICAL DATA (typical values)




Fig. 2.


coils	inductance mH	resistance Ω	current mA	connections
Line deflection coils	0,91 ± 5%	3,8 ± 10%	260 ± 5% (p-p)	transparent; yellow
Frame deflection coils	2,8 ± 5%	12,7 ± 10%	114 ± 5% (p-p)	brown; grey
Focus coil*		60 ± 10%	120 ± 5%	green; blue

^{*} Polarity: the north-seeking pole of a compass should be attracted to the image end of the unit.

Requirements for normal operation (XQ1427; XQ2427)

Tube setting	V_{g2}	=	300	V)
	V_{g3}	=	430	V	
	Vg4*	=	750	V	1
	V _{target}	=	45	V	J
signal current	Is	=	150	nA	
beam current	lb	=	300	nA	
Alignment magnet fie	eld intensity	max. min.	0,24	mT mT	

max.



with respect to cathode potential

Fig. 3.

Geometric distortion

Ambient temperature 21 °C.

Measured at operating temperature.

Distortion

inside circle diam. H max. outside circle diam. H max.

Skew error

0,5% of picture height 1% of picture height 1% of picture height

Nominal scanning area: 6,6 mm x 8,8 mm (H = 6,6 mm)

Registration

The misregistration in any triplet (measured after skew correction) is not greater than:

30 ns in zone A

60 ns in zone B 120 ns in zone C

The errors are measured both in horizontal and vertical direction and are expressed in units of 1/52000 of an active scan duration which is equivalent (horizontally) to 1 ns for CCIR corresponding to approximately 0.00256% (25×10^{-6}) related to picture height.

Capacitance of tube target (XQ1427; XQ2427)

The capacitance between the target and the electrodes increases less than 3 pF when the tube is inserted into the deflection unit.

 $^{^{\}star}$ V_{g4} to be adjusted for minimum beam landing error to compensate for tube tolerances.

DEFLECTION UNITS FOR 2/3-INCH PLUMBICON TUBE

with low output capacitance

QUICK REFERENCE DATA

	inductance	resistance	
Line deflection coils	0,91 mH	3,8 Ω	
Frame deflection coils	2,8 mH	12,7 Ω	
Focus coil		60 Ω	

APPLICATION

The AT1109/10 is a triplet of rear-loaded deflection units for use in colour television cameras using 2/3 inch pick-up tubes e.g. Plumbicon[®] tubes, type XQ3427, with low output capacitance (LOC).

Their small dimensions and low weight make them specially suitable for use in portable ENG cameras.

DESCRIPTION

The deflection units contain the deflection and focus coils and are provided with permanent magnet alignment rings. The effective alignment field intensities and directions can be adjusted, the minimum field strength position is indicated. The focus coil is situated inside the deflection coils, hence the focus power is reduced.

The housing consists of a mu-metal can for optimum screening from external magnetic fields and to form the required magnetic circuit for the deflection fields.

The camera tubes are secured in position by an aluminium nut-ring at the rear of the units and by means of a nylon glass tube.

The first stage of the video preamplifier is built in the yoke.

Warning


No deformation of the calibrated mu-metal housing is allowed as this will strongly influence the performance and adjustments of the units.

Catalogue number

The catalogue number of the triplet is 3122 137 18730.

The catalogue number of a single unit, AT1109/10S, 3122 137 18720.

[®] Registered trade mark for television camera tubes.



258

ELECTRICAL DATA (typical values)




Fig. 2.

coils	inductance mH	resistance Ω	current mA	connections
Line deflection coils	0,91 ± 5%	3,8 ± 10%	230 ± 5% (p-p)	transparent; yellow
Frame deflection coils	2,8 ± 5%	12,7 ± 10%	104 ± 5% (p-p)	brown; grey
Focus coil*		60 ± 10%	115 ± 5%	green; blue

^{*} Polarity: the north-seeking end of a compass should be attracted to the image end of the unit.

Requirements for normal operation (XQ3427).

Tube setting $V_{g2} = 300 \text{ V}$ $V_{g3} = 430 \text{ V}$ $V_{g4}^* = 750 \text{ V}$ $V_{target} = 45 \text{ V}$

signal current $I_s = 150 \text{ nA}$ beam current $I_b = 300 \text{ nA}$

Alignment magnet field intensity max. 0,24 mT min. 0,015 mT

Geometric distortion

Ambient temperature 21 °C..

Measured at operating temperature.

Distortion

inside circle

max. 0,

0,5% of picture height 1% of picture height

Skew error

max.

1% of picture height

with respect to cathode potential




Fig. 3 Nominal scanning area: 6,6 mm x 8,8 mm (H = 6,6 mm).

Registration

The misregistration in any triplet (measured after skew correction) is not greater than:

20 ns in zone A,

40 ns in zone B,

80 ns in zone C.

The errors are measured both in horizontal and vertical direction and are expressed in units of 1/52000 of an active scan duration which is equivalent (horizontally) to 1 ns for CCIR corresponding to approximately 0.00256% (25×10^{-6}) related to picture height.

Capacitance of tube target (XQ3427).

The capacitance between the target and the electrodes increases less than 2 pF when the tube is inserted into the deflection unit.

 $^{^{\}ast}$ V_{g4} to be adjusted for minimum beam landing error to compensate for tube tolerances.

DEVELOPMENT DATA

This data sheet contains advance information and specifications are subject to change without notice.

DEFLECTION UNITS FOR 2/3-INCH PLUMBICON TUBE

with low output capacitance

QUICK REFERENCE DATA

	inductance	resistance
Line deflection coils	0,91 mH	3,8 Ω
Frame deflection coils	2,8 mH	12,7 Ω
Focus coil	_	60 Ω
Alignment coils	_	300 Ω

APPLICATION

The AT1109/16 is a rear-loaded deflection unit for use in colour television cameras using 2/3 inch pick-up tubes e.g. Plumbicon[®] tubes, type XQ3427, with low output capacitance (LOC).

The small dimensions and low weight make them specially suitable for use in portable ENG cameras.

DESCRIPTION

The deflection units contain the deflection and focus coils and are provided with alignment coils. The effective alignment field intensities and directions can be adjusted. The focus coil is situated inside the deflection coils, hence the focus power is reduced.

The housing consists of a mu-metal can for optimum screening from external magnetic fields and to form the required magnetic circuit for the deflection fields.

The camera tubes are secured in position by an aluminium nut-ring at the rear of the units and by means of a nylon glass tube.

The first stage of the video preamplifier is built in the yoke.

Warning


No deformation of the calibrated mu-metal housing is allowed as this will strongly influence the performance and adjustments of the units.


Catalogue number


The catalogue number 8222 034 80190 for single unit AT1109/16S.

The catalogue number 8222 034 80160 for selected triplet AT1109/16T.

[®] Registered trade mark for television camera tube.







19	17				9	7	5		1
_	~	_	_	~	~	_	~	7	5
1	•				0	0	0		0
•	0				0	•	0		0
~	~	5	~	~	~	5	~	~	7
20	18				10	8	6		2

Diagram of plug, viewed from cable side.

coils	inductance mH	resistance Ω	current mA	connections
Line deflection coils Frame deflection coils Focus coil*	0,91 ± 5% 2,8 ± 5%	3,8 ± 10% 12,7 ± 10% 60 ± 10%	230 ± 5% (p-p) 104 ± 5% (p-p) 115 ± 5%	transparent; yellow brown; grey green; blue
Alignment coils vertical horizontal		300 ± 10%	8,4 (for 0,2 mT)	red; red/white yellow; yellow/whit

^{*} Polarity: the north-seeking end of a compass should be attracted to the image end of the unit.

AT1109/16

Requirements for normal operation (XQ3427).

$$V_{g2} = 300 V$$

$$V_{g3}$$

 V_{a4}^*


Geometric distortion

Ambient temperature 21 °C.

Measured at operating temperature.

Distortion

1% of picture height



with respect to cathode potential

Fig. 3 Nominal scanning area: $6.6 \text{ mm} \times 8.8 \text{ mm} (H = 6.6 \text{ mm}).$

Registration

The misregistration in any triplet (measured after skew correction) is not greater than:

- 30 ns in zone A.
- 60 ns in zone B.
- 120 ns in zone C.

The errors are measured both in horizontal and vertical direction and are expressed in units of 1/52000 of an active scan duration which is equivalent (horizontally) to 1 ns for CCIR corresponding to approximately 0,00256% (25 x 10⁻⁶) related to picture height.

Capacitance of tube target (XQ3427).

The capacitance between the target and the electrodes increases less than 2 pF when the tube is inserted into the deflection unit.

^{*} V_{q4} to be adjusted for minimum beam landing error to compensate for tube tolerances.

DEFLECTION UNITS FOR 1-INCH PLUMBICON TUBE computer-selected triplet

QUICK REFERENCE DATA

	inductance	resistance
Line deflection coils	0,78 mH	2,4 Ω
Frame deflection coils	26 mH	64 Ω
Focus coil		1760 Ω

APPLICATION

The AT1115/01 is a triplet of rear loaded deflection units for use in broadcast colour television cameras using 1-inch tubes, e.g. Plumbicon® tubes XQ1080, XQ1500, XQ2070/02 series.

DESCRIPTION

The deflection units contain the deflection, alignment and focus coils.

Each unit is provided with a locking device at the front, in which a holder for a field flattener lens can be fitted without the use of tools.

The camera tubes are secured in position by a plastic nut-ring at the rear of a unit. By turning the ring the tube will be pushed forward until it touches the stop. Space has been provided to build in a video pre-amplifier (connections A, C and D see dimensional drawing).

Catalogue number


The catalogue number of the triplet is 3122 137 12710.

The catalogue number of a single unit, AT1119/01, is 3122 137 12700.

[®] Registered trade mark for television camera tubes.

AT1115/01

MECHANICAL DATA



560 g approx. Mass per unit


Body temperature

Temperature range

for continuous operation

-15 to + 75 °C -25 to +85 °C for non-operating

ELECTRICAL DATA (typical values)



Deflection units for 1-inch Plumbicon tube

coils	inductance mH	resistance Ω	connections
Line deflection coils	79 ± 3%	2,1 ± 5%	transparent (screened); yellow (screened)
Frame deflection coils	26	62 ± 8%	red-white; brown-white
Horizontal alignment coils		550 ± 10%	yellow-white; black-white
Vertical alignment coils		550 ± 10%	orange-white; blue-white
Focus coil*		1718 ± 10%	grey (+); white (-)

Required currents for normal operation (XQ1080)

Tube setting:

 $V_{g5} = +470 \text{ V}$ $V_{g6} = +750 \text{ V}$ with respect to cathode potential

Nominal scanning area: 9,6 mm x 12,8 mm

Dynamic focus on Va5

Line deflection current, p-p

260 mA

Frame deflection current, p-p

36 mA

Focus current

Skew error

32 mA

Alignment current

1 mA will cause a shift of ≤ 0,6% of picture height

Geometric distortion


Distortion, measured with dynamic focus

inside the circle max. 0,5% of picture height

outside the circle max. 1% of picture height

outside the chole


max. 0,4% of picture height



^{*} Polarity: the north-seeking pole of a compass should be attracted to the image end of the unit.

Registration

The deflection units are supplied in matched sets of three units wherein the misregistration in any set is not greater than:



in zone A 25 ns in zone B 40 ns in zone C 80 ns

The errors are measured horizontally and vertically.

The difference between the focus currents of the deflection units of a selected triplet shall not exceed \pm 1%, measured at one tube as a reference.

Capacitance of the tube target

The capacitance between the target and the tube electrodes increases less than 6 pF, when the tube is inserted in the deflection unit.

DEFLECTION UNITS FOR 1-INCH PLUMBICON TUBE computer-selected triplet

QUICK REFERENCE DATA

	inductance	resistance
Line deflection coils	0,79 mH	2,2 Ω
Frame deflection coils	28 mH	62 Ω
Focus coil		140 Ω

APPLICATION

The AT1116/06 is a triplet of front loaded deflection units for use in broadcast colour television cameras using 1-inch camera tubes, e.g. Plumbicon® tubes of the XQ1070/03 and XQ2070/03 series.

DESCRIPTION

The deflection units contain the deflection, alignment and focus coils.


The camera tubes are secured in position by a plastic nut-ring at the rear of a unit. By turning the ring the tube will be pushed backward until it touches the stop.

Catalogue number

The catalogue number of the triplet is 3122 137 15040.

The catalogue number of a single unit, AT1116S, is 3122 137 15050.

MECHANICAL DATA



Mass per unit 615 g approx.

Body temperature


Temperature range

for continuous operation $-15 \text{ to } + 75 \, ^{\circ}\text{C}$

for non-operating

-25 to +85 °C

ELECTRICAL DATA (typical values)



coils	inductance mH	resistance Ω	connections
Line deflection coils	0,79 ± 5%	2,2 ± 10%	transparent (screened); yellow (screened)
Frame deflection coils	28 ± 5%	62 ± 10%	red-white; brown-white
Horizontal alignment coils		550 ± 10%	yellow-white; black-white
Vertical alignment coils		550 ± 10%	orange-white; blue-white
Focus coil*		140 ± 10%	grey (+); white (-)

Required currents for normal operation (XQ1070)

Tube setting:

 $V_{g3} = +600 \text{ V}$ $V_{g4} = +960 \text{ V}$ with respect to cathode potential

Nominal scanning area: 9,6 mm x 12,8 mm

Line deflection current, p-p

280 mA

Frame deflection current, p-p

34 mA

Focus current
Alignment current

108 mA 1 mA will cause a shift of 0,6% of picture height


^{*} Polarity: the north-seeking pole of a compass should be attracted to the image end of the unit.

Geometric distortion

Distortion


inside the circle outside the circle

max. 0,5% of picture height max. 1% of picture height



Registration

The deflection units are supplied in matched sets of three units wherein the misregistration in any set is not greater than:



in zone A 25 ns in zone B 40 ns in zone C 80 ns

The errors are measured horizontally and vertically.

DEFLECTION UNITS FOR 1/2-INCH H.S. 'DIODE-GUN' PLUMBICON TUBE

computer selected triplet

OUICK REFERENCE DATA

	inductance	resistance
Line deflection coils	325 μH	6,2 Ω
Frame deflection coils	1,1 mH	14,1 Ω

APPLICATION

The AT1120T is a computer selected triplet of deflection units for use in colour television cameras using front-loading ½-inch H.S. diode electron gun Plumbicon® tubes with magnetic deflection and electrostatic focus, type XQ4087.

Their small size and low weight make these units specially suitable for use in portable ENG cameras.

DESCRIPTION

The deflection unit contains the horizontal and vertical deflection coils. With the H.S. diode gun Plumbicon tubes no alignment correction is required. The tube socket is integrated in the unit, all tube connections form part of the deflection unit assembly. The housing is a mu-metal can for optimum screening from external magnetic fields and forms the required magnetic circuit for the deflection fields.

WARNING

No deformation of the mu-metal housing is allowed as this would strongly affect the performance and adjustment of the unit.

CATALOGUE NUMBER

Triplet

AT1120T: 3122 137 18860

Single unit

AT1120S: 3122 137 18870

[®] Registered trade mark for television camera tubes.

ELECTRICAL DATA (Deflection coil + tube connections)




Fig. 1.

Horizontal deflection coil	inductance 325 μ H \pm 5%, resistance 6,2 Ω \pm 10%.
Vertical deflection coil	inductance 1,1 mH \pm 5%, resistance 14,1 Ω \pm 10%.

Measured with bridge f = 1000 Hz, Tamb = 25 °C:

Deflection current:

Horizontal deflection coil Vertical deflection coil 190 ± 5% mA 92 ± 5% mA

Distortion:

geometric

≤ 1% of picture height ≤ 1% of picture height

Registration

The deflection units are supplied in matched sets of three units. The misregistration in any set is not greater than:

40 ns in zone A 80 ns in zone B 120 ns in zone C




Fig. 2


Nominal scanning area: 4,8 mm x 6,4 mm (H = 4,8 mm).

The errors are measured both in horizontal and vertical direction after skew correction, with one tube as a reference. Tube settings according to the XQ4087 data sheet.

Capacitance

Target contact of the tube/coil assembly to any other contact

 $C_{as} \approx 3.5 \text{ pF}.$




Mass per unit : 53 g

Operating body temperature range: -15 to +70 °C

To replace a tube unscrew the ring at the front end of the deflection unit by turning the marker on the ring to position "0".

Remove the metal front part and push gently on the base of the tube through the hole in the rear end of the unit.

For proper insertion of a tube the index slot in the tube base should be in the position indicated by the arrow on the front end of the deflection unit. The deflection units should be mounted in the camera with the tube target contact positioned upwards.



DEFLECTION UNITS FOR 1-INCH PLUMBICON® TUBES with low output capacitance

QUICK REFERENCE DATA

	inductance	resistance
Line deflection coils	0,800 mH	2,2 Ω
Field deflection coils	4,4 mH	10 Ω
Focus coil		1300 Ω

APPLICATION

The AT1126 is a triplet of rear-loaded deflection units for use in colour television cameras using 1 inch pick-up tubes e.g. Plumbicon® tubes, types XQ1500 and XQ3070, with low output capacitance (LOC).

DESCRIPTION

The deflection units contain the deflection, focus and alignment coils.

The housing is a mu-metal can for optimum screening from external magnetic fields and to form the required magnetic circuit for the deflection fields.

The camera tubes are secured in position by a threaded ring at the rear of the units.

The first stage of the video preamplifier is built into the yoke.

Warning

The mu-metal housing must not be deformed as this will strongly influence the performance and adjustments of the units.

Catalogue number

Triplet AT1126: 3122 137 19060; Single unit AT1126S: 3122 137 19050.

® Registered trade mark for television camera tubes.




Fig. 1.

Operating body temperature range -15 to +65 $^{\rm 0}{\rm C}$

Mass per unit

MECHANICAL DATA

ELECTRICAL DATA (typical values)




Fig. 2.

coils (see Fig. 2)	inductance mH	resistance Ω	current mA
Line deflection coils	0,800 ± 5%	2,2 ± 10%	230 ± 5% (p-p)
Field deflection coils	4,4 ± 5%	10 ± 10%	80 ± 5% (p-p)
Focus coil*		1300 ± 10%	30 ± 5%
Alignment coils		530 ± 10%	

^{*} Polarity: the image end of the unit should attract the north pole of a compass.

Requirements for normal operation (XQ1500)

Alignment current of 1 mA will cause a shift of ≤ 0,7% of picture height.

Geometric distortion

Ambient temperature 21 °C.

Measured at operating temperature.

Distortion inside zone A outside zone A

max.

0,5% of picture height 1% of picture height

Skew error max.

1% of picture height
0,5% of picture height

with respect to cathode potential

Fig. 3.

4/3 H -

Nominal scanning area: 9,6 mm x 12,8 mm (H = 9.6 mm)

7Z75638

Registration

The misregistration in any triplet (measured after skew correction) is not greater than:

40 ns in zone A

50 ns in zone B

80 ns in zone C

The errors are measured both in horizontal and vertical direction and are expressed in units of 1/52000 of an active scan duration which is equivalent (horizontally) to 1 ns for CCIR corresponding to approximately 0,00256% (25 x 10⁻⁶) related to picture height.

Capacitance of tube target

The capacitance between the target and the electrodes increases less than 3,5 pF, when the tube is inserted into the deflection unit, and measured without FET-preamplifier.

^{*} V_{q6} to be adjusted for minimum beam landing error to compensate for tube tolerances.

DEFLECTION UNITS FOR 30 mm PLUMBICON® TUBE

QUICK REFERENCE DATA

	inductance	resistance
Line deflection coils	0,835 mH	2,1 Ω
Field deflection coils	5,5 mH	14,5 Ω
Focus coil		1125 Ω

APPLICATION

The AT1130 is a triplet of rear-loaded deflection units for use in colour television cameras using 30 mm pick-up tubes e.g. Plumbicon® tubes, types XQ1410, XQ1520.

DESCRIPTION

The deflection units contain the deflection, focus and alignment coils.

The housing is a mu-metal can for optimum screening from external magnetic fields and to form the required magnetic circuit for the deflection fields.

The camera tubes are secured in position by a threaded ring at the rear of the units.

The first stage of the video preamplifier is built into the yoke.

Warning

The mu-metal housing must not be deformed as this will strongly influence the performance and adjustments of the units.

Catalogue number

Triplet AT1130: 3122 137 18880; Single unit AT1130S: 3122 137 18890.

[®] Registered trade mark for television camera tubes.

900

Operating body temperature range -15 to +65 °C

approx. 865 g

Mass per unit

ELECTRICAL DATA (typical values)




Fig. 2.

coils (see Fig. 2)	inductance mH	resistance Ω	current mA
Line deflection coils	0,835 ± 5%	2,1 ± 10%	180 ± 5% (p-p)
Field deflection coils	5,5 ± 5%	14,5 ± 10%	55 ± 5% (p-p)
Focus coil*		1125 ± 10%	35 ± 5%
Alignment coils		530 ± 10%	

^{*} Polarity: the image end of the unit should repel the north pole of a compass.

Requirements for normal operation (XQ1410)

Tube setting
$$V_{g2} = 300 \text{ V}$$
 $V_{g3} = 600 \text{ V}$
 $V_{g4}^* = 675 \text{ V}$
 $V_{target} = 45 \text{ V}$
signal current $I_e = 300 \text{ nA}$

lb Alignment current of 8,8 mA will cause a flux of 0,2 mT.

0.8H H 7Z75638 4/3 H -

with respect to cathode potential

Fig. 3.

Geometric distortion

beam current

Ambient temperature 21 °C.

Measured at operating temperature.

Distortion

inside zone A outside zone A max. max. 0.5% of picture height 1% of picture height

600 nA

Skew error max. 0,5% of picture height

Nominal scanning area: 12,8 mm x 17,1 mm (H = 12.8 mm)

Registration

The misregistration in any triplet (measured after skew correction) is not greater than:

40 ns in zone A

50 ns in zone B

80 ns in zone C

The errors are measured both in horizontal and vertical direction and are expressed in units of 1/52000 of an active scan duration which is equivalent (horizontally) to 1 ns for CCIR corresponding to approximately 0,00256% (25 x 10⁻⁶) related to picture height.

Capacitance of tube target (XQ1410, XQ1520)

The capacitance between the target and the electrodes increases less than 5,5 pF when the tube is inserted into the deflection unit.

^{*} V_{q4} to be adjusted for minimum beam landing error to compensate for tube tolerances.

DEVELOPMENT DATA

This data sheet contains advance information and specifications are subject to change without notice.

FOCUSING UNIT FOR 2/3 INCH PLUMBICON TUBES

with M.S. Diode gun

QUICK REFERENCE DATA

F	25.0.0
Focus coil resistance	25,2 Ω
Alignment coils resistance	567 Ω
-	

APPLICATION

The KV4722 is a focusing and alignment unit for 2/3 inch "diode" electron gun Plumbicon[®] tubes with magnetic focus and electrostatic deflection (M.S.), type XQ3457.

DESCRIPTION

The unit contains the focus coil and the horizontal and vertical alignment coils. The housing is a mu-metal can for optimum screening from external magnetic fields.

Warning

No deformation of the mu-metal housing is allowed as this would strongly affect the performance of the unit.


Catalogue number

Single unit KV4722: 9390 304 60000;


For a 3-tube colour camera 3 single units must be ordered.

[®] Registered trade mark for television camera tubes.

MECHANICAL DATA



ELECTRICAL DATA



coils (see Fig. 2)	resistance Ω	current mA	field mT
focus coil	25,2 ± 10%	198 ± 10%	7 ± 10%
alignment coils	567 ± 10%	17,5 ± 10%	0,4 ± 10%

Tube settings according to XQ3457 tube data.

DEVELOPMENT DATA

This data sheet contains advance information and specifications are subject to change without notice.

DEFLECTION UNIT FOR 2/3 INCH PLUMBICON TUBES

with H.S. "Diode" gun, computer selected triplet

QUICK REFERENCE DATA

	inductance	resistance
Line deflection coils	1,14 mH	4,6 Ω
Frame deflection coils	2,37 mH	25,4 Ω

APPLICATION

The KV4736-3 is a computer selected triplet of deflection units for use in colour television cameras using front-loading 2/3 inch H.S. ''diode'' electron Plumbicon[®] tubes with magnetic deflection and electrostatic focus, type XQ4187. Their small size and low weight make these units specially suitable for use in portable ENG cameras.

DESCRIPTION

The deflection unit contains the horizontal and vertical deflection coils. With the H.S. "diode" electron gun Plumbicon tubes no alignment correction is required. The tube socket is integrated in the unit, all tube connections form part of the deflection unit assembly. The housing is a mu-metal can for optimum screening from external magnetic fields and forms the required magnetic circuit for the deflection fields.

Warning

No deformation of the mu-metal housing is allowed as this would strongly affect the performance and adjustment of the unit,

Catalogue number

Triplet KV4736-3AT : 9390 304 90000 Single unit KV4736-3AS : 9390 304 80000

[®] Registered trade mark for television camera tubes.

Operating body temperature range: -15 to 70 °C Mass per unit: 115 g

To replace a tube unscrew the front cap of the deflection unit. Remove the metal front part and push gently on the base of the tube through the hole in the rear end of the unit.

The deflection units should be mounted in the camera with the tube target contact positioned upward.

MECHANICAL DATA

ELECTRICAL DATA




Fig. 1.

coils	inductance mH	resistance Ω	current mA
horizontal deflection	1,14 ± 5%	4,6 ± 5%	170 ± 5%
vertical deflection	2,37 ± 5%	25,4 ± 5%	85 ± 5%

Measured with bridge f = 1000 Hz, Tamb = 25 °C

Distortion

≤ 1% of picture height

geometric skew

≤ 1% of picture height

Registration

The deflection units are supplied in matched sets of three units. The misregistration in any set is not greater than:

40 ns in zone A 80 ns in zone B 120 ns in zone C




Fig. 2.

Nominal scanning area: 6,6 mm x 8,8 mm (H = 6,6 mm).

The errors are measured both in horizontal and vertical direction after skew correction, with one tube as a reference. Tube settings according to the XQ4187 data.

Capacitance

Target contact of the tube/coil assembly to any other contact

Cas ≈ 3,5 pF

DEVELOPMENT DATA

This data sheet contains advance information and specifications are subject to change without notice.

DEFLECTION UNIT FOR 2/3 INCH PLUMBICON TUBES with electrostatic focus

QUICK REFERENCE DATA

	inductance	resistance
Line deflection coils	1,17 mH	5,03 Ω
Frame deflection coils	5,3 mH	33 Ω
Alignment coils		146 Ω

APPLICATION

The KV4780 is a deflection unit for 2/3 inch Plumbicon® tubes with magnetic deflection and electrostatic focus, type XQ3467.

DESCRIPTION

The deflection unit contains the horizontal and vertical deflection coils and the alignment coils. The housing is a mu-metal can for optimum screening from external magnetic fields.

Warning

No deformation of the mu-metal housing is allowed as this would strongly affect the performance and adjustment of the unit.


Catalogue number

Single unit KV4780: 9390 304 70000

For a 3-tube colour camera 3 single units must be ordered.

[®] Registered trade mark for television camera tubes.

MECHANICAL DATA



Mass per unit: 110 g
Operating body temperature range: -10 to 60 °C

ELECTRICAL DATA




Fig. 2.

coils, see Fig. 2	inductance mH	resistance Ω	current mA	field mT
Horizontal deflection	1,17 ± 10%	5,03 ± 10%	175 ± 10%	
Vertical deflection	5,3 ± 10%	33 ± 10%	30 ± 10%	
Alignment		146 ± 10%	22 ± 10%	0,4 ± 10%

Distortion

geometric

≤ 1% of picture height

skew

≤ 1,5% of picture height

Registration

The misregistration in any set of 3 units is not greater than:

40 ns in zone A 80 ns in zone B 120 ns in zone C





Fig. 2.

Nominal scanning area: 6,6 mm x 8,8 mm (H = 6,6 mm).

The errors are measured both in horizontal and vertical direction after skew correction, with one tube as a reference. Tube settings according to the XQ3467 data.



INDEX OF TYPE NUMBERS

type number	page	type number	page	type number	page
AT1109/01	253	XQ1075	99	XQ2074	157
AT1109/10	257	XQ1076	99	XQ2075	157
AT1109/16	261	XQ1080	121	XQ2076	157
AT1115/01	265	XQ1083	121	XQ2172	167
AT1116/06	269	XQ1085	121	XQ2427	197
AT1119	265	XQ1090	137	XQ2428	197
AT1120	273	XQ1093	137	XQ3070	177
AT1126	277	XQ1095	137	XQ3071	177
AT1130	281	XQ1410	53	XQ3073	177
KV4722	285	XQ1413	53	XQ3074	177
KV4736 KV4780 XQ1020 XQ1021 XQ1022	287 290 39 39 47	XQ1415 XQ1427 XQ1428 XQ1500 XQ1503	53 189 189 139	XQ3075 XQ3076 XQ3427 XQ3440 XQ3443	177 177 205 81 81
XQ1023	39	XQ1505	139	XQ3445	81
XQ1024	39	XQ1510	155	XQ3457	213
XQ1025	39	XQ1513	155	XQ3467	221
XQ1026	39	XQ1515	155	XQ4087	241
XQ1070	99	XQ1520	65	XQ4187	229
XQ1071 XQ1072 XQ1073 XQ1073X XQ1074	99 109 99 115 99	XQ1523 XQ1525 XQ2070 XQ2071 XQ2073	65 65 157 157 157	XQ4502	89

For type numbers of Newvicon and Vidicon camera tubes see relevant Data Handbook.

A TOTAL WAR A STATE OF THE ACTUAL ACTION

Electronic components and materials for professional, industrial and consumer uses from the world-wide Philips Group of Companies

Argentina: PHILIPS ARGENTINA S.A., Div. Elcoma, Vedia 3892, 1430 BUENOS AIRES, Tel, 541-7141/7242/7343/7444/7545. Australia: PHILIPS INDUSTRIES HOLDINGS LTD., Elcoma Division, 11 Waltham Street, ARTARMON, N.S.W. 2064, Tel. (02) 439 3322.

Austria: ÖSTERREICHISCHE PHILIPS BAUELEMENTE INDUSTRIE G.m.b.H., Triester Str. 64, A-1101 WIEN, Tel. 629111.

Belgium: N.V. PHILIPS & MBLE ASSOCIATED, 9 rue du Pavillon, B-1030 BRUXELLES, Tel, (02) 2427400,

Brazil: IBRAPE, Caixa Postal 7383, Av. Brigadeiro Faria Lima, 1735 SAO PAULO, SP, Tel. (011) 211-2600.

Canada: PHILIPS ELECTRONICS LTD., Electron Devices Div., 601 Milner Ave., SCARBOROUGH, Ontario, M1B 1M8, Tel. 292-5161.

Chile: PHILIPS CHILENA S.A., Av. Santa Maria 0760, SANTIAGO, Tel. 39-4001.

Colombia: IND. PHILIPS DE COLOMBIA S.A., c/o IPRELENSO LTD., Calle 17, No. 9-21, Of. 202, BOGOTA, D.E., Tel. 57-2347493.

Denmark: MINIWATT A/S, Strandlodsvej 2, P.O. Box 1919, DK 2300 COPENHAGEN S, Tel. (01) 541133.

Finland: OY PHILIPS AB, Elcoma Division, Kaivokatu 8, SF-00100 HELSINKI 10, Tel. 17271 France: R.T.C. LA RADIÓTECHNIQUE-CÓMPELEC, 130 Avenue Ledru Rollin, F-75540 PARIS 11, Tel. 338 80-00.

Germany (Fed. Republic): VALVO, UB Bauelemente der Philips G.m.b.H., Valvo Haus, Burchardstrasse 19, D-2 HAMBURG 1, Tel. (040) 3296-0.

Greece: PHILIPS S.A. HELLENIQUE, Elcoma Division, 52, Av. Sygrou, ATHENS, 12, 15111.

Hong Kong: PHILIPS HONG KONG LTD., Elcoma Division, 52, Av. Sygrou, ATHENS, Tel. 9215111.

Hong Kong: PHILIPS HONG KONG LTD., Elcoma Division, 52, Av. Sygrou, ATHENS, 12, 151111.

Hong Kong: PHILIPS HONG KONG LTD., Elcoma Division, 52, Av. Sygrou, ATHENS, 12, 151111.

Hong Kong: PHILIPS HONG KONG LTD., Elcoma Division, 52, Av. Sygrou, ATHENS, 12, 151111.

Hong Kong: PHILIPS HONG KONG LTD., Elcoma Division, 52, Av. Sygrou, ATHENS, 12, 151111.

Hong Kong: PHILIPS HONG KONG LTD., Elcoma Division, 52, Av. Sygrou, ATHENS, 12, 151111.

Hong Kong: PHILIPS HONG KONG LTD., Elcoma Division, 52, Av. Sygrou, ATHENS, 12, 151111.

Hong Kong: PHILIPS HONG KONG LTD., Elcoma Division, 52, Av. Sygrou, ATHENS, 12, 151111.

Hong Kong: PHILIPS HONG KONG LTD., Elcoma Division, 52, Av. Sygrou, ATHENS, 12, 151111.

Hong Kong: PHILIPS HONG KONG LTD., Elcoma Division, 52, Av. Sygrou, ATHENS, 12, 151111.

Hong Kong: PHILIPS HONG KONG LTD., Elcoma Division, 52, Av. Sygrou, ATHENS, 12, 151111.

Hong Kong: PHILIPS HONG KONG LTD., Elcoma Division, 52, Av. Sygrou, ATHENS, 12, 151111.

Hong Kong: PHILIPS HONG KONG LTD., Elcoma Division, 52, Av. Sygrou, ATHENS, 12, 151111.

Hong Kong: PHILIPS HONG KONG LTD., Elcoma Division, 52, Av. Sygrou, ATHENS, 12, 151111.

Hong Kong: PHILIPS HONG KONG LTD., Elcoma Division, 52, Av. Sygrou, ATHENS, 12, 151111.

Hong Kong: PHILIPS HONG KONG LTD., Elcoma Division, 52, Av. Sygrou, ATHENS, 12, 151111.

Hong Kong: PHILIPS HONG KONG LTD., Elcoma Division, 52, Av. Sygrou, ATHENS, 12, 151111.

Hong Kong: PHILIPS HONG KONG LTD., Elcoma Division, 52, Av. Sygrou, ATHENS, 12, 151111.

Hong Kong: PHILIPS HONG KONG LTD., Elcoma Division, 52, Av. Sygrou, ATHENS, 12, 151111.

Hong Kong: PHILIPS HONG KONG LTD., Elcoma Division, 52, Av. Sygrou, ATHENS, 12, 151111.

Hong Kong: PHILIPS HONG KONG LTD., Elcoma Division, 52, Av. Sygrou, 54, 151111.

Hong Kong: PHILIPS HONG KONG LTD., Elcoma Division, 52, Av. Sygrou, 54, 151111.

Hong Kong: PHILI

Indonesia: P.T. PHILIPS-RALIN ELECTRONICS, Elcoma Div., Panim Bank Building, 2nd Fl., Jl. Jend. Sudirman, P.O. Box 223, JAKARTA, Tel. 716131. Ireland: PHILIPS ELECTRICAL (IRELAND) LTD.. Newstead. Clonskeach. DUBLIN 14. Tel. 693355.

Italy: PHILIPS S.p.A., Sezione Elcoma, Piazza IV Novembre 3, I-20124 MILANO, Tel. 2-6752.1.

Japan: NIHON PHILIPS CORP., Shuwa Shinagawa Bldg., 26-33 Takanawa 3-chome, Minato-ku, TOKYO (108), Tel. 448-5611.

(IC Products) SIGNETICS JAPAN LTD., 8-7 Sanbancho Chiyoda-ku, TOKYO 102, Tel. (03) 230-1521.

Korea (Republic of): PHILIPS ELECTRONICS (KOREA) LTD., Elcoma Div., Philips House, 260-199 Itaewon-dong, Yongsan-ku, SEOUL, Tel. 794-4202. Malaysia: PHILIPS MALAYSIA SDN. BERHAD, No. 4 Persiaran Barat, Petaling Jaya, P.O.B. 2163, KUALA LUMPUR, Selangor, Tel. 774411.

Mexico: ELECTRONICA, S.A de C.V., Carr. México-Toluca km. 62.5, TOLUCA, Edo. de México 50140, Tel. Toluca 91 (721) 613-00. Netherlands: PHILIPS NEDERLAND, Marktgroep Elonco, Postbus 90050, 5600 PB EINDHOVEN, Tel. (040) 793333.

New Zealand: PHILIPS NEW ZEALAND LTD., Elcoma Division, 110 Mt. Eden Road, C.P.O. Box 1041, AUCKLAND, Tel. 605-914.

Norway: NORSK A/S PHILIPS, Electronica Dept., Sandstuveien 70, OSLO 6, Tel. 680200. Peru: CADESA, Av. Alfonso Ugarte 1268, LIMA 5, Tel. 326070.

Philippines: PHILIPS INDUSTRIAL DEV. INC., 2246 Pasong Tamo, P.O. Box 911, Makati Comm. Centre, MAKATI-RIZAL 3116, Tel. 86-89-51 to 59.

Portugai: PHILIPS PORTUGUESA S.A.R.L., Av. Eng. Duarte Pacheco 6, 1009 LISBOA Codex, Tel. 683121.

Singapore: PHILIPS PROJECT DEV. (Singapore) PTE LTD., Elcoma Div., Lorong 1, Toa Payoh, SINGAPORE 1231, Tel. 3502000.

South Africa: EDAC (PTV.) LTD., 3rd Floor Rainer House, Upper Railway Rd. & Ove St., New Doornfontein, JOHANNESBURG 2001, Tel. 614-2362/9.

Spain: MINIWATT S.A., Balmes 22, BARCELONA 7, Tel. 3016312.
Sweden: PHILIPS KOMPONENTER A.B., Lidingövägen 50, S-11584 STOCKHOLM 27, Tel. 08/7821000.

Switzerland: PHILIPS A.G., Elcoma Dept., Allmendstrasse 140-142, CH-8027 ZÜRICH, Tel. 01-4882211

Taiwan: PHILIPS TAIWAN LTD., 3rd Fl., San Min Building, 57-1, Chung Shan N. Rd, Section 2, P.O. Box 22978, TAIPEI, Tel. (02)-5631717.
Thailand: PHILIPS ELECTRICAL CO. OF THAILAND LTD., 283 Silom Road, P.O. Box 961, BANGKOK, Tel. 233-6330-9.

Turkey: TÜRK PHILIPS TICARET A.S., Elcoma Department, Inönü Cad. No. 78-80, ISTANBUL, Tel. 435910. United Kingdom: MULLARD LTD., Mullard House, Torrington Place, LONDON WC1E 7HD, Tel. 01-580 6633.

United States: (Active Devices & Materials) AMPEREX SALES CORP., Providence Pike, SLATERSVILLE, R.I. 02876, Tel. (401) 762-9000.
(Passive Devices) MEPCO/ELECTRA INC., Columbia Rd., MORRISTOWN, N.J. 07960, Tel. (201) 539-2000.
(Passive Devices & Electromechanical Devices) CENTRALAB INC., 5855 N. Glen Park Rd., MILWAUKEE, WI 53201, Tel. (414)228-7380.

(IC Products) SIGNETICS CORPORATION, 811 East Arques Avenue, SUNNYVALE, California 94086, Tel. (408) 739-7700.

Uruguay: LUZILECTRON S.A., Avda Uruguay 1287, P.O. Box 907, MONTEVIDEO, Tel. 914321.

Venezuela: IND. VENEZOLANAS PHILIPS S.A., Elcoma Dept., A. Ppal de los Ruices, Edif. Centro Colgate, CARACAS, Tel. 360511

For all other countries apply to: Philips Electronic Components and Materials Division, International Business Relations, Building BAE, P.O. Box 218, 5600 MD EINDHOVEN, The Netherlands, Tel. +3140723304, Telex 35000 phtcnl

A45

© Philips Export B.V 1985

This information is furnished for guidance, and with no guarantee as to its accuracy or completeness; its publication conveys no licence under any patent or other right, nor does the publisher assume liability for any consequence of its use; specifications and availability of goods mentioned in it are subject to change without notice; it is not to be reproduced in any way, in whole or in part, without the written consent of the publisher.

Printed in The Netherlands