

MINISTRY OF SUPPLY - D.L.R.D.(A)/R.A.E.

Specification MOSA/CV2115 Issue 4 Dated 11.11.1953. To be read in conjunction with K1001, ignoring clauses 5.2, 5.8.	<u>SECURITY</u>	
	<u>Specification</u>	<u>Valve</u>
	UNCLASSIFIED	UNCLASSIFIED

→ Indicates a change

TYPE OF VALVE - Halfwave Rectifier		<u>MARKING</u>	
CATHODE - Directly Heated		See K1001/4	
ENVELOPE - Glass, unmetallised		<u>BASE</u>	
PROTOTYPES - E.2004		I.O.	
<u>RATING</u>		<u>MOUNTING POSITION</u>	
		Any	
		<u>CONNECTIONS</u>	
		Pin	Electrode
		1	Internal connection
		2	Filament
		3	Internal connection
		4	Omitted
		5	Internal connection
		6	Omitted
		7	Filament
		8	Internal connection
		T.C.	Anode
		<u>TOP CAP</u>	
		See K1001/A1/D5.1.	
		<u>DIMENSIONS</u>	
		See K1001/A1/D1.	
		Dimension	Min. Max.
		Ann	93.7 103.1
		Bnn	- 32.5
<u>NOTES</u>			
A. Should the filament be supplied from an R.F. source it must be run at the same temperature as it would attain at 1.25V. D.C.			
B. Pins 1, 3, 5 and 8 must not be used for external connections. All unused valve holder connections should be strapped to Pin 7 to reduce corona discharge.			
C. When the valve is used at max. voltage and/or current ratings, the supply source impedance shall be not less than 150,000 ohms.			

Z.5211.R.

CV2115/W1

To be performed in addition to those applicable in K.1001.

	Test Conditions			Test	Limits		No. Tested	Note
					Min.	Max.		
a	See K.1001/ALII Measurement to be made in Adaptor Type 44 Ref. No. 10A/13340.			Capacitance (pF) Cap	1.0	2.0	100% or S	
	Links to H.P.	Links to L.P.	Links to E.					
	T.C.	1,2,3,5,7,8.	9,10 T.C. 2					
b	Vr(V)	Va(V)		If (mA)	180	220	100% or S	
	1.25 A.C.	-						
c	1.10	190		Emission (mA)	5.0	15.0	100%	2
d	1.25 A.C.	See Note (3) PIV 33kV		Load Test D.C. Output Current (mA) Run for five minutes. Reject for softness and persistent flashover	2	-	6 per week	1,3,4

NOTES

1. This test shall be performed at a frequency of not less than 75 kc/s.
2. Applied only for sufficient time to obtain steady reading.
3. Filament and Anode Voltages shall be applied simultaneously. Load Resistance = 7 Megohms; Reservoir Condenser = 450 pF; Heating time = 90 sec. (minimum). Peak D.C. Anode Current = 18.7 mA. minimum.
4. Should the filament be supplied from an R.F. source it must be run at the same temperature as it would attain at 1.25V. D.C.