

ELECTRONIC VALVE SPECIFICATIONS.
SPECIFICATION AD/CV.4111 ISSUE NO. 1 DATED 1.10.62
AMENDMENT NO. 1

Page 1 DIMENSIONS

'A' Seated Height, Max. Amend "55.6" to read
"49.2".

October 1964.

T.V.C. for A.S.W.E.

CV4111

Specification AD/CV4111 incorporating MIL-E-1/1301B/NAVY Issue 1 dated 1.10.62 To be read in conjunction with K1006 and BS.448	<u>SECURITY</u> <u>Specification</u> Unclassified	<u>Valve</u> Unclassified
--	---	------------------------------

<u>TYPE OF VALVE:</u> Medium Mu Low Noise Double Triode with flexible leads.	<u>MARKING</u> See K1001/4 Additional marking: 7308
<u>CATHODE:</u> Indirectly heated	
<u>ENVELOPE:</u> Glass	
<u>PROTOTYPE:</u> 7308	<u>BASE</u> BS448/B9A/F

<u>RATING, CONNECTIONS, CAPACITANCES AND NOTES</u> See specification AD/CV4110, Issue 1 dated 1.10.62	<u>DIMENSIONS</u>		
	<u>Dimensions (mm)</u>	<u>Min.</u>	<u>Max.</u>
	A. Seated Height B. Diameter C. Lead Length	- 19 38	55.6 22.2
<u>MOUNTING POSITION</u> Any			

NOTE

A. The Joint Services Catalogue Number is:- 5960-99-037-2505

TESTS

The tests required by specification AD/CV4110, Issue 1 dated 1.10.62 shall be performed except as follows:-

Ref.	Test	Test Conditions	AQL %	Insp Level	Sym.	LIMITS						Units
						Min.	LAL	Bogie	UAL	Max.	ALD	
4.9.6.1	DELETED: Base Strain		-	-	-	-	-	-	-	-	-	-
K1001 5.12	<u>ADD:</u> Lead fragility	No voltages	6.5	I.A.	-	-	-	-	-	-	-	-