



## Current Equipment Type



B9A (Noval) Base

**TYPE ECF80  
MINIATURE  
TRIODE PENTODE  
FREQUENCY  
CHANGER**



The BRIMAR ECF80 is a triode pentode with separate cathodes designed for use as a frequency changer in television equipment up to 220 Mc/s.

Heater Current	...	...	...	...	...	...	...	...	...	0.43 amp.
Heater Voltage	...	...	...	...	...	...	...	...	...	6.3 volts

## RATINGS

		Triode	Pentode	
Anode Voltage ( $I_a = 0$ )	...	550	550	volts max.
Anode Voltage	...	250	250	volts max.
Anode Dissipation	...	1.5	1.7	watts max.
Screen Voltage ( $I_a = 0$ )	...	—	550	volts max.
Screen Voltage ( $I_k = 14 \text{ mA}$ )	...	—	175	volts max.
Screen Voltage ( $I_k \leq 10 \text{ mA}$ )	...	—	200	volts max.
Screen Dissipation ( $P_{a>} > 1.2 \text{ W}$ )	...	—	0.5	watts max.
Screen Dissipation ( $P_{a<} < 1.2 \text{ W}$ )	...	—	0.75	watts max.
Cathode Current	...	14	14	$\text{mA}$ max.
Control Grid Resistance	...	500	—	$k \Omega$ max.
Control Grid Resistance (cathode bias)	...	—	1.0	$M \Omega$ max.
Control Grid Resistance (fixed bias)	...	—	500	$k \Omega$ max.
Heater-Cathode Potential (cathode negative)	...	100	100	volts max.
Heater-Cathode Potential (cathode positive)*	...	200	200	volts max.

\* Maximum d.c. component 120 volts.

## CHARACTERISTICS

		Triode	Pentode	
Anode Voltage	...	100	170	volts
Screen Voltage	...	—	170	volts
Control Grid Voltage	...	—2	—2	volts
Anode Current	...	14	10	$\text{mA}$
Screen Current	...	—	2.8	$\text{mA}$
Mutual Conductance	...	5	6.2	$\text{mA/V}$
Amplification Factor	...	20	—	
Inner Amplification Factor ( $\mu g_1 - g_3$ )	...	—	47	
Anode Impedance (approx.)	...	4	400	$k \Omega$
Input Impedance at 50 Mc/s.	...	—	10	$k \Omega$
Equivalent noise resistance	...	—	1.5	$k \Omega$

## TYPICAL OPERATION AS A MIXER (Pentode Section)

		Triode	Pentode	
Anode Voltage	...	170	170	volts
Screen Voltage	...	170	170	volts
Grid Leak Resistor	...	100	100	$k \Omega$
Cathode Bias Resistor	...	330	820	$k \Omega$
Heterodyne Voltage	...	3.5	3.5	volts rms
Anode Current	...	6.5	5.2	$\text{mA}$
Screen Current	...	2.0	1.5	$\text{mA}$
Grid Current	...	20	0	$\mu\text{A}$
Conversion Conductance	...	2.2	2.1	$\text{mA/V}$
Input Impedance	...	800	870	$k \Omega$

		Triode	Pentode	
Pentode Grid 1 to Pentode Anode	...	...	...	0.025 pF
Pentode Input	...	...	...	5.2 pF
Pentode Output	...	...	...	3.4 pF
Triode Grid to Triode Anode	...	...	...	1.5 pF
Triode Grid to Triode Cathode and Heater	...	...	...	2.5 pF
Triode Anode to Triode Cathode and Heater	...	...	...	1.8 pF
Pentode Anode to Triode Anode	...	...	...	0.07 pF
Pentode Anode to Triode Grid	...	...	...	0.02 pF
Pentode Grid 1 to Triode Anode	...	...	...	0.16 pF

