

Medium-Mu Triode— Beam Power Tube

DUODECAR TYPE

Electrical:

Heater Characteristics and Ratings:

Voltage (AC or DC). 6.3 ± 0.6 volts
 Current at heater volts = 6.3 1.200 amp
 Peak heater-cathode voltage (Each unit):

Heater negative with respect to cathode 200 max. volts
 Heater positive with respect to cathode 200^a max. volts

Direct Interelectrode Capacitances (Approx.):^b

Triode Unit:

G _T to P _T	3.6	pf
Input: G _T to (K _T , H)	2.2	pf
Output: P _T to (K _T , H)	0.7	pf


Beam Power Unit:

G _{1B} to P _B	0.34	pf
Input: G _{1B} to (K _B +G _{3B} , G _{2B} , H)	11.0	pf
Output: P _B to (K _B +G _{3B} , G _{2B} , H)	7.0	pf

Mechanical:

Operating Position. Any
 Types of Cathodes Coated Unipotential
 Maximum Overall Length. 2.375"
 Seated Length 1.750" to 2.000"
 Diameter. 1.062" to 1.188"
 Dimensional Outline See General Section
 Bulb. T9
 Base. Small-Button Duodecar 12-Pin (JEDEC No. E12-70)
 Basing Designation for BOTTOM VIEW. 12DZ

- Pin 1 - Heater
- Pin 2 - Triode Plate
- Pin 3 - No Internal Connection
- Pin 4 - Beam Power Plate
- Pin 5 - Same as Pin 3
- Pin 6 - Beam Power Grid No. 1
- Pin 7 - Beam Power Grid No. 1
- Pin 8 - Beam Power Grid No. 2
- Pin 9 - Beam Power Cathode,
Beam Power Grid No. 3
- Pin 10 - Triode Grid
- Pin 11 - Triode Cathode
- Pin 12 - Heater



Characteristics, Class A₁ Amplifier:

	Triode Unit	Beam Power Tube
Plate Voltage	150	45 120 volts
Grid-No.2 Voltage	-	110 110 volts
Grid-No.1 Voltage	-5	0 -8 volts
Amplification Factor.	20	- -



	<i>Triode Unit</i>	<i>Beam Power Tube</i>	
Plate Resistance (Approx.)	8500	- 1700	ohms
Transconductance	2350	- 1400	μ hos
Plate Current	5.5	122 46	ma
Grid-No.2 Current	-	16.5 3.5	ma
Grid-No.1 Voltage (Approx.)			
for plate μ a=10	-11	- -	volts
100.	-	- -25	volts

VERTICAL-DEFLECTION OSCILLATOR

Triode Unit

Maximum Ratings, Design-Maximum Values:

For operation in a 525-line, 30-frame system^c

DC Plate Voltage	250	max.	volts
Peak Negative Pulse-Grid Voltage	400	max.	volts
Cathode Current:			
Peak	70	max.	ma
Average	20	max.	ma
Plate Dissipation	1	max.	watt

Maximum Circuit Values:

Grid-Circuit Resistance:

For fixed-bias operation	1	max.	megohm
For cathode-bias operation	2.2	max.	megohms

VERTICAL-DEFLECTION AMPLIFIER

Beam Power Unit

Maximum Ratings, Design-Maximum Values:

For operation in a 525-line, 30-frame system^c

DC Plate Voltage	250	max.	volts
Peak Positive-Pulse Plate Voltage	2000	max.	volts
Grid No.2 Voltage	200	max.	volts
Cathode Current:			
Peak	245	max.	ma
Average	70	max.	ma
Plate Dissipation ^d	7	max.	watts
Grid-No.2 Input	1.8	max.	watts

Maximum Circuit Values:

Grid-Circuit Resistance:

For fixed-bias operation	1	max.	megohm
For cathode-bias operation	2.2	max.	megohms

^a The dc component must not exceed 100 volts.

^b Without external shield.

^c This rating is applicable where the duration of the voltage pulse does not exceed 15 per cent of one vertical scanning cycle. In a 525-line, 30-frame system, 15 per cent of one vertical scanning cycle is 2.5 milliseconds.

^d In stages operating with grid-leak bias, an adequate cathode-bias-resistor or other suitable means is required to protect the tube in the absence of excitation.

