



**5HA7**

**COMPACTRON DISSIMILAR DOUBLE TRIODE**

**DESCRIPTION AND RATING**

The 5HA7 is a compactron containing a high-mu triode and a medium-mu triode. Except for heater characteristics, the 5HA7 is identical to the 4HA7.

**GENERAL**

**ELECTRICAL**

Cathode - Coated Unipotential

Heater Characteristics and Ratings

Heater Voltage, AC or DC*	. . . . .	5.6	Volts
Heater Current†.	. . . . .	0.45±0.03	Amperes
Heater Warm-up Time, Average§	. . . . .	11	Seconds

**NOTES**

- \* Heater voltage for a bogey tube at  $I_f = 0.45$  amperes.
- † The equipment designer should design the equipment so that heater current is centered at the specified bogey value, with heater supply variations restricted to maintain heater current within the specified tolerance.
- § The time required for the voltage across the heater to reach 80 percent of the bogey value after applying 4 times the bogey heater voltage to a circuit consisting of the tube heater in series with a resistance equal to 3 times the bogey heater voltage divided by the bogey heater current.

from JEDEC release #4449A, May 25, 1964

The tubes and arrangements disclosed herein may be covered by patents of General Electric Company or others. Neither the disclosure of any information herein nor the sale of tubes by General Electric Company conveys any license under patent claims covering combinations of tubes with other devices or elements. In the absence of an

express written agreement to the contrary, General Electric Company assumes no liability for patent infringement arising out of any use of the tubes with other devices or elements by any purchaser of tubes or others.