




Typ	Výrobce	U_f	I_f	U_a	I_a	$-U_{g1}$	U_{g2}	U_{g3}	U_{g4g6}
1	2	3	4	5	6	7	8	9	10
EQ40	Philips	6,3	0,2	250	190	—	20		
EQ80	Philips	6,3	0,2	250	280	—	20		
EQ171	RFT	6,3	0,2	250	300	—	20	4	20



241



291



321

U_{g5}	I_{g2}	I_{g3}	I_{g5}	S	R_i	R_a	Poznámka	Typ	Patice
11	12	13	14	15	16	17	18	19	20
-4,7	1,45	0,1	0,025	—	5000	400	det; zes C; $C_{ak}=8,9$ pF; $C_{g3k}=7,4$ pF; $P_0=0,1$ W	EQ40	241
-4	1,5	0,09	0,030	—	5000	500	det; zes C; $C_{ak}=8,9$ pF; $C_{g3k}=7,4$ pF	EQ80	291
-4	1,5	—	—	—	5000	—	$U_{fk}=100$ V; $P_{0\max}=0,1$ W; $U_{a\max}=300$ V; $P_{g2\max}=0,1$ W; $U_{g2\max}=100$ V; $R_{g1}=3$ M Ω max; $I_{k\max}=3$ mA	EQ171	321